Central Processor Unit		
AMD		
Socket AM2/AM2+/AM3 sempron		
CP-AAS1250		Amd socket AM2 sempron LE-1250 , 2200mhz - 128k L1 + 512k L2 ; , 45w low power consumption , 1600mhz HT2.0 link x 1 - 6.4Gb/sec , memory bandwidth - 10.6gb/sec - box cpu
Socket AM2/AM2+/AM3 athlon64		
CP-AAA1640		Amd socket AM2 athlon64 LE-1640 (2700mhz) - 128k L1 + 1mb L2 ; 65nm , 45w low power consumption ; 2000mhz HT2.0 link x 1 - 8Gb/sec , memory bandwidth - 10.6gb/sec , with PVT - box cpu
Socket AM2/AM2+/AM3 Dual core		
CP-AAD52		Amd socket AM2 athlon64 x2 Dual core 5200+ (2.6Ghz) , dual core - 2 x 128k L1 + 2 x 1mb L2 ; 65nm , 65w , 2000mhz HT2.0 link x 1 - 8Gb/sec , memory bandwidth - 12.8gb/sec , with PVT - box cpu
CP-AAD7750B	N	Amd socket AM2+ athlon64 x2 Dual-core 7750 Black edition , (2.7Ghz) , unlocked clock multiplier , dual core ; 2 x 128k L1 + 2x512k L2 + 1x shared 2mb L3 ; 65nm , 95w , 3600mhz HT3.0 link x 1 (20.8gb/sec) , with PVT - box cpu
CP-AAD56		Amd socket AM2 athlon64 x2 Dual core 5600+ (2.8Ghz) , dual core - 2 x 128k L1 + 2 x 1mb L2 ; 65nm , 65w , 2000mhz HT2.0 link x 1 - 8Gb/sec , memory bandwidth - 12.8gb/sec , with PVT - box cpu
Socket AM2 Dual core Opteron		
CP-AAD1216		Amd socket AM2 Dual core opteron 1216 , support core-to-core , 2000mhz HT2.0 link x 1 - 8Gb/sec , memory bandwidth - 12.8gb/sec , 2400mhz - 2x 128k L1 + 2x 1mb L2 - box cpu
CP-AAD1218		Amd socket AM2 Dual core opteron 1218 , support core-to-core , 2000mhz HT2.0 link x 1 - 8Gb/sec , memory bandwidth - 12.8gb/sec , 2600mhz - 2x 128k L1 + 2x 1mb L2 - box cpu
Socket AM2+/AM3 Tripple core		
CP-AAT8650		Amd socket AM2+ Phenomx3 Tripple-core 8650 (2.3Ghz) ; 3 x 128k L1 + 3 x 512k L2 + 1x shared 2mb L3 ; 65nm , 95w , 3600mhz HT3.0 link x 1 (33.1gb/sec) , with PVT - box cpu
CP-AAT8750B		Amd socket AM2+ Phenomx3 Tripple-core 8750 Black edition (2.4Ghz) , unlocked clock multiplier ; 3 x 128k L1 + 3 x 512k L2 + 1x shared 2mb L3 ; 65nm , 95w , 3600mhz HT3.0 link x 1 (33.1gb/sec) , with PVT - box cpu
CP-AAT710	N	Amd socket AM3 (AM2/AM2+ backward compatiable) Phenom2 x3 , Tripple-core 710 (2.6Ghz) ; 3 x 128k L1 + 3 x 512k L2 + 1x shared 6mb L3 ; 45nm, 95w , 3600mhz HT3.0 link x 1 (37gb/sec)
CP-AAT720B	N	Amd socket AM3 (AM2/AM2+ backward compatiable) Phenom2 x3 , Tripple-core 720 Black edition (2.8Ghz) , unlocked clock multiplier ; 3 x 128k L1 + 3 x 512k L2 + 1x shared 6mb L3 ; 45nm, 95w , 3600mhz HT3.0 link x 1 (37gb/sec)
Socket AM2+/AM3 Quad core		
CP-AAQ9750		Amd socket AM2+ Phenomx4 Quad-core 9750 (2400mhz) , with B3 stepping ; 4 x 128k L1 + 4 x 512k L2 + 1x shared 2mb L3 ; 65nm , 125w , 3600mhz HT3.0 link x 1 (33.1gb/sec) , with PVT - box cpu (with fan)
CP-AAQ9950B		Amd socket AM2+ Phenomx4 , Quad-core 9950 (2.6Ghz) Black edition , with B3 stepping , unlocked clock multiplier ; 4 x 128k L1 + 4 x 512k L2 + 1x shared 2mb L3 ; 65nm , 125w , 3600mhz HT3.0 link x 1 (33.1gb/sec) , with PVT - box cpu (with fan)
CP-AAQ810	N	Amd socket AM3 (AM2/AM2+ backward compatiable) Phenom2 x4 , Quad-core 810 (2.6Ghz) ; 4 x 128k L1 + 4 x 512k L2 + 1x shared 4mb L3 ; 45nm, 95w , 3600mhz HT3.0 link x 1 (37gb/sec)

CP-AAQ910	C	Amd socket AM3 (AM2/AM2+ backward compatiable) Phenom2 x4 , Quad-core 910 (2.6Ghz) ; 4 x 128k L1 + 4 x 512k L2 + 1x shared 6mb L3 ; 45nm, 95w , 3600mhz HT3.0 link x 1 (37gb/sec)
CP-AAQ920	N	Amd socket AM2+ Phenom2 x4 , Quad-core 920 (2.8Ghz) ; 4 x 128k L1 + 4 x 512k L2 + 1x shared 6mb L3 ; 45nm , 125w , 3600mhz HT3.0 link x 1 (33.1gb/sec) , with PVT - box cpu (with fan)
CP-AAQ940B	N	Amd socket AM2+ Phenom2 x4 , Quad-core 940 (3.0Ghz) Black edition , unlocked clock multiplier ; 4 x 128k L1 + 4 x 512k L2 + 1x shared 6mb L3 ; 45nm , 125w , 3600mhz HT3.0 link x 1 (33.1gb/sec) , with PVT - box cpu (with fan)
Socket L1 (1207FX)		
CP-ALFX70		Amd socket-L1 (1207FX) FX-70 , 2600mhz dual core cpu , support DSDC dual socket platform for QuadFX - 2x128k L1 + 2 x 1mb L2 ; 2000mhz HT2.0 link x 1 - 8Gb/sec , memory bandwidth - 12.8gb/sec - box cpu
S940 opteron dual core		http://www.amd.com/us-en/Processors/ProductInformation/0,,30_118_8796,00.html
CP-A9265D		Amd socket 940 opteron 265 , 1800mhz , 95w , dual core , support core-to-core , 2000mhz HT 2.0 link x 3 - 24GB/sec , memory bandwidth - 12.8gb/sec - 2x128k L1 + 2x 1mb L2 ; 2000mhz fsb hypertransport , support dual cpu - box cpu
CP-A9285D		Amd socket 940 opteron 285 , 2600mhz , 95w , dual core , support core-to-core , 2000mhz HT 2.0 link x 3 - 24GB/sec , memory bandwidth - 12.8gb/sec - 2x128k L1 + 2x 1mb L2 ; 2000mhz fsb hypertransport , support dual cpu - box cpu
Socket-F opteron dual core		
CP-AF2350		Amd socket-F (1207) opteron 2350 , 2.0Ghz , 75w , quad core , support core-to-core , HT 2.0 link x 3 - 24GB/S , 2000mhz - 4x128k L1 + 4x 512 L2 + 1x shared 2mb L3 cache ; 2000mhz fsb hypertransport , support dual cpu socket - box cpu - no FAN
CP-AF2354	R	Amd socket-F (1207) opteron 2354 , 2.2Ghz , 75w , quad core , support core-to-core , HT 2.0 link x 3 - 24GB/S , 2000mhz - 4x128k L1 + 4x 512 L2 + 1x shared 2mb L3 cache ; 2000mhz fsb hypertransport , support dual cpu socket - box cpu - no FAN
CP-AF2356	R	Amd socket-F (1207) opteron 2356 , 2.3Ghz , 75w , quad core , support core-to-core , HT 2.0 link x 3 - 24GB/S , 2000mhz - 4x128k L1 + 4x 512 L2 + 1x shared 2mb L3 cache ; 2000mhz fsb hypertransport , support dual cpu socket - box cpu - no FAN
Intel		
LGA775 Celeron-D		
CP-i430		Intel 430 Celeron 1.8ghz box cpu , 65nm conroe-L , Lga775 , 800mhz fsb - 64k L1+ 512k L2 cache -with EDB , EM64T , WDE , ASC , SMA , ADMB
CP-iE1400		Intel Celeron dual-core E1400 2.0ghz box cpu , 65nm conroe-L , Lga775 , 800mhz fsb - 2 x 64k L1+ 2 x 512k L2 cache -with EiST, EDB , EM64T , WDE , ASC , SMA , ADMB
CP-iE1500	N	Intel Celeron dual-core E1500 2.2ghz box cpu , 65nm conroe-L , Lga775 , 800mhz fsb - 2 x 64k L1+ 2 x 512k L2 cache -with EiST, EDB , EM64T , WDE , ASC , SMA , ADMB
LGA775 Pentium Dual core		
CP-iE2200		Intel pentium E2200 - dual core 2.2ghz box cpu , (no VT, vPro, ViiV) , 65nm , Lga775 , 800mhz fsb - 2x64k L1+ shared 1mb L2 cache - with EDB , EiST, EM64T , WDE , ASC , SMA , ADMB
CP-iE5200		Intel pentium E5200 - dual core 2.5ghz box cpu , (no VT, vPro, ViiV) , 45nm , Lga775 , 800mhz fsb - 2x64k L1+ shared 2mb L2 cache - with EDB , EiST, EM64T , WDE , ASC , SMA . ADMB

CP-iE5300		Intel pentium E5300 - dual core 2.6ghz box cpu , (no VT, vPro, ViiV) , 45nm , Lga775 , 800mhz fsb - 2x64k L1+ shared 2mb L2 cache - with EDB , EiST, EM64T , WDE , ASC , SMA , ADMB
CP-iE5400	N	Intel pentium E5400 - dual core 2.7ghz box cpu , (no VT, vPro, ViiV) , 45nm , Lga775 , 800mhz fsb - 2x64k L1+ shared 2mb L2 cache - with EDB , EiST, EM64T , WDE , ASC , SMA , ADMB
LGA775 Core2		http://www.intel.com/core2duo/
CP-iE7400		Intel Core2 Duo E7400 - dual core 2.8ghz box cpu , no VT , 45nm , Lga775 , 1066mhz fsb - 2x64k L1+ shared 3mb L2 cache - with EDB , EiST, EM64T , WDE , ASC , SMA , ADMB, 128bit SSE4
CP-iE7500	N	Intel Core2 Duo E7500 - dual core 2.93ghz box cpu , no VT , 45nm , Lga775 , 1066mhz fsb - 2x64k L1+ shared 3mb L2 cache - with EDB , EiST, EM64T , WDE , ASC , SMA , ADMB, 128bit SSE4
CP-iE8400		Intel Core2 Duo E8400 - dual core 3.0ghz box cpu , with VT+TXT , 45nm , Lga775 , 1333mhz fsb - 2x64k L1+ shared 6mb L2 cache - with EDB , EiST, EM64T , WDE , ASC , SMA , ADMB, 128bit SSE4
CP-iE8500		Intel Core2 Duo E8500 - dual core 3.16ghz box cpu , with VT+TXT , 45nm , Lga775 , 1333mhz fsb - 2x64k L1+ shared 6mb L2 cache - with EDB , EiST, EM64T , WDE , ASC , SMA , ADMB, 128bit SSE4
CP-iE8600	N	Intel Core2 Duo E8600 - dual core 3.33ghz box cpu , with VT+TXT , 45nm , Lga775 , 1333mhz fsb - 2x64k L1+ shared 6mb L2 cache - with EDB , EiST, EM64T , WDE , ASC , SMA , ADMB, 128bit SSE4
LGA775 Core2 - Quad		http://www.intel.com/products/processor/core2quad/index.htm?iid=prod_desktopcore+body_core2quad
CP-iQ8200		Intel Core2 Quad Q8200 - quad core 2.33ghz box cpu , no VT , 45nm , Lga775 , 1333mhz fsb - 4x64k L1+ 2 x shared 4mb L2 cache - with EDB , EiST, EM64T , WDE , ASC , SMA , ADMB, 128bit SSE4
CP-iQ8300	N	Intel Core2 Quad Q8300 - quad core 2.5ghz box cpu , no VT , 45nm , Lga775 , 1333mhz fsb - 4x64k L1+ 2 x shared 4mb L2 cache - with EDB , EiST, EM64T , WDE , ASC , SMA , ADMB, 128bit SSE4
CP-iQ9400		Intel Core2 Quad Q9400 - quad core 2.66ghz box cpu , with VT+TXT , 45nm , Lga775 , 1333mhz fsb - 4x64k L1+ 2 x shared 3mb L2 cache - with EDB , EiST, EM64T , WDE , ASC , SMA , ADMB, 128bit SSE4
CP-iQ9550		Intel Core2 Quad Q9550 - quad core 2.83ghz box cpu , with VT+TXT , 45nm , Lga775 , 1333mhz fsb - 4x64k L1+ 2 x shared 6mb L2 cache - with EDB , EiST, EM64T , WDE , ASC , SMA , ADMB, 128bit SSE4
CP-iQ9650		Intel Core2 Quad Q9650 - quad core 3.0ghz box cpu , with VT+TXT , 45nm , Lga775 , 1333mhz fsb - 4x64k L1+ 2 x shared 6mb L2 cache - with EDB , EiST, EM64T , WDE , ASC , SMA , ADMB, 128bit SSE4
LGA1366 Core2 - Quad + HT		
CP-ii7Q920	N	Intel i7/Nehalem 920 - Quad core+Hyper-Threading / 8 threads , 2.66ghz box cpu , LGA1366 , 4.8GT/s QPi , built-in tripple channel DDR3-1333 memory controler , 45nm - 4x64k L1 + 1mb(4 x 256kb) L2 cache + 8mb L3 cache
CP-ii7Q940	N	Intel i7/Nehalem 940 - Quad core+Hyper-Threading / 8 threads , 2.93ghz box cpu , LGA1366 , 4.8GT/s QPi , built-in tripple channel DDR3-1333 memory controler , 45nm - 4x64k L1 + 1mb(4 x 256kb) L2 cache + 8mb L3 cache
CP-ii7Q965XE	N	Intel i7/Nehalem 965XE - Quad core+Hyper-Threading / 8 threads , unlocked clock multiplier , 3.2ghz box cpu , LGA1366 , 6.4GT/s QPi , built-in tripple channel DDR3-1333 memory controler , 45nm - 4x64k L1 + 1mb(4 x 256kb) L2 cache + 8mb L3 cache
Xeon - socket771		

CC-THR013U	N	thermalright HR-01 3U , aluminum fins with 4 copper heatpipes to copper base ; for Amd AM2/1207 ; for intel xeon socket 603/604/771 , 110x60x110mm , 374g - heatsink only ; with clip for optional 60mm fan
CC-THR014U	N	thermalright HR-01 4U , aluminum fins with 4 copper heatpipes to copper base ; for Amd AM2/1207 ; for intel xeon socket 603/604/771 , 110x60x145mm , 489g - heatsink only ; with clip for optional 92mm fan
CC-THR01X	N	thermalright HR-01 X , aluminum fins with 6 copper heatpipes to copper base ; for intel xeon socket 603/604/771 , 110x60x159.5mm , 600g - heatsink only ; with clip for optional 120mm fan
CP-iXE5405A		Intel Xeon E5405 Active , socket 771 , quad core 2.0ghz box cpu with active cooler , 80w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T
CP-iXE5405P	R	Intel Xeon E5405 Passive , socket 771 , quad core 2.0ghz box cpu with passive cooler , 80w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T
CP-iXE5410A		Intel Xeon E5410 Active , socket 771 , quad core 2.33ghz box cpu with active cooler , 80w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T
CP-iXE5410P	R	Intel Xeon E5410 Passive , socket 771 , quad core 2.33ghz box cpu with passive cooler , 80w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T
CP-iXE5420A		Intel Xeon E5420 Active , socket 771 , quad core 2.5ghz box cpu with active cooler , 80w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T
CP-iXE5420P	R	Intel Xeon E5420 Passive , socket 771 , quad core 2.5ghz box cpu with passive cooler , 80w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T
CP-iXE5430A	R	Intel Xeon E5430 Active , socket 771 , quad core 2.66ghz box cpu with active cooler , 80w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T
CP-iXE5430P	R	Intel Xeon E5430 Passive , socket 771 , quad core 2.66ghz box cpu with passive cooler , 80w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T
CP-iXE5440A	R	Intel Xeon E5440 Active , socket 771 , quad core 2.83ghz box cpu with active cooler , 80w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T
CP-iXE5440P	R	Intel Xeon E5440 Passive , socket 771 , quad core 2.83ghz box cpu with passive cooler , 80w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T
CP-iXX5450A	R	Intel Xeon X5450 Active , socket 771 , quad core 3.0ghz box cpu with active cooler , 120w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T
CP-iXX5450P	R	Intel Xeon X5450 Passive , socket 771 , quad core 3.0ghz box cpu with passive cooler , 120w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T
CP-iXE5450A	R	Intel Xeon E5450 Active , socket 771 , quad core 3.0ghz box cpu with active cooler , 80w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T
CP-iXE5450P	R	Intel Xeon E5450 Passive , socket 771 , quad core 3.0ghz box cpu with passive cooler , 80w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T
CP-iXX5460A	R	Intel Xeon X5460 Active , socket 771 , quad core 3.16ghz box cpu with active cooler , 120w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T

CP-iXX5460P	R	Intel Xeon X5460 Passive , socket 771 , quad core 3.16ghz box cpu with passive cooler , 120w , 1333mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T
CP-iXQX9775		Intel Xeon QX9775 (Core2 extreme) , socket 771 , quad core 3.2ghz box cpu with no fan (require LGA775 cooler) , 150w , 1600mhz fsb , with VT , 45nm - 4x64k L1 , shared 2x6mb L2 cache - with EDB , EiST, EM64T

Memory - desktop

Memory Cooler

MC-VMA		vizo DDR-ALM SDR/DDR/DDR2 memory heat spreader - Aluminum
MC-VMAT		vizo DDR-ALM-TW SDR/DDR/DDR2 memory heat spreader - Aluminum - Twin pack
MC-VMC		Vizo DDR-CPR SDR/DDR/DDR2 memory heat spreader - Copper
MC-VMCT		vizo DDR-CPR-TW SDR/DDR/DDR2 memory heat spreader , Twin pack - Copper
MC-V201	N	Vizo Armada 2 RCL-201 dual-fan memory cooler with blue led , for SDR/DDR/DDR2 , 2 x 40x40mm blue led fan , 4500rpm , 20dbn , 13.86x2 CFM
MC-V301		Vizo Armada RCL-301 tri-fan memory cooler with blue led , for SDR/DDR/DDR2 , 3 x 40x40mm blue led fan , 4500rpm , 27.98dbn , 13.86x3 CFM
MC-CMXAF1		Corsair CMXAF1 memory cooler with 3 x 40x40mm fan - with extra height - ideal for Corsair Dominator memory
MC-THR07		Thermalright HR-07 - memory cooler , 150x27x86mm - copper heatsink + 2 copper heatpipes - 150g , support optional 72/80/92mm fan
MC-THR07DL		Thermalright HR-07 Duo type-H - 2 x Highrise memory cooler , 128x19x85.28mm - copper heatsink + 2x2 copper heatpipes
MC-THR07DH		Thermalright HR-07 Duo type-L - 2 x Low-rise memory cooler , 128x19x56.28mm - copper heatsink + 2x2 copper heatpipes

184pin DDR

DDR - Non-ECC

A-grade - 5 years warranty

ME-256D400	a-grade 256mb ddr400 (pc3200) - 184pin - 5 years warranty
ME-512D400	a-grade 512mb ddr400 (pc3200) - 184pin - 5 years warranty
ME-1GD400	a-grade 1024mb ddr400 (pc3200) - 184pin - 5 years warranty

Corsair - lifetime warranty

ME-C512DV4	Corsair Valueselect VS512MB400 512mb ddr-400 (pc3200) , CL2.5 - 184pin - lifetime warranty
ME-C1GDV4	Corsair Valueselect VS1GB400C3 1Gb/1024mb ddr-400 (pc3200) , CL3 - 184pin - lifetime warranty

Kingston - lifetime warranty

ME-K512DV400	Kingston ValueRam KVR400X64C3A/25/512 512mb ddr-400 (pc3200) , 184pin - lifetime warranty
ME-K512DX433A	Kingston Hyper-X KHX3500A/512 512mb ddr433 (pc3500) , CL2.5 , 2.5-3-3-7-1 , 2.6v , with heatsink - 184pin - lifetime warranty
ME-K512DX500	Kingston Hyper-X KHX4000LL/512 512mb ddr500 (pc4000) , CL3 , 3-3-3-8-1 , 2.6v , with heatsink - 184pin - lifetime warranty
ME-K1GDV400	Kingston ValueRam KVR400X64C3A/25/1G 1024mb ddr-400 (pc3200) , CL3 , 3-3-3 , 2.6v - 184pin - lifetime warranty

DDR - ECC

Kingston - lifetime warranty

ME-K512DV400E	Kingston ValueRam KVR400X72C3A/512 ECC 512mb ddr-400 (pc3200) , dual rank, CL3 , 3-3-3 , 2.6v - 184pin - lifetime warranty

ME-K1GDV400E		Kingston ValueRam KVR400X72C3A/1G ECC 1024mb ddr-400 (pc3200) , dual rank, CL3 , 3-3-3 , 2.6v - 184pin - lifetime warranty
DDR - ECC Registered		
Kingston - lifetime warranty		
ME-K1GDV400ER		Kingston ValueRam KVR400D8R3A/1G ECC Registered 1024mb ddr-400 (pc3200) , dual rank x8 , CL3 , 2.6v - 184pin - lifetime warranty
ME-K2GDV400ER	R	Kingston ValueRam KVR400D4R3A/2G ECC Registered 2048mb ddr-400 (pc3200) , dual rank x4 , CL3 , 2.6v - 184pin - lifetime warranty
240pin DDR2		
DDR2 - Non-ECC		
A-grade - 5 years warranty		
ME-512D2667		512mb ddr2-667 (pc2-5300) - 240pin - 5 years warranty
ME-512D2800		512mb ddr2-800 (pc2-6400) - 240pin - 5 years warranty
ME-1GD2667		1Gb/1024mb ddr2-667 (pc2-5300) - 240pin - 5 years warranty
ME-1GD2800		1Gb/1024mb ddr2-800 (pc2-6400) - 240pin - 5 years warranty
ME-1GD21066	N	1Gb/1024mb ddr2-1066 (pc2-8500) - 240pin - 5 years warranty
ME-2GD2667	N	2Gb/2048mb ddr2-667 (pc2-5300) - 240pin - 5 years warranty
ME-2GD2800		2Gb/2048mb ddr2-800 (pc2-6400) - 240pin - 5 years warranty
ME-2GD21066		2Gb/2048mb ddr2-1066 (pc2-8500) - 240pin - 5 years warranty
Corsair - lifetime warranty		
ME-C512D2V6		Corsair Valuselect VS512MB667D2 G , 512mb ddr2-667 (pc2-5400) , CL5 , 1.8v - 240pin - lifetime warranty
ME-C512D2V6x2	N	Corsair Valuselect VS1GBKiT667D2 G , 2x512mb kit ddr2-667 (pc2-5400) , CL5 , 1.8v - 240pin - lifetime warranty
ME-C512D2X8Lx2		Corsair TWIN2X1024-6400C4 - XMS2 , with heatsink , Low-latency , 2x512mb kit , ddr2-800 (pc2-6400) , CL4 , 2.1v - 240pin - lifetime warranty
ME-C1GD2V6		Corsair Valuselect VS1GB667D2 G , 1Gb/1024mb ddr2-667 (pc2-5400) , CL5 , 1.8v - 240pin - lifetime warranty
ME-C1GD2V6x2		Corsair Valuselect VS2GBKIT667D2 , 2x1Gb/1024mb kit , ddr2-667 (pc2-5400) , CL5 , 1.8v - 240pin - lifetime warranty
ME-C1GD2X6L		Corsair CM2X1024-5400C4 - XMS2 , with heatsink , Low-latency , 1Gb/1024mb , ddr2-675 (pc2-5400) , CL4 , 1.9v - 240pin - lifetime warranty
ME-C1GD2X8		Corsair CM2X1024-6400 - XMS2 , with heatsink , 1Gb/1024mb , ddr2-800 (pc2-6400) , CL5 , 1.8v - 240pin - lifetime warranty
ME-C1GD2X8x2		Corsair TWIN2X2048-6400 - XMS2 , with heatsink , 2x1Gb/1024mb kit , ddr2-800 (pc2-6400) , CL5 , 1.9v - 240pin - lifetime warranty
ME-C1GD2X8Lx2		Corsair TWIN2X2048-6400C4 - XMS2 , with heatsink , Low-latency , 2x1Gb/1024mb kit , ddr2-800 (pc2-6400) , CL4 , 2.1v - 240pin - lifetime warranty
ME-C1GD2X8Dx2		Corsair TWIN2X2048-6400C5DHX - XMS2 , with DHX technology , 2x1Gb/1024mb kit , ddr2-800 (pc2-6400) , CL5 , 1.8v - 240pin - lifetime warranty
ME-C1GD2X8DLx2		Corsair TWIN2X2048-6400C4DHX - XMS2 , with DHX technology , Low-latency , 2x1Gb/1024mb kit , ddr2-800 (pc2-6400) , CL4 , 2.1v - 240pin - lifetime warranty
ME-C1GD2D8DUFx2		Corsair TWIN2X2048-6400C3DF - Dominator , with DHX technology + Ultra low latency + airflow Fan , Nvidia SLi certrified with EPP , designed for nForce 590/680 SLi , 2x1Gb/1024mb kit , ddr2-800 (pc2-6400) , CL3 , 2.4v - 240pin - lifetime warranty
ME-C1GD2X10Lx2	N	Corsair TWIN2X2048-8500C5 - XMS2 , with heatsink , 2x1Gb/1024mb kit , ddr2-1066 (pc2-8500) , CL5 , 2.1v - 240pin - lifetime warranty

ME-C1GD2D10Dx2		Corsair TWIN2X2048-8500C5D , Dominator , with DHX technology , Nvidia SLi certrified with EPP , 2x1G/1024mb kit , ddr2-1066 (pc2-8500) , CL5 , 5-5-5-15 , 2.1v , with heatsink - 240pin - lifetime warranty
ME-C1GD2D12DFx2		Corsair TWIN2X2048-10000C5DF - Dominator , with DHX technology + airflow Fan , Nvidia SLi certrified with EPP , 2x1Gb/1024mb kit , ddr2-1250 (pc2-10000) , CL5 , 2.4v - 240pin - lifetime warranty
ME-C2GD2V6		Corsair Valuselect VS2GB667D2 , 2Gb/2048mb ddr2-667 (pc2-5300) , CL5 , 1.8v - 240pin - lifetime warranty
ME-C2GD2V6x2	N	Corsair Valuselect VS4GBKIT667D2 , 2x2Gb/2048mb kit ddr2-667 (pc2-5300) , CL5 , 1.8v - 240pin - lifetime warranty
ME-C2GD2X8		Corsair CM2X2048-6400C5 - XMS2 , with heatsink , 2Gb/2048mb , ddr2-800 (pc2-6400) , CL5 , 1.9v - 240pin - lifetime warranty
ME-C2GD2X8x2		Corsair TWIN2X4096-6400C5 G - XMS2 , with heatsink , 2x2Gb/2048mb kit , ddr2-800 (pc2-6400) , CL5 , 1.8v - 240pin - lifetime warranty
ME-C2GD2X8Dx2		Corsair TWIN2X4096-6400C5DHX - XMS2 , with heatsink + DHX technology , 2x2Gb/2048mb kit , ddr2-800 (pc2-6400) , CL5 , 1.8v - 240pin - lifetime warranty
ME-C2GD2X8DLx2		Corsair TWIN2X4096-6400C4DHX - XMS2 , with DHX technology , Low-latency , 2x2Gb/2048mb kit , ddr2-800 (pc2-6400) , CL4 , 2.1v - 240pin - lifetime warranty
ME-C2GD2X8DLx4		Corsair Q2X8G6400C4DHX - XMS2 , with DHX technology , Low-latency , 4x2Gb/2048mb kit , ddr2-800 (pc2-6400) , CL4 , 2.1v - 240pin - lifetime warranty
ME-C2GD2X10x2	N	Corsair TWIN2X4096-8500C7 G - XMS2 , with heatsink , 2x2Gb/2048mb kit , ddr2-1066 (pc2-8500) , CL7 , 1.8v - 240pin - lifetime warranty
ME-C2GD2X10Lx2	N	Corsair TWIN2X4096-8500C5 G - XMS2 , with heatsink , 2x2Gb/2048mb kit , ddr2-1066 (pc2-8500) , CL5 , 1.8v - 240pin - lifetime warranty
ME-C2GD2D10Dx2	N	Corsair TWIN2X4096-8500C5D , Dominator , with DHX technology , Nvidia SLi certrified with EPP , designed for nForce 590/680 SLi , 2 x 2G/2048mb kit , ddr2-1066 (pc2-8500) , CL5 , 5-5-5-15 , 2.1v , with heatsink - 240pin - lifetime warranty
Kingston - lifetime warranty		
ME-K512D2V533		Kingston ValueRam KVR533D2N4/512 512mb ddr2-533 (pc2-4300) , CL4 , 1.8v - 240pin - lifetime warranty
ME-K512D2V667		Kingston ValueRam KVR667D2N5/512 512mb ddr2-667 (pc2-5300) , CL5 , 1.85v - 240pin - lifetime warranty
ME-K512D2V800		Kingston ValueRam KVR800D2N5/512 512mb ddr2-800 (pc2-6400) , CL5 , 1.8v - 240pin - lifetime warranty
ME-K512D2X800L		Kingston Hyper-X KHX6400D2LL/512 Low-latency , 512mb ddr2-800 (pc2-6400) , CL4 , 4-4-4-12 , 2.0v , with heatsink - 240pin - lifetime warranty
ME-K512D2X8LNx2		Kingston Hyper-X KHX6400D2LLK2/1GN , Low latency , Nvidia SLi certrified with EPP , designed for nForce 590/680 SLi , 2x512mb kit , ddr2-800 (pc2-6400) , CL4 , 4-4-4-12 , 2.0v , with heatsink - 240pin - lifetime warranty
ME-K512D2X900		Kingston Hyper-X KHX7200D2/512 512mb ddr2-900 (pc2-7200) , CL5 , 5-5-5-15 , 2.0v , with heatsink - 240pin - lifetime warranty
ME-K1GD2V533		Kingston ValueRam KVR533D2N4/1G 1024mb ddr2-533 (pc2-4300) , CL4 , 1.8v - 240pin - lifetime warranty
ME-K1GD2V667		Kingston ValueRam KVR667D2N5/1G 1024mb ddr2-667 (pc2-5300) , CL5 , 1.8v - 240pin - lifetime warranty
ME-K1GD2V8		Kingston ValueRam KVR800D2N5/1G , 1Gb/1024mb ddr2-800 (pc2-6400) , CL5 , 1.8v - 240pin - lifetime warranty

ME-K1GD2V8x2		Kingston ValueRam KVR800D2N5K2/2G , 2x1Gb/1024mb kit , ddr2-800 (pc2-6400) , CL5 , 1.8v - 240pin - lifetime warranty
ME-K1GD2X8		Kingston Hyper-X KHX6400D2/1G , 1Gb/1024mb ddr2-800 (pc2-6400) , CL5 , 5-5-5-15 , 1.95v , with heatsink - 240pin - lifetime warranty
ME-K1GD2X8x2		Kingston Hyper-X KHX6400D2K2/2G , 2x1Gb/1024mb kit , ddr2-800 (pc2-6400) , CL5 , 5-5-5-15 , 1.95v , with heatsink - 240pin - lifetime warranty
ME-K1GD2X8Tx2	N	Kingston Hyper-X KHX6400D2T1K2/2G , with Tall HeatSink , 2x1Gb/1024mb kit , ddr2-800 (pc2-6400) , CL5 , 5-5-5-15 , 2.0v , 240pin - lifetime warranty
ME-K1GD2X8L		Kingston Hyper-X KHX6400D2LL/1G , Low latency , 1Gb/1024mb ddr2-800 (pc2-6400) , CL4 , 4-4-4-12 , 2.0v , with heatsink - 240pin - lifetime warranty
ME-K1GD2X8Lx2		Kingston Hyper-X KHX6400D2LLK2/2G , Low latency , 2x1Gb/1024mb kit , ddr2-800 (pc2-6400) , CL4 , 4-4-4-12 , 2.0v , with heatsink - 240pin - lifetime warranty
ME-K1GD2X8LNx2		Kingston Hyper-X KHX6400D2LLK2/2GN , Low latency , Nvidia SLi certrified with EPP , designed for nForce 590/680 SLi , 2x1Gb/1024mb kit , ddr2-800 (pc2-6400) , CL4 , 4-4-4-12 , 2.0v , with heatsink - 240pin - lifetime warranty
ME-K1GD2X10L		Kingston Hyper-X KHX8500D2/1G , 1Gb/1024mb ddr2-1066 (pc2-8500) , CL5 , 5-5-5-15 , 2.2v , with heatsink - 240pin - lifetime warranty
ME-K1GD2X10Lx2		Kingston Hyper-X KHX8500D2K2/2G , 2x1G/1024mb kit , ddr2-1066 (pc2-8500) , CL5 , 5-5-5-15 , 2.2v , with heatsink - 240pin - lifetime warranty
ME-K2GD2V667		Kingston ValueRam KVR667D2N5/2G , 2Gb/2048mb ddr2-667 (pc2-5300) , CL5 , 1.8v - 240pin - lifetime warranty
ME-K2GD2V667x2		Kingston ValueRam KVR667D2N5K2/4G , 2x2Gb/2048mb kit , ddr2-667 (pc2-5300) , CL5 , 1.8v - 240pin - lifetime warranty
ME-K2GD2V8		Kingston ValueRam KVR800D2Nx/2G , 2Gb/2048mb ddr2-800 (pc2-6400) , 1.8v - 240pin - lifetime warranty
ME-K2GD2V8x2		Kingston ValueRam KVR800D2N5K2/4G , 2x2Gb/2048mb kit , ddr2-800 (pc2-6400) , CL5, 1.8v - 240pin - lifetime warranty
ME-K2GD2X8		Kingston Hyper-X KHX6400D2/2G 2048mb ddr2-800 (pc2-6400) , CL5 , 5-5-5-15 , 2.0v , with heatsink - 240pin - lifetime warranty
ME-K2GD2X8x2		Kingston Hyper-X KHX6400D2K2/4G , 2x2Gb/2048mb kit , ddr2-800 (pc2-6400) , CL5 , 5-5-5-15 , 2.0v , with heatsink - 240pin - lifetime warranty
ME-K2GD2X8L	N	Kingston Hyper-X KHX6400D2LL/2G 2048mb ddr2-800 (pc2-6400) , CL4 , 4-4-4-12 , 2.0v , with heatsink - 240pin - lifetime warranty
ME-K2GD2X8Lx2	N	Kingston Hyper-X KHX6400D2LLK2/4G , 2x2Gb/2048mb kit , ddr2-800 (pc2-6400) , CL4 , 4-4-4-12 , 2.0v , with heatsink - 240pin - lifetime warranty
ME-K2GD2X8Lx4	N	Kingston Hyper-X KHX6400D2LLK4/8G , 4x2Gb/2048mb kit , ddr2-800 (pc2-6400) , CL4 , 4-4-4-12 , 2.1v , with heatsink - 240pin - lifetime warranty
ME-K2GD2X10	N	Kingston Hyper-X KHX8500AD2/2G , 2G/2048mb , ddr2-1066 (pc2-8500) , CL7 , 7-7-7-20 , 2.0v , with heatsink - 240pin - lifetime warranty
ME-K2GD2X10x2	N	Kingston Hyper-X KHX8500AD2K2/4G , 2x2G/2048mb kit , ddr2-1066 (pc2-8500) , CL7 , 7-7-7-20 , 2.0v , with heatsink - 240pin - lifetime warranty
ME-K2GD2X10L	N	Kingston Hyper-X KHX8500D2/2G , 2G/2048mb , ddr2-1066 (pc2-8500) , CL5 , 5-5-5-15 , 2.3v , with heatsink - 240pin - lifetime warranty

ME-K2GD2X10Lx2	N	Kingston Hyper-X KHX8500D2K2/4G , 2x2G/2048mb kit , ddr2-1066 (pc2-8500) , CL5 , 5-5-5-15 , 2.3v , with heatsink - 240pin - lifetime warranty
ME-K2GD2X10LTx2	N	Kingston Hyper-X KHX8500D2T1K2/4G , with Tall HeatSink , 2x2G/2048mb kit , ddr2-1066 (pc2-8500) , CL5 , 5-5-5-15 , 2.2v , with heatsink - 240pin - lifetime warranty
ME-K4GD2V8	R	Kingston ValueRam KVR800D2N6/4G , 4Gb/4096mb ddr2-800 (pc2-6400) , CL6 , 1.8v - 240pin - lifetime warranty
ME-K4GD2V8x2	R	Kingston ValueRam KVR800D2N6K2/8G , 2x 4Gb/4096mb kit ddr2-800 (pc2-6400) , CL6 , 1.8v - 240pin - lifetime warranty
DDR2 - Ecc / Ecc Fb-dimm		
Corsair - lifetime warranty		
ME-C1GD2V6EF		Corsair CM72FB1024-667 , 1Gb/1024mb ddr2-667 (pc2-5300) , Valueselect , ECC FB-DiMM with AMB , single rank , CL5 , 240pin - lifetime warranty
ME-C1GD2X6EFx2		Corsair VSA2GBKITFB667D2 , for pc / mac with Mac Pro specific heatsink , 2x1Gb/1024mb kit ddr2-667 (pc2-5300) , ECC FB-DiMM with AMB , single rank , CL5 , 240pin - lifetime warranty
ME-C2GD2V6EF		Corsair CM72FB2048-667 , 2Gb/2024mb ddr2-667 (pc2-5300) , Valueselect , ECC FB-DiMM with AMB , single rank , CL5 , 240pin - lifetime warranty
ME-C2GD2X6EFx2		Corsair VSA4GBKITFB667D2 , for pc / mac with Mac Pro specific heatsink , 2x2Gb/2024mb kit ddr2-667 (pc2-5300) , ECC FB-DiMM with AMB , single rank , CL5 , 240pin - lifetime warranty
ME-C2GD2V8EF	N	Corsair CM72FB2048-800 , 2Gb/2024mb ddr2-800 (pc2-6400) , Valueselect , ECC FB-DiMM with AMB , single rank , CL5 , 240pin - lifetime warranty
ME-C2GD2X8EFx2		Corsair VSA4GBKITFB800D2 , for pc / mac with Mac Pro specific heatsink , 2x2Gb/2024mb kit ddr2-800 (pc2-6400) , ECC FB-DiMM with AMB , single rank , CL5 , 240pin - lifetime warranty
ME-C4GD2X8EFx2	N	Corsair VSA8GBKITFB800D2 , for pc / mac with Mac Pro specific heatsink , 2x4Gb/4096mb kit ddr2-800 (pc2-6400) , ECC FB-DiMM with AMB , single rank , CL5 , 240pin - lifetime warranty
Kingston - lifetime warranty		
ME-K512D2V533EF		Kingston ValueRam KVR533D2S8F4/512 ECC FB-DiMM with AMB , 512mb ddr2-533 (pc2-4300) , CL4 , 240pin - lifetime warranty
ME-K512D2V667E		Kingston ValueRam KVR667D2E5/512 ECC 512mb ddr2-667 (pc2-5300) , CL5 , 1.8v , 240pin - lifetime warranty
ME-K512D2V667Ei		Kingston ValueRam KVR667D2E5/512i intel validated ECC 512mb ddr2-667 (pc2-5300) , CL5 , 1.8v , 240pin - lifetime warranty
ME-K1GD2V667E		Kingston ValueRam KVR667D2E5/1G ECC 1024mb ddr2-667 (pc2-5300) , CL5 , 5-5-5 , 1.8v - 240pin - lifetime warranty
ME-K1GD2V667EF		Kingston ValueRam KVR667D2D8F5/1G ECC FB-DiMM with AMB , 1024mb ddr2-667 (pc2-5300) , CL5 , 240pin - lifetime warranty
ME-K1GD2V6EFi		Kingston ValueRam KVR667D2D8F5/1Gi intel validated ECC FB-DiMM with AMB , 1024mb ddr2-667 (pc2-5300) , CL5 , 240pin - lifetime warranty
ME-K1GD2V8E		Kingston ValueRam KVR800D2E5/1G ECC 1024mb ddr2-800 (pc2-6400) , CL5 , 5-5-5 , 1.8v - 240pin - lifetime warranty
ME-K1GD2V8Ex2		Kingston ValueRam KVR800D2E5K2/2G ECC 2x1Gb/1024mb kit , ddr2-800 (pc2-6400) , CL5 , 5-5-5 , 1.8v - 240pin - lifetime warranty
ME-K1GD2V8EF		Kingston ValueRam KVR800D2D8F5/1G ECC FB-DiMM with AMB , 1Gb/1024mb ddr2-800 (pc2-6400) , dual rank , CL5 , 240pin - lifetime warranty
ME-K1GD2V8EFx2		Kingston ValueRam KVR800D2D8F5K2/2G ECC FB-DiMM with AMB , 2x1Gb/1024mb kit ddr2-800 (pc2-6400) , dual rank , CL5 , 240pin - lifetime warranty

ME-K1GD2X8EFLx2	N	Kingston hyperX KHX6400F2LLK2/2G ECC FB-DiMM with AMB , Low-latency , with heatsink , 2x1Gb/1024mb kit ddr2-800 (pc2-6400) , dual rank , CL4 , 240pin - lifetime warranty
ME-K2GD2V667E	N	Kingston ValueRam KVR667D2E5/2G ECC 2048mb ddr2-667 (pc2-5300) , CL5 , 5-5-5 , 1.8v - 240pin - lifetime warranty
ME-K2GD2V667EF		Kingston ValueRam KVR667D2D8F5/2G ECC FB-DiMM with AMB , 2048mb ddr2-667 (pc2-5300) , dual rank x8 , CL5 , 1.8v , 240pin - lifetime warranty
ME-K2GD2V6EFi		Kingston ValueRam KVR667D2D8F5/2Gi intel validated ECC FB-DiMM with AMB , 2048mb ddr2-667 (pc2-5300) , dual rank x8 , CL5 , 1.8v , 240pin - lifetime warranty
ME-K2GD2V8E	N	Kingston ValueRam KVR800D2E5/2G ECC 2048mb ddr2-800 (pc2-6400) , CL5 , 5-5-5 , 1.8v - 240pin - lifetime warranty
ME-K2GD2V8EF	N	Kingston ValueRam KVR800D2D4F5/2G ECC FB-DiMM with AMB , 2Gb/2048mb ddr2-800 (pc2-6400) , dual rank , CL5 , 240pin - lifetime warranty
ME-K2GD2V8EFx2	R	Kingston ValueRam KVR800D2D8F5K2/4G ECC FB-DiMM with AMB , 2x2Gb/2048mb kit ddr2-800 (pc2-6400) , dual rank , CL5 , 240pin - lifetime warranty
ME-K4GD2V8E	N	Kingston ValueRam KVR800D2E6/4G ECC 4Gb/4096mb ddr2-800 (pc2-6400) , CL6 , 1.8v - 240pin - lifetime warranty
ME-K4GD2V8EF	R	Kingston ValueRam KVR800D2D4F5/4G ECC FB-DiMM with AMB , 4Gb/4096mb ddr2-800 (pc2-6400) , dual rank x 4 , CL5 , 240pin - lifetime warranty
ME-K4GD2V8EFx2	R	Kingston ValueRam KVR800D2D4F5K2/8G ECC FB-DiMM with AMB , 2x4Gb/4096mb kit ddr2-800 (pc2-6400) , dual rank x4 , CL5 , 240pin - lifetime warranty
ME-K8GD2V667EF	R	Kingston ValueRam KVR667D2D4F5/8G ECC FB-DiMM with AMB , 8G/8192mb ddr2-667 (pc2-5300) , dual rank x4 , CL5 , 1.8v , 240pin - lifetime warranty
ME-K8GD2V6EFx2	R	Kingston ValueRam KVR667D2D4F5K2/16G ECC FB-DiMM with AMB , 2x8G/8192mb kit ddr2-667 (pc2-5300) , dual rank x4 , CL5 , 1.8v , 240pin - lifetime warranty
DDR2 - ECC Registered		
Corsair - lifetime warranty		
ME-C1GD2V6ERP		Corsair CM72DD1024R-667 , ECC Registered with Parity check dual rank x8 , 1Gb/1024mb ddr2-667 - 240pin - lifetime warranty
ME-C2GD2V6ERP		Corsair CM72DD2048R-667 , ECC Registered with Parity check dual rank x8 , 2Gb/2048mb ddr2-667 - 240pin - lifetime warranty
Kingston - lifetime warranty		
ME-K1GD2V6ERP		Kingston ValueRam KVR667D2D8P5/1G ECC Registered with Parity check , 1024mb ddr2-667 , dual rank x8 - 240pin - lifetime warranty
ME-K1GD2V8ERP	N	Kingston ValueRam KVR800D2D8P5/1G ECC Registered with Parity check , 1024mb ddr2-800 , dual rank x8 - 240pin - lifetime warranty
ME-K2GD2V6ERP	R	Kingston ValueRam KVR667D2D8P5/2G ECC Registered with Parity check , 2048mb ddr2-667 , dual rank x8 - 240pin - lifetime warranty
ME-K2GD2V8ERP	N	Kingston ValueRam KVR800D2D8P6/2G ECC Registered with Parity check , 2048mb ddr2-800 , dual rank x8 - 240pin - lifetime warranty
ME-K4GD2V6ERP	R	Kingston ValueRam KVR667D2D4P5/4G ECC Registered with Parity check , 4096mb ddr2-667 , dual rank x4 - 240pin - lifetime warranty

ME-K4GD2V8ERP	R	Kingston ValueRam KVR800D2D4P6/4G ECC Registered with Parity check , 4096mb ddr2-800 , dual rank x4 - 240pin - lifetime warranty
ME-K8GD2V6ERP	R	Kingston ValueRam KVR667D2D4P5/8G ECC Registered with Parity check , 8Gb/4096mb ddr2-667 , dual rank x4 - 240pin - lifetime warranty
240pin DDR3		
DDR3 non-ecc		
A-grade - 5 years warranty		
ME-1GD31066		1Gb/1024mb ddr3-1066 (PC3-8500) - 240pin - 5 years warranty
ME-1GD31333		1Gb/1024mb ddr3-1333 (PC3-10600) , CL9 - 240pin - 5 years warranty
ME-2GD31333		2Gb/2048mb ddr3-1333 (PC3-10600) , CL9 - 240pin - 5 years warranty
Corsair - lifetime warranty		
ME-C1G3X13X9x2		Corsair TWIN3X2048-1333C9 G , XMS 3 , with heatsink , 2 x 1Gb/1024mb kit , ddr3-1333 (PC3-10600) , CL9 , 1.6v - 240pin - lifetime warranty
ME-C1G3X13X9x3		Corsair TR3X3G1333C9 G , XMS 3 , with heatsink , 3 x 1Gb/1024mb kit - support Intel XMP (eXtreme Memory Profiles) , ddr3-1333 (PC3-10600) , CL9 , 1.5v - 240pin - lifetime warranty
ME-C1G3X13D9x2		Corsair TWIN3X2048-1333C9DHX G , XMS 3 , with DHX technology , 2 x 1Gb/1024mb kit , ddr3-1333 (PC3-10600) , CL9 , 1.5v - 240pin - lifetime warranty
ME-C1G3X16X9x3		Corsair TR3X3G1600C9 , XMS 3 , with heatsink , 3 x 1Gb/1024mb kit - support Intel XMP (eXtreme Memory Profiles) , ddr3-1600 (PC3-12800) , CL9 , 1.65v - 240pin - lifetime warranty
ME-C1G3X16D9x2		Corsair TW3X2G1600C9DHX , XMS3 , with DHX technology , 2 x 1Gb/1024mb kit , ddr3-1600 (PC3-12800) , CL9 , 1.8v - 240pin - lifetime warranty
ME-C1G3X16D9x2N		Corsair TW3X2G1600C9DHXNV , XMS3 , with DHX technology - support Nvidia SLi certrified with EPP2.0 , designed for nForce 790 Sli , 2 x 1Gb/1024mb kit , ddr3-1600 (PC3-12800) , CL9 , 1.8v - 240pin - lifetime warranty
ME-C1G3D16D8x3		Corsair TR3X3G1600C8D , Dominator with DHX technology , 3 x 1Gb/1024mb kit - support Intel XMP (eXtreme Memory Profiles) , ddr3-1600 (PC3-12800) , CL8 , 1.65v - 240pin - lifetime warranty
ME-C1G3X16D7x2		Corsair TWIN3X2048-1600C7DHX G , XMS 3 , with DHX technology , 2 x 1Gb/1024mb kit , ddr3-1600 (PC3-12800) , CL7 , 1.8v - 240pin - lifetime warranty
ME-C1G3D18F9x3		Corsair TR3X3G1866C9DF , Dominator , with DHX technology + airflow Fan , 3 x 1Gb/1024mb kit - support Intel XMP (eXtreme Memory Profiles) , ddr3-1866 (pc3-14400) , CL9 , 1.65v - 240pin - lifetime warranty
ME-C1G3D18F7x2		Corsair TWIN3X2048-1800C7DF G , Dominator , with DHX technology + airflow Fan , 2 x 1Gb/1024mb kit , ddr3-1800 (pc3-14400) , CL7 , 2.0v - 240pin - lifetime warranty
ME-C1G3D18F7x2i		Corsair TWIN3X2048-1800C7DFin G , Dominator , with DHX technology + airflow Fan - support Intel XMP (eXtreme Memory Profiles) , 2 x 1Gb/1024mb kit , ddr3-1800 (pc3-14400) , CL7 , 2.0v - 240pin - lifetime warranty
ME-C1G3D20F9x2N		Corsair TW3X2G2000C9DFNV , Dominator , with DHX technology + airflow Fan - support Nvidia SLi certrified with EPP2.0 , designed for nForce 790 Sli , 2 x 1Gb/1024mb kit , ddr3-2000 (pc3-16000) , CL9 , 2.0v - 240pin - lifetime warranty

ME-C2G3X13X9x2		Corsair TW3X4G1333C9 , XMS 3 , with heatsink , 2 x 2Gb/2048mb kit , ddr3-1333 (PC3-10600) , CL9 , 1.6v - 240pin - lifetime warranty
ME-C2G3X13X9x3		Corsair TR3X6G1333C9 , XMS 3 , with heatsink , 3 x 2Gb/2048mb kit - support Intel XMP (eXtreme Memory Profiles) , ddr3-1333 (PC3-10600) , CL9 , 1.5v - 240pin - lifetime warranty
ME-C2G3X13D9x2		Corsair TW3X4G1333C9DHX G , XMS 3 , with DHX technology , 2 x 2Gb/2048mb kit , ddr3-1333 (PC3-10600) , CL9 , 1.5v - 240pin - lifetime warranty
ME-C2G3X16D9x2		Corsair TW3X4G1600C9DHX , XMS3 , with DHX technology , 2 x 2Gb/2048mb kit , ddr3-1600 (PC3-12800) , CL9 , 1.8v - 240pin - lifetime warranty
ME-C2G3X16X9x3		Corsair TR3X6G1600C9 , XMS 3 , with heatsink , 3 x 2Gb/2048mb kit - support Intel XMP (eXtreme Memory Profiles) , ddr3-1600 (PC3-12800) , CL9 , 1.65v - 240pin - lifetime warranty
ME-C2G3D16D8x3		Corsair TR3X6G1600C8D , Dominator with DHX technology , 3 x 2Gb/2048mb kit - support Intel XMP (eXtreme Memory Profiles) , ddr3-1600 (PC3-12800) , CL8 , 1.65v - 240pin - lifetime warranty
ME-C2G3X16D7x2		Corsair TWIN3X4096-1600C7DHX G , XMS3 , with DHX technology , 2 x 2Gb/2048mb kit , ddr3-1600 (PC3-12800) , CL7 , 1.9v - 240pin - lifetime warranty
ME-C2G3X16D7x2i		Corsair TWIN3X4096-1600C7DHXiN G , XMS3 , with DHX technology - support Intel XMP (eXtreme Memory Profiles) , 2 x 2Gb/2048mb kit , ddr3-1600 (PC3-12800) , CL7 , 1.9v - 240pin - lifetime warranty
ME-C2G3D18F8x2		Corsair TW3X4G1800C8DF , Dominator , with DHX technology + airflow Fan , 2 x 2Gb/2048mb kit , ddr3-1800 (pc3-14400) , CL8 , 2.0v - 240pin - lifetime warranty
ME-C2G3D18F9x3		Corsair TR3X6G1866C9DF , Dominator , with DHX technology + airflow Fan , 3 x 2Gb/2048mb kit - support Intel XMP (eXtreme Memory Profiles) , ddr3-1866 (pc3-14400) , CL9 , 1.65v - 240pin - lifetime warranty
ME-C2G3D20F9x2		Corsair TW3X4G2000C9DF , Dominator , with DHX technology + airflow Fan , 2 x 2Gb/2048mb kit , ddr3-2000 (pc3-16000) , CL9 , 2.0v - 240pin - lifetime warranty
Kingston - lifetime warranty		
ME-K512D3V10		Kingston ValueRam KVR1066D3N7/512 512mb ddr3-1066 , CL7 , 1.5v - 240pin - lifetime warranty
ME-K1GD3V13		Kingston ValueRam KVR1333D3N9/1G , 1Gb/1024mb ddr3-1333 , CL9 , 1.5v - 240pin - lifetime warranty
ME-K1GD3V13x2		Kingston ValueRam KVR1333D3N9K2/2G 2x 1Gb/1024mb kit , ddr3-1333 , CL9 , 1.5v - 240pin - lifetime warranty
ME-K1GD3V13x3		Kingston ValueRam KVR1333D3N9K3/3G 3x 1Gb/1024mb kit , ddr3-1333 , CL9 , 1.5v - 240pin - lifetime warranty
ME-K1GD3X13		Kingston Hyper-X KHX11000D3LL/1G , 1Gb/1024mb ddr3-1375 , CL7 , 1.7v - 240pin - lifetime warranty
ME-K1GD3X13x2		Kingston Hyper-X KHX11000D3LLK2/2GX , 2x 1Gb/1024mb kit - support Intel XMP (eXtreme Memory Profiles) , ddr3-1375 , CL7 , 1.65v - 240pin - lifetime warranty
ME-K1GD3X13x3	N	Kingston Hyper-X KHX11000D3LLK3/3GX , 3x 1Gb/1024mb kit - support Intel XMP (eXtreme Memory Profiles) , ddr3-1375 , CL7 , 1.65v - 240pin - lifetime warranty
ME-K1GD3X16		Kingston Hyper-X KHX13000D3LL/1G , 1Gb/1024mb ddr3-1625 , CL7 , 1.9v - 240pin - lifetime warranty
ME-K1GD3X16x2		Kingston Hyper-X KHX13000D3LLK2/2G , 2x 1Gb/1024mb kit , ddr3-1625 , CL7 , 1.9v - 240pin - lifetime warranty

ME-K1GD3X16x3	N	Kingston Hyper-X KHX12800D3LLK3/3GX , 3x1Gb/1024mb kit - support Intel XMP (eXtreme Memory Profiles) , ddr3-1600, CL8 , 1.65v - 240pin - lifetime warranty
ME-K1GD3X18	R	Kingston Hyper-X KHX14400D3/1G , 1Gb/1024mb ddr3-1800 , CL8 , 1.9v - 240pin - lifetime warranty
ME-K1GD3X18x2		Kingston Hyper-X KHX14400D3K2/2GX , 2x 1Gb/1024mb kit , ddr3-1800 , CL8 , 1.9v - 240pin - lifetime warranty
ME-K1GD3X18Tx2		Kingston Hyper-X KHX14400D3T1K2/2G , with Tall HeatSink , 2x 1Gb/1024mb kit , ddr3-1800 , CL8 , 1.9v - 240pin - lifetime warranty
ME-K1GD3X18x3	N	Kingston Hyper-X KHX14400D3K3/3GX , 3x 1Gb/1024mb kit , ddr3-1800 , CL9 , 1.65v - 240pin - lifetime warranty
ME-K1GD3X18Tx3	N	Kingston Hyper-X KHX14400D3T1K3/3GX , with Tall HeatSink , 3x 1Gb/1024mb kit , ddr3-1800 , CL9 , 1.65v - 240pin - lifetime warranty
ME-K1GD3X20x2	N	Kingston Hyper-X KHX16000D3K2/2GN , 2x 1Gb/1024mb kit , support Nvidia SLi certrified with EPP2.0 , ddr3-2000 , CL9 , 1.65v - 240pin - lifetime warranty
ME-K1GD3X20Tx2	C	Kingston Hyper-X KHX16000D3T1K2/2GN , with Tall HeatSink , 2x 1Gb/1024mb kit , support Nvidia SLi certrified with EPP2.0 , ddr3-2000 , CL9 , 2.0v - 240pin - lifetime warranty
ME-K1GD3X20x3	N	Kingston Hyper-X KHX16000D3K3/3GX , 3x 1Gb/1024mb kit , ddr3-2000 , CL9 , 1.65v - 240pin - lifetime warranty
ME-K1GD3X20Tx3	C	Kingston Hyper-X KHX16000D3T1K3/3GX , with Tall HeatSink , 2x 1Gb/1024mb kit , ddr3-2000 , CL9 , 1.65v - 240pin - lifetime warranty
ME-K2GD3V10x3		Kingston ValueRam KVR1066D3N7K3/6G , 3x 2Gb/2048mb kit ddr3-1066 , CL7 , 1.5v - 240pin - lifetime warranty
ME-K2GD3V13		Kingston ValueRam KVR1333D3N9/2G , 2Gb/2048mb ddr3-1333 , CL9 , 1.5v - 240pin - lifetime warranty
ME-K2GD3V13x2		Kingston ValueRam KVR1333D3N9K2/4G , 2x 2Gb/2048mb kit , ddr3-1333 , CL9 , 1.5v - 240pin - lifetime warranty
ME-K2GD3V13x3	N	Kingston ValueRam KVR1333D3N9K3/6G 3x 2Gb/2048mb kit , ddr3-1333 , CL9 , 1.5v - 240pin - lifetime warranty
ME-K2GD3X13x2	N	Kingston Hyper-X KHX11000D3K2/4G , 2x 2Gb/2048mb kit , ddr3-1375 , CL9 , 1.6v - 240pin - lifetime warranty
ME-K2GD3X13L	R	Kingston Hyper-X KHX11000D3LL/2G , 2Gb/2048mb ddr3-1375 , CL7 , 1.7v - 240pin - lifetime warranty
ME-K2GD3X13Lx2	N	Kingston Hyper-X KHX11000D3LLK2/4G , 2x 2Gb/2048mb kit , ddr3-1375 , CL7 , 1.7v - 240pin - lifetime warranty
ME-K2GD3X16	R	Kingston Hyper-X KHX12800D3/2G , 2Gb/2048mb ddr3-1600 , CL9 , 1.9v - 240pin - lifetime warranty
ME-K2GD3X16x2	C	Kingston Hyper-X KHX12800D3K2/4G , 2x 2Gb/2048mb kit ddr3-1600 , CL9 , 1.9v - 240pin - lifetime warranty
ME-K2GD3X16Lx3	R	Kingston Hyper-X KHX12800D3LLK3/6GX , 3x 2Gb/2048mb kit - support Intel XMP (eXtreme Memory Profiles) , ddr3-1600 , CL8 , 1.65v - 240pin - lifetime warranty
ME-K2GD3X18	R	Kingston Hyper-X KHX14400D3/2G , 2Gb/2048mb ddr3-1600 , CL8 , 1.9v - 240pin - lifetime warranty
ME-K2GD3X18x2	R	Kingston Hyper-X KHX14400D3K2/4G , 2x 2Gb/2048mb kit , ddr3-1600 , CL8 , 1.9v - 240pin - lifetime warranty
ME-K2GD3X20LTx3	R	Kingston Hyper-X KHX16000D3ULT1K3/6GX , with Tall HeatSink , 2x 2Gb/2048mb kit , ddr3-2000 , CL8 , 1.65v - 240pin - lifetime warranty

168pin SDRAM

Kingston - lifetime warranty

ME-K256S133	Kingston KVR133X64C2/256 256mb pc133 sdram - 168pin - lifetime warranty

ME-K512S133		Kingston KVR133X64C2/512 512mb pc133 sdram - 168pin - lifetime warranty

Memory - So-dimm / micro-dimm

200pin DDR SO-Dimm

A-grade - 5 years warranty

ME-512D400N		512mb so-dimm , 200 pin - DDR-400 , CL3 , 1.8v - 5 years warranty - retail pack
ME-1GD400N		1Gb/1024mb so-dimm , 200 pin - DDR-400 , CL3 , 1.8v - 5 years warranty - retail pack

Corsair for Notebook - lifetime warranty

ME-CN512D4		Corsair VS512SDS400 valueselect , 512mb so-dimm , 200 pin - DDR-400 , CL3 , 1.8v - lifetime warranty
ME-CN1GD4		Corsair VS1GSDS400 valueselect , 1G/1024mb so-dimm , 200 pin - DDR-400 , CL3 , 1.8v - lifetime warranty

Kingston - lifetime warranty

ME-KN256D400		kingston KVR400X64SC3A/256 256mb so-dimm , 200 pin - ddr400 , pc3200 - lifetime warranty
ME-KN512D400		kingston KVR400X64SC3A/512 512mb so-dimm , 200 pin - ddr400 , pc3200 , 3-3-3 - lifetime warranty
ME-KN1GD400		kingston KVR400X64SC3A/1G 1024mb so-dimm , 200 pin - ddr400 , pc3200 , 3-3-3 - lifetime warranty

200pin DDR2 SO-Dimm - for notebook / apple pc

A-grade - 5 years warranty

ME-512D2667N		512mb so-dimm , 200 pin - DDR2-667 , CL5 , 1.8v - 5 years warranty - retail pack
ME-1GD2667N		1Gb/1024mb so-dimm , 200 pin - DDR2-667 , CL5 , 1.8v - 5 years warranty - retail pack
ME-1GD2800N	N	1Gb/1024mb so-dimm , 200 pin - DDR2-800 , CL5 , 1.8v - 5 years warranty - retail pack
ME-2GD2667N		2Gb/2048mb so-dimm , 200 pin - DDR2-667 , CL5 , 1.8v - 5 years warranty - retail pack
ME-2GD2800N	N	2Gb/2048mb so-dimm , 200 pin - DDR2-800 , CL5 , 1.8v - 5 years warranty - retail pack

Corsair for Notebook - lifetime warranty

ME-CN512D26		Corsair VS512SDS667D2 valueselect , 512mb so-dimm , 200 pin - DDR2-667 , CL5 , 1.8v - lifetime warranty
ME-CN1GD26		Corsair VS1GSDS667D2 valueselect , 1Gb/1024mb so-dimm , 200 pin - DDR2-667 , CL5 , 1.8v - lifetime warranty
ME-CN2GD26		Corsair VS2GSDS667D2 valueselect , 2Gb/2048mb so-dimm , 200 pin - DDR2-667 , CL5 , 1.8v - lifetime warranty
ME-CN2GD26A		Corsair VSA2GSDS667D2 valueselect , for pc / notebook / Apple MacBook , 2Gb/2048mb so-dimm , 200 pin - DDR2-667 , CL5 , 1.8v - lifetime warranty
ME-CN2GD26Ax2	N	Corsair VSA4GSDSKIT667 valueselect , for pc / notebook / Apple MacBook , 2x2Gb/2048mb kit so-dimm , 200 pin - DDR2-667 , CL5 , 1.8v - lifetime warranty
ME-CN2GD28	N	Corsair CGM2X2GS800 , 2Gb/2048mb so-dimm , 200 pin - DDR2-800 , CL5 , 1.8v - lifetime warranty
ME-CN2GD28x2	N	Corsair VS4GSDSKIT800D2 valueselect , 2x 2Gb/2048mb kit , so-dimm , 200 pin - DDR2-800 , CL5 , 1.8v - lifetime warranty
ME-CN2GD210A	N	Corsair VSA2GSDS1066 valueselect , for pc / notebook / Apple MacBook , 2Gb/2048mb so-dimm , 200 pin - DDR2-1066 , CL5 , 1.8v - lifetime warranty
ME-CN2GD210Ax2	N	Corsair VSA4GSDSKIT1066 valueselect , for pc / notebook / Apple MacBook , 2x2Gb/2048mb kit so-dimm , 200 pin - DDR2-1066 , CL5 , 1.8v - lifetime warranty
ME-CA4GD26	N	Corsair VSA4GSDS667D2 valueselect , for pc / notebook / Apple MacBook , 4Gb/4096mb so-dimm , 200 pin - DDR2-667 , CL5 , 1.8v - lifetime warranty

Kingston - lifetime warranty		
ME-KN256D2533		kingston KVR533D2S4/256 256mb so-dimm , 200 pin - DDR2-533 , CL4 , 1.8v - lifetime warranty
ME-KN256D2667		kingston KVR667D2S5/256 256mb so-dimm , 200 pin - DDR2-667 , CL5 , 1.8v - lifetime warranty
ME-KN512D2533		kingston KVR533D2S4/512 512mb so-dimm , 200 pin - DDR2-533 , CL4 , 1.8v - lifetime warranty
ME-KN512D2667		kingston KVR667D2S5/512 512mb so-dimm , 200 pin - DDR2-667 , CL5 , 1.8v - lifetime warranty
ME-KN1GD2533		kingston KVR533D2S4/1G 1024mb so-dimm , 200 pin - DDR2-533 , CL4 , 1.8v - lifetime warranty
ME-KN1GD2667		kingston KVR667D2S5/1G 1024mb so-dimm , 200 pin - DDR2-667 , CL5 , 1.8v - lifetime warranty
ME-KN1GD26XLx2	N	kingston KHX5300S2LLK2/2G - hyperX , Low-latency CL4 - 2x 1Gb/1024mb kit so-dimm , 200 pin - DDR2-667 , 1.8v - lifetime warranty
ME-KN1GD28		kingston KVR800D2S5/1G 1024mb so-dimm , 200 pin - DDR2-800 , CL5 , 1.8v - lifetime warranty
ME-KN2GD2667		kingston KVR667D2S5/2G 2048mb so-dimm , 200 pin - DDR2-667 , CL5 , 1.8v - lifetime warranty
ME-KN2GD26XLx2	N	kingston KHX5300S2LLK2/4G - hyperX , Low-latency CL4 - 2x 2Gb/2048mb kit so-dimm , 200 pin - DDR2-667 , 1.8v - lifetime warranty
ME-KN2GD28	N	kingston KVR800D2S5/2G 2048mb so-dimm , 200 pin - DDR2-800 , CL5 , 1.8v - lifetime warranty
ME-KN2GD28XLx2	N	kingston KHX6400S2ULK2/4G - hyperX , Low-latency CL4 - 2x 2Gb/2048mb kit so-dimm , 200 pin - DDR2-800 , 1.8v - lifetime warranty
ME-KN4GD2667	R	kingston KVR667D2S5/4G 4Gb/4096mb so-dimm , 200 pin - DDR2-667 , CL5 , 1.8v - lifetime warranty
ME-KN4GD28	R	kingston KVR800D2S6/4G 4Gb/4096mb so-dimm , 200 pin - DDR2-800 , CL5 , 1.8v - lifetime warranty
204pin DDR3 SO-Dimm		
corsair - lifetime warranty		
ME-CN2GD31066	N	Corsair CM3X2GSD1066 valueselect , 2Gb/2048mb so-dimm , 204 pin - DDR3-1066 - lifetime warranty
Kingston - lifetime warranty		
ME-KN1GD31066	N	Kingston KVR1066D3S7/1G valueselect , 1Gb/1024mb so-dimm , 204 pin - DDR3-1066 , CL7 , 1.5v - lifetime warranty
ME-KN2GD31066	N	Kingston KVR1066D3S7/2G valueselect , 2Gb/2048mb so-dimm , 204 pin - DDR3-1066 , CL7 , 1.5v - lifetime warranty
144pin Sdram SO-Dimm		
Kingston - lifetime warranty		
ME-KN256S133		kingston KVR133X64SC3L/256 256mb so-dimm , 144 pin - pc133 , low-profile - lifetime warranty
ME-KN512S133		kingston KVR133X64SC3L/512 512mb so-dimm , 144 pin - pc133 , low-profile - lifetime warranty
Flash Drive - usb		
accessories		
CA-U3E		3m usb 2.0 extension cable (type A male - type A female) - 1 port - ideal for wireless network USB adapter or other USB device
CA-U5E		5m usb 2.0 extension cable (type A male - type A female) - 1 port - ideal for wireless network USB adapter or other USB device
CA-U5E2		Sunix UEC2200 5m usb 2.0 extension cable (type A male - type A female) , NEC UPD720110 chipset - 2 port , retail pack - ideal for wireless network USB adapter or other USB device
oem		

FD-2G		2Gb usb2.0 flash drive , with write protection , with neck strap - 2 years warranty
FD-4G		4Gb usb2.0 flash drive , with write protection , with neck strap - 2 years warranty
FD-8G		8Gb usb2.0 flash drive , with write protection , with neck strap - 2 years warranty
FD-L8G		Legend 8Gb usb2.0 flash drive with key chain - 2 yeard warranty
Pc winner		
FD-P8GFP	N	pc-winner Fingerprint Reader + 8Gb flash drive with retractable USB connector , sliding sensor, with lanyard - 1 year warranty
Corsair		
FD-C4GV		Corsair Voyager , 4Gb flash drive , support readyboost , durable + water resistant , include True Crypt security application for AES-256 encryption , 19mb/sec , 75x23x13mm , with lanyard + usb extension cable - 10 years warranty
FD-C4GVM	N	Corsair Voyager Mini , 4Gb flash drive , retractable USB connector , support readyboost , durable + water resistant , include True Crypt security application for AES-256 encryption , 19mb/sec , 36x20x9mm - 10 years warranty
FD-C4GP	N	Corsair Padlock , 4Gb flash drive , with hardware-secured lock (with customizable digit PIN combination lock) , support readyboost , durable + water resistant , include True Crypt security application for AES-256 encryption , 19mb/sec , with lanyard + usb extension cable - 10 years warranty
FD-C8GV		Corsair Voyager , 8Gb flash drive , support readyboost , durable + water resistant , include True Crypt security application for AES-256 encryption , 19mb/sec , 75x23x13mm , with lanyard + usb extension cable - 10 years warranty
FD-C8GVM	N	Corsair Voyager Mini , 8Gb flash drive , retractable USB connector , support readyboost , durable + water resistant , include True Crypt security application for AES-256 encryption , 19mb/sec , 36x20x9mm - 10 years warranty
FD-C8GS		Corsair Survivor , 8Gb flash drive , support readyboost , strong CNC-milled, anodized aircraft-grade aluminum , EPDM waterproof seal , include True Crypt security application for AES-256 encryption , 19mb/sec , with dog tag + usb extension cable - 10 years warranty
FD-C16GV		Corsair Voyager , 16Gb flash drive , support readyboost , durable + water resistant , include True Crypt security application for AES-256 encryption , 19mb/sec , 75x23x13mm , with lanyard + usb extension cable - 10 years warranty
FD-C16GVGT	N	Corsair Voyager GT , 16Gb flash drive , support readyboost , durable + water resistant , include True Crypt security application for AES-256 encryption , 34mb/sec , 75x23x13mm , with lanyard + usb extension cable - 10 years warranty
FD-C16GS	N	Corsair Survivor , 16Gb flash drive , support readyboost , strong CNC-milled, anodized aircraft-grade aluminum , EPDM waterproof seal , include True Crypt security application for AES-256 encryption , 19mb/sec , with dog tag + usb extension cable - 10 years warranty
FD-C32GV		Corsair Voyager , 32Gb flash drive , support readyboost , durable + water resistant , include True Crypt security application for AES-256 encryption , 19mb/sec , 75x23x13mm , with lanyard + usb extension cable - 10 years warranty
FD-C32GS	N	Corsair Survivor , 32Gb flash drive , support readyboost , strong CNC-milled, anodized aircraft-grade aluminum , EPDM waterproof seal , include True Crypt security application for AES-256 encryption , 19mb/sec , with dog tag + usb extension cable - 10 years warranty

FD-C64GV	N	Corsair Voyager , 64Gb flash drive , support readyboost , durable + water resistant , include True Crypt security application for AES-256 encryption , 19mb/sec , 75x23x13mm , with lanyard + usb extension cable - 10 years warranty
Kingston		http://www.kingston.com/flash/datatraveler_home.asp
FD-K1G		kingston DTi/1GB datatraveler , 1Gb flash drive , 6mb/sec , 72.7x24x10mm - 5 years warranty
FD-K1G110		kingston DT110P/1GB Datatraveler 110 , 1Gb flash drive , Purple , retractable USB connector , 54.4x21.24x13mm , support Linux , Mac OS - 5 years warranty
FD-K1GMF		kingston DTMFY/1GB Mini Fun Yellow , 1gb/1024mb , stackable mini flash drive with 2 pre-loaded games , 38x19x8mm - 5 years warranty
FD-K1GCR		kingston DTCR/1G Datatraveler , 1Gb/1024mb flash drive with built-in SD/SDHC/MMC card reader , 11mb/sec , 67.7x20.8x9mm - 5 years warranty
FD-K1GCRSDC		kingston FCR-MRB+SDC/1GB , Black , 32.89x15.3x7.66mm miCro-SD card reader + 1024mb miCro-sd , 13mb/sec - 2 years warranty
FD-K1GR		kingston DTR/1Gb datatraveler Readyflash , support windows Vista Readyboost (adjustable size can added as system memory) , 1024mb flash drive , 5mb/sec , 67.7x20.8x9mm - 5 years warranty
FD-K1G2P		kingston DTii+M/1GB datatraveler2 Plus Migo Edition , 1024mb flash drive , 19mb/sec , 67.7x20.8x9mm , with password protection , to work on multiple PCs in different locations, using your own desktop's Microsoft Outlook®* email contents, Explorer settings , favorites, cookies and history, plus your files, folders and icons. - 5 years warranty
FD-K1GDTCRC		kingston DTCRC/1GB , Black - sony M2 + miCro-SDHC card reader + 1Gb/1024mb miCro-sd , 64x19.8x10.4mm , 6/3 mb/sec - 5 years warranty
FD-K2G		kingston DTi/2GB datatraveler , 2Gb flash drive , 6mb/sec , 72.7x24x10mm - 5 years warranty
FD-K2G100		kingston DT100/2G , datatraveler 100 , 2Gb flash drive , retractable USB connector , 59.7x22.3x9.5mm , support Linux , Mac OS - 5 years warranty
FD-K2GG2	N	kingston DTiG2/2G , datatraveler G2 , 2Gb flash drive , retractable USB connector , 58.3x23.6x9mm , support Linux , Mac OS - 5 years warranty
FD-K2GMSK		kingston DTMS/2GB datatraveler Mini Slim , blacK , 2Gb flash drive , 6mb/sec , ultra compact 38.85x16.4x6.44mm - 2 years warranty
FD-K2GMSB		kingston DTMSB/2GB datatraveler Mini Slim , Blue , 2Gb flash drive , 6mb/sec , ultra compact 38.85x16.4x6.44mm - 2 years warranty
FD-K2GMSP		kingston DTMSN/2GB datatraveler Mini Slim , Pink , 2Gb flash drive , 6mb/sec , ultra compact 38.85x16.4x6.44mm - 2 years warranty
FD-K2G101C		kingston DT101C/2GB Datatraveler 101 , 2Gb flash drive , Cyan , capless swivel USB connector , 55.6x17.3x9.05mm - with password protected privacy zone (2 partitions) , support Linux , Mac OS - 5 years warranty
FD-K2G101P		kingston DT101N/2GB Datatraveler 101 , 2Gb flash drive , Pink , capless swivel USB connector , 55.6x17.3x9.05mm - with password protected privacy zone (2 partitions) , support Linux , Mac OS - 5 years warranty

FD-K2G101Y		kingston DT101Y/2GB Datatraveler 101 , 2Gb flash drive , Yellow , capless swivel USB connector , 55.6x17.3x9.05mm - with password protected privacy zone (2 partitions) , support Linux , Mac OS - 5 years warranty
FD-K2G110		kingston DT110B/2GB Datatraveler 110 , 2Gb flash drive , Blue , retractable USB connector , 54.4x21.24x13mm , support Linux , Mac OS - 5 years warranty
FD-K2GR		kingston DTR/2Gb datatraveler Readyflash , Pink , support windows Vista Readyboost (adjustable size can added as system memory) , 2048mb flash drive , 5mb/sec , 67.7x20.8x9mm - 5 years warranty
FD-K2GCRSDC2A		kingston MBLY//2GB , Red , miCro-SD card reader + 2Gb/2048mb miCro-sd + 2x Adapter (sd and mini-sd) , 32.89x15.3x7.66mm , 13mb/sec - 2 years warranty
FD-K2G400		kingston DT400/2GB Datatraveler 400 , 2Gb flash drive , read: 20mb , write: 10mb/sec , support windows Vista Readyboost (adjustable size can added as system memory) , retractable USB connector ; mingo ready - to work on multiple PCs in different locations, using your own desktop's Microsoft Outlook®* email contents, Explorer settings , favorites, cookies and history, plus your files, folders and icons , 65.4x18x10.4mm , support Linux , Mac OS - 5 years warranty
FD-K2GS		kingston DTS/2GB Datatraveler Secure , support windows Vista Readyboost (adjustable size can added as system memory) , 2048mb , titanium coated stainless steel , waterproof , 24mb/sec , 67.7x20.8x9mm , with password protection + 256bit AES hardware security on privacy zone (2 partitions) , support Linux , Mac OS - 5 years warranty
FD-K2GSP		kingston DTSP/2GB datatraveler Secure Privacy edition , 2Gb flash drive , titanium coated stainless steel , waterproof , 24mb/sec , 67.7x20.8x9mm , with password protection + 256bit AES hardware security on all data - 5 years warranty
FD-K2GBB		kingston DTBB/2GB datatraveler BlackBox edition , FIPS 140-2 Level 2 certified + 256-bit hardware-based AES security on all data , rugged and waterproof Secure Privacy edition , 2Gb flash drive , read/write : 24/20 mb/sec , 78x22x12mm - 5 years warranty
FD-K4G		kingston DTi/4GB datatraveler , 4Gb/4096mb flash drive , 6mb/sec , 72.7x24x10mm - 5 years warranty
FD-K4G100		kingston DT100/4GB Datatraveler 100 , 4Gb/4096mb flash drive , retractable USB connector , 59.7x22.3x9.5mm , support Linux , Mac OS - 5 years warranty
FD-K4GG2	N	kingston DTiG2/4G , datatraveler G2 , 4Gb flash drive , retractable USB connector , 58.3x23.6x9mm , support Linux , Mac OS - 5 years warranty
FD-K4G120	N	kingston DT120/4GB Datatraveler 120 , 4Gb flash drive , Lime green , retractable USB connector , 58.8x23.6x9.5mm , support Linux , Mac OS - 5 years warranty
FD-K4GMSK		kingston DTMS/4GB datatraveler Mini Slim , blacK , 4Gb flash drive , 6mb/sec , ultra compact 38.85x16.4x6.44mm - 2 years warranty
FD-K4GMSB		kingston DTMSB/4GB datatraveler Mini Slim , Blue , 4Gb flash drive , 6mb/sec , ultra compact 38.85x16.4x6.44mm - 2 years warranty
FD-K4GMSP		kingston DTMSN/4GB datatraveler Mini Slim , Pink , 4Gb flash drive , 6mb/sec , ultra compact 38.85x16.4x6.44mm - 2 years warranty

FD-K4G101C		kingston DT101C/4GB Datatraveler 101 , 4Gb flash drive , Cyan , capless swivel USB connector , 55.6x17.3x9.05mm - with password protected privacy zone (2 partitions) , support Linux , Mac OS - 5 years warranty
FD-K4G101P		kingston DT101N/4GB Datatraveler 101 , 4Gb flash drive , Pink , capless swivel USB connector , 55.6x17.3x9.05mm - with password protected privacy zone (2 partitions) , support Linux , Mac OS - 5 years warranty
FD-K4G101Y		kingston DT101Y/4GB Datatraveler 101 , 4Gb flash drive , Yellow , capless swivel USB connector , 55.6x17.3x9.05mm - with password protected privacy zone (2 partitions) , support Linux , Mac OS - 5 years warranty
FD-K4GCRSDC2A		kingston MBLY//4GB , black , miCro-SD card reader + 4Gb/4096mb miCro-sd + 2x Adapter (sd and mini-sd) , 32.89x15.3x7.66mm , 13mb/sec - 2 years warranty
FD-K4G400		kingston DT400/4GB Datatraveler 400 , 4Gb flash drive , read: 20mb , write: 10mb/sec , support windows Vista Readyboost (adjustable size can added as system memory) , retractable USB connector ; mingo ready - to work on multiple PCs in different locations, using your own desktop's Microsoft Outlook®* email contents, Explorer settings , favorites, cookies and history, plus your files, folders and icons , 65.4x18x10.4mm , support Linux , Mac OS - 5 years warranty
FD-K4GDTCRC		kingston DTCRC/4GB , Black - sony M2 + miCro-SDHC card reader + 4Gb/4096mb miCro-sd , 64x19.8x10.4mm , 6/3 mb/sec - 5 years warranty
FD-K4GHX	C	kingston DTHX/4GB datatraveler HyperX , 4Gb flash drive , read/write : 25/16 mb/sec , retractable USB connector , 54.4x21.24x13mm , support Linux , Mac OS - 5 years warranty
FD-K4GSP		kingston DTSP/4GB datatraveler Secure Privacy edition , 4Gb flash drive , titanium coated stainless steel , waterproof , 24mb/sec , 67.7x20.8x9mm , with password protection + 256bit AES hardware security on all data - 5 years warranty
FD-K4GVP	R	kingston DTVP/4GB datatraveler Vault Privacy , 256-bit hardware-based AES security on all data , aluminum and waterproof , 4Gb/4096mb flash drive , read/write : 24/10 mb/sec , 78x22x12mm - 5 years warranty
FD-K4GBB	N	kingston DTBB/4GB datatraveler BlackBox edition , FIPS 140-2 Level 2 certified + 256-bit hardware-based AES security on all data , rugged and waterproof Secure Privacy edition on all data , 4Gb flash drive , read/write : 24/20 mb/sec , 78x22x12mm - 5 years warranty
FD-K8G		kingston DTi/8GB datatraveler , 8Gb flash drive , 6mb/sec , 72.7x24x10mm - 5 years warranty
FD-K8G100		kingston DT100/8GB Datatraveler 100 , 8Gb flash drive , retractable USB connector , 59.7x22.3x9.5mm , support Linux , Mac OS - 5 years warranty
FD-K8GG2	N	kingston DTiG2/8G , datatraveler G2 , 8Gb flash drive , retractable USB connector , 58.3x23.6x9mm , support Linux , Mac OS - 5 years warranty
FD-K8G120	N	kingston DT120/8GB Datatraveler 120 , 8Gb flash drive , Orange , retractable USB connector , 58.8x23.6x9.5mm , support Linux , Mac OS - 5 years warranty
FD-K8GMSK		kingston DTMS/8GB datatraveler Mini Slim , blacK , 8Gb flash drive , 6mb/sec , ultra compact 38.85x16.4x6.44mm - 2 years warranty
FD-K8GMSB		kingston DTMSB/8GB datatraveler Mini Slim , Blue , 8Gb flash drive , 6mb/sec , ultra compact 38.85x16.4x6.44mm - 2 years warranty

FD-K8GMSP		kingston DTMSN/8GB datatraveler Mini Slim , Pink , 8Gb flash drive , 6mb/sec , ultra compact 38.85x16.4x6.44mm - 2 years warranty
FD-K8G101C		kingston DT101C/8GB Datatraveler 101 , 8Gb flash drive , Cyan , capless swivel USB connector , 55.6x17.3x9.05mm - with password protected privacy zone (2 partitions) , support Linux , Mac OS - 5 years warranty
FD-K8G101Y		kingston DT101Y/8GB Datatraveler 101 , 8Gb flash drive , Yellow , capless swivel USB connector , 55.6x17.3x9.05mm - with password protected privacy zone (2 partitions) , support Linux , Mac OS - 5 years warranty
FD-K8GCRSDC2A		kingston MBLY//8GB , black , miCro-SD card reader + 8Gb miCro-sd + 2x Adapter (sd and mini-sd) , 32.89x15.3x7.66mm , 13mb/sec - 2 years warranty
FD-K8G400		kingston DT400/8GB Datatraveler 400 , 8Gb flash drive , read: 20mb , write: 10mb/sec , support windows Vista Readyboost (adjustable size can added as system memory) , retractable USB connector ; mingo ready - to work on multiple PCs in different locations, using your own desktop's Microsoft Outlook®* email contents, Explorer settings , favorites, cookies and history, plus your files, folders and icons , 65.4x18x10.4mm , support Linux , Mac OS - 5 years warranty
FD-K8GHX	C	kingston DTHX2/8GB datatraveler HyperX , 8Gb flash drive , read/write : 25/16 mb/sec , retractable USB connector , 54.4x21.24x13mm , support Linux , Mac OS - 5 years warranty
FD-K8GVP	R	kingston DTVP/8GB datatraveler Vault Privacy , 256-bit hardware-based AES security on all data , aluminum and waterproof , 8Gb flash drive , read/write : 24/10 mb/sec , 78x22x12mm - 5 years warranty
FD-K8GBB	R	kingston DTBB/8GB datatraveler BlackBox edition , FIPS 140-2 Level 2 certified + 256-bit hardware-based AES security on all data , rugged and waterproof Secure Privacy edition on all data , 8Gb flash drive , read/write : 24/20 mb/sec , 78x22x12mm - 5 years warranty
FD-K16G		kingston DTi/16GB datatraveler , 16Gb flash drive , 6mb/sec , 72.7x24x10mm - 5 years warranty
FD-K16G100		kingston DT100/16GB Datatraveler 100 , 16Gb flash drive , retractable USB connector , 59.7x22.3x9.5mm , support Linux , Mac OS - 5 years warranty
FD-K16G120	N	kingston DT120/16GB Datatraveler 120 , 16Gb flash drive , Light blue , retractable USB connector , 58.8x23.6x9.5mm , support Linux , Mac OS - 5 years warranty
FD-K16GG2	N	kingston DTiG2/16G , datatraveler G2 , 16Gb flash drive , retractable USB connector , 58.3x23.6x9mm , support Linux , Mac OS - 5 years warranty
FD-K16GMSK	N	kingston DTMS/16GB datatraveler Mini Slim , blacK , 16Gb flash drive , 6mb/sec , ultra compact 38.85x16.4x6.44mm - 2 years warranty
FD-K16G400		kingston DT400/16GB Datatraveler 400 , 16Gb flash drive , read: 20mb , write: 10mb/sec , support windows Vista Readyboost (adjustable size can added as system memory) , retractable USB connector ; mingo ready - to work on multiple PCs in different locations, using your own desktop's Microsoft Outlook®* email contents, Explorer settings , favorites, cookies and history, plus your files, folders and icons , 65.4x18x10.4mm , support Linux , Mac OS - 5 years warranty
FD-K16GHX	C	kingston DTHX2/16GB datatraveler HyperX , 16Gb flash drive , read/write : 25/16 mb/sec , retractable USB connector , 54.4x21.24x13mm , support Linux , Mac OS - 5 years warranty

FD-K16GVP	R	kingston DTVP/16GB datatraveler Vault Privacy , 256-bit hardware-based AES security on all data , aluminum and waterproof , 16Gb flash drive , read/write : 24/10 mb/sec , 78x22x12mm - 5 years warranty
FD-K32G120	N	kingston DT120/32GB Datatraveler 120 , 32Gb flash drive , Gray , retractable USB connector , 58.8x23.6x9.5mm , support Linux , Mac OS - 5 years warranty
FD-K32G150	N	kingston DT150/32GB Datatraveler 150 , 32Gb flash drive , orange , 77.9x22x12.05 mm , support Linux , Mac OS - 5 years warranty
FD-K32GG2	C	kingston DTiG2/32G , datatraveler G2 , 32Gb flash drive , retractable USB connector , 58.3x23.6x9mm , support Linux , Mac OS - 5 years warranty
FD-K32G400	R	kingston DT400/32GB Datatraveler 400 , 32Gb flash drive , read: 20mb , write: 10mb/sec , support windows Vista Readyboost (adjustable size can added as system memory) , retractable USB connector ; mingo ready - to work on multiple PCs in different locations, using your own desktop's Microsoft Outlook®* email contents, Explorer settings , favorites, cookies and history, plus your files, folders and icons , 65.4x18x10.4mm , support Linux , Mac OS - 5 years warranty
FD-K32GHX	C	kingston DTHX2/32GB datatraveler HyperX , 32Gb flash drive , read/write : 25/16 mb/sec , retractable USB connector , 54.4x21.24x13mm , support Linux , Mac OS - 5 years warranty
FD-K32GVP	R	kingston DTVP/32GB datatraveler Vault Privacy , 256-bit hardware-based AES security on all data , aluminum and waterproof , 32Gb flash drive , read/write : 24/10 mb/sec , 78x22x12mm - 5 years warranty
FD-K64G150		kingston DT150/64GB Datatraveler 150 , 64Gb flash drive , orange , 77.9x22x12.05 mm , support Linux , Mac OS - 5 years warranty

Flash memory

SD - 32x24x2.1mm

SD-1GK		Kingston 1Gb Secure Digital , with SDMI , read/write : 5/1.5 mb/sec - lifetime warranty , retail pack
SD-2GK		Kingston 2Gb Secure Digital , with SDMI , read/write : 5/2.2 mb/sec -lifetime warranty , retail pack
SD-4GK4		Kingston SD4/4Gb SDHC (Secure Digital High Capacity) class4 , with SDMI , transfer rate : 4 mb/sec -lifetime warranty , retail pack
SD-4GK6		Kingston SD6/4Gb SDHC (Secure Digital High Capacity) class6 , with SDMI , transfer rate : 6 mb/sec -lifetime warranty , retail pack
SD-4GKV	N	Kingston SDV/4Gb (60min) SDHC (Video Secure Digital High Capacity) class4 , with SDMI , transfer rate : 4 mb/sec -lifetime warranty , retail pack
SD-8GK2		Kingston SD2/8Gb SDHC (Secure Digital High Capacity) class2 , with SDMI , transfer rate : 2 mb/sec -lifetime warranty , retail pack
SD-8GK4		Kingston SD4/8Gb SDHC (Secure Digital High Capacity) class4 , with SDMI , transfer rate : 4 mb/sec -lifetime warranty , retail pack
SD-8GK6		Kingston SD6/8Gb SDHC (Secure Digital High Capacity) class6 , with SDMI , transfer rate : 6 mb/sec -lifetime warranty , retail pack
SD-8GKV	N	Kingston SDV/8Gb (120min) SDHC (Video Secure Digital High Capacity) class4 , with SDMI , transfer rate : 4 mb/sec -lifetime warranty , retail pack

SD-16GK4		Kingston SD4/16Gb SDHC (Secure Digital High Capacity) class4 , with SDMI , transfer rate : 4 mb/sec -lifetime warranty , retail pack
SD-16GKV	N	Kingston SDV/16Gb (240MIN) SDHC (Video Secure Digital High Capacity) class4 , with SDMI , transfer rate : 4 mb/sec -lifetime warranty , retail pack
SD-32GK4	N	Kingston SD4/32Gb SDHC (Secure Digital High Capacity) class4 , with SDMI , transfer rate : 4 mb/sec -lifetime warranty , retail pack
Mini sd (mini Secure Digital) - 21.5x20x1.4mm		
SD-128TM		Tatu 128mb Mini SD with SD adapter , also work as SD , MMC ; 21.5x20x1.4mm - lifetime warranty , retail pack
SD-256TM		Tatu 256mb Mini SD with SD adapter , also work as SD , MMC ; 21.5x20x1.4mm - lifetime warranty , retail pack
Micro sd (micro Secure Digital / T-Flash / Trend-flash) - 15x11x1mm		
FD-K1GCRSDC		kingston FCR-MRB+SDC/1GB , Black , 32.89x15.3x7.66mm miCro-SD card reader + 1024mb miCro-sd , 13mb/sec - 2 years warranty
FD-K1GDTCRC		kingston DTCRC/1GB , Black - sony M2 + miCro-SDHC card reader + 1Gb/1024mb miCro-sd , 64x19.8x10.4mm , 6/3 mb/sec - 5 years warranty
SD-2GKC		Kingston SDC/2G - 2Gb/2048mb miCro-SD with SD adapter ; 15x11x1mm , lifetime warranty , retail pack
SD-2GKC2A		Kingston SDC/2G-2ADP - 2Gb/2048mb miCro-SD with SD + miniSD adapter ; 15x11x1mm , lifetime warranty , retail pack
FD-K2GCRSDC2A		kingston MBLY//2GB , Red , miCro-SD card reader + 2Gb/2048mb miCro-sd + 2x Adapter (sd and mini-sd) , 32.89x15.3x7.66mm , 13mb/sec - 2 years warranty
SD-4GKC4		Kingston SDC4/4G , class4 - 4mb/sec - 4Gb/4096mb miCro SDHC with SD adapter ; 15x11x1mm , lifetime warranty , retail pack
SD-4GKC42A		Kingston SDC4/4G-2ADP , class4 - 4mb/sec - 4Gb/4096mb miCro SDHC with SD + miniSD adapter ; 15x11x1mm , lifetime warranty , retail pack
FD-K4GCRSDC2A		kingston MBLY//4GB , black , miCro-SD card reader + 4Gb/4096mb miCro-sd + 2x Adapter (sd and mini-sd) , 32.89x15.3x7.66mm , 13mb/sec - 2 years warranty
FD-K4GDTCRC		kingston DTCRC/4GB , Black - sony M2 + miCro-SDHC card reader + 4Gb/4096mb miCro-sd , 64x19.8x10.4mm , 6/3 mb/sec - 5 years warranty
SD-8GKC4		Kingston SDC4/8G , class4 - 4mb/sec - 8Gb miCro SDHC with SD adapter ; 15x11x1mm , lifetime warranty , retail pack
SD-8GKC42A		Kingston SDC4/8G-2ADP , class4 - 4mb/sec - 8Gb miCro SDHC with SD + miniSD adapter ; 15x11x1mm , lifetime warranty , retail pack
FD-K8GCRSDC2A		kingston MBLY//8GB , black , miCro-SD card reader + 8Gb miCro-sd + 2x Adapter (sd and mini-sd) , 32.89x15.3x7.66mm , 13mb/sec - 2 years warranty
SD-16GKC2	C	Kingston SDC2/16G , class2 - 2mb/sec - 16Gb miCro SDHC , no SD adapter ; 15x11x1mm , lifetime warranty , retail pack
Rs-MMC (Reduced Size Multi-Media Card) - 24x18x1.4mm		
MM-128TRD		Tatu 128mb MMC-Mobile (Dual-Voltage RS-MMC) with MMC adapter , also work as SD , RS-MMC , MMC ; 24x18x1.4mm - lifetime warranty , retail pack
Memory Stick		
MS-1GD		sony memory stick pro Duo 1Gb + adapter , work as normal MS , 31x20x1.6mm , for sony camera , PSP
MS-2GD		sony memory stick pro Duo 2Gb + adapter , work as normal MS , 31x20x1.6mm , for sony camera , PSP

MS-4GD		sony memory stick pro Duo 4Gb + adapter , work as normal MS , 31x20x1.6mm , for sony camera , PSP
MS-8GD		sony memory stick pro Duo 8Gb + adapter , work as normal MS , 31x20x1.6mm , for sony camera , PSP
MS-16GD		sony memory stick pro Duo 16Gb + adapter , work as normal MS , 31x20x1.6mm , for sony camera , PSP
MS-1GM2		sony M2 (Memory stick Micro) 1Gb + adapter , work as normal MS Pro Duo , 15x12x1.2mm , for sony camera , cellphone
MS-2GM2		sony M2 (Memory stick Micro) 2Gb + adapter , work as normal MS Pro Duo , 15x12x1.2mm , for sony camera , cellphone
MS-4GM2		sony M2 (Memory stick Micro) 4Gb + adapter , work as normal MS Pro Duo , 15x12x1.2mm , for sony camera , cellphone
MS-8GM2		sony M2 (Memory stick Micro) 8Gb + adapter , work as normal MS Pro Duo , 15x12x1.2mm , for sony camera , cellphone
CF (Compact Flash) - 42.8x36.4x3.3mm		
CF-2GK		Kingston 2Gb Compact Flash , read/write : 3.7/1.5 mb/sec - lifetime warranty , retail pack
CF-2GK266		Kingston CF/2GB-U2 , 2GB Compact Flash Ultimate (266x) , read/write : 45/40 mb/sec - lifetime warranty , retail pack
CF-4GK		Kingston 4Gb Compact Flash , read/write : 3.7/1.5 mb/sec - lifetime warranty , retail pack
CF-4GK133		Kingston CF/4GB-S2 , 4GB Compact Flash Elite Pro (133x) , read/write : 25/20 mb/sec - lifetime warranty , retail pack
CF-4GK266		Kingston CF/4GB-U2 , 4GB Compact Flash Ultimate (266x) , read/write : 45/40 mb/sec - lifetime warranty , retail pack
CF-8GK133		Kingston CF/8GB-S2 , 8GB Compact Flash Elite Pro (133x) , read/write : 25/20 mb/sec - lifetime warranty , retail pack
CF-8GK266		Kingston CF/8GB-U2 , 8GB Compact Flash Ultimate (266x) , read/write : 45/40 mb/sec - lifetime warranty , retail pack
CF-16GK133		Kingston CF/16GB-S2 , 16GB Compact Flash Elite Pro (133x) , read/write : 25/20 mb/sec - lifetime warranty , retail pack
CF-16GK266	N	Kingston CF/16GB-U2 , 16GB Compact Flash Ultimate (266x) , read/write : 45/40 mb/sec - lifetime warranty , retail pack
CF-32GK133	N	Kingston CF/32GB-S2 , 32GB Compact Flash Elite Pro (133x) , read/write : 25/20 mb/sec - lifetime warranty , retail pack
System / Barebone		
Shuttle XPC barebone		
for intel		
SY-SX100		Shuttle X100 , ultra slim SFF pc , built-in WiFi ; for 667mhz socket479 mobile Core2 Duo/ Core Duo/ Core Solo/ P4/ celeron - i945PM+ iCH7-M chipset size : 210x296x55mm , external ac-adapter , support 1 x 3.5" SATA hdd , built-in card reader (sd/ mmc/ ms/ mspro)+ Slot-in DVD+/-RW vga : ATi mobility Radeon X1400 128mb MXM module - DV-i + DVi to D-sub converter + TV-OUT ; no ps/2 mb : 2x dual channel DDR2-533 so-dimm , 3.5" s-ata2 , on-board ALC880HD 7.1 audio with optical spdif in+out + iEEE1394a (6 pin) + 5 x usb (4+1) + gigabit lan + WiFi
accessories		
SY-SAPF27		Shuttle PF27 VFD module + MCE remote control , for G2, G5 series shuttle chassis
SY-SAPF60		Shuttle PF60 side carry bag , black , Ballistic + Nylon PU , 365x265x185mm - for all shuttle XPC
SY-SAPF30		Shuttle PF30 backpack , black , Nylon Polyester Dobby , 490x300x205mm - for all shuttle XPC
SY-SAPF100		Shuttle PF100 side carry bag , black , PP Fabric , 279x314x63mm - for X100, X200

SY-SAPN18		Shuttle PN18 - add-on wifi module + antenna (extension cable from mb to mounting hole at back of chassis) - for chassis G, G2, G4, G5, K, I, L, P / X200
SY-SAPC17		Shuttle PC17 optical s/pdif in+out module for - for chassis G2, G5
SY-SAPC8		Shuttle PC8 - add-on 25pin printer port (extension cable from mb to mounting hole at back of chassis) - for chassis G, G2, G4, G5, K, I, L
SY-SAPC9		Shuttle PC9 - add-on 2 x extra USB port (extension cable from mb to mounting hole at back of chassis) - for chassis G2, G5
Mother Board		
Accessories		
MB-AACoM		1 port com / serial RS232 cable - connect from on-board COM header to pci bracket
MB-AAUSB	N	2 port usb cable set - connect from on-board usb header to pci bracket
MB-AASPDiF		SPDiF cable with Coaxial + optical out - connect from on-board spdif header to pci bracket
MB-VASPKR		Vantec SPK-08UV-RD Slot Protector Kit - UV reactive Red - for 3 x memory slot + 5 x pci slot
MB-VASPKY		Vantec SPK-08UV-YL Slot Protector Kit - UV reactive Yellow - for 3 x memory slot + 5 x pci slot
MB-VASPKB		Vantec SPK-08UV-BK Slot Protector Kit - UV reactive Black - for 3 x memory slot + 5 x pci slot
MB-VASPKG		Vantec SPK-08UV-GR Slot Protector Kit - UV reactive Green - for 3 x memory slot + 5 x pci slot
MB-VASPKL		Vantec SPK-08UV-BL Slot Protector Kit - UV reactive bLue - for 3 x memory slot + 5 x pci slot
for AMD desktop cpu		
Socket L1 / F / 1207FX		
MB-AL1N64SLiWS		Asus L1N64-SLi WS , dual socket L1 (F/1207FX) for QuadFX platform , fanless heatpipe design : 2 full-bandwidth 16 lane pci-e (16x) ; nvidia nForce® 680a SLiTM + 2 x MCP55PXE chipset (support EPP SLi memory , support linkboost , FirstPacket , 2gigabit Teaming network bandwidth) , 4x dual channel DDR2-800 (upto 2.5v) , 13 (12 internal+1 external) s-ata2 with raid 0/1/5/0+1/10 , 1 x parallel ata133 , on-board ieee1394 (via optional cable) + ADi1988B 7.1 digital audio with coaxial+optical s/pdif out + dual gigabit lan + NV firewall ; 1 x Pci +1 x pci-e(1x) + 4 x pci-e x16 (as x16+ x8+ x16+ x8) , ATX - - need EPS12V psu
for AMD socket AM2/AM2+/AM3 - all-in-one with on-board VGA		
XFX		
MB-X8300		Xfx Mi-A78U-8309 , support hybrid SLi , support hypertransport 3.0 , on-board LCD P.O.S.T display + clear-CMoS button , all-in-one ; socket AM2+ , nVidia 8300 chipset , 4 x dual channel DDR2-1066 , 7 (6 internal+1 external) s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board nvidia 8300 directX10 vga (1.5Ghz shader engine , core : 500mhz) with tripple-output (HDMi + DVi-D + D-SUB) , with HDMi AV output (HD DVD , Blu-ray 1080p HDCP compliant) , 7.1 audio + gigabit lan ; 1x pci-e (1x) , 1x pci-e (16x - pci-e 2.0) , 2 x pci - micro atx
MSi		

MB-MK9N6PGM2V	N	MSi K9N6PGM2-V , all-in-one ; socket AM2/AM2+ (95W only) , support hypertransport 3.0 , nvidia MCP61/nForce430a chipset , 2x dual channel DDR2-1066/800/667 , 2 x s-ata with raid 0/1 , 1x parallel ata133 , on-board 128mb UMA vga + ALC 7.1 audio + 10/100 lan ; 1x pci-e (1x) , 1x pci-e (16x) , 2 x pci , with com/serial port - micro atx
MB-MK9A2GMFV3	N	MSi K9A2GM-F V3 , all-in-one ; socket AM2/AM2+ (95W only) , support hypertransport 3.0 , AMD 740G/sb700 chipset , 2x dual channel DDR2-1066/800/667 , 2 x s-ata with raid 0/1/0+1/5/10 , 1x parallel ata133 , on-board ati x2100 vga + ALC888 7.1 audio + gigabit lan ; 1x pci-e (1x) , 1x pci-e (16x) , 2 x pci , with com/serial port - micro atx
MB-MK9A2GMFiH	N	MSi K9A2GM-FiH , all-in-one ; socket AM2/AM2+ , support hypertransport 3.0 , with Clear CMOS jumper , AMD 780G/sb700 chipset , 2x dual channel DDR2-1066/800/667 , 2 x s-ata with raid 0/1/0+1/5/10 , 1x parallel ata133 , on-board ati HD3200 dual output vga (hdmi+d-sub) + iEEE1394 + ALC888 7.1 audio + gigabit lan ; 1x pci-e (1x) , 1x pci-e (16x) , 2 x pci - micro atx
Asus		
MB-AM2N68VM		Asus M2N68-VM , all-in-one ; socket AM2/AM2+/AM3 , nvidia GeForce7050PV + nForce630a chipset , 4x dual channel DDR2-1066/800/667 , 4 (3 internal+1 external e-sata) x s-ata with raid 0/1/5/0+1/10 , 1 x parallel ata133 , on-board 256mb UMA vga with tripple-output (HDMi + DVi-D + D-SUB) , with HDMi AV output (HD DVD , Blu-ray 1080p HDCP compliant) + VT1708B 7.1 audio with optical s/pdif out + gigabit lan ; 1x pci-e (1x) , 1x pci-e (16x) , 2 x pci - micro atx, 1 x PS2 only for kb
MB-AM3N78VM		Asus M3N78-VM Hdmi , support hybrid SLi , support hypertransport 3.0 , all-in-one ; socket AM2/AM2+/AM3 , nVidia 8200 chipset , 4 x dual channel DDR2-1066 , 6 (5 internal+1 external e-sata) s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board directX10 vga with tripple-output (HDMi + DVi-D + D-SUB) , with HDMi AV output (HD DVD , Blu-ray 1080p HDCP compliant) , VT1708B 7.1 audio with optical spdif out + gigabit lan ; 1x pci-e (1x) , 1x pci-e 2.0 (16x) , 2 x pci - micro atx , 1 x PS2 only for kb
MB-AM3NHH		Asus M3N-H/Hdmi , socket AM2/AM2+/AM3 , support Hybrid SLi , fanless heatpipe design ; nVidia GeForce 8300 chipset , 4x dual channel DDR2-1066 , 6x s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board HDMi or DVi VGA output (HD DVD , Blu-ray 1080p HDCP compliant) + ieee1394 + ALC1200 7.1 digital audio with coaxial s/pdif out + gigabit lan + NV firewall ; 2x pci-e (1x) , 3 x Pci , 1 x pci-e 2.0 (16x) , atx , 1 x PS2 only for kb
MB-AM4N78P	N	Asus M4N78 Pro , support new upcoming 140W Powered CPU , socket AM2/AM2+/AM3 , support Hybrid SLi , support Hybrid SLi , fanless heatpipe design ; nVidia GeForce 8300 chipset , 4x dual channel DDR2-1066 , 6x s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board tripple -output (HDMi + D-SUB + DVi) , with HDMi AV output (HD DVD , Blu-ray 1080p HDCP compliant) + ieee1394 + VIA1708S 7.1 digital audio with optical s/pdif out + gigabit lan + NV firewall ; 2x pci-e (1x) , 3 x Pci , 1 x pci-e 2.0 (16x) , atx , 1 x PS2 only for kb

MB-AM3AHH		Asus M3A-H/Hdmi , support new upcoming 140W Powered CPU , support Hybrid CrossFireX , support hypertransport 3.0 , all-in-one ; socket AM2/AM2+/AM3 , AMD 780G/sb700 chipset , 4 x dual channel DDR2-1066 (upto 2.5v) , 6 x s-ata2 with raid 0/1/0+1/10 , 1 x parallel ata133 , on-board directX10 ATi HD3200 dual output VGA (with D-SUB + HDMi/DVi - 1080P HDCP compliant) , ALC1208 7.1 audio with coaxial s/pdif out + gigabit lan ; 2x pci-e (1x) , 1x pci-e 2.0 (16x) , 3 x pci - atx
MB-AM4A78VM	**C**	Asus M4A78-VM , support new upcoming 140W Powered CPU , support hypertransport 3.0 , all-in-one ; for AM2/AM2+/AM3 , AMD 780G/sb700 chipset , 2 x dual channel DDR2-1066 (upto 2.5v) , 6 x s-ata2 with raid 0/1/0+1/10 , 1 x parallel ata133 , on-board directX10 ATi HD3200 Tripple output VGA (with D-SUB + HDMi + DVi / 1080i HDCP compliant) , ALC887 7.1 audio with optical s/pdif out + gigabit lan ; 1x pci-e (1x) , 1x pci-e 2.0 (16x) , 2 x pci - micro atx , 1 x PS2 only for kb
MB-AM3A78VM		Asus M3A78-VM , support new upcoming 140W Powered CPU , support hypertransport 3.0 , all-in-one ; for AM2/AM2+/AM3 , AMD 780G/sb700 chipset , 4 x dual channel DDR2-1066 (upto 2.5v) , 6 x s-ata2 with raid 0/1/0+1/10 , 1 x parallel ata133 , on-board directX10 ATi HD3200 Tripple output VGA (with D-SUB + HDMi + DVi / 1080i HDCP compliant) , 7.1 audio + gigabit lan ; 1x pci-e (1x) , 1x pci-e 2.0 (16x) , 2 x pci - micro atx , 1 x PS2 only for kb
MB-AM3A78EM		Asus M3A78-EM , support new upcoming 140W Powered CPU , support hypertransport 3.0 , all-in-one ; socket AM2/AM2+/AM3 , AMD 780G/sb700 chipset , 4 x dual channel DDR2-1066 (upto 2.5v) , 6 (5 internal+1 external e-sata) s-ata2 with raid 0/1/0+1/10 , 1 x parallel ata133 , on-board directX10 ATi HD3200 QUAD output VGA (with D-SUB + HDMi + DVi + new coming Display Port / 1080i HDCP compliant) + ieee1394 + Realtek ALC1200 7.1 audio with optical s/pdif out + gigabit lan ; 1x pci-e (1x) , 1x pci-e 2.0 (16x) , 2 x pci - micro atx , 1 x PS2 only for kb
MB-AM4A78EM	**C**	Asus M4A78-EM , support new upcoming 140W Powered CPU , support hypertransport 3.0 , all-in-one ; socket AM2/AM2+/AM3 , AMD 780G/sb700 chipset , 4 x dual channel DDR2-1066 (upto 2.5v) , 6 (5 internal+1 external e-sata) s-ata2 with raid 0/1/0+1/10 , 1 x parallel ata133 , on-board directX10 ATi HD3200 tripple output VGA (with D-SUB + HDMi + DVi / 1080i HDCP compliant) + ALC887 7.1 audio with optical s/pdif out + gigabit lan ; 1x pci-e (1x) , 1x pci-e 2.0 (16x) , 2 x pci - micro atx , 1 x PS2 only for kb
MB-AM4A78PRo	**N**	Asus M4A78-Pro , support hypertransport 3.0 , all-in-one ; for AM2/AM2+/AM3 , AMD 780G/sb700 chipset , 4 x dual channel DDR2-1066 (upto 2.5v) , 6 x s-ata2 with raid 0/1/0+1/10 , 1 x parallel ata133 , on-board directX10 ATi HD3200 tripple output VGA (with D-SUB + HDMi + DVi / 1080i HDCP compliant) + VT1708B 7.1 audio with optical s/pdif out + gigabit lan ; 2x pci-e (1x) , 1x pci-e 2.0 (16x) , 3 x pci - atx

MB-AM3N72D		Asus M3N72-D ; support 140W Powered CPU , socket AM2/AM2+/AM3 , support PCi-E2.0 SLi , Hybrid SLi , hypertransport 3.0 , 8+2 phase cap-less Power , fanless heatpipe design ; nVidia nForce750a SLi chipset , 4x dual channel DDR2-1066 (upto 2.5v) , 6x s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board HDMi or DVi VGA output (HD DVD , Blu-ray 1080p HDCP compliant) + ieee1394 + Realtek ALC1200 7.1 digital audio with coaxial s/pdif out + gigabit lan + NV firewall ; 2x pci-e (1x) , 2 x Pci , 2 x pci-e 2.0 (16x) (at 8x+8x) , atx , 1 x PS2 only for kb
MB-AM3NHDH		Asus M3N-HD/Hdmi ; socket AM2/AM2+/AM3 , support PCi-E2.0 Hybrid SLi , nVidia ESA ready , hypertransport 3.0 , 8+2 phase cap-less Power , fanless heatpipe design ; nVidia nForce750a SLi chipset , 4x dual channel DDR2-1066 (upto 2.5v) , 7 (6 internal+1 external e-sata) s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board HDMi or DVi VGA output (HD DVD , Blu-ray 1080p HDCP compliant) + ieee1394 + Realtek ALC1200 7.1 digital audio with coaxial s/pdif out + gigabit lan + NV firewall ; 2x pci-e (1x) , 2 x Pci , 2 x pci-e 2.0 (16x) (at 8x+8x) , atx , 1 x PS2 only for kb
MB-AM4A78E	N	Asus M4A78-E ; with sideport memory for GPU , socket AM2/AM2+/AM3 (upto 140w) , support PCi-E2.0 Hybrid CrossfireX , hypertransport 3.0 , 8+1 phase cap-less Power , fanless heatpipe design ; Amd 790GX+ATi sb750 chipset , 4x dual channel DDR2-1066 (upto 2.5v) , 6 (5 internal+1 external e-sata) s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board HD3300 directX10 vga (64mb ddr2 800mhz sideport memory) with tripple -output (HDMi + D-SUB + DVi) , with HDMi AV output (HD DVD , Blu-ray 1080p HDCP compliant) + ieee1394 + Realtek ALC1200 7.1 digital audio with optical s/pdif out + gigabit lan ; 2x pci-e (1x) , 2 x Pci , 2 x pci-e 2.0 (16x) (at 8x+8x or 16x) , atx , 1 x PS2 only for kb
MB-AM3A78T		Asus M3A78-T ; with sideport memory for GPU , socket AM2/AM2+/AM3 , support PCi-E2.0 Hybrid CrossfireX , hypertransport 3.0 , 8+2 phase cap-less Power , fanless heatpipe design ; Amd 790GX+ATi sb750 chipset , 4x dual channel DDR2-1066 (upto 2.5v) , 6 (5 internal+1 external e-sata) s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board HD3300 directX10 vga (128mb ddr3 1333mhz sideport memory) with tripple -output (HDMi + D-SUB + DVi) , with HDMi AV output (HD DVD , Blu-ray 1080p HDCP compliant) + ieee1394 + Realtek ALC1200 7.1 digital audio with optical s/pdif out + gigabit lan ; 1x pci-e (1x) , 2 x Pci , 3 x pci-e 2.0 (16x) (at 8x+8x or 16x+4x or 8x+4x+8x) , atx , 1 x PS2 only for kb
MB-AM4A78TE	N	Asus M4A78T-E ; with sideport memory for GPU , socket AM3 only (upto 140w) , support PCi-E2.0 Hybrid CrossfireX , hypertransport 3.0 , 8+2 phase cap-less Power , fanless heatpipe design ; Amd 790GX+ATi sb750 chipset , 4x dual channel DDR3-1600(O.C)/1333 , 6 (5 internal+1 external e-sata) s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board HD3300 directX10 vga (128mb ddr3 1333mhz sideport memory) with tripple -output (HDMi + D-SUB + DVi) , with HDMi AV output (HD DVD , Blu-ray 1080p HDCP compliant) + ieee1394 + VIA VT1708S 7.1 digital audio with optical s/pdif out + gigabit lan ; 2x pci-e (1x) , 2 x Pci , 2 x pci-e 2.0 (16x) (at 8x+8x or 16x) , atx , 1 x PS2 only for kb

MB-AM3NHTDH		Asus M3N-HT Delux/Hdmi ; socket AM2/AM2+/AM3 , support 3-way PCi-E2.0 SLi , Hybrid SLi , nVidia ESA ready , hypertransport 3.0 , 8+2 phase cap-less Power , fanless heatpipe design ; nVidia nForce780a SLi chipset , 4x dual channel DDR2-1066 (upto 2.5v) , 7 (6 internal+1 external e-sata) s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board directX10 vga with tripple -output (HDMi + D-SUB + DVi) , with HDMi AV output (HD DVD , Blu-ray 1080p HDCP compliant) + ieee1394 + 7.1 digital audio with coaxial+optical s/pdif out + gigabit lan + NV firewall ; 1x pci-e (1x) , 2 x Pci , 3 x pci-e 2.0 (16x) (at 16x+16x or 16x+8x+8x) , atx , 1 x PS2 only for kb
MB-AM3NHTDM	N	Asus M3N-HT Delux/Mempipe ; socket AM2/AM2+ , support 3-way PCi-E2.0 SLi , Hybrid SLi , nVidia ESA ready , hypertransport 3.0 , 8+2 phase cap-less Power , fanless heatpipe design with 2 x memory heatpipe ; nVidia nForce780a SLi chipset , 4x dual channel DDR2-1066 (upto 2.5v) , 7 (6 internal+1 external e-sata) s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board directX10 vga with tripple -output (HDMi + D-SUB + DVi) , with HDMi AV output (HD DVD , Blu-ray 1080p HDCP compliant) + ieee1394 + 7.1 digital audio with coaxial+optical s/pdif out + gigabit lan + NV firewall ; 1x pci-e (1x) , 2 x Pci , 3 x pci-e 2.0 (16x) (at 16x+16x or 16x+8x+8x) , atx , 1 x PS2 only for kb
MB-AC2F		Asus Crosshair 2 Formula - Republic of Gamers socket AM2/AM2+/AM3 , support 3-way PCi-E2.0 SLi , Hybrid SLi , nVidia ESA ready , hypertransport 3.0 , on-board voltiminder E-Led , external LCD P.O.S.T , on-board on/off/reset switch , clear CMOS button , 8+2 phase cap-less Power , fanless heatpipe design ; two-slot thermal fanless design ; nVidia nForce780a SLi chipset , 4x dual channel DDR2-1066 (upto 3.4v) , 6x s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board directX10 vga with tripple -output (HDMi + D-SUB + DVi) , with HDMi AV output (HD DVD , Blu-ray 1080p HDCP compliant) + ieee1394 + SupremeFX II ADI 1988B 7.1 digital audio with coaxial+optical s/pdif out + dual gigabit lan + NV firewall ; 2x pci-e (1x) , 2 x Pci , 3 x pci-e 2.0 (16x) (at 16x+16x or 16x+8x+8x) , atx , with bundled game , 1 x PS2 only for kb
for AMD socket AM2/AM2+ - discrete		
MSi		
MB-MK9A2CFF		Msi K9A2 CF-F ; socket AM2+ , support hypertransport 3.0 , PCi-E2.0 , crossfire : 2 full-bandwidth 16 lane pci-e (16x) ; socket AM2/AM2+ , amd 790x + SB600 chipset (support EPP SLi memory , linkboost , FirstPacket) , 4x dual channel DDR2-1066 , 4 x s-ata2 with raid 0/1/0+1/10 , 1 x parallel ata133 , on-board on/off/reset switch , alc888 7.1 audio with optical s/pdif out + gigabit lan + NV firewall ; 2 x Pci , 1 x pci-e(1x) , 2 x pci-e2.0 (8x+8x at crossfire) , atx
Asus		
MB-AM2N68		Asus M2N68 ; socket AM2/AM2+/AM3 , nvidia nForce630a chipset , 4x dual channel DDR2-1066 , 4 x s-ata2 with raid 0/1/5/0+1/10 , 1 x parallel ata133 , on-board 7.1 digital audio with optical s/pdif out + gigabit lan + NV firewall ; 4x pci , 2 x pci-e(1x) , 1 x pci-e(16x) , with com/serial + parallel port , atx - bundle asus array stereo mic + windvd suite
MB-AM4N78SE	N	Asus M4N78 SE ; socket AM2/AM2+/AM3 , support hypertransport 3.0 ; nforce720D chipset , 2x dual channel DDR2-1066 , 6 x s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board ALC662 7.1 audio + gigabit lan ; 2x pci-e (1x) , 1 x pci-e 2.0 (16x) , 3 x pci , with com/serial + parallel port - atx , 1 x PS2 only for kb

MB-AM4N78	**N**	Asus M4N78 ; with EPU-4 (Energy Processing Unit) , socket AM2/AM2+/AM3 , support hypertransport 3.0 ; nforce720D chipset , 4x dual channel DDR2-1066 , 6 (5 internal+1 external) s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board ALC887 7.1 audio with optical s/pdif out + gigabit lan ; 2x pci-e (1x) , 1 x pci-e 2.0 (16x) , 3 x pci , with com/serial + parallel port - atx , 1 x PS2 only for kb
MB-AM3A78		Asus M3A78 ; support new upcoming 140W Powered CPU , socket AM2/AM2+ , support hypertransport 3.0 ; amd770 + SB700 chipset , 4x dual channel DDR2-1066 , 6 x s-ata2 with raid 0/1/0+1/10 , 1 x parallel ata133 , on-board via1708B 7.1 audio with optical S/PDiF out + gigabit lan ; 2x pci-e (1x) , 1 x pci-e 2.0 (16x) , 3 x pci , with com/serial + parallel port - atx , 1 x PS2 only for kb
MB-AM4A78	**C**	Asus M4A78 ; socket AM2/AM2+/AM3 , with EPU (Energy Processing Unit) , support hypertransport 3.0 ; amd770 + SB700 chipset , 4x dual channel DDR2-1066 , 6 (5 internal+1 external) s-ata2 with raid 0/1/0+1/10 , 1 x parallel ata133 , on-board ALC887 7.1 audio with optical S/PDiF out + gigabit lan ; 2x pci-e (1x) , 1 x pci-e 2.0 (16x) , 3 x pci , with com/serial + parallel port - atx , 1 x PS2 only for kb
MB-AM4A78PLUS	**C**	Asus M4A78 PLUS ; socket AM2/AM2+/AM3 , with EPU (Energy Processing Unit) , support PCi-E2.0 crossfire , hypertransport 3.0 , 8+1 phase cap-less Power ; amd770 + SB700 chipset , 4x dual channel DDR2-1066 , 6 (5 internal+1 external) s-ata2 with raid 0/1/0+1/10 , 1 x parallel ata133 , on-board ALC887 7.1 audio with optical S/PDiF out + gigabit lan ; 1x pci-e (1x) , 2 x pci-e 2.0 16x (at 16x or 8x+8x) , 3 x pci - atx , 9x usb upto 15
MB-AM4N72E	**N**	Asus M4N72-E ; support new upcoming 140W Powered CPU , socket AM2/AM2+/AM3 , support PCi-E2.0 SLi , hypertransport 3.0 , 8+1 phase cap-less Power ; nVidia nForce750a SLi chipset , 4x dual channel DDR2-1066 , 6 x s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board iEEE1394 + via1708s 7.1 audio with optical S/PDiF out + gigabit lan ; 2x pci-e (1x) , 2 x pci-e 2.0 16x (at 16x or 8x+8x) , 2 x pci - atx
MB-AM3A79TD		Asus M3A79-T Delux ; support new upcoming 140W Powered CPU , for AM2/AM2+/AM3 , support hypertransport 3.0 , PCi-E2.0 Quad crossfire-X , on-board on/off/reset switch , 8+2 phase cap-less Power , fanless heatpipe design : amd 790fx + SB750 chipset , 4x dual channel DDR2-1066 (upto 2.5v) , 7 (6 internal+1 external) s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board ieee1394 + 7.1 digital audio with coaxial+optical s/pdif out + gigabit lan ; 2 x Pci , 4 x pci-e(16x) (2 x pci-e2.0 + 2 x pci-e 1.0)(at 16x16 or 16+8+8 or 8+8+8+8) , atx , 1 x PS2 only for kb
MB-AM4A79D	**N**	Asus M4A79 Delux , support hypertransport 3.0 , PCi-E2.0 Quad crossfire-X , on-board on/off/reset switch ; for AM2/AM2+/AM3 , AMD 790fx/sb750 chipset , 4 x dual channel DDR2-1066 (upto 2.5v) , 6 (5 internal+ 1 external e-sata) s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board ieee1394 + VT1708B 7.1 audio with coaxial+optical s/pdif out + gigabit lan ; 4x pci-e 2.0 (16x+16x or 16x+8x+8x or quad 8x) , 2 x pci - atx
MB-AM4A79TD	**N**	Asus M4A79T Delux , support hypertransport 3.0 , PCi-E2.0 Quad crossfire-X , on-board on/off/reset switch ; for AM3 only , AMD 790fx/sb750 chipset , 4 x dual channel DDR3-1600(O.C)/1333 , 6 (5 internal+ 1 external e-sata) s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board ieee1394 + VT1708B 7.1 audio with coaxial+optical s/pdif out + gigabit lan ; 4x pci-e 2.0 (16x+16x or 16x+8x+8x or quad 8x) , 2 x pci - atx

for Dual AMD Opteron serverboard		
Socket - F (1207)		
MB-MK9NDSWA6		MSi K9ND Speedster WA6 dual opteron board : nforce professional 3600MCP chipset , 8 x dual channel DDR2-667 (must be pair of ecc-registered) , 6 x S-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board ieee1394 firewire (4+6pin) + ALC888 7.1 audio with optical SPDIF out + 2 x gigabit lan ; 2x pci , 2 x pci-e(16x) for SLi , 1 x pci-e(4x) - ATX
MB-AKFN4-D16		ASUS KFN4-D16 dual opteron board (support quad-core barcelona) , rackmount optimized : nforce professional 2200MCP chipset , 16 x dual channel DDR2-667 (must be pair of ecc-registered) , 4 x S-ata2 with raid 0/1/0+1/5/10 , 2 x parallel ata133 , on-board ATi ES100032 32MB DDR2 VGA + 2 x gigabit lan ; 1 x ZCR , 1 x HTX , 1x pci , 3x pci-x 64bit/133mhz , 1 x pci-e(16x) - E-ATX
for intel desktop cpu		
for intel LGA775 with on-board VGA		
XFX		
MB-XG31i	N	Xfx G31i all-in-one lga775 mb , with on-board power/reset/clear cmos button ; support intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel G31 + iCH7 chipset , 1333/1066/800 fsb , 2 x dual channel ddr2 800 , 5 x s-ata2 (4 x internal + 1x eSATA) , 1 x parallel ata133 , on-board GMA3100 VGA (DVMT upto 256mb , 10.6GB/sec) + 7.1 audio + gigabit lan ; 2x pci , 1 x pci-e(16x) - micro-atx
MB-X630i		Xfx MG-63Mi-7159 , 630i all-in-one lga775 mb , support intel Core2 / Core2-Extreme / P4 / Penitum-D , nVidia nForce 7150/630i chipset , 1333/1066/800 fsb , 2x DDR2 800/667 , 4 x s-ata2 with raid 0/1 ; 1 x parallel ata , on-board geForece 3D VGA (D-SUB+HDMi) + 7.1 audio + gigabit lan ; 2x pci , 1 x pci-e(1x) , 1 x pci-e(16x) , with com/serial port - micro atx
Asus		http://www.asus.com/products.aspx?l1=3&l2=11
MB-AP5GCMX1333	N	Asus P5GC-MX/1333 ; support intel Core2 / P4 / Penitum-D , intel 945GC + iCH7 chipset , 1333(oc)/1066/800/533 fsb , 2x DDR2-667 upto 2.1v , 4 x s-ata2 ; 1 x parallel ata , on-board VGA + realtek ALC883 5.1 audio + 10/100 lan ; 2x pci , 1 x pci-e(1x) , 1 x pci-e(16x) , with com/serial + parallel port - micro-atx
MB-AP5KPLAMSE	N	ASUS P5KPL-AM SE , all-in-one lga775 mb ; support intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel G31 + iCH7 chipset , 1600(oc)/1333/1066/800 fsb , 2 x dual channel ddr2 1066(oc) , 2 x s-ata2 , 1 x parallel ata133 , on-board GMA3100 VGA (DVMT upto 256mb , 10.6GB/sec) + ALC662 5.1 audio + 10/100 lan ; 1x pci , 1 x pci-e (1x) , 1 x pci-e(16x) , with com/serial port - micro-atx
MB-AP5KPLCM		ASUS P5KPL-CM all-in-one lga775 mb ; support intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel G31 + iCH7 chipset , 1600(oc)/1333/1066/800 fsb , 2 x dual channel ddr2 1066(oc) , 4 x s-ata2 , 1 x parallel ata133 , on-board GMA3100 VGA (DVMT upto 256mb , 10.6GB/sec) + VT1708B 7.1 audio + gigabit lan ; 2x pci , 1 x pci-e (1x) , 1 x pci-e(16x) , with com/serial + parallel port - micro-atx
MB-AP5N73AM		Asus P5N73-AM ; all-in-one lga775 mb , support intel Core2 / Core2-Extreme / P4 / Penitum-D , nVidia nForce 7050 / 610i chipset , 1333/1066/800 fsb , 2x DDR2 800(oc)/667 , 4 x s-ata2 with raid 0,1 ; 1 x parallel ata , on-board VGA + VT1708B 7.1 audio + 10/100 lan ; 2x pci , 1 x pci-e(1x) , 1 x pci-e(16x) , with com/serial + parallel port - micro atx

MB-AP5QPLVM	**N**	Asus P5QPL-VM ; all-in-one lga775 mb , support intel Core2 / Core2-Extreme / P4 / Penitum-D , intel G41 + iCH7 chipset , 1333/1066/800 fsb , 2x DDR2 1066(oc)/800/667 , 4 x s-ata2 with raid 0,1 ; 1 x parallel ata , on-board VGA with triipple -output (displayport + D-SUB + DVi / 1080p HDCP compliant) + 7.1 audio optical s/pdif out + 10/100 lan ; 2x pci , 1 x pci-e(1x) , 1 x pci-e(16x) - micro atx
MB-AP5QLCM		ASUS P5QL-CM all-in-one lga775 mb ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel G43 + iCH10 chipset , 1333/1066/800 fsb , 2 x dual channel ddr2 1066(oc) , 6 x s-ata2 (6 x internal + 1 eSATA) , 1 x parallel ata133 , on-board directX10 GMA X4500 hardware (MPEG2+ upto 352mb shared memory) 3D VGA with tripple -output (displayport + D-SUB + DVi / 1080p HDCP compliant) , with HDMi AV output (HD DVD , Blu-ray 1080p HDCP compliant) + VT1708B 7.1 audio + gigabit lan ; 1x pci , 1 x pci-e (1x) , 1 x pci-e 2.0 (16x) , 1 x PS2 only for kb - micro-atx
MB-AP5QLEM		ASUS P5QL-EM all-in-one lga775 mb , with EPU-4 (Energy Processing Unit) ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel G43 + iCH10 chipset , 1333/1066/800 fsb , 4 x dual channel ddr2 1066(oc) , 7 x s-ata2 (6 x internal + 1 eSATA) , 1 x parallel ata133 , on-board directX10 GMA X4500 hardware (MPEG2+ upto 352mb shared memory) 3D VGA with tripple -output (HDMi + D-SUB + DVi / 1080p HDCP compliant) , with HDMi AV output (HD DVD , Blu-ray 1080p HDCP compliant) + Realtek ALC 1200 7.1 audio with coaxial s/pdif out + ieee1394a + gigabit lan ; 1x pci , 2 x pci-e (1x) , 1 x pci-e 2.0 (16x) , 1 x PS2 only for kb - micro-atx
MB-AP5QVM		ASUS P5Q-VM all-in-one lga775 mb , with EPU-4 (Energy Processing Unit) ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel G45 + iCH10R chipset , 1600/1333/1066/800 fsb , 2 x dual channel ddr2 1066(oc) , 6 x s-ata2 , 1 x parallel ata133 , on-board directX10 GMA X4500HD hardware (MPEG2+VC1+AVC+ upto 1849mb shared memory) 3D VGA with Clear Video technology with dual output (D-SUB + DVi / 1080p HDCP compliant) , with HDMi AV output (HD DVD , Blu-ray 1080p HDCP compliant) + Realtek ALC 1200 7.1 audio + gigabit lan ; 1x pci , 2 x pci-e (1x) , 1 x pci-e 2.0 (16x) , 1 x PS2 only for kb - micro-atx
MB-AP5QEM		ASUS P5Q-EM all-in-one lga775 mb , with EPU-4 (Energy Processing Unit) ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel G45 + iCH10R chipset , 1600/1333/1066/800 fsb , 2 x dual channel ddr2 1066(oc) , 6 x s-ata2 with matrix raid raid 0/1/5/0+1/10 , 1 x parallel ata133 , on-board directX10 GMA X4500HD hardware (MPEG2+VC1+AVC+ upto 1849mb shared memory) 3D VGA with Clear Video technology with tripple -output (HDMi + D-SUB + DVi / 1080p HDCP compliant) , with HDMi AV output (HD DVD , Blu-ray 1080p HDCP compliant) + Realtek ALC 1200 7.1 audio with coaxial s/pdif out + ieee1394a + gigabit lan ; 1x pci , 2 x pci-e (1x) , 1 x pci-e 2.0 (16x) , 1 x PS2 only for kb - micro-atx
INTEL		
MB-i945GCLF2		intel 945GCLF2 Little Falls 2 , all-in-one , Integrated Intel Atom330 Dual core cpu (533mhz fsb) ; intel Core2 / P4 / Pentium D / celeron , 1066/800/533 mhz FSB ; intel 945GC + iCH7 chipset , 1x DDR2 667 , 2 x s-ata2 , 1 x parallel ata133 , on-board GMA 950 VGA , 10/100 lan , 4.0 audio + 1xserial + 1x parallel ; 1x pci , no pci-e(16x) , with com/serial + parallel port , mini-iTX / micro-atx - bulk pack - 1 year warranty

MB-i945GCNLR	**N**	intel 945GCNL Newburry Lake - Retail pack , all-in-one ; intel Core2 / P4 / Pentium D / celeron , 1066/800/533 mhz FSB ; intel 945GC + iCH7 chipset , 2x dual channel DDR2 667 , 4 x s-ata2 , 1 x parallel ata133 , on-board GMA 950 VGA , gigabit lan , Intel 5.1 HD audio ; 2x pci , 1 x pci-e(1x) , 1 x pci-e(16x) , micro atx - bulk pack
MB-iG31GL		intel G31GL GrangerLake , all-in-one; intel Quad-core/ Core2 / P4 / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel G31 + iCH7 chipset , 2x dual channel DDR2 800/667 , 2 x s-ata2 , 1 x parallel ata133 , on-board GMA X3100 hardware 3D VGA with Clear Video technology (DVMT upto 224mb , 12.8GB/sec) , 10/100 lan , ALC268-GR 4 channel audio ; 2x pci , micro-atx - bulk pack
MB-iG31PR		intel G31PR PeaRl crek , all-in-one; intel Quad-core/ Core2 / P4 / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel G31 + iCH7 chipset , 2x dual channel DDR2 800/667 , 4 x s-ata2 , 1 x parallel ata133 , on-board GMA X3100 hardware 3D VGA with Clear Video technology (DVMT upto 224mb , 12.8GB/sec) , gigabit lan , Intel 5.1 HD audio ; 2x pci , 1 x pci-e(1x) , 1 x pci-e(16x) , micro-atx - bulk pack
MB-iG31PRR		intel G31PR PeaRl crek - Retail pack, all-in-one; intel Quad-core/ Core2 / P4 / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel G31 + iCH7 chipset , 2x dual channel DDR2 800/667 , 4 x s-ata2 , 1 x parallel ata133 , on-board GMA X3100 hardware 3D VGA with Clear Video technology (DVMT upto 224mb , 12.8GB/sec) , gigabit lan , Intel 5.1 HD audio ; 2x pci , 1 x pci-e(1x) , 1 x pci-e(16x) , micro-atx
MB-iG35EC		intel G35EC EvaCove , all-in-one; intel Quad-core/ Core2 / P4 / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel G35 + iCH8 chipset , 4x dual channel DDR2 800/667 , 4 x s-ata2 , 1 x parallel ata133 , on-board directX10 GMA X3500 hardware 3D VGA with Clear Video technology (support 1080p HDCP) , ieee1394a , gigabit lan , Intel 5.1 HD audio ; 1x pci , 2 x pci-e(1x) , 1 x pci-e(16x) , micro-atx - bulk pack
MB-iG35ECR	**N**	intel G35EC EvaCove - Retail pack , all-in-one; intel Quad-core/ Core2 / P4 / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel G35 + iCH8 chipset , 4x dual channel DDR2 800/667 , 4 x s-ata2 , 1 x parallel ata133 , on-board directX10 GMA X3500 hardware 3D VGA with Clear Video technology (support 1080p HDCP) , ieee1394a , gigabit lan , Intel 5.1 HD audio ; 1x pci , 2 x pci-e(1x) , 1 x pci-e(16x) , micro-atx
MB-iG41RQ	**N**	intel G41RQ , all-in-one; intel Quad-core/ Core2 / P4 / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel G41 + iCH7 chipset , 2x dual channel DDR2 800/667 , 4 x s-ata2 , 1x parallel ata133 , on-board directX10 GMA X4500 hardware (MPEG2+ upto 352mb shared memory) 3D VGA with Clear Video technology (d-sub) , gigabit lan , ALC888VC 5.1 HD audio ; 2x pci , 1 x pci-e 2.0 (16x) , micro-atx - bulk pack
MB-iG41TY	**N**	intel G41TY Trinity Valley , all-in-one; intel Quad-core/ Core2 / P4 / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel G41 + iCH7 chipset , 2x dual channel DDR2 800/667 , 4 x s-ata2 , 1x parallel ata133 , on-board directX10 GMA X4500 hardware (MPEG2+ upto 352mb shared memory) 3D VGA with Clear Video technology (d-sub+DVi - support 1080p HDCP) , gigabit lan , ALC662 5.1 HD audio ; 2x pci , 1 x pci-e(1x) , 1 x pci-e 2.0 (16x) , with parallel port , micro-atx - bulk pack

MB-iG43NB		intel G43NB NoBle town , all-in-one; intel Quad-core/ Core2 / P4 / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel G43 + iCH10 chipset , 2x dual channel DDR2 800/667 , 6 x s-ata2 , 1x parallel ata133 , on-board directX10 GMA X4500 hardware (MPEG2+ upto 352mb shared memory) 3D VGA with Clear Video technology (d-sub+DVi - support 1080p HDCP) , ieee1394a , gigabit lan , realtek ALC888VC 5.1 audio ; 3x pci , 3 x pci-e(1x) , 1 x pci-e 2.0 (16x) , atx - bulk pack
MB-iG43NBR	**C**	intel G43NB NoBle town Retail pack , all-in-one; intel Quad-core/ Core2 / P4 / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel G43 + iCH10 chipset , 2x dual channel DDR2 800/667 , 6 x s-ata2 , 1x parallel ata133 , on-board directX10 GMA X4500 hardware (MPEG2+ upto 352mb shared memory) 3D VGA with Clear Video technology (d-sub+DVi - support 1080p HDCP) , ieee1394a , gigabit lan , realtek ALC888VC 5.1 audio ; 3x pci , 3 x pci-e(1x) , 1 x pci-e 2.0 (16x) , atx
MB-iG45iD		intel G45iD IceDale , all-in-one; intel Quad-core/ Core2 / P4 / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel G45 + iCH10R chipset , 4x dual channel DDR2 800/667 , 6 x s-ata2 with matrix raid raid 0/1/5/0+1/10 (5 x internal + 1 eSATA) , no parallel ata133 , on-board directX10 GMA X4500HD hardware (MPEG2+VC1+AVC+ upto 1849mb shared memory) 3D VGA with Clear Video technology (HDMi + DVi - support 1080p HDCP) , ieee1394a , gigabit lan , IDT 92HD73E 7.1 HD audio ; 1x pci , 2 x pci-e(1x) , 1 x pci-e 2.0 (16x) , micro-atx - bulk pack
MB-iG45iDR	**N**	intel G45iD IceDale Retail pack , all-in-one; intel Quad-core/ Core2 / P4 / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel G45 + iCH10R chipset , 4x dual channel DDR2 800/667 , 6 x s-ata2 with matrix raid raid 0/1/5/0+1/10 (5 x internal + 1 eSATA) , no parallel ata133 , on-board directX10 GMA X4500HD hardware (MPEG2+VC1+AVC+ upto 1849mb shared memory) 3D VGA with Clear Video technology (HDMi + DVi - support 1080p HDCP) , ieee1394a , gigabit lan , IDT 92HD73E 7.1 HD audio ; 1x pci , 2 x pci-e(1x) , 1 x pci-e 2.0 (16x) , micro-atx
MB-iG45FC		intel G45FC Fly Creek , all-in-one; intel Quad-core/ Core2 / P4 / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel G45 + iCH10R chipset , 2x dual channel DDR2 800/667 , 5 x s-ata2 with matrix raid raid 0/1/5/0+1/10 (4 x internal + 1 eSATA) , no parallel ata133 , on-board directX10 GMA X4500HD hardware (MPEG2+VC1+AVC+ upto 1849mb shared memory) 3D VGA with Clear Video technology (HDMi + DVi - support 1080p HDCP) , gigabit lan , IDT 92HD73E 7.1 HD audio with optical SPDiF out ; 1 x pci-e(1x) , mini-iTX / micro-atx - bulk pack
MB-iQ45CB		intel Q45CB CuBe cove , vPro , all-in-one; intel Quad-core/ Core2 / P4 / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel Q45 + iCH10D chipset , 4x dual channel DDR2 800/667 , 6 x s-ata2 with matrix raid raid 0/1/5/0+1/10 (5 x internal + 1 eSATA) , no parallel ata133 , on-board directX10 GMA 4500 hardware (VC1+AVC) 3D VGA with Clear Video technology (DVi - support 1080p HDCP) , ieee1394a , gigabit lan , 4CH audio ; 1x pci , 2 x pci-e(1x) , 1 x pci-e 2.0 (16x) , micro-atx - bulk pack

MB-iQ45CBR	**N**	intel Q45CB CuBe cove Retail pack , vPro , all-in-one; intel Quad-core/ Core2 / P4 / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel Q45 + iCH10D chipset , 4x dual channel DDR2 800/667 , 6 x s-ata2 with matrix raid raid 0/1/5/0+1/10 (5 x internal + 1 eSATA) , no parallel ata133 , on-board directX10 GMA 4500 hardware (VC1+AVC) 3D VGA with Clear Video technology (DVi - support 1080p HDCP) , ieee1394a , gigabit lan , 4CH audio ; 1x pci , 2 x pci-e(1x) , 1 x pci-e 2.0 (16x) , micro-atx

for intel LGA775 - discrete	
MSi	
MB-MX48CP	Msi X48C Platinum , cicru-pipe , dual channel PWM , on-board power/reset/clear cmos button , ATi coressfire ready , intel Quad-core / Core2 / Core2-Extreme / p4 / Pentium D ; intel X48+iCH9R , 1600/1333/1066/800 fsb , 2x dual channel ddr2-800 + 4x dual channel DDR3-1600 (DDR2 and DDR3 can not be used together) , 6 x s-ata2 with raid 0/1/5/0+1/10 (4 x internal + 2 x external) , 1 x parallel ata133 , on-board ALC888 7.1 audio with optical S/Pdif out + gigabit lan + ieee1394a ; 3x pci , 2 x pci-e(1x) , 2 x pci-e 2.0 (16x+16x)
XFX	
MB-X780iSH	XFX N780-iSH , nForce 780i , 3-way SLi , nVidia ESA ready - for intel Lga775 Quad-core/ Core2/ Core2-Extreme/ p4/ Pentium-D cpu ; nVidia nForce780i SLi (support EPP SLi memory , linkboost , FirstPacket , 2gigabit Teaming network) , fanless heatpipe design , on-board LCD P.O.S.T display + on/off/reset switch , 1333/1066/800 fsb , 4x dual channel ddr2 1200 , 6 x s-ata2 with raid 0/1/5/0+1/10 , 1 x parallel ata133 , on-board 7.1 audio with optical S/Pdif out + 2 x gigabit lan + ieee1394a + NV firewall ; 2x pci , 1 x pci-e(1x) , 3 x pci-e 16x (2 x pci-e 2.0 + 1 x pci-e 1.0 @ 16x+16x+16x) , with 1 x bundled fan
MB-X790iUL	XFX N790-iUL , nForce 790i ultra , 3-way SLi , nVidia ESA ready - for intel Lga775 Quad-core/ Core2/ Core2-Extreme/ p4/ Pentium-D cpu ; nVidia nForce780i SLi (support EPP2 SLi memory , linkboost , FirstPacket , 2gigabit Teaming network) , fanless heatpipe design , on-board LCD P.O.S.T display + on/off/reset switch , 1600/1333/1066/800 fsb , 4x dual channel ddr3-2000 , 7 x s-ata2 with raid 0/1/5/0+1/10 (6 x internal + 1 x external) , 1 x parallel ata133 , on-board 7.1 audio with optical S/Pdif out + 2 x gigabit lan + ieee1394a + NV firewall ; 2x pci , 2 x pci-e(1x) , 3 x pci-e 16x (2 x pci-e 2.0 + 1 x pci-e 1.0 @ 16x+16x+16x) , with 1 x bundled fan
ASUS	http://www.asus.com/products.aspx?l1=3&l2=11
MB-AP5KPL1600	ASUS P5KPL/1600 ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel G31 + iCH7 chipset , 1600(oc)/1333/1066/800 fsb , 4 x dual channel ddr2 1066(oc) , 4 x s-ata2 , 1 x parallel ata133 , on-board VT1708B 7.1 audio + gigabit lan ; 3x pci , 2 x pci-e(16x) (x16+x4 for crossfire) , with com/serial + parallel port - atx
MB-AP5KSEEPU	ASUS P5K SE/EPU , with EPU (Energy Processing Unit) ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P35 + iCH9 chipset , 1600/1333/1066/800 fsb , 4x dual channel ddr2-1200o.c (upto 2.6v) , 5 x s-ata2 (4 x internal + 1 x external) , 1 x parallel ata133 , on-board ALC883 7.1 audio with coaxial S/Pdif out + gigabit lan ; 2x pci , 3 x pci-e(1x) , 1 x pci-e(16x) , 1 x PS2 only for kb - atx

MB-AP5QLSE	**N**	ASUS P5QL-SE ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P43 + iCH10 chipset , 1600(o.c)/1333/1066/800 fsb , 2x dual channel ddr2-1066 upto 8Gb , 4 x s-ata2 , 1 x parallel ata133 , on-board ALC662 5.1 audio + gigabit lan ; 3x pci , 2 x pci-e(1x) , 1x pci-e 2.0 (16x) , with com/serial + parallel port , 1 x PS2 only for kb - atx
MB-AP5QLP		ASUS P5QL-Pro , with EPU-4 (Energy Processing Unit) ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P43 + iCH10 chipset , 1600(o.c)/1333/1066/800 fsb , 4x dual channel ddr2-1066 upto 16Gb , 6 x s-ata2 , 1 x parallel ata133 , on-board ALC1200 7.1 audio with coaxial S/Pdif out + gigabit lan ; 3x pci , 2 x pci-e(1x) , 1x pci-e 2.0 (16x) - atx
MB-AP5QLE		ASUS P5QL-E , with EPU-6 (Energy Processing Unit) ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P43 + iCH10R chipset , 1600(o.c)/1333/1066/800 fsb , 4x dual channel ddr2-1066 upto 16Gb , 7 x s-ata2 with raid 0/1/5/0+1/10 (6 x internal + 1 x external e-sata) , 1 x parallel ata133 , on-board ALC1200 7.1 audio with coaxial+optical S/Pdif out + 1394a + gigabit lan ; 3x pci , 2 x pci-e(1x) , 1 x pci-e2.0 (16x) - atx
MB-AP5QSE2	**N**	ASUS P5Q SE2 ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P45 + iCH10 chipset , 1600/1333/1066/800 fsb , 4x dual channel ddr2-1200 (upto 2.6v) upto 16Gb , 6 x s-ata2 , 1 x parallel ata133 , on-board via VT1708S 7.1 audio with coaxial S/Pdif out + gigabit lan ; 3x pci , 2 x pci-e(1x) , 1 x pci-e2.0 (16x)
MB-AP5QSE		ASUS P5Q SE , with EPU-4 (Energy Processing Unit) ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P45 + iCH10 chipset , 1600/1333/1066/800 fsb , 4x dual channel ddr2-1200 (upto 2.6v) upto 16Gb , 6 x s-ata2 , 1 x parallel ata133 , on-board ALC1200 7.1 audio with coaxial S/Pdif out + gigabit lan ; 3x pci , 2 x pci-e(1x) , 1 x pci-e2.0 (16x)
MB-AP5QSEP	**N**	ASUS P5Q SE Plus , with EPU-4 (Energy Processing Unit) , 8-phase Power Design ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P45 + iCH10 chipset , 1600/1333/1066/800 fsb , 4x dual channel ddr2-1200 (upto 2.6v) upto 16Gb , 6 x s-ata2 , 1 x parallel ata133 , on-board ALC1200 7.1 audio with optical S/Pdif out + gigabit lan ; 3x pci , 2 x pci-e(1x) , 1 x pci-e2.0 (16x)
MB-AP5Q		ASUS P5Q , with EPU-6 (Energy Processing Unit) , 8-phase Power Design ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P45 + iCH10R chipset , 1600/1333/1066/800 fsb , 4x dual channel ddr2-1200 (upto 2.6v) upto 16Gb , 8 x s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board ALC1200 7.1 audio with coaxial S/Pdif out + 1394a + gigabit lan ; 3x pci , 2 x pci-e(1x) , 1 x pci-e2.0 (16x) - atx
MB-AP5QT	**C**	ASUS P5Q Turbo , with EPU (Energy Processing Unit) , 8-phase Power Design ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P45 + iCH10R chipset , 1600/1333/1066/800 fsb , 4x dual channel ddr2-1300 (upto 2.6v) upto 16Gb , 8 x s-ata2 with raid 0/1/0+1/5/10 (7x internal + 1x external e-sata) , 1 x parallel ata133 , on-board VT1708S 7.1 audio with optical S/Pdif out + 1394a + gigabit lan ; 2x pci , 3 x pci-e(1x) , 1 x pci-e2.0 (16x) - atx

MB-AP5QPRo		ASUS P5Q-PRo , support crossfire-x (8x+8x) , with EPU-6 (Energy Processing Unit) , 8-phase Power Design ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P45 + iCH10R chipset , 1600/1333/1066/800 fsb , 4x dual channel ddr2-1200 (upto 3.08v) upto 16Gb , 8 x s-ata2 with raid 0/1/5/0+1/10 , 1 x parallel ata133 , on-board ALC1200 7.1 audio with coaxial S/Pdif out + 1394a + gigabit lan ; 2x pci , 3 x pci-e(1x) , 2x pci-e 16x (@ 8x+8x) - atx
MB-AP5QPRoT	C	ASUS P5Q PRo Turbo , support crossfire-x (8x+8x) , with EPU-6 (Energy Processing Unit) , 8-phase Power Design ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P45 + iCH10R chipset , 1600/1333/1066/800 fsb , 4x dual channel ddr2-1300 (upto 3.08v) upto 16Gb , 8 x s-ata2 with raid 0/1/5/0+1/10 (7x internal + 1x external e-sata) , 1 x parallel ata133 , on-board VT1708S 7.1 audio with optical S/Pdif out + 1394a + gigabit lan ; 2x pci , 3 x pci-e(1x) , 2x pci-e 16x (@ 8x+8x) - atx
MB-AP5QC		ASUS P5QC , DDR2+DDR3 , with EPU-6 (Energy Processing Unit) ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P45 + iCH10R chipset , 1600/1333/1066/800 fsb , , 4x dual channel ddr2 1066 (upto 2.5v) + 2x dual channel DDR3 1333 (upto 2.2v) upto 16Gb , 8 x s-ata2 with raid 0/1/0+1/5/10 , 1 x parallel ata133 , on-board ALC1200 7.1 audio with coaxial S/Pdif out + 1394a + gigabit lan ; 2x pci , 3 x pci-e(1x) , 1 x pci-e2.0 (16x) - atx
MB-AP5QE		ASUS P5Q-E , support crossfire-x (8x+8x+4x) , with EPU-6 (Energy Processing Unit) , on-board on/off switch , 8-phase Power Design ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P45 + iCH10R chipset , 1600/1333/1066/800 fsb , 4x dual channel ddr2-1200 (upto 2.6v) upto 16Gb , 9x s-ata2 with raid 0/1/5/0+1/10 (8x internal + 1x external e-sata) , 1 x parallel ata133 , on-board AD2000B 7.1 audio with optical+coaxial S/Pdif out + 1394a + dual gigabit lan ; 2x pci , 2 x pci-e(1x) , 3x pci-e 16x (2 x pci-e 2.0 + 1 x pci-e 1.0 / 8x+8x+4x) , 1 x PS2 only for kb - atx
MB-AP5QD		ASUS P5Q Delux , support crossfire-x (8x+8x+4X) , with Dual BIOS , EPU-6 (Energy Processing Unit) , on-board on/off switch , 16-phase Power Design , copper heatpipe to south-bridge ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P45 + iCH10R chipset , 1600/1333/1066/800 fsb , 4x dual channel ddr2-1200 (upto 2.6v) upto 16Gb , 9 x s-ata2 with raid 0/1/5/0+1/10 (7 x internal + 2 x external e-sata) , 1 x parallel ata133 , on-board AD2000B 7.1 audio with optical+coaxial S/Pdif out + 1394a + dual gigabit lan ; 2x pci , 2 x pci-e(1x) , 3x pci-e 16x (2 x pci-e 2.0 + 1 x pci-e 1.0 / 8x+8x+4x) , 1 x PS2 only for kb - atx
MB-AP5QWS		ASUS P5Q WS , EPU- WS (Energy Processing Unit) , include G.P. Diagnosis card , 16-phase Power Design , copper heatpipe to south-bridge ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P45 + iCH10R chipset , 1600/1333/1066/800 fsb , 4x dual channel ddr2-1200 (upto 2.6v) upto 16Gb , 8 x s-ata2 with raid 0/1/5/0+1/10 (6 x internal + 2 x external e-sata) , 1 x parallel ata133 , on-board AD2000B 7.1 audio with optical+coaxial S/Pdif out + 1394a + dual gigabit lan ; 1x pci , 1x pci-X , 2 x pci-e(1x) , 2x pci-e 2.0 (16x+16x) , 1 x PS2 only for kb - atx

MB-AM2F	ASUS Maximus II Formula - Republic of Gamers extra feature : EPU-6 , external debug LED poster , voltiminder LED (cpu/mem/nb/sb voltage warning led) , on-board on/off/clear CMOS switch , fanless heatpipe design ATi coressfireX ready , intel Quad-core / Core2 / Core2-Extreme / p4 / Pentium D ; intel P45 + iCH10R chipset , 1600/1333/1066/800 fsb , 4x dual channel 2-phase DDR2 1200 (upto 3.4v , support XMP) upto 16Gb , 9 x s-ata2 with raid 0/1/5/0+1/10 (8 x internal + 1 x external -sata) , 1 x parallel ata133 , on-board SupremeFX X-Fi creative X-Fi xtreme fidelity Dobly Digital live 7.1 audio with coaxial+optical S/Pdif out + dual gigabit lan + ieee1394a ; 2x pci , 3 x pci-e(1x) , 2 x pci-e 2.0 16x (8x+8x) - bundled with 2 x asus add-on fan + 3d game STALKER , 1 x PS2 only for kb - atx
MB-AP5Q3DW	ASUS P5Q3 Deluxe/WiFi-AP@n , support crossfire-x (8x+8x) , with Dual BIOS , EPU-6 (Energy Processing Unit) , on-board on/off switch ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P45 + iCH10R chipset , 1600/1333/1066/800 fsb , 4x dual channel 2-phase ddr3 2000(oc) , 9 x s-ata2 with raid 0/1/5/0+1/10 (7 x internal + 2 x external e-sata) , 1 x parallel ata133 , on-board AD2000B 7.1 audio with optical+coaxial S/Pdif out + 1394a + dual gigabit lan + Wifi (802.11n) ; 2x pci , 2 x pci-e(1x) , 3x pci-e 16x (2 x pci-e 2.0 + 1 x pci-e 1.0 / 8x+8x+4x) , 1 x PS2 only for kb - atx
MB-AP5QPRE	ASUS P5Q Premium , support crossfire-x (16x+8x+4x+4x) , with Dual BIOS , EPU-6 (Energy Processing Unit) , on-board on/off switch , 16-phase Power Design , copper heatpipe to south-bridge ; intel Quad-core / Core2 / Core2-Extreme / Celeron-L (800fsb) / p4 / Pentium D ; intel P45 + iCH10R chipset , 1600/1333/1066/800 fsb , 4x dual channel ddr2-1200 (upto 3.08v) upto 16Gb , 10 x s-ata2 with raid 0/1/5/0+1/10 , 1 x parallel ata133 , on-board AD2000B 7.1 audio with optical+coaxial S/Pdif out + 1394a + Quad gigabit lan ; 2x pci , 1 x pci-e(1x) , Quad pci-e 16x (2 x pci-e 2.0 + 2 x pci-e 1.0 / 16X+8x+4x+4x) , with bundled fan + TPM module , 1 x PS2 only for kb - atx
MB-AP5ND	ASUS P5N-D : support SLi , with EPU (Energy Processing Unit) , 8-phase cap-less Power , fanless heatpipe design ; two-slot thermal fanless design - for intel Lga775 Quad-core/ Core2/ Core2-Extreme/ p4/ Pentium-D cpu ; nVidia nForce750i SLi (support EPP SLi memory , linkboost , FirstPacket) , 1333/1066/800/533 fsb , 4x dual channel ddr2 800 (upto 3.11v) , 4 x s-ata2 with raid 0/1/5/0+1/10 , 1 x parallel ata133 , on-board 1988B 7.1 audio with coaxial+optical S/Pdif out + gigabit lan + ieee1394a + NV firewall ; 2x pci , 2 x pci-e(1x) , 2 x pci-e 16x (2 x pci-e 2.0 @ 16x+16x) , with com/serial + parallel port - atx - bundled with 1 x asus add-on fan - atx

MB-AP5N72TP	ASUS P5NT72-T Premium - nVidia ESA certified : support 3-way SLi , with EPU (Energy Processing Unit) , on-board on/off/clear CMOS switch , 8-phase cap-less Power , fanless heatpipe design ; two-slot thermal fanless design - for intel Lga775 Quad-core/ Core2/ Core2-Extreme/ p4/ Pentium-D cpu ; nVidia nForce780i SLi (support EPP SLi memory , linkboost , FirstPacket) , 1600(oc)/1333/1066/800/533 fsb , 4x dual channel ddr2 1200(oc)/1066 (upto 3.11v) , 7 x s-ata2 with raid 0/1/5/0+1/10 (6 x internal + 1 x external) , 1 x parallel ata133 , on-board SupremeFX II ADI 1988B Dobly Digital live 7.1 audio with coaxial+optical S/Pdif out + dual gigabit lan + ieee1394a + NV firewall ; 2x pci , 2 x pci-e(1x) , 3 x pci-e 16x (2 x pci-e 2.0 + 1 x pci-e 1.0 @ 16x+16x+16x) , 1 x PS2 only for kb - atx
MB-AS2E	ASUS Striker 2 Extreme - Republic of Gamers - nVidia ESA certified extra feature : support 3-way SLi , with EPU (Energy Processing Unit) , on-board voltiminder E-Led , external LCD P.O.S.T , on-board on/off/reset switch , clear CMOS button , 8-phase cap-less Power , fanless heatpipe design with Fusion Block System (for 3 x chipsets + MoSFET water cooling) ; two-slot thermal fanless design - for intel Lga775 Quad-core/ Core2/ Core2-Extreme/ p4/ P-D cpu ; nVidia nForce790i Ultra SLi (support EPP2 SLi memory linkboost , FirstPacket , 2gigabit Teaming network bandwidth) , 1600/1333/1066/800 fsb , 4x dual channel ddr3 1600(O.C)/1333/1066/800 (upto 3.1v) , 8 x s-ata2 with raid 0/1/5/0+1/10 (6 x internal + 2 x external) , 1 x parallel ata133 , on-board SupremeFX ii ADI 1988B Dobly Digital live 7.1 audio with coaxial+optical S/Pdif out + dual gigabit lan + ieee1394a + NV firewall ; 2x pci , 2 x pci-e(1x) , 3 x pci-e 16x (2 x pci-e 2.0 + 1 x pci-e 1.0 @ 16x+16x+16x) , 1 x PS2 only for kb - bundled with 2 x asus add-on fan + bundle game company of heroes - atx
MB-ARF	ASUS Rampage Formula - Republic of Gamers extra feature : EPU , Crosslinx , external debug LED poster , Voltminder LED (cpu/mem/nb/sb voltage warning led) , on-board on/off switch , clear CMOS switch at rear i/o panel , fanless heatpipe design ATi coressfire ready , intel Quad-core / Core2 / Core2-Extreme / p4 / Pentium D ; intel X48+iCH9R , 1600/1333/1066/800 fsb , 4x dual channel 2-phase DDR2 1200(oc)/1066 (upto 3.4v , support XMP) , 6 x s-ata2 with raid 0/1/0+1/5 , 1 x parallel ata133 , on-board SupremeFX II ADI 1988B Dobly Digital live 7.1 audio with coaxial+optical S/Pdif out + dual gigabit lan + ieee1394a ; 2x pci , 3 x pci-e(1x) , 2 x pci-e 2.0 (16x+16x) - bundled with 2 x asus add-on fan + 3d game STALKER , 1 x PS2 only for kb - atx
MB-ARE	ASUS Rampage Extreme - Republic of Gamers extra feature : EPU , Crosslinx , external debug LED poster , Voltminder LED (cpu/mem/nb/sb voltage warning led) , on-board on/off switch , clear CMOS switch at rear i/o panel , fanless heatpipe design ATi coressfire-x ready , intel Quad-core / Core2 / Core2-Extreme / p4 / Pentium D ; intel X48+iCH9R , 1600/1333/1066/800 fsb , 4x dual channel 2-phase DDR3 200 (upto 3.04v , support XMP) , 6 x s-ata2 with raid 0/1/0+1/5 , 1 x parallel ata133 , on-board SupremeFX II ADI 1988B Dobly Digital live 7.1 audio with coaxial+optical S/Pdif out + dual gigabit lan + ieee1394a ; 2x pci , 3 x pci-e(1x) , 2 x pci-e 2.0 (16x+16x) - bundled with 2 x asus add-on fan + 3d game STALKER , 1 x PS2 only for kb - atx

INTEL

MB-iP43TF		intel P43TF TopsField ; intel Quad-core / Core2 / Core2-extreme / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel P43 + iCH10 chipset , 4x dual channel DDR2 800 , 6 x s-ata2 , 1 x parallel ata133 ; on-board gigabit lan + ieee1394a + realtek ALC888VC 5.1 audio ; 3x pci, 3 x pci-e(1x), 1 x pci-e 2.0 (16x) , atx , no PS2 - bulk pack
MB-iP43TFR	N	intel P43TF TopsField Retail pack ; intel Quad-core / Core2 / Core2-extreme / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel P43 + iCH10 chipset , 4x dual channel DDR2 800 , 6 x s-ata2 , 1 x parallel ata133 ; on-board gigabit lan + ieee1394a + realtek ALC888VC 5.1 audio ; 3x pci, 3 x pci-e(1x), 1 x pci-e 2.0 (16x) , atx , no PS2
MB-iP45SG		intel P45SG SkyberG ; intel Quad-core / Core2 / Core2-extreme / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel P45 + iCH10R chipset , 4x dual channel DDR3-1333 (support XMP) upto 16Gb , 5 x s-ata2 + 1x e-SATA with raid 0,1,0+1,10,5 , no parallel ata133 ; on-board gigabit lan + ieee1394a + Intel 7.1 HD audio with optical spdif out ; 3x pci, 2 x pci-e(1x), 2 x pci-e 2.0 (16x / 8X+8X) , atx , no PS2 - bulk pack
MB-iP45SGR		intel P45SG SkyberG Retail pack; intel Quad-core / Core2 / Core2-extreme / Pentium D / Celeron-L (800fsb) , 1333/1066/800fsb , intel P45 + iCH10R chipset , 4x dual channel DDR3-1333 (support XMP) upto 16Gb , 5 x s-ata2 + 1x e-SATA with raid 0,1,0+1,10,5 , no parallel ata133 ; on-board gigabit lan + ieee1394a + Intel 7.1 HD audio with optical spdif out ; 3x pci, 2 x pci-e(1x), 2 x pci-e 2.0 (16x / 8X+8X) , atx , no PS2
MB-iS3210SHLC	N	intel S3210SHLC Snow Hill LC - LGA775 single cpu server board ; intel Quad-core / Core2 / Core2-extreme / Pentium D , 1333/1066/800fsb , intel 3210 with PXH-V chipset , 4x dual channel DDR2-800 , 6 x s-ata2 with raid 0/1//0+1/5/10 , 1x parallel ata133 ; on-board 32mb VGA + dual gigabit lan ; 2x pci, 1 x pci-e 16x, 1xpci-e 4x, 2 x pci-e 8x , atx
MB-iS3210SHLX		intel S3210SHLX Snow Hill LX - LGA775 single cpu server board ; intel Quad-core / Core2 / Core2-extreme / Pentium D , 1333/1066/800fsb , intel 3210 with PXH-V chipset , 4x dual channel DDR2-800 , 6 x s-ata2 with raid 0/1//0+1/5/10 , 1x parallel ata133 ; on-board 32mb VGA + dual gigabit lan ; 1x pci, 2x pci-X 64bit/133mhz , 1 x pci-e 16x, 1 x pci-e 8x , atx
for intel LGA1366 - discrete		
XFX		
MB-XX58i	N	XFX X58i ; LGA1366/i7 mb ; on-board LCD P.O.S.T display + on-board on/off/clear CMOS switch , fanless heatpipe design , 16+2 phase power design , 3-way nVidia SLI / ATi coressfire ready ; intel X58+iCH10R , 6x tripple channel 2-phase DDR3 1333 (support XMP upto 1.69v) , 8 x s-ata2 with raid 0/1//0+1/5/10 (6 x SATA + 2 x e-SATA) , 1 x parallel ata133 , on-board 7.1 audio with coaxial+optical S/Pdif out + dual gigabit lan + ieee1394a ; 2x pci , 1 x pci-e(1x) , 3 x pci-e 2.0 (16x+16x+1x or 16x+8x+8x) - 1 x PS2 only for kb
ASUS		
MB-AP6T	N	ASUS P6T ; LGA1366/i7 mb ; on-board on-board on/off/clear CMOS switch , fanless heatpipe design , 8+2 phase power design , 3-way nVidia SLI / ATi coressfire ready ; intel X58+iCH10R , 6x tripple channel 2-phase DDR3 2000 (support XMP upto 1.69v) , 9 x s-ata2 with raid 0/1//0+1/5/10 (8 x SATA + 1 x e-SATA) , 1 x parallel ata133 , on-board ALC1200 7.1 audio with coaxial+optical S/Pdif out + gigabit lan + ieee1394a ; 2x pci , 1 x pci-e(1x) , 3 x pci-e 2.0 (16x+16x+4x)

MB-AR2G	N	ASUS Rampage 2 Gene - Republic of Gamers LGA1366/i7 mb ; with Dual BIOS , external debug LED poster , Voltminder LED (cpu/mem/nb/sb voltage warning led) , on-board on-board on/off/clear CMOS switch , fanless heatpipe design , 16+2 phase power design , nVidia SLI / ATi coressfire ready ; intel X58+iCH10R , 6x tripple channel 2-phase DDR3 2000 (support XMP upto 1.69v) , 8 x s-ata2 with raid 0/1//0+1/5/10 (7 x SATA + 1 x e-SATA) , 1 x parallel ata133 , on-board SupremeFX Dobly Digital live 7.1 audio with optical S/Pdif out + gigabit lan + ieee1394a ; 1x pci , 1 x pci-e(4x) , 2 x pci-e 2.0 (16x+16x) - 1 x PS2 only for kb - micro atx
MB-AP6TDV2	N	ASUS P6T-Delux V2 ; LGA1366/i7 mb ; on-board on-board on/off/clear CMOS switch , fanless heatpipe design , 16+2 phase power design , 3-way , nVidia SLI / ATi coressfire ready ; intel X58+iCH10R , 6x tripple channel 2-phase DDR3 2000 (support XMP upto 1.69v) , 7 x s-ata2 with raid 0/1//0+1/5/10 (6 x SATA + 1 x e-SATA) , 1 x parallel ata133 , on-board ADI 2000B Dobly Digital live 7.1 audio with coaxial+optical S/Pdif out + dual gigabit lan + ieee1394a ; 2x pci , 1 x pci-e(1x) , 3 x pci-e 2.0 (16x+16x+1x or 16x+8x+8x) - 1 x PS2 only for kb
MB-AP6TD	N	ASUS P6T-Delux ; LGA1366/i7 mb ; on-board on-board on/off/clear CMOS switch , fanless heatpipe design , 16+2 phase power design , 3-way , nVidia SLI / ATi coressfire ready ; intel X58+iCH10R , 6x tripple channel 2-phase DDR3 2000 (support XMP upto 1.69v) , 9 x s-ata2 with raid 0/1//0+1/5/10 (2x SAS/SATA + 6 x SATA + 1 x e-SATA) , 1 x parallel ata133 , on-board ADI 2000B Dobly Digital live 7.1 audio with coaxial+optical S/Pdif out + dual gigabit lan + ieee1394a ; 2x pci , 1 x pci-e(1x) , 3 x pci-e 2.0 (16x+16x+1x or 16x+8x+8x) - 1 x PS2 only for kb
MB-AP6TDoCP	N	ASUS P6T-Delux OC Palm ; with extra OC palm lcd for over-clocking + hardware monintoing LGA1366/i7 mb ; on-board on-board on/off/clear CMOS switch , fanless heatpipe design , 16+2 phase power design , 3-way nVidia SLI / ATi coressfire ready ; intel X58+iCH10R , 6x tripple channel 2-phase DDR3 2000 (support XMP upto 1.69v) , 9 x s-ata2 with raid 0/1//0+1/5/10 (2x SAS/SATA + 6 x SATA + 1 x e-SATA) , 1 x parallel ata133 , on-board ADI 2000B Dobly Digital live 7.1 audio with coaxial+optical S/Pdif out + dual gigabit lan + ieee1394a ; 2x pci , 1 x pci-e(1x) , 3 x pci-e 2.0 (16x+16x+1x or 16x+8x+8x) - 1 x PS2 only for kb
MB-AP6TWSP	N	ASUS P6T-WS Professional ; LGA1366/i7 mb ; include G.P. Diagnosis card , fanless heatpipe design , 16+2 phase power design , nVidia SLI / ATi coressfire ready ; intel X58+iCH10R , 6x tripple channel 2-phase DDR3 1600 (support XMP upto 1.69v) , 10 x s-ata2 with raid 0/1//0+1/5/10 (2x SAS/SATA + 6 x SATA + 2x e-SATA) , no parallel ata133 , on-board ADI 2000B Dobly Digital live 7.1 audio with coaxial+optical S/Pdif out + dual gigabit lan + ieee1394a ; 1x pci, 2x pci-X 64bit/133mhz , 1 x pci-e(1x) , 2 x pci-e 2.0 (16x+16x) - 1 x PS2 only for kb

MB-AR2E	N	ASUS Rampage 2 Extreme - Republic of Gamers LGA1366/i7 mb ; with on-board extreme OC tweakIt , Dual BIOS , external debug LED poster , EL i/o , Voltminder LED (cpu/mem/nb/sb voltage warning led) , on-board on-board on/off/clear CMOS switch , fanless heatpipe design , 16+2 phase power design , nVidia SLI / ATi coressfire ready ; intel X58+iCH10R , 6x tripple channel 2-phase DDR3 2000 (support XMP upto 1.69v) , 9 x s-ata2 with raid 0/1//0+1/5/10 (8 x SATA + 1 x e-SATA) , 1 x parallel ata133 , on-board SupremeFX II ADI 2000B Dobly Digital live 7.1 audio with coaxial+optical S/Pdif out + dual gigabit lan + ieee1394a ; 2x pci , 1 x pci-e(1x) , 3 x pci-e 2.0 (16x+16x+1x or 16x+8x+8x) - 1 x PS2 only for kb
MB-AP6T6WSR	N	ASUS P6T6-WS Revolution ; LGA1366/i7 mb ; include G.P. Diagnosis card , fanless heatpipe design , 16+2 phase power design , nVidia SLI / ATi coressfire ready ; intel X58+iCH10R , 6x tripple channel 2-phase DDR3 1600 (support XMP upto 1.69v) , 10 x s-ata2 with raid 0/1//0+1/5/10 (2x SAS/SATA + 6 x SATA + 2x e-SATA) , no parallel ata133 , on-board ADI 2000B Dobly Digital live 7.1 audio with coaxial+optical S/Pdif out + dual gigabit lan ; 6 x pci-e 2.0 (support 16x+16x+16x) - 1 x PS2 only for kb
INTEL		
MB-iX58So	N	Intel X58So SmackOver ; LGA1366/i7 mb ; on-board on-board on/off/clear CMOS switch , fanless heatpipe design , 16+2 phase power design , CoressfireX ready , intel X58+iCH10R , 4x tripple channel DDR3 1600 (support XMP) , 8 x s-ata2 with raid 0/1//0+1/5/10 (6 x SATA + 2 x e-SATA) , on-board 7.1 audio with optical S/Pdif out + gigabit lan + ieee1394a ; 1x pci , 2 x pci-e(1x) , 3 x pci-e 2.0 (16x+16x+1x or 16x+8x+8x) - bulk pack
MB-iX58SoR	N	Intel X58So SmackOver Retail pack ; LGA1366/i7 mb ; on-board on-board on/off/clear CMOS switch , fanless heatpipe design , 16+2 phase power design , CoressfireX ready , intel X58+iCH10R , 4x tripple channel DDR3 1600 (support XMP) , 8 x s-ata2 with raid 0/1//0+1/5/10 (6 x SATA + 2 x e-SATA) , on-board 7.1 audio with optical S/Pdif out + gigabit lan + ieee1394a ; 1x pci , 2 x pci-e(1x) , 3 x pci-e 2.0 (16x+16x+1x or 16x+8x+8x)
intel Xeon server board		
socket 775		
MB-iS3210SHLC	N	intel S3210SHLC Snow Hill LC - LGA775 single cpu server board ; intel Quad-core / Core2 / Core2-extreme / Pentium D , 1333/1066/800fsb , intel 3210 with PXH-V chipset , 4x dual channel DDR2-800 , 6 x s-ata2 with raid 0/1//0+1/5/10 , 1x parallel ata133 ; on-board 32mb VGA + dual gigabit lan ; 2x pci, 1 x pci-e 16x, 1xpci-e 4x, 2 x pci-e 8x , atx
MB-iS3210SHLX	N	intel S3210SHLX Snow Hill LX - LGA775 single cpu server board ; intel Quad-core / Core2 / Core2-extreme / Pentium D , 1333/1066/800fsb , intel 3210 with PXH-V chipset , 4x dual channel DDR2-800 , 6 x s-ata2 with raid 0/1//0+1/5/10 , 1x parallel ata133 ; on-board 32mb VGA + dual gigabit lan ; 1x pci, 2x pci-X 64bit/133mhz , 1 x pci-e 16x, 1 x pci-e 8x , atx
socket 771		
MB-iS5VSASATA		intel S5000VSASATA , intel 5000V chipset , SApello , for dual multi-core xeon (667/ 1066/ 1333mhz) : 8 x quad channel ddr2-667 (must be ECC FB-Dimm) , 6 x S-ata with raid 0/1/10 (raid5 optional) , 1 x parallel ata100 , on-board ATi ES1000 16mb VGA + Dual intel 82563EB gigabit lan with i/oAT ; 1x pci , 2x 64bit 133mhz PCi-X , 2 x Pci-Express (8x) at 4x speed - E-atx

MB-iS5VSASAS	R	intel S5000VSASAS , intel 5000V chipset , SApello , for dual multi-core xeon (667/ 1066/ 1333mhz) : 8 x quad channel ddr2-667 (must be ECC FB-Dimm) , 2 x S-ata with raid 0/1 (raid5/10 optional) , 4 x SAS scsi with raid 0/1/10 (raid 5 optional) , 1 x parallel ata100 , on-board ATi ES1000 16mb VGA + Dual intel 82563EB gigabit lan with i/oAT ; 1x pci , 2x 64bit 133mhz PCi-X , 2 x Pci-Express (8x) at 4x speed - E-atx
MB-iS5PSLSATA		intel S5000PSLSATA , intel 5000P chipset , Star Lake , for dual multi-core xeon (667/ 1066/ 1333mhz) : 8 x quad channel ddr2-667 (must be ECC FB-Dimm) , 6 x S-ata with raid 0/1/10 (raid5 optional) , 1 x parallel ata100 , on-board ATi ES1000 16mb VGA + Dual intel 82563EB gigabit lan with i/oAT ; 1x 64bit 100mhz PCi-X , 1x 64bit 133mhz PCi-X , 2 x Pci-Express (8x) , 2 x Pci-Express (4x) - E-atx
MB-iS5PSLSAS	R	intel S5000PSLSAS , intel 5000P chipset , Star Lake , for dual multi-core xeon (667/ 1066/ 1333mhz) : 8 x quad channel ddr2-667 (must be ECC FB-Dimm) , 2 x S-ata with raid 0/1 (raid5,10 optional) , 4 x SAS scsi with raid 0/1/10 (raid 5 optional) , 1 x parallel ata100 , on-board ATi ES1000 16mb VGA + Dual intel 82563EB gigabit lan with i/oAT ; 1x 64bit 100mhz PCi-X , 1x 64bit 133mhz PCi-X , 2 x Pci-Express (8x) , 2 x Pci-Express (4x) - E-atx
MB-iS5XVNSATA		intel S5000XVNSATA , intel 5000X chipset , VerNonia , for dual multi-core xeon (667/ 1066/ 1333mhz) : 8 x quad channel ddr2-667 (must be ECC FB-Dimm) , 6 x S-ata with raid 0/1/10 (raid5 optional) , 1 x parallel ata100 , on-board Dual intel 82563EB gigabit lan with i/oAT ; 1x 64bit 100mhz PCi-X , 1x 64bit 133mhz PCi-X , 1 x pci-express (16x) , 2 x Pci-Express (8x) at 4x speed - E-atx
MB-iS5XVNSAS	R	intel S5000XVNSAS , intel 5000X chipset , VerNonia , for dual multi-core xeon (667/ 1066/ 1333mhz) : 8 x quad channel ddr2-667 (must be ECC FB-Dimm) , 2 x S-ata with raid 0/1 (raid5/10 optional) , 4 x SAS scsi with raid 0/1/10 (raid 5 optional) , 1 x parallel ata100 , on-board Dual intel 82563EB gigabit lan with i/oAT ; 1x 64bit 100mhz PCi-X , 1x 64bit 133mhz PCi-X , 1 x pci-express (16x) , 2 x Pci-Express (8x) at 4x speed - E-atx
MB-iD5400XS		intel D5400XS Skulltrail , support crossfire or SLi , for Core2 Extreme processor QX9775 quad core cpu (1600mhz) or dual multi-core xeon (1600/1333/1066mhz) - require optional LGA775 cpu cooler : on-board reset/power switch , intel 5400 chipset , 4 x quad channel ddr2-800/667 (must be ECC FB-Dimm) , 8 x S-ata with raid 0/1//0+1/5/10 (6 x internal + 2 x external) , 1 x parallel ata100 , on-board intel 82573L gigabit lan + ieee1394 firewire, iDT STAC9274 7.1 audio with optical S/PDiF out ; 2 x pci , 4 x pci-express (16x) - E-atx
Screen Card		
CO-DVIDSUB	**N**	DVi-i to D-sub converter
EXTERNAL		
SC-SVGA2614		Sunix VGA2614 usb to VGA (d-sub) , ideal for desktop or notebook , support upto 1680x1200 / 1680x1050 (wide screen) , clone or extend ur desktop - support upto 6 display with 6 units
SC-V100U	**C**	Vantec nbv-100U usb to VGA (Dvi/d-sub) , ideal for desktop or notebook , support upto 1600x1200 , clone or extend ur desktop - support upto 2 display with 2 units
Pci		
SC-SVGA0011		Sunix VGA0011 , PCI , XGI Volari Z7 chipset , 16mb ddr , d-sub , ultra-low power consumption , heatsink free
PCi-EXPRESS-Nvidia		
ASUS		http://www.asus.com/products.aspx?l1=2&l2=6

SC-A84GS-S		ASUS EN8400GS Silent/HTP/256M , Silencer with heatsink only , no SLi , geforce 8400GS , Pci-E 16x , HDCP Compliant , 256mb 64bit DDR2 , support DirectX 10.0 ; max dual link DVI resolution 2048x1536 , 2.7 billion/sec texture fill rate , 6.4Gb/sec memory transfer , 24 stream processors @ 1200Mhz (pixel shader engine + vertex pipelines) , core/memory : 459/800mhz , d-sub + dvi , HDTV tvout - retail pack
SC-A84GS-L		ASUS EN8400GS/HTP/256M(LP) include Low-profile kit , no SLi , geforce 8400GS , Pci-E 16x , HDCP Compliant , 256mb 64bit DDR2 , support DirectX 10.0 ; max dual link DVI resolution 2048x1536 , 2.7 billion/sec texture fill rate , 6.4Gb/sec memory transfer , 24 stream processors @ 1200Mhz (pixel shader engine + vertex pipelines) , core/memory : 459/800mhz , d-sub + dvi , HDTV tvout - retail pack
SC-A84GS512-S		ASUS EN8400GS SILENT/HTP/512M , Silencer with heatsink only , no SLi , geforce 8400GS , Pci-E 2.0 16x , HDCP Compliant , 512mb 64bit DDR2 , support DirectX 10.0 ; max dual link DVI resolution 2048x1536 , 2.7 billion/sec texture fill rate , 6.4Gb/sec memory transfer , 24 stream processors @ 1200Mhz (pixel shader engine + vertex pipelines) , core/memory : 567/1000mhz , d-sub + dvi , HDTV tvout - retail pack
SC-A94GTH512D2L	N	Asus EN9400GT/Di/512D2(LP) , include Low-profile kit , geforce 9400GT , HDMi ready , no SLi , Pci-E 2.0 16x , 512mb 128bit DDR2 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 4 , 16 stream processors @ 1.375Ghz (pixel shader engine + vertex pipelines) , core/memory : 550/800mhz , d-sub+dvi+HDMi , HDTV tvout
SC-A94GT512D3		Asus EN9400GT D3/HTP/512M , geforce 9400GT , SLi support , Pci-E 2.0 16x , 512mb 128bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 4 , 16 stream processors @ 1.375Ghz (pixel shader engine + vertex pipelines) , core/memory : 550/1800mhz , d-sub+dv , HDTV tvout
SC-A94GTH1GD2L	N	Asus EN9400GT/Di/1GD2(LP) , include Low-profile kit , geforce 9400GT , HDMi ready , no SLi , Pci-E 2.0 16x , 1Gb/1024mb 128bit DDR2 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 4 , 16 stream processors @ 1.375Ghz (pixel shader engine + vertex pipelines) , core/memory : 550/800mhz , d-sub+dvi+HDMi , HDTV tvout
SC-A86GT512D2		ASUS EN8600GT magic/HTDP/512M , geforce 8600GT , SLi support , Pci-E 16x , HDCP Compliant , 512mb 128bit DDR2 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max dual link DVI resolution 3800x2400 , 8.64 billion/sec texture fill rate , 22.4Gb/sec memory transfer , 32 stream processors @ 1190Mhz (pixel shader engine + vertex pipelines) , core/memory : 540/880mhz , 2 x dvi , HDTV tvout - retail pack
SC-A95GTMH512		Asus EN9500GT MAGIC/Di/512M , geforce 9500GT , HDMi ready , SLi support , Pci-E 2.0 16x , 512mb 128bit DDR2 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 8 , 32 stream processors @ 1.375Ghz (pixel shader engine + vertex pipelines) , core/memory : 550/800mhz , d-sub+dv , HDTV+HDMi tvout

SC-A95GTH1G		Asus EN9500GT/DI/1G , geforce 9500GT , HDMi ready , SLi support , Pci-E 2.0 16x , 1Gb 128bit DDR2 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 8 , 32 stream processors @ 1.375Ghz (pixel shader engine + vertex pipelines) , core/memory : 550/800mhz , d-sub+dv , HDTV+HDMi tvout
SC-A95GTTH512		Asus EN9500GT TOP/DI/512M , geforce 9500GT , HDMi ready , SLi support , Pci-E 2.0 16x , 512mb 128bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 8 , 32 stream processors @ 1.75Ghz (pixel shader engine + vertex pipelines) , core/memory : 700/2000mhz , d-sub+dv , HDTV+HDMi tvout
SC-A96GSo512D2		Asus EN9600GSO Magic/HTDP/512M , geforce 9600GSo , SLi support , Pci-E 2.0 16x , 512mb 128bit DDR2 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 40.8Gb/sec memory transfer , 96 stream processors @ 1.375Ghz (pixel shader engine + vertex pipelines) , core/memory : 550/1000mhz , 2 x dvi , HDTV tvout
SC-A96GSo384D3		Asus EN9600GSO/HTDP/384M , geforce 9600GSo , SLi support , Pci-E 2.0 16x , 384mb 192bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 40.8Gb/sec memory transfer , 96 stream processors @ 1.375Ghz (pixel shader engine + vertex pipelines) , core/memory : 550/1600mhz , 2 x dvi , HDTV tvout
SC-A96GT512D2	N	Asus EN9600GT MG/HTDP/512 , geforce 9600GT , SLi support , Pci-E 2.0 16x , 512mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 64 stream processors @ 1.625Ghz (pixel shader engine + vertex pipelines) , core/memory : 650/800mhz , 2 x dvi (with dvi to d-sub + dvi to HDMi converter) , HDTV+HDMi tvout
SC-A96GTH512		Asus EN9600GT/HTDi/512 , with Hdmi , geforce 9600GT , SLi support , Pci-E 2.0 16x , 512mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 64 stream processors @ 1.625Ghz (pixel shader engine + vertex pipelines) , core/memory : 650/1800mhz , 2 x dvi (with dvi to d-sub + dvi to HDMi converter) , HDTV+HDMi tvout
SC-A96GTH512-S		Asus EN9600GT SILENT/HTDI/512M , with Hdmi , Silencer with V-cool heatsink only , geforce 9600GT , SLi support , Pci-E 2.0 16x , 512mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 64 stream processors @ 1.625Ghz (pixel shader engine + vertex pipelines) , core/memory : 650/1800mhz , 2 x dvi (with dvi to d-sub + dvi to HDMi converter) , HDTV+HDMi tvout
SC-A96GTTH512		Asus EN9600GT TOP/HTDI/512M , with Hdmi , geforce 9600GT , SLi support , Pci-E 2.0 16x , 512mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 64 stream processors @ 1.8Ghz (pixel shader engine + vertex pipelines) , core/memory : 720/2000mhz , 2 x dvi (with dvi to d-sub + dvi to HDMi converter) , HDTV+HDMi tvout

SC-A96GTH1G		Asus EN9600GT/HTDi/1G , with Hdmi , geforce 9600GT , SLi support , Pci-E 2.0 16x , 1Gb/1024mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 64 stream processors @ 1.625Ghz (pixel shader engine + vertex pipelines) , core/memory : 650/1800mhz , 2 x dvi (with dvi to d-sub + dvi to HDMi converter) , HDTV+HDMi tvout
SC-A96GTMH512		Asus EN9600GT MATRIX/HTDI/512M , with Hdmi , Advanced Dynamic GPU Loading Detection , Hybrid Engine + Hybrid Cooler (3d fansink mode or 2d heaatsink mode for silence and energy saving) , geforce 9600GT , SLi support , Pci-E 2.0 16x , 512mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 64 stream processors @ 1.625Ghz (pixel shader engine + vertex pipelines) , core/memory : 650/1800mhz , 2 x dvi (with dvi to d-sub + dvi to HDMi converter) , HDTV+HDMi tvout
SC-A88GT512		ASUS EN8800GT/HTDP/512 , geforce 8800GT , SLi support , Pci-E 2.0 16x , 512mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 112 stream processors @ 1.5Ghz (pixel shader engine + vertex pipelines) , core/memory : 600/1800mhz , 2 x dvi , HDTV tvout - retail pack with bundle DX10 game (Company of Heroes – Opposing Fronts) - recommend to use 500w on single card and 850w on SLi
SC-A88GT1G		ASUS EN8800GT/HTDP/1G , geforce 8800GT , SLi support , Pci-E 2.0 16x , 1Gb/1024mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 112 stream processors @ 1.5Ghz (pixel shader engine + vertex pipelines) , core/memory : 600/1800mhz , 2 x dvi , HDTV tvout - retail pack with bundle DX10 game (Company of Heroes – Opposing Fronts) - recommend to use 500w on single card and 850w on SLi
SC-A98GT	N	ASUS EN9800GT/HTDP/512MD3 , geforce 9800GT , SLi support , Pci-E 2.0 16x , 512mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 112 stream processors @ 1.5Ghz (pixel shader engine + vertex pipelines) , core/memory : 600/1800mhz , 2 x dvi (with dvi to d-sub) , HDTV tvout - retail pack
SC-A98GT1G		ASUS EN9800GT EN9800GT/HTDP/1GMD3 , with Hdmi , geforce 9800GT , SLi support , Pci-E 2.0 16x , 1024mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 112 stream processors @ 1.5Ghz (pixel shader engine + vertex pipelines) , core/memory : 600/1800mhz , 2 x dvi (with dvi to d-sub) , HDTV tvout - retail pack

SC-A98GTMH		ASUS EN9800GT MATRIX/HTDI/512M , with Hdmi , Advanced Dynamic GPU Loading Detection , Hybrid Engine + Hybrid Cooler (3d fansink mode or 2d heaatsink mode for silence and energy saving) , geforce 9800GT , SLi support , Pci-E 2.0 16x , 512mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 112 stream processors @ 1.5Ghz (pixel shader engine + vertex pipelines) , core/memory : 612/1800mhz , 2 x dvi (with dvi to d-sub + dvi to HDMi converter) , HDTV tvout - retail pack
SC-A98GTX+DK		Asus EN9800GTX+ DK/HTDI/512M , Dark Knight series with enthusiastic 4 Heat-pipe dark knight cooler , HDMi ready , geforce 9800GTX+ , SLi support , Pci-E 2.0 16x , 512mb 256bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 70.4Gb/sec memory transfer , 128 stream processors @ 1.84Ghz (pixel shader engine + vertex pipelines) , core/memory : 740/2200mhz , 2 x dvi (with dvi to d-sub converter + dvi to HDMi converter) , HDTV tvout
SC-A98GTX+TDK		Asus EN9800GTX+ DK TOP/HTDI/512M , Dark Knight series with enthusiastic 4 Heat-pipe dark knight cooler , HDMi ready , geforce 9800GTX+ , SLi support , Pci-E 2.0 16x , 512mb 256bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 70.4Gb/sec memory transfer , 128 stream processors @ 1.95Ghz (pixel shader engine + vertex pipelines) , core/memory : 775/2360mhz , 2 x dvi (with dvi to d-sub converter + dvi to HDMi converter) , HDTV tvout
SC-AGTS250	**C**	Asus ENGTS250/HTDi/512MD3 , with Hdmi , geforce GTS250 , SLi support , Pci-E 2.0 16x , 512mb 256bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 70.4Gb/sec memory transfer , 128 stream processors @ 1.84Ghz (pixel shader engine + vertex pipelines) , core/memory : 740/2200mhz , 2 x dvi (with dvi to d-sub converter + dvi to HDMi converter) , HDTV tvout
SC-AGTS250DK	**C**	Asus GTS250 DK/HTDi/512M , Dark Knight series with enthusiastic 4 Heat-pipe dark knight cooler , with Hdmi , geforce GTS250 , SLi support , Pci-E 2.0 16x , 512mb 256bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 70.4Gb/sec memory transfer , 128 stream processors @ 1.84Ghz (pixel shader engine + vertex pipelines) , core/memory : 740/2200mhz , 2 x dvi (with dvi to d-sub converter + dvi to HDMi converter) , HDTV tvout
SC-AGTS250DKT	**C**	Asus GTS250 DK Top/HTDi/512M , Dark Knight series with enthusiastic 4 Heat-pipe dark knight cooler, with Hdmi, geforce GTS250, SLi support, Pci-E 2.0 16x, 512mb 256bit DDR3, support DirectX 10+ shader model 4.0 +FP32 HDR+ 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 70.4Gb/sec memory transfer , 128 stream processors @ 1.84Ghz (pixel shader engine + vertex pipelines), core/memory : 775/2360mhz, 2 x dvi (with dvi to d-sub converter + dvi to HDMi converter) , HDTV tvout

SC-AGTS250DK1G	C	Asus GTS250 DK/HTDi/1GD3 , Dark Knight series with enthusiastic 4 Heat-pipe dark knight cooler , with Hdmi , geforce GTS250 , SLi support , Pci-E 2.0 16x , 1Gb/1024mb 256bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 70.4Gb/sec memory transfer , 128 stream processors @ 1.84Ghz (pixel shader engine + vertex pipelines) , core/memory : 740/2200mhz , 2 x dvi (with dvi to d-sub converter + dvi to HDMi converter) , HDTV tvout
SC-AGTX260		Asus ENGTX260/HTDP/896M , geforce GTX260 , SLi support , Pci-E 2.0 16x , support HybridPower , 896mb 448bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 111.9Gb/sec memory transfer , 192 stream processors @ 1.242Ghz (pixel shader engine + vertex pipelines) , core/memory : 576/1980mhz , 2 x dvi (with dvi to d-sub) , HDTV tvout
SC-AGTX260T	C	Asus ENGTX260 TOP/HTDP/896M , geforce GTX260 , SLi support , Pci-E 2.0 16x , support HybridPower , 896mb 448bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 111.9Gb/sec memory transfer , 192 stream processors @ 1.4Ghz (pixel shader engine + vertex pipelines) , core/memory : 650/2300mhz , 2 x dvi (with dvi to d-sub) , HDTV tvout
SC-AGTX260M	C	Asus ENGTX260 MATRIX/HTDI/896MD3 , Advanced Dynamic GPU Loading Detection , Hybrid Engine + Hybrid Cooler (3d fansink mode or 2d heaatsink mode for silence and energy saving) , geforce GTX260 , SLi support , Pci-E 2.0 16x , support HybridPower , 896mb 448bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 111.9Gb/sec memory transfer , 192 stream processors @ 1.242Ghz (pixel shader engine + vertex pipelines) , core/memory : 576/1980mhz , 2 x dvi (with dvi to d-sub) , HDTV tvout
SC-AGTX285	N	Asus ENGTX285/HTDP/1GD3 , geforce GTX285 , SLi support , Pci-E 2.0 16x , support HybridPower , 1Gb/1024mb 512bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 32 , 159Gb/sec memory transfer , 240 stream processors @ 1.476Ghz (pixel shader engine + vertex pipelines) , core/memory : 648/2484mhz , 2 x dvi (with dvi to d-sub + dvi to hdmi) , HDTV tvout
SC-AGTX285T	N	Asus ENGTX285 TOP/HTDi/1GD3 , geforce GTX285 , SLi support , Pci-E 2.0 16x , support HybridPower , 1Gb/1024mb 512bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 32 , 159Gb/sec memory transfer , 240 stream processors @ 1.55Ghz (pixel shader engine + vertex pipelines) , core/memory : 670/2600mhz , 2 x dvi (with dvi to d-sub + dvi to hdmi) , HDTV tvout
SC-A98GX2H		ASUS , EN9800GX2/G/2DI/1G , geforce 9800GX2 , dual GPU , Quad SLi support , Pci-E 2.0 16x , HDMi , support HybridPower , 1024mb 2x256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 2x16 , 2x64Gb/sec memory transfer , 2x128 stream processors @ 1.5Ghz (pixel shader engine + vertex pipelines) , core/memory : 600/2000mhz , 2 x dvi + 1 x HDMi , HDTV tvout , with bundled games - company of heros - require 1x6 pin + 1x8 pin power connector

SC-AGTX295	N	Asus ENGTX295/2Di/1792MD3 , geforce GTX295 Dual GPU , SLi support , Pci-E 2.0 16x , native HDMi , support HybridPower , 1792mb (2x896mb) 896bit (2x448bit) DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 2x28 , 223.8Gb/sec memory transfer , 2x240 stream processors @ 1.242Ghz (pixel shader engine + vertex pipelines) , core/memory : 576/2000mhz , 2 x dvi+ 1 x HDMi (with dvi to d-sub) , HDTV tvout
XFX		http://www.xfxforce.com/web/product/index.jspa?categoryId=1
SC-XALPK		XFX Low-Profile Kit - low-profile pci bracket for XFX vga card with low-profile PCB - single bracket for DVI+tv-out or bouble bracket for DVI+D-SUB+tv-out
SC-X84GSTC-L		XFX , no SLi , geforce 8400GS with TurboCache , Pci-E 16x , HDCP Compliant , 256+256mb (64bit 256mb DDR2 on-board + 128bit 256mb from system memory) , support DirectX 10.0 ; max dual link DVI resolution 2048x1536 , 3.6 billion/sec texture fill rate , 6.4Gb/sec memory transfer , 24 stream processors @ 1200Mhz (pixel shader engine + vertex pipelines) , core/memory : 450/800mhz , d-sub + dvi , HDTV tvout - retail pack ; support optional low-profile pci bracket
SC-X94GT512-L		XFX T94G-YAL/J , geforce 9400GT , Pci-E 2.0 16x , 512mb 128bit DDR2 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 4 , 16 stream processors @ 1.375Ghz (pixel shader engine + vertex pipelines) , core/memory : 550/800mhz , d-sub+dv , HDTV tvout ; support optional Low-profile pci bracket
SC-X94GT512	N	XFX T94G-YAR , geforce 9400GT , SLi support , Pci-E 2.0 16x , 512mb 128bit DDR2 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 4 , 16 stream processors @ 1.375Ghz (pixel shader engine + vertex pipelines) , core/memory : 550/800mhz , d-sub+dv , HDTV tvout
SC-X94GT1G-L		XFX T94G-ZAF , geforce 9400GT , Pci-E 2.0 16x , 1Gb/1024mb 128bit DDR2 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 4 , 16 stream processors @ 1.375Ghz (pixel shader engine + vertex pipelines) , core/memory : 550/800mhz , d-sub+dv , HDTV tvout ; support optional Low-profile pci bracket
SC-X95GT256D3		XFX T95G-UDF geforce 9500GT , SLi support , Pci-E 2.0 16x , 256mb 128bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 8 , 32 stream processors @ 1.093Ghz (pixel shader engine + vertex pipelines) , core/memory : 550/1600mhz , 2 x dvi+ dvi to HDMi converter , HDTV+HDMi tvout
SC-X95GT512D3		XFX T95G-YDF geforce 9500GT , SLi support , Pci-E 2.0 16x , 512mb 128bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 8 , 32 stream processors @ 1.093Ghz (pixel shader engine + vertex pipelines) , core/memory : 550/1600mhz , 2 x dvi+ dvi to HDMi converter , HDTV+HDMi tvout
SC-X95GT1GD2-L		XFX T95G-ZAF geforce 9500GT , SLi support , Pci-E 2.0 16x , 1Gb/1024mb 128bit DDR2 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 8 , 32 stream processors @ 1.093Ghz (pixel shader engine + vertex pipelines) , core/memory : 550/800mhz , 2 x dvi+ dvi to HDMi converter , HDTV+HDMi tvout ; support optional Low-profile pci bracket

SC-X96GSo384D3		XFX geforce 9600GSo , SLi support , Pci-E 2.0 16x , 384mb 192bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 40.8Gb/sec memory transfer , 96 stream processors @ 1.45Ghz (pixel shader engine + vertex pipelines) , core/memory : 580/1800mhz , 2 x dvi , HDTV tvout
SC-X96GSo384D3X		XFX geforce 9600GSo XXX edition , SLi support , Pci-E 2.0 16x , 384mb 192bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 40.8Gb/sec memory transfer , 96 stream processors @ 1.45Ghz (pixel shader engine + vertex pipelines) , core/memory : 680/1900mhz , 2 x dvi , HDTV tvout
SC-X96GSo768D2		XFX geforce 9600GSo , SLi support , Pci-E 2.0 16x , 768mb 192bit DDR2 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 40.8Gb/sec memory transfer , 96 stream processors @ 1.45Ghz (pixel shader engine + vertex pipelines) , core/memory : 580/2000mhz , 2 x dvi , HDTV tvout
SC-X96GSo768D2F	N	XFX geforce 9600GSo Fatal1ty edition , SLi support , Pci-E 2.0 16x , 768mb 192bit DDR2 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 40.8Gb/sec memory transfer , 96 stream processors @ 1.45Ghz (pixel shader engine + vertex pipelines) , core/memory : 580/2000mhz , 2 x dvi , HDTV tvout
SC-X96GT512		XFX geforce 9600GT , SLi support , Pci-E 2.0 16x , 512mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 64 stream processors @ 1.625Ghz (pixel shader engine + vertex pipelines) , core/memory : 650/1800mhz , 2 x dvi , HDTV tvout
SC-X96GTH512		XFX geforce 9600GT , HDMi ready , SLi support , Pci-E 2.0 16x , 512mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 64 stream processors @ 1.625Ghz (pixel shader engine + vertex pipelines) , core/memory : 650/1800mhz , 2 x dvi+ dvi to HDMi converter , HDTV+HDMi tvout
SC-X96GT1G	N	XFX geforce 9600GT , SLi support , Pci-E 2.0 16x , 1024mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 64 stream processors @ 1.625Ghz (pixel shader engine + vertex pipelines) , core/memory : 650/1800mhz , 2 x dvi , HDTV tvout - with bundled games - company of heros
SC-X98GT		XFX geforce 9800GT , SLi support , Pci-E 2.0 16x , 512mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 112 stream processors @ 1.5Ghz (pixel shader engine + vertex pipelines) , core/memory : 600/1800mhz , 2 x dvi , HDTV tvout - retail pack with bundle DX10 game (Company of Heroes – Opposing Fronts)
SC-X98GT1G		XFX geforce 9800GT , SLi support , Pci-E 2.0 16x , 1Gb/1024mb 256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 57.6Gb/sec memory transfer , 112 stream processors @ 1.5Ghz (pixel shader engine + vertex pipelines) , core/memory : 600/1800mhz , 2 x dvi , HDTV tvout - retail pack with bundle DX10 game (Company of Heroes – Opposing Fronts)

SC-XGTS250	N	XFX geforce GTS250 , 3-way SLi support , Pci-E 2.0 16x , support HybridPower , 512mb 256bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 70.4Gb/sec memory transfer , 128 stream processors @ 1.84Ghz (pixel shader engine + vertex pipelines) , core/memory : 738/2200mhz , 2 x dvi (with dvi to d-sub converter)
SC-XGTS2501G	C	XFX geforce GTS250 , 3-way SLi support , Pci-E 2.0 16x , support HybridPower , 1Gb/1024mb 256bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 70.4Gb/sec memory transfer , 128 stream processors @ 1.84Ghz (pixel shader engine + vertex pipelines) , core/memory : 738/2200mhz , 2 x dvi (with dvi to d-sub converter)
SC-XGTX280		Xfx geforce GTX280 , SLi support , Pci-E 2.0 16x , support HybridPower , 1024mb 512bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 16 , 141.7Gb/sec memory transfer , 240 stream processors @ 1.296Ghz (pixel shader engine + vertex pipelines) , core/memory : 602/2210mhz , 2 x dvi (with dvi to d-sub) , HDTV tvout
SC-XGTX285	N	Xfx GX-285N-ZDF , geforce GTX285 , SLi support , Pci-E 2.0 16x , support HybridPower , 1Gb/1024mb 512bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 32 , 159Gb/sec memory transfer , 240 stream processors @ 1.476Ghz (pixel shader engine + vertex pipelines) , core/memory : 648/2484mhz , 2 x dvi (with dvi to d-sub + dvi to hdmi) , HDTV tvout
SC-XGTX285X	N	Xfx GX-285N-ZDD XXX edition, geforce GTX285 , SLi support , Pci-E 2.0 16x , support HybridPower , 1Gb/1024mb 512bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 32 , 159Gb/sec memory transfer , 240 stream processors @ 1.476Ghz (pixel shader engine + vertex pipelines) , core/memory : 670/2500mhz , 2 x dvi (with dvi to d-sub + dvi to hdmi) , HDTV tvout
SC-XGTX285B	N	Xfx GX-285N-ZDB Black edition, geforce GTX285 , SLi support , Pci-E 2.0 16x , support HybridPower , 1Gb/1024mb 512bit DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 32 , 159Gb/sec memory transfer , 240 stream processors @ 1.476Ghz (pixel shader engine + vertex pipelines) , core/memory : 690/2600mhz , 2 x dvi (with dvi to d-sub + dvi to hdmi) , HDTV tvout
SC-X98GX2HB		XFX geforce 9800GX2 , dual GPU , Quad SLi support , Pci-E 2.0 16x , HDMi , support HybridPower , 1024mb 2x256bit DDR3 , support DirectX 10.0 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 2x16 , 2x64Gb/sec memory transfer , 2x128 stream processors @ 1.7Ghz (pixel shader engine + vertex pipelines) , core/memory : 700/2100mhz , 2 x dvi + 1 X HDMi , HDTV tvout - with bundled game Assassin's Creed ; require 1x6 pin + 1x8 pin power connector

SC-XGTX295	N	Xfx GX-295N , geforce GTX295 Dual GPU , SLi support , Pci-E 2.0 16x , native HDMi , support HybridPower , 1792mb (2x896mb) 896bit (2x448bit) DDR3 , support DirectX 10 + shader model 4.0 +FP32 HDR + 16x AA ; max resolution 2560x1600 , HDCP Compliant , RoPs : 2x28 , 223.8Gb/sec memory transfer , 2x240 stream processors @ 1.242Ghz (pixel shader engine + vertex pipelines) , core/memory : 576/2000mhz , 2 x dvi+ 1 x HDMi (with dvi to d-sub) , HDTV tvout

PCi-EXPRESS- ATi		
XFX		
SC-X4350512-SL	N	XFX HD-435X-YAH , HD4350 chipset , Silent heatsink only ; include Low-profile pci bracket , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 64bit DDR2 , RoPs : 4 , 80 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/1000mhz , DVi+d-sub , HDTV-out - retail pack
SC-X4650512	N	XFX HD-465X-YAF , HD4650 chipset , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 128bit DDR2 , RoPs : 8 , 21.3Gb/sec memory transfer , 320 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/800mhz , DVi+d-sub , HDTV-out - retail pack
SC-X46501G	N	XFX HD-465X-ZDF , HD4650 chipset , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1Gb/1024mb 128bit DDR2 , RoPs : 8 , 21.3Gb/sec memory transfer , 320 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/1000mhz , dual DVi + dvi to d-sub converter , HDTV-out - retail pack
SC-X4830512	N	XFX HD-483X-YDH , HD4830 chipset , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 256bit 4 channel DDR3 , 640 stream processors (pixel shader engine + vertex pipelines) , core/memory : 575/1800mhz , dual dvi (with dvi to d-sub converter) , HDTV tv-out - full retail pack
SC-X4850H512X	N	XFX HD-485X-YDD , XXX edition , HD4850 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 256bit 4 channel DDR3 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 650/2100mhz , dual dvi (with dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out - full retail pack
SC-X4870H512	N	XFX HD-487A-YDF , HD4870 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 256bit 4 channel DDR5 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 750/3600mhz , dual dvi (with dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out - full retail pack
SC-X4870H1G	N	XFX HD-487A-ZDF , HD4870 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1Gb/1024mb 256bit 4 channel DDR5 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 750/3600mhz , dual dvi (with dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out - full retail pack

SC-X4870H1GX	N	XFX HD-487A-ZDD , XXX edition , HD4870 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1Gb/1024mb 256bit 4 channel DDR5 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 775/3800mhz , dual dvi (with dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out - full retail pack
SC-X4890H	C	Xfx HD-489A-ZDF , HD4890 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1024mb 256bit 4 channel DDR5 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 850/3900mhz , dual dvi (with 1 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out
SC-X4890HRT	C	Xfx HD-489A-ZDE , HD4890 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1024mb 256bit 4 channel DDR5 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 875/3900mhz , dual dvi (with 1 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out
Sapphire		
SC-S3450256-SL		Sapphire 11125-02-20R , HD3450 chipset , HDMi ready , Silencer , include Low-profile pci bracket , built-in HDMi codec+5.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 256mb 64bit DDR2 , 40 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/1000mhz , dvi + d-sub + dvi to HDMi converter , HDTV-out - lite retail pack
SC-S3450512-S		Sapphire 11125-04-20R , HD3450 chipset , Silencer , built-in HDMi codec+5.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 64bit DDR2 , 40 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/1000mhz , dual dvi (with dvi to d-sub converter) , HDTV-out - lite retail pack
SC-S3470H256-S		Sapphire 11126-00-20R , HD3470 chipset , HDMi ready , Silencer , support crossfire-X , built-in HDMi codec+5.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 256mb 64bit DDR3 , 40 stream processors (pixel shader engine + vertex pipelines) , core/memory : 800/1400mhz , dual dvi (with dvi to d-sub + dvi to hdmi converter) , HDTV-out - lite retail pack
SC-S2600P		Sapphire 11117-01-20R , HD2600pro chipset , support DirectX 10.0 , HDCP Compliant , pci-e x16 , 256mb 128bit DDR2 , RoPs : 4 , 16Gb/sec memory transfer , 120 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/1000mhz , dual dvi (with 2 dvi to d-sub converter) , HDTV-out - retail pack
SC-S4350H-SL	N	Sapphire 11142-07-20R , Hdmi ready , Silent heatsink only + Low-profile pci bracket , no noise , HD4350 chipset , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 64bit DDR2 , RoPs : 4 , 80 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/800mhz , DVi+d-sub+Hdmi , HDTV-out - retail pack
SC-S4350HHM-SL	N	Sapphire 11142-09-20R , Hdmi ready , support Hyper Memory , Silent heatsink only + Low-profile pci bracket , no noise , HD4350 chipset , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 64bit DDR2 512mb upto 1Gb hyper memory , RoPs : 4 , 80 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/800mhz , DVi+d-sub+Hdmi , HDTV-out - retail pack

SC-S4550H-SL	N	Sapphire 11141-05-20R , HD4550 chipset , HDMi ready , Silent heatsink only + Low-profile pci bracket , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 64bit DDR3 , RoPs : 4 , 80 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/1600mhz , DVi+d-sub+HDMi , HDTV-out - retail pack
SC-S4550HHM-SL	N	Sapphire 11141-06-20R , HD4550 chipset , HDMi ready , support Hyper Memory , Silent heatsink only + Low-profile pci bracket , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 64bit DDR3 512mb upto 1Gb hyper memory , RoPs : 4 , 80 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/1600mhz , DVi+d-sub+HDMi , HDTV-out - retail pack
SC-S4650H512D2		Sapphire 11140-02-40R , HD4650 chipset , HDMi ready , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 128bit DDR2 , RoPs : 8 , 21.3Gb/sec memory transfer , 320 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/1000mhz , DVi+d-sub , with DVi to HDMi adapter , HDTV-out - retail pack
SC-S4650H1GD2		Sapphire 11140-01-40R , HD4650 chipset , HDMi ready , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1Gb/1024mb 128bit DDR2 , RoPs : 8 , 21.3Gb/sec memory transfer , 320 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/1000mhz , DVi+d-sub , with dvi to hdmi converter , HDTV-out - retail pack
SC-S4670H512		Sapphire 11138-13-40R HD4670 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 128bit DDR3 , RoPs : 16 , 32Gb/sec memory transfer , 320 stream processors (pixel shader engine + vertex pipelines) , core/memory : 750/2008mhz , dvi+d-sub+hdmi , HDTV-out - retail pack
SC-S4670H1G	N	Sapphire 11138-01-40R HD4670 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1Gb/1024mb 128bit DDR3 , RoPs : 16 , 32Gb/sec memory transfer , 320 stream processors (pixel shader engine + vertex pipelines) , core/memory : 750/2008mhz , dual dvi (with dvi to d-sub + dvi to HDMi converter) , HDTV-out - retail pack
SC-S4830H512	N	Sapphire 11147-00-40R , HD4830 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 256bit 4 channel DDR3 , 640 stream processors (pixel shader engine + vertex pipelines) , core/memory : 575/1800mhz , dual dvi (with dvi to d-sub + dvi to HDMi converter) , HDTV+HDMi tv-out - full retail pack with bundle software
SC-S4830H1G	N	Sapphire 11147-02-40R , HD4830 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1Gb/1024mb 256bit 4 channel DDR3 , 640 stream processors (pixel shader engine + vertex pipelines) , core/memory : 575/1800mhz , dual dvi (with dvi to d-sub + dvi to HDMi converter) , HDTV+HDMi tv-out - full retail pack with bundle software

SC-S4850H512		Sapphire 11132-12-40R , HD4850 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 256bit 4 channel DDR3 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 625/1986mhz , dual dvi (with 2 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out - full retail pack
SC-S4850H512T		Sapphire 11132-04-40R , Toxic , HD4850 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 256bit 4 channel DDR3 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 675/2200mhz , dual dvi (with 2 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out - full retail pack
SC-S4850H1G		Sapphire 11132-00-40R , HD4850 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1Gb 256bit 4 channel DDR3 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 625/1986mhz , dual dvi (with 2 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out - full retail pack
SC-S4850Hx22G	N	Sapphire , HD4850X2 (Dual hd4850) chipset , 4xDVi + HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 2Gb(2x1024mb) 256bit 4 channel DDR3 , 2x800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 2x625/2x1986mhz , quad dvi (with dvi to d-sub + dvi to HDMi converter) , HDTV+HDMi tv-out - full retail pack
SC-S3870Hx2		Sapphire 21122-05-40R , Dual HD3870 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+5.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1Gb/1024mb 256bit 4 channel DDR3 , 320 stream processors (pixel shader engine + vertex pipelines) , core/memory : 775/2250mhz , dual dvi (with dvi to d-sub + dvi to HDMi converter) , HDTV+RCA+s-video+component+HDMi tv-out - full retail pack with bundled 3d mark + dvd suite + powerdvd + games voucher - Half Life2 + Team Fortress 2, Portal
SC-S4870H512		Sapphire 21133-00-40R , HD4870 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 256bit 4 channel DDR5 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 750/3600mhz , dual dvi (with 2 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out - full retail pack
SC-S4870H512T	N	Sapphire 21133-06-40R , Toxic , HD4870 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 256bit 4 channel DDR5 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 780/4000mhz , dual dvi (with 2 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out - full retail pack
SC-S4870x2H		Sapphire 21137-00-40R , HD4870X2 (Dual hd4870) chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 2Gb(2x1024mb) 256bit 4 channel DDR5 , 2x800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 750/3600mhz , dual dvi (with 2 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out - full retail pack

SC-S4870x2HT	N	Sapphire 11137-00-40R , HD4870X2 Toxic edition , water cooling ready , gift box packaging , Dual hd4870 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 2Gb(2x1024mb) 256bit 4 channel DDR5 , 2x800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 750/3600mhz , dual dvi (with 2 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out - full retail pack
ASUS		http://www.asus.com/products.aspx?l1=2&l2=8
SC-A3450H256-SL		Asus EAH3450/DI/256M , Silent heatsink only , include Low-profile pci bracket , HDMi ready , no noise , HD3450 chipset , built-in HDMi codec+5.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 256mb 64bit DDR2 , 40 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/800mhz , dvi-i +d-sub+HDMi
SC-A3450512-S		Asus EAH3450/HTP/512M , Silent heatsink only , no noise , HD3450 chipset , built-in HDMi codec+5.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 64bit DDR2 , 40 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/1000mhz , dvi-i +d-sub , HDTV-out
SC-A4350H512-S		Asus EAH4350 silent/Di/512MD2 , Silent heatsink only , no noise , HD4350 chipset , HDMi ready , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 64bit DDR2 , RoPs : 4 , 80 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/800mhz , DVi+d-sub+HDMi , HDTV-out
SC-A4550H512-L		Asus EAH4550/DI/512MD3 , HD4550 chipset , HDMi ready , include Low-profile pci bracket , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 64bit DDR3 , RoPs : 4 , 80 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/1600mhz , DVi+d-sub+HDMi , HDTV-out
SC-A4650H512D2		Asus EAH4650/Di/512MD2 , HD4650 chipset , HDMi ready , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 128bit DDR2 , RoPs : 8 , 21.3Gb/sec memory transfer , 320 stream processors (pixel shader engine + vertex pipelines) , core/memory : 600/800mhz , DVi+d-sub+HDMi , HDTV-out
SC-A4670H512D3		Asus EAH4670/Di/512M , HD4670 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 128bit DDR3 , RoPs : 16 , 32Gb/sec memory transfer , 320 stream processors (pixel shader engine + vertex pipelines) , core/memory : 750/2008mhz , DVi+d-sub with dvi to HDMi converter , HDTV-out
SC-A4830512		Asus EAH4830/HTDP/512MD3 , HD4830 chipset , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 256bit 4 channel DDR3 , 640 stream processors (pixel shader engine + vertex pipelines) , core/memory : 575/2000mhz , dual dvi (with dvi to d-sub converter) , HDTV+HDMi tv-out
SC-A4850H512		Asus EAH4850/HTDI/512M , HD4850 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 256bit 4 channel DDR3 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 625/1986mhz , dual dvi (with 2 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out

SC-A4850H1G		Asus EAH4850/HTDI/1G , HD4850 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1024mb 256bit 4 channel DDR3 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 625/1986mhz , dual dvi (with 2 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out
SC-A4870H512		Asus EAH4870/HTDI/512M , HD4870 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 256bit 4 channel DDR5 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 750/3600mhz , dual dvi (with 1 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out
SC-A4870H512DK		Asus EAH4870 DK/HTDI/512MD5 , Dark Knight series with enthusiastic 4 Heat-pipe dark knight cooler , HD4870 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 512mb 256bit 4 channel DDR5 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 750/3600mhz , dual dvi (with 1 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out
SC-A4870H1GDK		Asus EAH4870 DK/HTDI/1GD5 , Dark Knight series with enthusiastic 4 Heat-pipe dark knight cooler , HD4870 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1Gb 256bit 4 channel DDR5 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 750/3600mhz , dual dvi (with 1 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out - full retail pack
SC-A4890H	C	Asus EAH4890/HTDI/1GD5 , HD4890 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1Gb/1024mb 256bit 4 channel DDR5 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 850/3900mhz , dual dvi (with 1 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out
SC-A4890HT	C	Asus EAH4890 ToP/HTDI/1GD5 , HD4890 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1Gb/1024mb 256bit 4 channel DDR5 , 800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 900/4000mhz , dual dvi (with 1 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out
SC-A3870HX2		Asus EAH3870X2/G/HTDi/1G , dual HD3870 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+5.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1Gb/1024mb 256bit 4 channel DDR3 , 320 stream processors (pixel shader engine + vertex pipelines) , core/memory : 825/1800mhz , dual dvi (with 2 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out , support 8pin pci-e 2.0 power connector for overdrive - with bundled games company of heros

SC-A3870HX2T-4D		Asus EAH3870X2 Top/G/3DHTi/1G , 4 Dvi , dual HD3870 chipset , HDMi ready , support crossfire-X , built-in HDMi codec+5.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 1Gb/1024mb 256bit 4 channel DDR3 , 320 stream processors (pixel shader engine + vertex pipelines) , core/memory : 851/1900mhz , 4 x dvi (with 1 x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out , support 8pin pci-e 2.0 power connector for overdrive - full retail pack with bundled games company of heros
SC-A4870X2H		Asus EAH4870X2/HTDI/2G , HD4870x2 (Dual hd4870) chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 2Gb(2x1024mb) 512bit 4 channel DDR5 , 2x800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 750/3600mhz , dual dvi (with 1x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out
SC-A4870X2TH		Asus EAH4870X2 Top/HTDI/2G , HD4870x2 (Dual hd4870) chipset , HDMi ready , support crossfire-X , built-in HDMi codec+7.1 audio , support DirectX 10.1 , 1080p HDCP Compliant , pci-e 2.0 x16 , 2Gb(2x1024mb) 512bit 4 channel DDR5 , 2x800 stream processors (pixel shader engine + vertex pipelines) , core/memory : 790/3666mhz , dual dvi (with 1x dvi to d-sub + 1 x dvi to HDMi converter) , HDTV+HDMi tv-out
AGP- nViDiA		
XFX		
SC-XALPK		XFX Low-Profile Kit - low-profile pci bracket for XFX vga card with low-profile PCB - single bracket for DVI+tv-out or bouble bracket for DVI+D-SUB+tv-out
SC-XA62256-SL		XFX T44A/D-WAN/H/M , AGP 8x , geforce fx6200 , 256mb 64bit ddr , core/memory : 350/500mhz , dvi+d-sub , tvout - NO dvi to d-sub converter ; support optional low-profile pci bracket
SC-XA62512-SL	N	XFX T44A-YAJ , AGP 8x , geforce fx6200 , 512mb 64bit ddr2 , core/memory : 350/533mhz , dvi+d-sub , tvout - NO dvi to d-sub converter ; support optional low-profile pci bracket
AGP- ATi		
SC-SA3650H512		Sapphire 11129-00-20R , HD3650 chipset , support DirectX 10.1 , AGP x8 , 512mb 128bit DDR2 , 120 stream processors (pixel shader engine + vertex pipelines) , core/memory : 725/1600mhz , dual dvi (with dvi to d-sub converter) , HDTV-out - lite retail pack
SC-SA3850H512		Sapphire 11124-00-40R , HD3850 chipset , support DirectX 10.1 , AGP x8 , 512mb 256bit DDR3 , 320 stream processors (pixel shader engine + vertex pipelines) , core/memory : 670/1666mhz , dual dvi (with dvi to d-sub converter) , HDTV-out - retail pack - include 3dmark , cyberlink DVD suite , powerdvd
Screen Card for 3D graphic workstation		
PCi-EXPRESS		
SC-PQF370		PNY Quadro Fx370 - for professional 3D applications , hardware OpenGL 2.1+ directX 10 , support HPDR + HDCP , Pci-E 16x , 2.88 billion texels/sec , 66 million triangles/sec , 64bit 256mb DDR2 (transfer rate : 6.4gb/sec) , 16 CUDA parallel processor cores , 16 x RG FSAA , 1dvi + 1 x Dual-Link DVi + d-sub connector + s-video out - upto 3840x2400 on each display - retail pack - 3 years warranty

SC-PQF370L	R	PNY Quadro Fx370 , with Low-profile bracket - for professional 3D applications , hardware OpenGL 2.1+ directX 10 , support HPDR + HDCP , Pci-E 16x , 2.88 billion texels/sec , 66 million triangles/sec , 64bit 256mb DDR2 (transfer rate : 6.4gb/sec) , 16 CUDA parallel processor cores , 16 x RG FSAA , 1dvi + 1 x Dual-Link DVi + d-sub connector + s-video out - upto 3840x2400 on each display - retail pack - 3 years warranty
SC-PQF570		PNY Quadro Fx570 - for professional 3D applications , hardware OpenGL 2.1+ directX 10 , support HPDR + HDCP , Pci-E 16x , 3.68 billion texels/sec , 137 million triangles/sec , 128bit 256mb DDR2 (transfer rate : 12.8gb/sec) , 16 CUDA parallel processor cores , 16 x RG FSAA , 2 x Dual-Link DVi + d-sub connector + s-video out - upto 3840x2400 on each display - retail pack - 3 years warranty
SC-PQF1700		PNY Quadro Fx1700 - for professional 3D applications , hardware OpenGL 2.1+ directX 10 , support HPDR + HDCP , Pci-E 16x , 7.36 billion texels/sec , 191 million triangles/sec , 128bit 512mb DDR2 (transfer rate : 12.8gb/sec) , 32 CUDA parallel processor cores , 32 x RG FSAA , 2 x Dual-Link DVi + d-sub connector + s-video out - upto 3840x2400 on each display - retail pack - 3 years warranty
SC-PQF1700V		PNY Quadro Fx1700 Video edition with bundle video breakout box (component + s-video + RCA video out) - for professional 3D applications , hardware OpenGL 2.1+ directX 10 , support HPDR + HDCP , Pci-E 16x , 7.36 billion texels/sec , 191 million triangles/sec , 128bit 512mb DDR2 (transfer rate : 12.8gb/sec) , 32 CUDA parallel processor cores , 32 x RG FSAA , 2 x Dual-Link DVi + d-sub connector + s-video out - upto 3840x2400 on each display - retail pack - 3 years warranty
SC-PQF3700	R	PNY Quadro Fx3700 - for professional 3D applications , hardware OpenGL 2.1+ directX 10 , support SLi + HPDR , Pci-E 16x , 28 billion texels/sec , 250 million triangles/sec , 256bit 512mb GDDR3 (transfer rate : 51.2gb/sec) , 112 CUDA parallel processor cores , 32 x RG FSAA , DVi + d-sub + stereo connector - retail pack - 3 years warranty
SC-PQF4800	**C**	PNY Quadro Fx4800 - for professional 3D applications , hardware OpenGL 3.0+ directX 10 , support SLi + HPDR , Pci-E 16x , dual 400MHz DAC , 38.4 billion texels/sec , 300 million triangles/sec , dual 400mhz ramdac , 384bit 1.5gb GDDR3 (transfer rate : 76.8gb/sec) , 192 CUDA parallel processor cores , 16x RG FSAA , 1xDVi + converter + 2xdisplay port+ stereo connector + s-video out - retail pack - 3 years warranty
SC-PQF4700x2	R	PNY Quadro Fx4700x2 - for professional 3D applications , hardware OpenGL 2.1+ directX 10 , 2 GPU for 4 x DVi display , support SLi + HPDR , Pci-E 16x , dual 400MHz DAC , 32 billion texels/sec , 250 million triangles/sec , dual 400mhz ramdac , 256bit 2Gb/2048mb (2x1Gb) GDDR3 (transfer rate : 51.2gb/sec) , 2x128 CUDA parallel processor cores , 64x FSAA , 4xDVi + converter + stereo connector + s-video out - retail pack - 3 years warranty
SC-PQF5800	R	PNY Quadro Fx5800 - for professional 3D applications , hardware openGL 3.0+directX10 , support SLi + HPDR , Pci-E 16x , dual 400MHz DAC , 52 billion texels/sec , 300 million triangles/sec , dual 400mhz ramdac , 512bit 4Gb(4096mb) GDDR3 (transfer rate : 102gb/sec) , 240 CUDA parallel processor cores , 2xDVi + converter + stereo connector + display port + s-video out - retail pack - 3 years warranty

Video Switch

VS-SHDMS21C		Sunix HDMS21C - 2 port HDMI video switch (for audio + video) with remote control , support HDCP, HDMI ver1.3 , HD Dolby + DTS-HD master audio , bandwideth : 340Mhz/10.2Gbps , 30/36/48bit color - for PS3 , PC , HD/Blu-ray dvd player .. ETC
VS-APE221	N	Aavara PE221 1080p HDMI v1.3 extender over cat5/utp (70m for 1080i or 45m for 1800p) , include sender+receiver , 2x input + 1x output - support 7.1 dolby digital
VS-APS122	N	Aavara PS122 - 1 signal to 2 display 1080p HDMI splitter for audio+video , support daisy chain upto 128x hdmi display , with remote control , support HDCP, HDMI ver1.3 , 7.1 HD Dolby + DTS-HD master audio , bandwideth : 340Mhz/10.2Gbps , 36bit color - for PS3 , PC , HD/Blu-ray dvd player .. ETC - support daisy chain
VS-APS124	N	Aavara PS124 - 1 signal to 4 display 1080p HDMI splitter for audio+video , support daisy chain upto 256x hdmi display , with remote control , support HDCP, HDMI ver1.3 , 7.1 HD Dolby + DTS-HD master audio , bandwideth : 340Mhz/10.2Gbps , 36bit color - for PS3 , PC , HD/Blu-ray dvd player .. ETC - support daisy chain
VS-APS128	N	Aavara PS128 - 1 signal to 8 display 1080p HDMI splitter for audio+video , support daisy chain upto 512x hdmi display , with remote control , support HDCP, HDMI ver1.3 , 7.1 HD Dolby + DTS-HD master audio , bandwideth : 340Mhz/10.2Gbps , 36bit color - for PS3 , PC , HD/Blu-ray dvd player .. ETC - support daisy chain
VS-ASW421	N	Aavara SW421 - 4 signal to 1 display 1080p HDMI switch (for audio + video) with remote control , support HDCP, HDMI ver1.3 , 7.1 HD Dolby + DTS-HD master audio , bandwideth : 340Mhz/10.2Gbps , 36bit color - for PS3 , PC , HD/Blu-ray dvd player .. ETC
VS-ASS422	N	Aavara SS422 - 4 signal to 2 display 1080p HDMI switch (for audio + video) with remote control , support HDCP, HDMI ver1.3 , 7.1 HD Dolby + DTS-HD master audio , bandwideth : 340Mhz/10.2Gbps , 36bit color - for PS3 , PC , HD/Blu-ray dvd player .. ETC - support daisy chain
VS-APM4X2	R	Aavara PM4X2 - 4 signal to 2 display 1080p HDMI matrix switch/spliter (for audio + video) with remote control , support HDCP, HDMI ver1.3 , 7.1 HD Dolby + DTS-HD master audio , bandwideth : 340Mhz/10.2Gbps , 36bit color - for PS3 , PC , HD/Blu-ray dvd player .. ETC - support daisy chain - transmit same source or 2 different sources to 2 display
VS-APM4X4	R	Aavara PM4X4 - 4 signal to 4 display 1080p HDMI matrix switch/spliter (for audio + video) with remote control , support HDCP, HDMI ver1.3 , 7.1 HD Dolby + DTS-HD master audio , bandwideth : 340Mhz/10.2Gbps , 36bit color - for PS3 , PC , HD/Blu-ray dvd player .. ETC - support daisy chain - transmit same source or 4 different sources to 4 display
CA-SDH1	N	Sunix DTHGP1M - DVI to HDMI cable , for video - 1m
CA-SDH2		Sunix DTHGP2M - DVI to HDMI cable , for video - 2m
CA-SDH3		Sunix DTHGP3M - DVI to HDMI cable , for video - 3m
CA-SHH1	N	Sunix HTHGP1M - HDMI to HDMI cable , carry video+audio signal - 1m
CA-SHH2		Sunix HTHGP2M - HDMI to HDMI cable , carry video+audio signal - 2m
CA-AHH2	N	Aavara SDC20 - HDMI to HDMI cable , carry video+audio signal - 2m - retail pack
CA-SHH3		Sunix HTHGP3M - HDMI to HDMI cable , carry video+audio signal - 3m
CA-AHH5	N	Aavara PHC50 - HDMI to HDMI cable , carry video+audio signal - 5m - retail pack
CA-AHH10	N	Aavara PHC100 - HDMI to HDMI cable , carry video+audio signal - 10m - retail pack

CA-AHH15	N	Aavara PHC150 - HDMI to HDMI cable , carry video+audio signal - 15m - oem pack
Tv-Tuner		
RE-CK100		Compro K100 remote control for MCE (Media Center Edition) , ideal for upgrading vista home preminum / ultimate to MCE , 51-keys , with bundled microsoft certified MPEG-2 encoder , reatil pack - usb receiver included
RE-CK200	N	Compro K200 remote control for MCE (Media Center Edition) , ideal for upgrading vista home preminum / ultimate to MCE , 48-keys , with bundled microsoft certified MPEG-2 encoder , reatil pack - usb receiver included
RE-AVEZ	N	Antec Veris E-Z remote control for MCE (Media Center Edition) , clipable design usb receiver for Lcd or notebook , designed by iMON , ideal for upgrading vista home preminum / ultimate to MCE , 18-keys , with bundled microsoft certified MPEG-2 encoder , reatil pack
RE-AVB	N	Antec Veris Basic remote control for MCE (Media Center Edition) , receiver for 3.5" bay , black , designed by iMON , ideal for upgrading vista home preminum / ultimate to MCE , 18-keys , with bundled microsoft certified MPEG-2 encoder , reatil pack
CH-AAVE	N	Antec Veris Elite VFD module with MCE (Media Center Edition) remote control + control knob , for 5.25" bay , black , designed by iMON , ideal for upgrading vista home preminum / ultimate to MCE , 58-keys , with bundled microsoft certified MPEG-2 encoder , reatil pack
CH-AAVP	N	Antec Veris Premier VFD module with MCE (Media Center Edition) remote control + 2 x control knob + multimedia buttons , for 2 x 5.25" bay , black , designed by iMON , ideal for upgrading vista home preminum / ultimate to MCE , 58-keys , with bundled microsoft certified MPEG-2 encoder , reatil pack
video catpure / video recording		
VR-CC100	C	Compro C100 videomate capture card , pci , capture video and save to hard disk or burn directly to DVD with Straight-to-Disc technology , audio (R+L) input + video (RCA+S-video) input - with bnndle Ulead videostudio 11 + dvd moviefactory
VR-CC200		Compro C200 videomate capture usb stick , usb2.0 , capture video and save to hard disk or burn directly to DVD with Straight-to-Disc technology , audio (R+L) input + video (RCA+S-video) input , 94x32x18mm - with bnndle Ulead videostudio 11 + dvd moviefactory
DVB-S digital		
TT-CS500		COMPRO videomate S500 , external palm size Usb digital satellite (DVB-S) TV tuner with remote control , with pc power-up scheduling + pc power on/off on remote , support DiSEqC Version 1.2 , HDTV , 1080i HD ; philips chipset , MPEG 1/2/4 encoding , video in (s-video+rca) + audio in/out (3.5mm) ; support timeshifting, channel surfing, still frame capture, digital EPG, subtitle and Teletext , Picture Purifying Technology ; support PIP/POP up to 4 sub channels watching , support TV screen as wallpaper , Straight-to-Disc for direct burn TV shows on VCD and DVD ; bundle software : Ulead photo explorer 8.5SE

TT-CS300		COMPRO videomate S300 , internal pci digital satellite (DVB-S) TV tuner card with remote control , support DiSEqC Version 1.2 , HDTV , 1080i HD ; philips chipset , MPEG 1/2/4 encoding , video in (s-video+rca) + audio in/out (3.5mm) ; support timeshifting, channel surfing, still frame capture, digital EPG, subtitle and Teletext , Picture Purifying Technology ; support PIP/POP up to 4 sub channels watching , support TV screen as wallpaper , Straight-to-Disc for direct burn TV shows on VCD and DVD ; bundle software : Ulead photo explorer 8.5SE
TT-CS350		COMPRO videomate S350 , internal pci digital satellite (DVB-S) TV tuner card with remote control , with pc power-up scheduling + pc power on/off on remote , support DiSEqC Version 1.2 , HDTV , 1080i HD ; philips chipset , MPEG 1/2/4 encoding , video in (s-video+rca) + audio in/out (3.5mm) ; support timeshifting, channel surfing, still frame capture, digital EPG, subtitle and Teletext , Picture Purifying Technology ; support PIP/POP up to 4 sub channels watching , support TV screen as wallpaper , Straight-to-Disc for direct burn TV shows on VCD and DVD ; bundle software : Ulead photo explorer 8.5SE
TT-CS800F	**C**	COMPRO videomate S800F , internal pci-Express , analog + dual digital DVB-T + satellite (DVB-S) , TV tuner + FM radio , with remote control , with pc power-up scheduling + pc power on/off on remote , support DiSEqC Version 1.2 , HDTV , 1080i HD ; philips chipset , MPEG 1/2/4 encoding , video in (s-video+rca) + audio in/out (3.5mm) ; support timeshifting, channel surfing, still frame capture, digital EPG, subtitle and Teletext , Picture Purifying Technology ; support PIP/POP up to 4 sub channels watching , support TV screen as wallpaper , Straight-to-Disc for direct burn TV shows on VCD and DVD ; bundle software : Ulead movie factory - include low-profile bracket
Pcmcia		
TT-CP300		COMPRO P300 videomate with pc power-up scheduling + pc power on/off on remote (44 keys) , pcmcia , stereo sound , tv-tuner + FM radio , with remote control , Philips SAA7135 chipset , MPEG 1/2/4 encoding , video in (s-video+rca) + audio in/out (3.5mm) ; support PiP/PoP/video as desktop, teletext , timeshifting , Picture Purifying Technology , Straight-to-Disc for direct burn TV shows on VCD and DVD ; bundle software : Ulead photo explorer 8.5SE , movie factory 3SE
external set-top box		
TT-CV150	**N**	COMPRO V150 set-top box , black , pc-free external tv-tuner (turn your CRT/LCD/PDP/Projector into TV or Game console display) , support 16:9/16:10 wide screen display , support PiP/PoP/video as desktop , support upto 1440x900/1280x1024 , stereo sound , no FM , with remote control , video in (s-video+rca) , audio in (RCA + 3.5mm) , built-in speaker ; sleep mode timers
TT-CV150F	**N**	COMPRO V150F set-top box , black , pc-free external tv-tuner (turn your CRT/LCD/PDP/Projector into TV or Game console display) , support 16:9/16:10 wide screen display , support PiP/PoP/video as desktop , support upto 1440x900/1280x1024 , stereo sound , with FM , with remote control , video in (s-video+rca) , audio in (RCA + 3.5mm) , built-in speaker ; sleep mode timers

TT-CV200		COMPRO V200 set-top box , pearl white , pc-free external tv-tuner (turn your CRT/LCD/PDP/Projector into TV or Game console display) , support 16:9/16:10 wide screen display , support PiP/PoP/video as desktop , support upto 1680x1050/1600x1200 , stereo sound , no FM , with remote control , video in (s-video+rca) , audio in (RCA + 3.5mm) , built-in speaker ; sleep mode timers
TT-CV200F		COMPRO V200F set-top box with FM radio , pearl white , pc-free external tv-tuner (turn your CRT/LCD/PDP/Projector into TV or Game console display) , support 16:9/16:10 wide screen display , support PiP/PoP/video as desktop , support upto 1680x1050/1600x1200 , stereo sound ,with remote control , video in (s-video+rca) , audio in (RCA + 3.5mm), built-in speaker ; sleep mode timers
TT-CV300		COMPRO V300 set-top box , black , pc-free external tv-tuner (turn your CRT/LCD/PDP/Projector into TV or Game console display) , support 16:9/16:10 wide screen display , support PiP/PoP/video as desktop , support upto 1680x1050/1600x1200 , stereo sound , no FM , with remote control , video in (s-video+rca+component) , audio in (RCA + 3.5mm) ; sleep mode timers
TT-CV600		COMPRO V600 set-top box , pearl white , pc-free external tv-tuner with 2D+3D Y/C , (turn your CRT/LCD/PDP/Projector into TV or Game console display) , support 16:9/16:10 wide screen display , support PiP/PoP/video as desktop , support upto 1680x1050/1600x1200 , stereo sound , no FM , with remote control , video in (s-video+rca+component) , audio in (RCA + 3.5mm) ; sleep mode timers
External USB		
TT-CU890		COMPRO videomate U890 analog stick - flash drive size (94x32x18mm) , usb 2.0 tv-tuner , usb-powered , with pc power-up scheduling (from S3/S4 mode) , with (32 keys - credit card size) , MPEG 1/2/4 encoding , support PiP/PoP/video as desktop , teletext , timeshifting , Straight-to-Disc for direct burn TV shows on VCD and DVD ; bundle software : Ulead movie factory
TT-CU890FM		COMPRO videomate U890F Mce analog stick - flash drive size (94x32x18mm) , usb 2.0 , usb-powered , with pc power-up scheduling (from S3/S4 mode) , tv-tuner+FM , with MCE remote control (27 keys - credit card size) , MPEG 1/2/4 encoding , video in (s-video or RCA) + audio in ; support PiP/PoP/video as desktop , teletext , timeshifting , Straight-to-Disc for direct burn TV shows on VCD and DVD ; bundle software : Ulead movie factory
TT-CU750FM	**C**	COMPRO videomate U750F + Mce - Hybrid DVB-T + analog , usb 2.0 , usb-powered , with pc power-up scheduling (from S3/S4 mode) , tv-tuner+FM , with MCE remote control (43 keys - slim size) , MPEG 1/2/4 encoding , video in (s-video or RCA - 1080i HDTV) + audio in ; support PiP/PoP/video as desktop , teletext , timeshifting , Straight-to-Disc for direct burn TV shows on VCD and DVD
TT-CU2500F	**C**	COMPRO videomate U2500F stick - Hybrid DVB-T + analog , flash drive size (94x32x18mm) , usb 2.0 , usb-powered , with pc power-up scheduling (from S3/S4 mode) , tv-tuner+FM , no remote control , MPEG 1/2/4 encoding , video in (s-video or RCA - 1080i HDTV) + audio in ; support PiP/PoP/video as desktop , teletext , timeshifting , Straight-to-Disc for direct burn TV shows on VCD and DVD , with mobile-type digital TV antenna

TT-CU2600F	C	COMPRO videomate U2600F stick - Hybrid DVB-T + analog , flash drive size (94x32x18mm) , usb 2.0 , usb-powered , with pc power-up scheduling (from S3/S4 mode) , tv-tuner+FM , with remote control (32 keys - credit card size) , MPEG 1/2/4 encoding , video in (s-video or RCA - 1080i HDTV) + audio in ; support PiP/PoP/video as desktop , teletext , timeshifting , Straight-to-Disc for direct burn TV shows on VCD and DVD , with mobile-type digital TV antenna
TT-CU2800FM		COMPRO videomate U2800F Mce stick - Hybrid DVB-T + analog , flash drive size (94x32x18mm) , usb 2.0 , usb-powered , with pc power-up scheduling (from S3/S4 mode) , tv-tuner+FM , with MCE remote control (27 keys - credit card size) , MPEG 1/2/4 encoding , video in (s-video or RCA - 1080i HDTV) + audio in ; support PiP/PoP/video as desktop , teletext , timeshifting , Straight-to-Disc for direct burn TV shows on VCD and DVD , with mobile-type digital TV antenna ; bundle software : Ulead movie factory
TT-AUS2100	N	Asus mycinema U2S-100/PT/FM/RC Hybrid DVB-T+analog , with FM radio , usb 2.0 , usb-powered , tv-tuner with remote control (21 keys) , with atnenna extension , with powercinema 5.0
internal - Pci-Express		
TT-CE300		COMPRO videomate E300 , internal pci-express (1x) , stereo sound , tv-tuner+FM , with remote control , conxant chipset , MPEG 1/2/4 encoding , video in (s-video+rca) + audio in ; support PiP/PoP/video as desktop , teletext , timeshifting ; bundle software : Ulead photo explorer
TT-CE300FM	N	COMPRO videomate E300F Mce , internal pci-express (1x) , stereo sound , tv-tuner+FM , MCE remote control with pc power on/off on remote (51 keys) , conxant chipset , MPEG 1/2/4 encoding , video in (s-video+rca) + audio in ; support PiP/PoP/video as desktop , teletext , timeshifting ; bundle software : Ulead photo explorer
TT-CE500		COMPRO videomate E500 with pc power-up scheduling (from S3/S4/S5 mode) + pc power on/off on remote (37 keys) , internal pci-express (1x) , stereo sound , tv-tuner+FM , with remote control , conxant chipset , MPEG 1/2/4 encoding , video in (s-video+ rca+ YCbCr-component 480i/576i) + audio in ; support PiP/PoP/video as desktop , teletext , timeshifting ; bundle software : Ulead photo explorer , movie factory ..- include low-profile pci bracket
TT-CE650		COMPRO videomate E650F Mce , hybrid analog+digital (DVB-T) , support MCE in DVB-T , with pc power-up scheduling (from S3/S4/S5 mode) + pc power on/off on remote (37 keys) , internal pci-express (1x) , stereo sound , tv-tuner+FM , with remote control , conxant chipset , MPEG 1/2/4 encoding , video in (s-video+ rca+ YCbCr-component 480i/576i/1080i) + audio in ; support PiP/PoP/video as desktop , teletext , timeshifting ; bundle software : Ulead photo explorer , movie factory
TT-CE650FM	N	COMPRO videomate E650 , hybrid analog+digital (DVB-T) , support MCE in DVB-T , MCE remote control with pc power-up scheduling (from S3/S4/S5 mode) + pc power on/off on remote (37 keys) , internal pci-express (1x) , stereo sound , tv-tuner+FM , with remote control , conxant chipset , MPEG 1/2/4 encoding , video in (s-video+ rca+ YCbCr-component 480i/576i/1080i) + audio in ; support PiP/PoP/video as desktop , teletext , timeshifting ; bundle software : Ulead photo explorer , movie factory

TT-CE600FM	N	COMPRO videomate E600 Mce , with Hardware MPEG encoding , pc power-up scheduling (from S3/S4/S5 mode) + MCE remote control with pc power on/off on remote (51 keys) , internal pci-express (1x) , stereo sound , tv-tuner+FM , conexant chipset , MPEG 1/2/4 encoding , video in (s-video+ rca+ YCbCr-component 480i/576i/1080i) + audio in ; support PiP/PoP/video as desktop , teletext , timeshifting ; bundle Ulead movie factory .. - include low-profile pci bracket
TT-CE800FM	N	COMPRO videomate E800F Mce , with Hardware MPEG encoding + built-in 32mb memory , for analogue+digital (DVB-T) , support MCE in DVB-T , with pc power-up scheduling (from S3/S4/S5 mode) + MCE remote control with pc power on/off on remote (51 keys) , internal pci-express (1x) , stereo sound , tv-tuner+FM , with remote control , conxant chipset , MPEG 1/2/4 encoding , video in (S-video+ rca+ YCbCr-component 480i/576i/1080i) + audio in ; support PiP/PoP/video as desktop , teletext , timeshifting ; bundle software : Ulead photo explorer , movie factory ..
TT-CS800F	C	COMPRO videomate S800F , internal pci-Express , analog + dual digital DVB-T + satellite (DVB-S) , TV tuner + FM radio , with remote control , with pc power-up scheduling + pc power on/off on remote , support DiSEqC Version 1.2 , HDTV , 1080i HD ; philips chipset , MPEG 1/2/4 encoding , video in (s-video+rca) + audio in/out (3.5mm) ; support timeshifting, channel surfing, still frame capture, digital EPG, subtitle and Teletext , Picture Purifying Technology ; support PIP/POP up to 4 sub channels watching , support TV screen as wallpaper , Straight-to-Disc for direct burn TV shows on VCD and DVD ; bundle software : Ulead movie factory - include low-profile bracket
TT-CE850FM	N	COMPRO videomate E850F Mce - with 2D+3D Y/C + with Hardware MPEG encoding + built-in 32mb memory , for analogue+digital (DVB-T) , with pc power-up scheduling (from S3/S4/S5 mode) + MCE remote control with pc power on/off on remote (51 keys) , internal pci-express (1x) , stereo sound , tv-tuner+FM , with remote control , philips chipset , MPEG 1/2/4 encoding , video in (S-video+ rca+ YCbCr-component 480i/576i/1080i) + audio in ; support PiP/PoP/video as desktop , timeshifting ; bundle software : Ulead photo explorer , movie factory .. - include low-profile pci bracket
TT-CE900FM	N	COMPRO videomate E900F Mce - dual channel with 2D+3D Y/C + with Hardware MPEG encoding + built-in 32mb memory , for dual analogue + dual digital (DVB-T) , with pc power-up scheduling (from S3/S4/S5 mode) + MCE remote control with pc power on/off on remote (51 keys) , internal pci-express (1x) , stereo sound , tv-tuner+FM , with remote control , philips chipset , MPEG 1/2/4 encoding , video in (S-video+ rca+ YCbCr-component - 480i/576i/1080i) + audio in ; support PiP/PoP/video as desktop , timeshifting ; bundle software : Ulead photo explorer , movie factory .. - include low-profile pci bracket

internal - Pci		
TT-CX30		COMPRO X30 videomate , internal pci , stereo sound , tv-tuner , no FM, with remote control , conxant 23883 chipset , MPEG 1/2/4 encoding , optional video in (s-video) ; support teletext , timeshifting ; bundle software : Ulead photo explorer

TT-CX50		COMPRO X50 videomate , internal pci , stereo sound , tv-tuner+FM , with remote control , conxant 23883 chipset , MPEG 1/2/4 encoding , optional video in (s-video) ; support PiP/PoP/video as desktop , teletext , timeshifting , vista 64bit certified ; bundle software : Ulead photo explorer
TT-CM3FM	N	COMPRO videomate M3F Mce - with power-up scheduling (from S3/S4 mode) + MCE remote control (51 keys) , internal pci , stereo sound , tv-tuner+FM , with remote control , Philips 7131 chipset , MPEG 1/2/4 encoding , video in (s-video+ rca) ; support PiP/PoP/video as desktop , teletext , timeshifting , vista 64bit certified
TT-CM5FM	N	COMPRO videomate M5F Mce - with pc power-up scheduling (from S3/S4/S5 mode) + MCE remote control with pc power on/off on remote (51 keys) , internal pci , stereo sound , tv-tuner+FM , with remote control , Philips 7131 chipset , MPEG 1/2/4 encoding , video in (s-video+ rca) ; support PiP/PoP/video as desktop , teletext , timeshifting , Straight-to-Disc for direct burn TV shows on VCD and DVD , vista 64bit certified ; bundle software : Ulead MovieFactory
TT-CX500		COMPRO X500 videomate with pc power-up scheduling (from S3/S4/S5 mode) + pc power on/off on remote (37 keys) + internal AUX audio out , internal pci , stereo sound , tv-tuner + FM , with remote control , conxant 23883 chipset , MPEG 1/2/4 encoding , video in (s-video+rca) + audio in/out (3.5mm) ; support PiP/PoP/video as desktop , teletext , timeshifting , Picture Purifying Technology , Straight-to-Disc for direct burn TV shows on VCD and DVD ; bundle software : Ulead photo explorer , movie factory , Videostudio .. - include low-profile pci bracket
TT-LiFM		Lifeview LR229 FlyTV MCE , internal pci , support microsoft MCE (Media Center Edition) , stereo sound , tv-tuner with remote control , philips SAA7135 , hardware MPEG 1/2/4 encoding , vide in (s-video+rca) + audio in (L+R rca) ; support teletext , timeshifting
TT-H150MCE		Hauppauge WinTV-PVR 150 MCE , internal pci , support microsoft MCE (Media Center Edition) , stereo sound , tv-tuner , hardware MPEG 1/2/4 encoding , video in (s-video+rca) + audio in (L+R rca) ; support teletext , timeshifting - oem pack
TT-H150MCEL		Hauppauge WinTV-PVR 150 MCE , standard + low-profile pci bracket , support microsoft MCE (Media Center Edition) , stereo sound , tv-tuner , hardware MPEG 1/2/4 encoding , video in (s-video+rca) + audio in (L+R rca) ; support teletext , timeshifting - oem pack
TT-CX800		COMPRO X800 videomate with 2D+3D Y/C , pc power-up scheduling (from S3/S4/S5 mode) + pc power on/off on remote (37 keys) + internal AUX audio out , internal pci , stereo sound , tv-tuner + FM , with remote control , Conexant CX23883 chipset , MPEG 1/2/4 encoding , video in (s-video+rca) + audio in/out (3.5mm) ; support PiP/PoP/video as desktop , teletext , timeshiftingPicture Purifying Technology , Straight-to-Disc for direct burn TV shows on VCD and DVD ; bundle software : Compro Tweak Y/C Utility , Ulead photo explorer , movie factory , Videostudio ..- include low-profile pci bracket

TT-CT500FM	N	COMPRO videomate T500F Mce - hybrid - analogue+digital (DVB-T) , with pc power-up scheduling (from S3/S4/S5 mode) + MCE remote control with pc power on/off on remote (51 keys) , internal pci , stereo sound , tv-tuner+FM , with remote control , Philips 7131 chipset , MPEG 1/2/4 encoding , video in (s-video+ rca - 1080i HDTV) ; support PiP/PoP/video as desktop , teletext , timeshifting , Straight-to-Disc for direct burn TV shows on VCD and DVD , vista 64bit certified ; bundle software : Ulead MovieFactory
TT-CT750FM	N	COMPRO videomate T750F Mce - Dual channel hybrid - dual analogue + dual digital (DVB-T) , watch/record 2 channel at the one time - , with pc power-up scheduling (from S3/S4/S5 mode) + MCE remote control with pc power on/off on remote (51 keys) , internal pci , stereo sound , tv-tuner+FM , with remote control , Philips 7131 chipset , MPEG 1/2/4 encoding , video in (s-video+ rca - 1080i HDTV) ; support PiP/PoP/video as desktop , teletext , timeshifting , Straight-to-Disc for direct burn TV shows on VCD and DVD , vista 64bit certified ; bundle software : Ulead MovieFactory
TT-CH900		COMPRO H900 videomate , with Hardware MPEG encoding , 2D+3D Y/C , pc power-up scheduling (from S3/S4/S5 mode) + pc power on/off on remote (37 keys) + internal AUX audio out , internal pci , stereo sound , tv-tuner + FM , with remote control , Conexant CX23418 chipset , video in (s-video+rca) + audio in/out (3.5mm) ; support PiP/PoP/video as desktop , tele-text , timeshiftingPicture Purifying Technology , Straight-to-Disc for direct burn TV shows on VCD and DVD ; bundle software : Compro Tweak Y/C Utility , Ulead photo explorer 8.5SE , movie factory , Videostudio ..- include low-profile pci bracket
Monitor		
MT-LT713SH		LG T713SH , FLATRON , blacK , 17" FST , .27mm , shadow mask with AGASAR coating , 1280 x 1024 / 66 Hz , 1024 x 768 / 85 Hz
LCD / Lcd TV / Plasma Display		
accessories		
Vantec		
NB-VAS400	N	Vantec nbl-S400 - key security lock for PC / Notebook / Lcd / monitor / projector , with locks on to D-Sub or com/serial port) , length : 200cm - retail pack
NB-VAS450	N	Vantec nbl-S450 - 4 digit combination security lock for PC / Notebook / Lcd / monitor / projector , with locks on to D-Sub or com/serial port) , length : 200cm - retail pack
NB-VAS300	N	Vantec nbl-S300 - detachable key security lock for PC / Lcd / monitor , length : 200cm - retail pack
AG neovo		
LS-AYHA05P		AG NEOVO YHA-05P/ES-01 stand - height adjustable (80mm) + 90° swivelable + 30° tilt up and down + pivot for landscape or portrait , Compliant with VESA FPMPMI standards , support up to 7Kg
LS-AYHA07P		AG NEOVO YHA-07P stand - height adjustable (80mm) + 90° swivelable + 30° tilt up and down + pivot for landscape or portrait , Compliant with VESA FPMPMI standards , support up to 9Kg
LS-AYHA90P		AG NEOVO YHA-90P stand - height adjustable (80mm) + 90° swivelable + 30° tilt up and down + pivot for landscape or portrait , Compliant with VESA FPMPMI standards , support up to 11Kg

LS-APM01		AG NEOVO PMK-01 pivot mounting kit - to be used together with Wall Mount Kit , compliant with VESA FPMPMI standards , pivot upwards and downwards for 180° , swivel left and right for 180° , display pivot for 270° , support up to 14Kg
LS-AAG01		AG NEOVO AG-01 display arm - with advanced gas-spring suspension system , multi-directional swivel for virtually any viewing angle , for both desktop and wall mounting , Integrated cable management , support up to 8Kg
Aavra		http://www.aavara.com/en/products/index.php
LS-ATS011	N	Aavara TS011 flip mount for 1x lcd stand (support optional arm module for kb or printer) - 20º tilt & swivel angle adjustable , 90º rotation pivot for landscape or portrait , height adjustable , with ExperTorque technology , smart cable management , aluminum alloy/Steel , VESA mountin : 100x100 / 75x75mm , support up to 2 x 24"/12Kg
LS-ATC110	C	Aavara TC110 flip mount for 1x lcd - clamp base , with 1 arm / 2 joints , ideal for PoS application - 20º tilt & swivel angle adjustable , 90º rotation pivot for landscape or portrait , height adjustable , with ExperTorque technology , smart cable management , aluminum alloy/Steel , VESA mountin : 100x100 / 75x75mm , support up to 2 x 24"/12Kg
LS-ATC022	C	Aavara TC022 flip mount for 2x lcd (double sided) - clamp base , ideal for PoS application with mirror image - 20º tilt & swivel angle adjustable , 90º rotation pivot for landscape or portrait , height adjustable , with ExperTorque technology , smart cable management , aluminum alloy/Steel , VESA mountin : 100x100 / 75x75mm , support up to 2 x 24"/12Kg
LS-ATS742		Aavara TS742 dual flip mount 2x lcd stand - 2 independent swing arms , horizontal & vertical shift + 20° swivelable + 20° tilt + 90º rotation pivot for landscape or portrait , height adjustable , with ExperTorque technology , smart cable management , VESA mountin : 100x100 / 75x75mm , support up to 2 x 24"/12Kg
LS-ATC742	C	Aavara TC742 dual flip mount 2x lcd - clamp base - 2 independent swing arms , horizontal & vertical shift + 20° swivelable + 20° tilt + 90º rotation pivot for landscape or portrait , height adjustable , with ExperTorque technology , smart cable management , VESA mountin : 100x100 / 75x75mm , support up to 2 x 24"/12Kg
LS-ATS430	C	Aavara TS430 Tripple flip mount 3x lcd stand - 1 center fixed + 2 independent swing arms (4 arms/6 joints) , horizontal & vertical shift + 20° swivelable + 20° tilt + 90º rotation pivot for landscape or portrait , height adjustable , with ExperTorque technology , smart cable management , VESA mountin : 100x100 / 75x75mm , support up to 3 x 24"/12Kg
LS-ATC430	C	Aavara TS430 Tripple flip mount 3x lcd - clamp base - 1 center fixed + 2 independent swing arms (4 arms/6 joints) , horizontal & vertical shift + 20° swivelable + 20° tilt + 90º rotation pivot for landscape or portrait , height adjustable , with ExperTorque technology , smart cable management , VESA mountin : 100x100 / 75x75mm , support up to 3 x 24"/12Kg
LS-ATS744		Aavara TS744 Quattro flip mount 4x lcd stand - 4 independent swing arms , horizontal & vertical shift + 20° swivelable + 20° tilt + 90º rotation pivot for landscape or portrait , height adjustable , with ExperTorque technology , smart cable management , VESA mountin : 100x100 / 75x75mm , support up to 4 x 24"/12Kg

LS-ATC744	C	Aavara TC744 Quattro flip mount 4x lcd - clamp base - 4 independent swing arms , horizontal & vertical shift + 20° swivelable + 20° tilt + 90º rotation pivot for landscape or portrait , height adjustable , with ExperTorque technology , smart cable management , VESA mountin : 100x100 / 75x75mm , support up to 4 x 24"/12Kg
LS-ACH630		Aavara CH630 cable management column - support upto 4 x Y2638 AV/HiFi stand - upward & downward movement adjustable , aluminum alloy ; loading capacity: 60kg
LS-AY2638		Aavara Y2638 AV/HiFi support for CH630 - 110 degree wide spread & 358mm free stretch , height adjustable , support upto 4 x Y2638 in 1 x CH630 , aluminum alloy ; loading capacity:15kg per unit
BS-081111		LS-ACH630 + 3 x LS-AY2638 - Aavara CH630 cable management column - support upto 4 x Y2638 AV/HiFi stand - upward & downward movement adjustable , aluminum alloy ; loading capacity: 60kg - 3 x Aavara Y2638 AV/HiFi support for CH630 - 110 degree wide spread & 358mm free stretch , height adjustable , support upto 4 x Y2638 in 1 x CH630 , aluminum alloy ; loading capacity:15kg per unit
LS-APP3025		Aavara PP3025 ceiling mount projector hanger - Horizontal/vertical inclination +/-10º , 360° Rotation , 116-578mm length adjustable ; mounting: 350x350mm , support up to 15kg
LS-AR9250		Aavara R9250 ceiling mount for LCD / Plasma - single sided , 924-1424mm length adjustable - to be used with EF6540/4030/2020
LS-AD9250		Aavara D9250 ceiling mount for LCD / Plasma - Double sided , 924-1424mm length adjustable - to be used with 2 x EF6540
LS-AEL1010		Aavara EL1010 vesa wall mount kit - mounting: 75x75 / 100x100mm , support up to 23"/15kg
LS-AEL2010		Aavara EL2010 vesa wall mount kit - mounting: 100x100 / 200x100mm , with safety lock , 40mm ultra slim profile , support up to 32"/60kg
LS-AEL2020		Aavara EL2020 vesa wall mount kit - mounting: 100x100 / 200x100 / 200x200 mm , with safety lock , anti-theft lock , 40mm ultra slim profile , support up to 45"/60kg
LS-AEF2020		Aavara EF2020 vesa wall mount kit - mounting: 100x100 / 200x100 / 200x200 mm , +/- 15º tilt , with safety lock , anti-theft lock , 45mm ultra slim profile , support up to 45"/60kg
LS-AEL4030		Aavara EL4030 wall mount kit for lcd / plasma - aluminum alloy , automatic safety lock , anti-theft lock , left/right 20mm lateral shift , max. mounting: 450x330mm ; dim : 508x536x40mm, profile from wall: 40mm , 40mm ultra slim profile ;support up to 52" / 80Kg
LS-AEF4030		Aavara EF4030 wall mount kit for lcd / plasma - aluminum alloy , 0º, 5º, 10º, 13º, 15º tilt , automatic safety lock , anti-theft lock , left/right 20mm lateral shift , max. mounting: 440x330mm ; dim : 780x490x45mm, profile from wall: 45mm , 45mm ultra slim profile ;support up to 52" / 80Kg
LS-AEL6540		Aavara EL6540 wall mount kit for lcd / plasma - aluminum alloy , automatic safety lock , anti-theft lock , left/right 20mm lateral shift , max. mounting: 730x450mm ; dim : 788x478x40mm, profile from wall: 40mm , 40mm ultra slim profile ;support up to 62" / 80Kg

LS-AEF6540		Aavara EF6540 wall mount kit for lcd / plasma - aluminum alloy , 0º, 5º, 10º, 13º, 15º tilt , automatic safety lock , anti-theft lock , left/right 20mm lateral shift , max. mounting: 720x450mm ; dim : 788x490x45mm, profile from wall: 48mm , 40mm ultra slim profile ;support up to 62" / 80Kg
LS-ASH6540		Aavara SH6540 wall mount kit for lcd / plasma - aluminum alloy , +/-20º tilt , automatic safety lock , left/right 35mm lateral shift , max. mounting: 720x400mm ; dim : 750x430x75mm , profile from wall: 75mm ;support up to 60" / 80Kg
LS-AAR011		Aavara AR011 wall-mount LCD monitor arms , +/-20º free angle tilt , +/-20º swivel , 90º rotateable , with safety lock , with ExperTorque technology , compliant with VESA FPMPMI standards , max. mounting: 100x100 / 75x75mm ; dim : 115x115x90.7mm , profile from wall : 90.7mm , support up to 24" / 12Kg
LS-AAR110		Aavara AR110 wall-mount LCD monitor arms , 1 arm with 2 jointed pivot points , +/-20º tilt , +/-20º swivel , 90º rotateable , with safety lock , with ExperTorque technology , with smart cable management , compliant with VESA FPMPMI standards , max. mounting: 100x100 / 75x75mm ; dim : 115x180x265mm , profile from wall: max85-265mm , support up to 24" / 12Kg
LS-AAR210		Aavara AR210 wall-mount LCD monitor arms , 2 arms with 3 jointed pivot points , +/-20º tilt , +/-20º angle swivel , 90º rotateable , with safety lock , with ExperTorque technology , with smart cable management , compliant with VESA FPMPMI standards , max. mounting: 100x100 / 75x75mm ; dim : 115x195x445mm , profile from wall: max85-445mm , support up to 24" / 12Kg
LS-AA2020		Aavara A2020 wall-mount lcd / plasma arms - aluminum alloy , 4 arms with 5 joint , +/-15º tilt , +/-60º swivel , automatic safety lock , with ExperTorque technology , with smart cable management , max. mounting: 200x200mm ; dim : 636x320x105mm , profile from wall: max550mm ;support up to 46" / 60Kg
LS-AA8050		Aavara A8050 wall-mount lcd / plasma arms- aluminum alloy , 4 arms with 5 jointed pivot points , +/-15º tilt , +/-60 º swivel , automatic safety lock , with ExperTorque technology , with smart cable management , max. mounting: 810x500mm ; dim : 870x524x105mm , profile from wall: max550mm ;support up to 65" / 85Kg
ASUS		
LC-AVW198T	N	Asus VW198T , black , 19" Wide , with SPLENDID technology , 2 x 1w speaker , 16850x1050 (WSXGA+) ; brightness- 300cd/m2 ; contrast ratio- 3000:1 , response time- 5ms , with cable management , 100mm vesa-wall mountable - d-sub + Dvi
Acer		
LC-AAT3720		Acer AT3720 , 37" , HDTV ready with 1 x analog tv-tuner , 10:6 wide screen Lcd with HDCP support , 2x10w speaker , 8ms , 1366x768 ; brightness - 450cd/m2 ; contrast ratio - 1200:1 ; 2 x SCART in/out + 2 x HDMi in + D-sub in + 3.5mm audio in + RCA in - black bezel + aluminum silver stand
Zalman		
LC-ZTM190		Zalman Trimon zm-M190 2D/3D lcd , 19" , built-in 2wx2 speaker , support pivot display , height adjustable , .29mm , 1280x1024 ; brightness - 300cd/m2 ; contrast ratio - 1000:1 , response time - 5ms - d-sub+dvi+audio in/out , black , 2 pairs of stylish special 3D glasses (standard + clip type) - games support : FAQ : http://www.zalman.co.kr/eng/product/view.asp?idx=334&code=032

LC-ZTM220W		Zalman Trimon zm-M220W 2D/3D lcd , 22" wide , built-in 2wx2 speaker , support pivot display , height adjustable , .28mm , 1680x1050 (WSXGA+) ; brightness - 400cd/m2 ; contrast ratio - 1000:1 , response time - 5ms - d-sub+dvi+audio in/out , black , 2 pairs of stylish special 3D glasses (standard + clip type) - games support : FAQ : http://www.zalman.co.kr/eng/product/view.asp?idx=334&code=032
Samsung		
plasma display		
PD-SPS42A410		Samsung PS42A410 , piano black , 42" wide plasma display , 720p/1080i Digital HD , 2 x 10w SRS TruSurround XT speaker , remote-controlled angled wall mount system , with FilterBright, DNIe , PIP , 1024x768 ; brightness- 1500cd/m2 ; contrast ratio- 20000:1 - d-sub+ 2xHDMi+component+s-video+RCA - 1 year warranty
PD-SPS42A450		Samsung PS42A450 , piano black , 42" wide plasma display with swivel stand , 720p/1080i Digital HD , 2 x 10w SRS TruSurround XT speaker , remote-controlled angled wall mount system , with Movie Plus , Ultra FilterBright , DNIe+ , PIP , 1024x768 ; brightness- 1500cd/m2 ; contrast ratio- 30000:1 - d-sub+ 3xHDMi+component+s-video+RCA - 1 year warranty
PD-SPS50A410		Samsung PS50A410 , piano black , 50" wide plasma display , 720p/1080i Digital HD , 2 x 10w SRS TruSurround XT speaker , remote-controlled angled wall mount system , with FilterBright, DNIe , PIP , 1365x768 ; brightness- 1500cd/m2 ; contrast ratio- 20000:1 - d-sub+ 2xHDMi+component+s-video+RCA - 1 year warranty
PD-SPS50A450		Samsung PS50A450 , piano black , 50" wide plasma display with swivel stand , 720p/1080i Digital HD , 2 x 15w SRS TruSurround XT speaker , remote-controlled angled wall mount system , with Movie Plus , Ultra FilterBright , DNIe , PIP , 1365x768 ; brightness- 1500cd/m2 ; contrast ratio- 30000:1 - d-sub+ 3xHDMi+component+s-video+RCA - 1 year warranty
PD-SPS50A550	R	Samsung PS50A550 , piano black , 50" wide plasma display with swivel stand , 1080P Full HD , 2 x 15w SRS TruSurround XT speaker , remote-controlled angled wall mount system , with Movie Plus , Ultra FilterBright , DNIe , PIP , 1920x1080 ; brightness- 1000cd/m2 ; contrast ratio- 30000:1 - d-sub+ 3xHDMi+component+s-video+RCA+usb - 1 year warranty
PD-SPS63P71	R	Samsung PS63P71 , piano black , 63" wide plasma display , 1080P Full HD , 2 x 15w SRS TruSurround XT speaker , remote-controlled angled wall mount system , with DNIe , PIP/PBP , 1920x1080 ; brightness- 1300cd/m2 ; contrast ratio- 10000:1 - d-sub+ 3xHDMi+component+s-video+RCA - 1 year warranty
Lcd / Lcd TV		
LC-S633NW		Samsung 633NW , glossy black , 15.6" Wide + MagicBright2 + MagicTune , 1366x768 ; brightness- 250cd/m2 ; DC contrast ratio- 10000:1 , response time- 8ms - d-sub - tilt stand
LC-S733N		Samsung 733N , glossy black , stylish curve design , 17" + MagicBright2 + MagicTune , 1280x1024 ; brightness- 300cd/m2 ; contrast ratio- 10000:1 , response time- 5ms - d-sub
LC-S933SN		Samsung 933SN , stylish curve design , glossy black , 18.5" Wide + MagicBright3 + MagicTune , 1360x768 ; brightness- 300cd/m2 ; DC contrast ratio- 15000:1 , response time- 5ms , 75mm vesa-wall mountable - d-sub

LC-S923NW		Samsung 923NW , black , 19" Wide + MagicBright3 + MagicTune , 1440x900 (WXGA+) ; brightness- 300cd/m2 ; contrast ratio- 1000:1 , response time- 5ms , 75mm vesa-wall mountable - d-sub
LC-S933BW	N	Samsung 933BW , glossy black , stylish curve design , 19" wide + MagicBright3 + MagicTune , 1440x900 (WXGA+) ; brightness- 300cd/m2 ; DC contrast ratio- 15000:1 , response time- 5ms , 75mm vesa-wall mountable - d-sub+Dvi
LC-S943NX	N	Samsung 943NX , glossy black , 19" + MagicBright2 + MagicTune , 1440x900 (WXGA+) ; brightness- 300cd/m2 ; DC contrast ratio- 8000:1 , response time- 5ms , 75mm vesa-wall mountable - d-sub - tilt stand
LC-SLD190	N	Samsung LD190 , glossy black , built-in laptop friendly usb vga , no stand design to line up the height with NB screen , 18.5" wide + MagicBright3 + MagicTune , 1366x768 (WXGA+) ; brightness- 250cd/m2 ; DC contrast ratio- 20000:1 , response time- 5ms - d-sub+usb
LC-S2033SWN		Samsung 2033SWN , glossy black , 20" Wide + MagicBright3 + MagicTune , 1600x900 ; brightness- 300cd/m2 ; DC contrast ratio- 15000:1 , response time- 5ms , 100mm vesa-wall mountable - d-sub+Dvi
LC-S2233BW		Samsung 2233BW , glossy black , stylish curve design , 22" wide + MagicBright3 + MagicTune , 1680x1050 (WSXGA+) ; brightness- 300cd/m2 ; DC contrast ratio- 20000:1 , response time- 5ms , 100mm vesa-wall mountable - d-sub+Dvi
LC-ST220		Samsung T220 , rose black + Touch of Color™ design , 22" Wide + MagicBright3 + MagicTune , 1680x1050 (WSXGA+) ; brightness- 300cd/m2 ; DC contrast ratio- 20000:1 , response time- 2ms (GTG) - d-sub+Dvi - tilt stand
LC-SLD220	C	Samsung LD220 , glossy black , built-in laptop friendly usb vga , no stand design to line up the height with NB screen , 21.5" wide + MagicBright3 + MagicTune , 1926x1020 (WUGA+) ; brightness- 300cd/m2 ; DC contrast ratio- 30000:1 , response time- 5ms - d-sub+usb , with 2xusb downstream hub for daisy-chain lcd display or usb peripherals
LC-S2333SW		Samsung 2333SW , glossy black , stylish curve design , 23" Wide lcd ; with MagicBright3 + MagicTune , 1920x1080 (WUXGA) ; brightness- 300cd/m2 ; DC contrast ratio- 20000:1 , response time- 5ms , 100mm vesa-wall mountable - d-sub+Dvi
LC-S2494HS	N	Samsung 2494HS with 4-way adjustable stand (tilt+swivel) , glossy black , 23.6" wide , 1080p Digital HD , 2 x 3w speaker , with MagicBright3 + MagicClear , vesa wall-mountable , 1920x1080 (WUXGA) ; brightness- 300cd/m2 ; DC contrast ratio- 50000:1 , response time- 5ms , 100x200mm vesa-wall mountable - d-sub+Dvi+HDMi - tilt+swivel+pivot+height adjustable stand
LC-ST240		Samsung T240 , rose black + Touch of Color™ design , 24" Wide , 1080P HDCP + MagicBright3 + MagicTune , 1920x1200 (WUXGA) ; brightness- 300cd/m2 ; DC contrast ratio- 20000:1 , response time- 5ms - d-sub+Dvi+HDMi+USB+SPDiF - tilt+swivel stand
LC-ST260		Samsung T260 , rose black + Touch of Color™ design , 25.5" Wide , 1080P HDCP + MagicBright3 + MagicTune , 1920x1200 (WUXGA) ; brightness- 300cd/m2 ; DC contrast ratio- 20000:1 , response time- 5ms - d-sub+Dvi+HDMi+USB+SPDiF - tilt+swivel stand

LC-S2693HM		Samsung 2693HM with 4-way adjustable stand (tilt+swivel+pivot+height) , glossy black , 26" wide , 1080p Digital HD , 2 x 2w speaker , with MagicBright3 + MagicClear , 1920x1200 (WUXGA) ; brightness- 400cd/m2 ; DC contrast ratio- 3000:1 , response time- 5ms , 100x200mm vesa-wall mountable - d-sub+Dvi+HDMi - tilt+swivel+pivot+height adjustable stand
LC-SLA32A330		Samsung LA32A330 , glossy black , 32" wide LCD TV , 720p/1080i Digital HD , 2 x 10w SRS TruSurround XT speaker , 1366x768 ; DC contrast ratio- 8000:1 , response time- 6ms, 100x200mm vesa-wall mountable - d-sub+ 2xHDMi+s-video+RCA - 1 year warrantv
LC-S320MX		Samsung 320MX , black , 32" wide , 720p/1080i Digital HD , 2 x 5w speaker , support MDC (multi display control) upto 25 lcd , DNiE ; support video wall (2x2 , 3x3, 4x4, 5x1 , 1x5 , 5x5 lcd), 1366x768 ; brightness- 500cd/m2 ; contrast ratio- 3000:1 , response time- 8ms - d-sub+DVi+HDMi+RS232 - no stand ; 200x200mm vesa wall-mountable
LC-S320MXN	R	Samsung 320MXN , with MagicInfo Pro (Schedule and publish content over a WAN environment) , black , 32" wide , 720p/1080i Digital HD , 2 x 5w speaker , support MDC (multi display control) upto 25 lcd , DNiE ; support video wall (2x2 , 3x3, 4x4, 5x1 , 1x5 , 5x5 lcd), 1366x768 ; brightness- 500cd/m2 ; contrast ratio- 3000:1 , response time- 8ms - d-sub+DVi+HDMi+RS232 - no stand ; 200x200mm vesa wall-mountable
LC-SLA32A550		Samsung LA32A550 , glossy black , 32" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , with DNIe , PIP , 1920x1080 ; brightness- 550cd/m2 ; DC contrast ratio- 15000:1 , response time- 5ms - d-sub+ 3xHDMi+component+s-video+RCA+USB - 1 year warranty
LC-SLA37A550	N	Samsung LA37A550 , glossy black , 37" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , with DNIe , PIP , 1920x1080 ; brightness- 550cd/m2 ; DC contrast ratio- 15000:1 , response time- 5ms - d-sub+ 3xHDMi+component+s-video+RCA+USB - 1 year warranty
LC-SLA40A330		Samsung LA40A330 , glossy black , 40" wide LCD TV , 720p/1080i Digital HD , 2 x 10w SRS TruSurround XT speaker , with DNIe , PIP , 1366x768 ; brightness- 450cd/m2 ; DC contrast ratio- 8000:1 , response time- 6ms - d-sub+ 2xHDMi+component+s-video+RCA - 1 year warranty
LC-SLA40A550		Samsung LA40A550 , glossy black , 40" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , with DNIe , PIP , 1920x1080 ; brightness- 550cd/m2 ; DC contrast ratio- 30000:1 , response time- 5ms - d-sub+ 3xHDMi+component+s-video+RCA+USB - 1 year warranty
LC-S400MX	R	Samsung 400MX , black , 40" wide , 720p/1080i Digital HD , support pivot display , 2 x 10w speaker , support MDC (multi display control) upto 25 lcd , DNiE ; support video wall (2x2 , 3x3, 4x4, 5x1 , 1x5 , 5x5 lcd), 1366x768 ; brightness- 450cd/m2 ; contrast ratio- 3000:1 , response time- 8ms - d-sub+DVi+HDMi+RS232 - no stand ; 200x200mm vesa wall-mountable
LC-S400MXN	R	Samsung 400MXN , with MagicInfo Pro (Schedule and publish content over a WAN environment) , black , 40" wide , 720p/1080i Digital HD , support pivot display , 2 x 10w speaker , support MDC (multi display control) upto 25 lcd , DNiE ; support video wall (2x2 , 3x3, 4x4, 5x1 , 1x5 , 5x5 lcd), 1366x768 ; brightness- 450cd/m2 ; contrast ratio- 3000:1 , response time- 8ms - d-sub+DVi+HDMi+RS232 - no stand ; 200x200mm vesa wall-mountable

LC-SLA40A610	N	Samsung LA40A610 , glossy black , 40" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , auto motion plus 100hz , with DNIe , PIP/PBP , 1920x1080 ; contrast ratio- 30000:1 , response time- 5ms - d-sub+ 4xHDMi+component+s-video+RCA+usb - 1 year warranty
LC-SLA40A750	N	Samsung LA40A750 with ToC , amber glossy black , 40" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , auto motion plus 100hz , with DLNA + DNIe PRO , PIP/PBP , 1920x1080 ; DC contrast ratio- 70000:1 , response time- 4ms - d-sub+ 4xHDMi+component+s-video+RCA+usb - 1 year warranty
LC-S460MX	R	Samsung 460MX , black , 46" wide , 720p/1080i Digital HD , 2 x 10w speaker , support MDC (multi display control) upto 25 lcd , DNiE ; support video wall (2x2 , 3x3, 4x4, 5x1 , 1x5 , 5x5 lcd), 1920x1080 ; brightness- 450cd/m2 ; contrast ratio- 3000:1 , response time- 8ms - d-sub+DVi+HDMi+RS232 - no stand ; 200x200mm vesa wall-mountable
LC-S460MXN	R	Samsung 460MXN , with MagicInfo Pro (Schedule and publish content over a WAN environment) , black , 46" wide , 720p/1080i Digital HD , 2 x 10w speaker , support MDC (multi display control) upto 25 lcd , DNiE ; support video wall (2x2 , 3x3, 4x4, 5x1 , 1x5 , 5x5 lcd), 1920x1080 ; brightness- 450cd/m2 ; contrast ratio- 3000:1 , response time- 8ms - d-sub+DVi+HDMi+RS232 - no stand ; 200x200mm vesa wall-mountable
LC-SLA46A550	N	Samsung LA46A550 , glossy black , 46" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , with DNIe , PIP/PBP , 1920x1080 ; contrast ratio- 30000:1 , response time- 5ms - d-sub+ 3xHDMi+component+s-video+RCA+usb - 1 year warranty
LC-SLA46A610	N	Samsung LA46A610 , glossy black , 46" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , auto motion plus 100hz , with DNIe , PIP/PBP , 1920x1080 ; contrast ratio- 30000:1 , response time- 5ms - d-sub+ 4xHDMi+component+s-video+RCA+usb - 1 year warranty
LC-SLA46A650	N	Samsung LA46A650 with ToC , amber glossy black , 46" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , auto motion plus 100hz , with DNIe , PIP/PBP , 1920x1080 ; contrast ratio- 50000:1 , response time- 4ms - d-sub+ 4xHDMi+component+s-video+RCA+usb - 1 year warranty
LC-SLA46A680	R	Samsung LA46A680 with ToC , amber glossy black , 46" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , auto motion plus 100hz , with DNIe , PIP , 1920x1080 ; DC contrast ratio- 60000:1 - d-sub+ 4xHDMi+component+s-video+RCA+USB - 1 year warranty
LC-SLA46A850		Samsung LA46A850 with ToC , amber glossy black , 46" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , auto motion plus 100hz , with DLNA + DNIe PRO , PIP/PBP , 1920x1080 ; DC contrast ratio- 70000:1 , response time- 4ms - d-sub+ 4xHDMi+component+s-video+RCA+usb - 1 year warranty
LC-SLA46A950	R	Samsung LA46A950 with ToC , glossy black , 46" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , auto motion plus 100hz , with Smart LED (auto-adjusting LED Backlight) + DLNA + DNIe PRO , PIP/PBP , 1920x1080 ; DC contrast ratio- 2000000:1 , response time- 4ms , swivelable stand - d-sub+ 4xHDMi+component+s-video+RCA+usb - 1 year warranty

LC-SLA52A610		Samsung LA52A610 , glossy black , 52" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , auto motion plus 100hz , with DNIe , PIP/PBP , 1920x1080 ; contrast ratio- 50000:1 , response time- 4ms - d-sub+ 4xHDMi+component+s-video+RCA+usb - 1 year warranty
LC-SLA52A650		Samsung LA52A650 with ToC , amber glossy black , 52" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , auto motion plus 100hz , with DNIe , PIP/PBP , 1920x1080 ; contrast ratio- 50000:1 , response time- 4ms - d-sub+ 4xHDMi+component+s-video+RCA+usb - 1 year warranty
LC-SLA52A680	R	Samsung LA52A680 with ToC , amber glossy black , 52" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , auto motion plus 100hz , with DNIe , PIP , 1920x1080 ; DC contrast ratio- 60000:1 - d-sub+ 4xHDMi+component+s-video+RCA+USB - 1 year warranty
LC-SLA52A750	R	Samsung LA52A750 with ToC , amber glossy black , 52" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , auto motion plus 100hz , with DLNA + DNIe PRO , PIP/PBP , 1920x1080 ; DC contrast ratio- 70000:1 , response time- 4ms - d-sub+ 4xHDMi+component+s-video+RCA+usb - 1 year warranty
LC-SLA55A950	R	Samsung LA55A950 with ToC , glossy black , 55" wide LCD TV , 1080P Full HD , 2 x 10w SRS TruSurround XT speaker , auto motion plus 100hz , with Smart LED (auto-adjusting LED Backlight) + DLNA + DNIe PRO , PIP/PBP , 1920x1080 ; DC contrast ratio- 2000000:1 , response time- 4ms , swivelable stand - d-sub+ 4xHDMi+component+s-video+RCA+usb - 1 year warranty
LC-SLA70F91	R	Samsung LA70F91 with ToC , glossy black , 70" wide LCD TV , 1080P Full HD , 2 x 15w SRS TruSurround XT speaker , auto motion plus 100hz , with Smart LED (auto-adjusting LED Backlight) + DLNA + DNIe PRO , PIP/PBP , 1920x1080 ; DC contrast ratio- 5000000:1 , response time- 8ms , swivelable stand - d-sub+ 3xHDMi+component+s-video+RCA+usb - 1 year warranty

LG

LC-LW1542S	N	LG W1542S-PF , wide screen 15" , with f Engine , .25mm , 1280x720 (WXGA) ; brightness- 250cd/m2 ; DFC contrast ratio - 5000:1 , response time- 5ms - d-sub
LC-L177WSB	N	LG 177WSB-PF , wide screen 17" , with f Engine , .25mm , 1440x900 (WXGA) ; brightness- 250cd/m2 ; DFC contrast ratio - 5000:1 , response time- 8ms - d-sub
LC-LW1742S	N	LG W1742S-PF , glossy black , wide screen 17" , with f Engine , .25mm , 1440x900 (WXGA) ; brightness- 250cd/m2 ; DFC contrast ratio - 8000:1 , response time- 8ms - d-sub
LC-L1734S		LG 1734S-BN , 17" , with f Engine , .26mm , 1280x1024 ; brightness- 300cd/m2 ; contrast ratio - 700:1 , response time- 5ms - d-sub
LC-L1742S	N	LG 1742S-PF , glossy black , 17" , with f Engine , .25mm , 1280x1024 ; brightness- 250cd/m2 ; DFC contrast ratio - 8000:1 , response time- 8ms - d-sub
LC-L1730SF		LG 1730SF , 17" touch screen , with RS232 lcd-to-lcd connectivity , .26mm , 1280x1024 ; brightness - 300cd/m2 ; contrast ratio - 500:1 , response time - 16ms - d-sub , silver
LC-LW1941S	N	LG W1941S-PF , wide screen , 18.5", with f Engine , .28mm , 1366x768 ; brightness - 300cd/m2 ; DFC contrast ratio - 8000:1 , response time - 5ms - d-sub , black
LC-LW1934S		LG W1934S-BN , wide screen , 19", with f Engine , .28mm , 1440x900 (WXGA+) ; brightness - 300cd/m2 ; contrast ratio - 1000:1 , response time - 5ms - d-sub , black

LC-LW1942S		LG W1942S-BF , wide screen , 19", with f Engine , .28mm , 1440x900 (WXGA+) ; brightness - 300cd/m2 ; DFC contrast ratio - 8000:1 , response time - 5ms - d-sub , black
LC-L1918SB		LG 1918S-BN , 19" , with f Engine , .29mm , 1280x1024 ; brightness - 300cd/m2 ; contrast ratio - 700:1 , response time - 5ms - d-sub , black
LC-L1942S	N	LG 1942S-BF , 19", with f Engine , .28mm , 1280x1024 ; brightness - 300cd/m2 ; DFC contrast ratio - 8000:1 , response time - 5ms - d-sub , black
LC-LW1952TQ		LG W1952TQ , wide screen , 19" , with ez Zooming button + f Engine , .285mm , 1440x900 ; brightness - 300cd/m2 ; DFC contrast ratio - 10000:1 , response time - 2ms (GTG) - d-sub+DVi
LC-L1960TQ	N	LG 1960TQ artistic series with piano black mirror finish , 19" , with f Engine , .29mm , 1280x1024 ; brightness - 300cd/m2 ; DFC contrast ratio - 2000:1 , response time - 4ms (GTG) - d-sub+DVi
LC-L1960TR	N	LG 1960TR artistic series with piano black mirror finish , 19" , with f Engine , .29mm , 1280x1024 ; brightness - 300cd/m2 ; DFC contrast ratio - 3000:1 , response time - 2ms (GTG) - d-sub+DVi
LC-LW2234S		LG W2234S-BN , 22" wide screen ; 0.28mm , 1680x1050 (WSXGA+) ; brightness - 300cd/m2 ; contrast ratio 1000:1 , response time - 5ms - d-sub , black
LC-LW2242S		LG W2242S-BN , 22" wide screen ; 0.28mm , 1680x1050 (WSXGA+) ; brightness - 300cd/m2 ; contrast ratio - DFC contrast ratio 8000:1 , response time - 5ms - d-sub , black
LC-LW2252S	N	LG W2252S-BN , 22" wide screen , ez-zooming by button ; 0.28mm , 1680x1050 (WSXGA+) ; brightness - 300cd/m2 ; contrast ratio - DFC contrast ratio 8000:1 , response time - 5ms - d-sub , black
LC-L226WTQ	N	LG 226WTQ , wide screen , 22" , ez-zooming by button ; 0.28mm , 1680x1050 (WSXGA+) ; brightness - 300cd/m2 ; DFC contrast ratio - 3000:1 , response time - 2ms (GTG) - d-sub + DVi with HDCP complinance , black
LC-LW2252TQ		LG W2252TQ-PF , 22" wide screen ; 0.28mm , 1680x1050 (WSXGA+) ; brightness - 300cd/m2 ; contrast ratio - DFC contrast ratio 10000:1 , response time - 2ms (GTG) - d-sub + DVi with HDCP complinance , black
LC-LW2271TC	N	LG W2271TC , 22" wide screen , with built-in 2x1w speaker , 2.0mp webcam + stero mic , ez-zooming by button ; 0.28mm , 1680x1050 (WSXGA+) ; brightness - 300cd/m2 ; contrast ratio - DFC contrast ratio 20000:1 , response time - 5ms - d-sub + DVi with HDCP complinance , black
LC-LW2600H	R	LG W2600H , 26" wide screen , with 3-way adjustable stand , ez-zooming by button , multi-screen upto 6 via usb singal provided ; .28mm , 1920x1200 (WUXGA) ; brightness - 300cd/m2 ; DFC contrast ratio - 5000:1 , response time - 5ms , 4xUSB + d-sub + DVi , with HDCP complinance , built-in 4 port usb downstream hub , black
LC-LW3000H	R	LG W3000H , 30" wide screen , with 3-way adjustable stand , S-iPS LCD with 178° wide view angle , ez-zooming by button , multi-screen upto 6 via usb singal provided ; .25mm , 2560x1600 (WQXGA) ; brightness - 370cd/m2 ; DFC contrast ratio - 3000:1 , response time - 5ms , 4xUSB +DVi , with HDCP complinance , built-in 4 port usb downstream hub , black
LC-L32LC7		LG 32LC7 xcanvas 32" wide LCD TV , 720p/1080i Digital HD , 2 x 7w SRS TruSurround XT speaker , 1366x768 ; brightness- 600cd/m2 ; DC contrast ratio- 10000:1 , response time- 5ms - d-sub+ 2xHDMi+component+s-video+RCA - 1 year warranty

LC-L37LG60UR	R	LG 37LG60UR Scarlet 37" wide LCD TV , 720p/1080i Digital HD , 2 x 10w invisible speaker , 1366x768 ; brightness- 500cd/m2 ; DCC contrast ratio- 50000:1 , response time- 4ms - d-sub+ 2xHDMi+component+s-video+RCA - 1 year warranty
LC-L42LG30R	N	LG Scarlet 42LG30R , 42" wide LCD TV , 1080i HD , 2 x 10w invisible speaker , 1366x768 ; brightness- 500cd/m2 ; DC contrast ratio- 15000:1 , response time- 4ms - d-sub+ 2xHDMi+component+s-video+RCA+USB - 1 year warranty
LC-L47LG60FR	R	LG Scarlet 47LG60FR , 47" wide LCD TV , 1080P Full HD , 2 x 10w invisible speaker , 1920x1080 ; brightness- 500cd/m2 ; DC contrast ratio- 50000:1 , response time- 4ms - d-sub+ 2xHDMi+component+s-video+RCA+USB - 1 year warranty
AG NEOVO		http://www.agneovo.com/global/
H series		
LC-AHW19		AG NEOVO H-W19 , 19" wide screen , 2 x 1w speakers , kensington security lock , support wall mount kit , display arm ; .285mm , WXGA 1440x900 , 380cd/m2 ; contrast ratio - 1000:1 , response time : 3ms ; D-Sub
LC-AHW22		AG NEOVO H-W22 , 22" wide screen , HDCP compliant , 2 x 2w speakers , kensington security lock , support wall mount kit , display arm ; .282mm , WSXGA+ 1680x1050 , 300cd/m2 ; contrast ratio - 1000:1 , response time : 3ms , with cable managment ; D-Sub+DVi
medical series		
LC-AER19		AG NEOVO ER-19" Endoscopy display , 12-Bits Gamma Correction , Monochrome Switch (DICOM-ready) , red+ green+ blue brightness and contrast to meet surgeon's visualisation , Built-in SD-SDI capability enables the ER-19 to transmit signals upto 200 meters , iP22 Dust + Water Resistance , with NeoV Optical Filter , support horizontal display parallel to your desk , kensington security lock , Lcd panel protection with harden glass ; support wall mount kit , display arm ; 1280x1024 , 300cd/m2 ; contrast ratio - 450:1 , response time : 10ms ; D-sub, DVi , Auto Composite System, S-video, SD-SDI, BNC
E series for Exceptionally Elegant		
LC-AE19		AG NEOVO E-19 black , 19" , with NeoV Optical Filter , 2 x 1w speakers with headphone jack , support horizontal display parallel to your desk , kensington security lock , Lcd panel protection with harden glass ; support wall mount kit , display arm ;.26mm , 1280x1024 , 300cd/m2 ; contrast ratio - 700:1 , response time : 4ms ; D-Sub+DVi
LC-AEW19		AG NEOVO E-W19 black , 19" wide , HDCP compliant support 1080P (via DVI-HDMI cable included) , with NeoV Optical Filter/harden glass , 2 x 2w speakers with headphone jack , support horizontal display parallel to your desk , kensington security lock , Lcd panel protection with harden glass ; support wall mount kit , display arm ;.28mm , WXGA 1440x900 , 380cd/m2 ; dynamic contrast ratio - 2000:1 , response time : 3ms ; D-Sub+DVi
LC-AEW22		AG NEOVO E-W22 black , 22" wide , HDCP compliant support 1080P (via DVI-HDMI cable included) , with NeoV Optical Filter/harden glass , 2 x 2w speakers with headphone jack , support horizontal display parallel to your desk , kensington security lock ; adjustable stand , auto-adjustment , Lcd panel protection with harden glass ; support wall mount kit , display arm ;.28mm , WSXGA+ 1680x1050 , 300cd/m2 ; dynamic contrast ratio - 2000:1 , response time : 3ms ; D-Sub+DVi
P series		

LC-AP19		AG NEOVO P-19 - iF Product Design Award , silver , support horizontal display parallel to your desk , 19" , with NeoV Optical Filter , built-in speakers sub-woofer + audio input , kensington security lock ; adjustable stand , auto-adjustment , Lcd panel protection with harden glass ; support wall mount kit , display arm ;.29mm , 1280x1024 , 300cd/m2 ; contrast ratio - 700:1 , response time : 3ms , built-in 4 port usb hub ; D-Sub+DVi+S-Video+ CVBS (Composite Video / RCA)
X series for performance minded		
LC-AX15AV		AG NEOVO X-15AV black , 15" , distinctive aluminum alloy housing , NeoV Optical Filter , kensington security lock ; auto-adjustment , Lcd panel protection with harden glass ; support wall mount kit , display arm ; .29mm , 1024x768 , 500cd/m2 ; contrast ratio - 400:1 , response time : 4ms ; D-Sub+ DVi+ S-Video+ CVBS (Composite Video / RCA)
LC-AX17AV		AG NEOVO X-17AV black , 17" , distinctive aluminum alloy housing , NeoV Optical Filter , kensington security lock ; auto-adjustment , Lcd panel protection with harden glass ; support wall mount kit , display arm ; .26mm , 1280x1024 , 400cd/m2 ; contrast ratio - 450:1 , response time : 4ms ; D-Sub+ DVi+ S-Video+ CVBS (Composite Video / RCA)
LC-AX19AV		AG NEOVO X-19AV black , 19" , distinctive aluminum alloy housing , NeoV Optical Filter , kensington security lock ; auto-adjustment , Lcd panel protection with harden glass ; support wall mount kit , display arm ; .29mm , 1280x1024 , 250cd/m2 ; contrast ratio - 700:1 , response time : 4ms ; D-Sub+ DVi+ S-Video+ CVBS (Composite Video / RCA)
LC-AXW19AV		AG NEOVO X-W19 black , 19" wide , HDCP compliant support 1080P (via DVI-HDMI cable included) , distinctive aluminum alloy housing , NeoV Optical Filter , kensington security lock ; auto-adjustment , Lcd panel protection with harden glass ; support wall mount kit , display arm ; .28mm , WXGA - 1440x900 , 400cd/m2 ; dynamic contrast ratio - 2000:1 , response time : 3ms ; D-Sub+ DVi+ S-Video+ CVBS (Composite Video / RCA)
LC-AXW22AV		AG NEOVO X-W22 black , 22" wide , HDCP compliant support 1080P (via DVI-HDMI cable included) , distinctive aluminum alloy housing , NeoV Optical Filter , kensington security lock ; auto-adjustment , Lcd panel protection with harden glass ; support wall mount kit , display arm ; .28mm , WSXGA+ - 1680x1050 , 300cd/m2 ; dynamic contrast ratio - 2000:1 , response time : 3ms ; D-Sub+ DVi+ S-Video+ CVBS (Composite Video / RCA)
Interface Converter		
iC-U2PS2		Usb to 2 x PS/2 port converter - bulk pack
iC-VUSBPS2	N	Vantec cb-USBPS2 - Usb to 2 x PS/2 port converter , 33cm - retail pack
iC-SSiV		Sunix SABR1000DV Interface Converter - divert IDE device (5.25" or 3.5") to sata interface , Vertical type , Silicon Image Sil3611 chipset , support hot-plug - with s-ata cable , 4pin power connector , retail pack
iC-V9218		Vi-power VP-9218 interface converter - USB2.0 to External eSATA smart dongle
iC-ViSU	N	Vantec CB-iSATAU2 Interface Converter - USB to IDE + SATA interface , for 44pin 2.5" ide / 40pin 3.5" IDE / 40pin 5.25" IDE / 3.5" SATA / external SATA / external e-SATA (require SATA to eSATA cable) , ide + 1 x sata can be used at the same time , include power cable for IDE/SATA device - retail pack

iC-SCBE1000		Sunix CBE1000 pcmcia/cardbus to express card 32 converter (for old notebook with pcmcia/cardbus to use new express card 32) - retail pack
AC-SPTC1010		Sunix PTC1010R pci to pcmcia adapter - for pcmcia card to be used in normal desktop
AC-SPTE1414	N	Sunix PTE1414 pci-e (1x) to express card (34/54) adapter , with internal USB port - ideal for 35mm/54mm express card to be used in normal desktop
Solid State disk drive		
HD-KNSSDM80	N	Kingston SNM125-S2/80GB SSD (Intel X25-M Mainstream MLC series SATA Solid-State Drive) , 2.5" 80Gb , SATA2 , native read : 250mb/sec / write 70mb/sec
HD-KNSSDM160	R	Kingston SNM125-S2/160GB SSD (Intel X25-M Mainstream MLC series SATA Solid-State Drive) , 2.5" 160Gb , SATA2 , native read : 250mb/sec / write 70mb/sec
HD-KNSSDE32	N	Kingston SNE125-S2/32GB SSD (Intel X25-E Extreme SLC series SATA Solid-State Drive) , 2.5" 32Gb , SATA2 , native read : 250mb/sec / write 170mb/sec
HD-iNSSDM80	N	Intel SSDSA2MH080G1 SSD (Intel X25-M Mainstream MLC series SATA Solid-State Drive) , 2.5" 80Gb , SATA2 , native read : 250mb/sec / write 70mb/sec
HD-iNSSDM160	N	Intel SSDSA2MH160G1 SSD (Intel X25-M Mainstream MLC series SATA Solid-State Drive) , 2.5" 160Gb , SATA2 , native read : 250mb/sec / write 70mb/sec
HD-iNSSDE32	N	Intel SSDSA2SH032G1 SSD - X25-E Extreme SLC series SATA Solid-State Drive) , 2.5" 32Gb , SATA2 , native read : 250mb/sec / write 170mb/sec
HD-iNSSDE64	N	Intel SSDSA2SH064G1 SSD - X25-E Extreme SLC series SATA Solid-State Drive) , 2.5" 64Gb , SATA2 , native read : 250mb/sec / write 170mb/sec
Hard Disk drive accessories		
oT-H2535S	N	icydock MB882 2.5" -> 3.5" sata hdd / SSD converter / housing (work as standard 3.5" hdd) - screwless + anti-vibration + airflow vents design
HD-VA250	N	vizo avk-250bk - 2.5" hdd anti-vibration / protection kit , ultra-light silica gel , stackable design , ideal for usage outside of chassis
HD-VA350	N	vizo avk-350bk - 3.5" hdd anti-vibration / protection kit , ultra-light silica gel , stackable design , ideal for usage outside of chassis
HD-AASi		Abit SECUREiDE - connects to your IDE hard disk and has a special decoder key ; eNOVA X-Wall Lx-40 chipset , 40bit DES - use an external security key to start the access of HDD - 2 security keys supplied 1. you can remove the security keys after startup ; 2. after install the SECURiDE , it is required to FDiSK and FORMAT the hdd
3.5" - PATA		
Seagate		
HD-S80i2		seagate barracuda 7200.9 st380215a 80gb, ata100, 7200rpm, 2mb cache , 11/12ms - 3 years warranty
HD-S160i8		seagate barracuda 7200.9 st3160815a 160gb, ata100, 7200rpm, 8mb cache , 11/12ms - 3 years warranty
HD-S250i8		seagate barracuda 7200.10 st3250820a 250gb, ata100, 7200rpm, 8mb cache , 11/12ms - 3 years warranty
Western Digital		
HD-W160i8		Western Digital CAViAR SE WD1600AAJB 160gb, ata100, 7200rpm, 8mb cache, 8.9ms - 3 years warranty

HD-W250i8	Western Digital CAViAR SE WD2500AAJB 250gb, ata100, 7200rpm, 8mb cache, 8.9ms - 3 years warranty
HD-W320i8	Western Digital CAViAR SE WD3200AAJB 320gb, ata100, 7200rpm, 8mb cache, 8.9ms - 3 years warranty
HD-W400i8	Western Digital CAViAR SE WD4000AAJB 400gb, ata100, 7200rpm, 8mb cache, 8.9ms - 3 years warranty
HD-W500i16	Western Digital CAViAR SE WD5000AAKB 500gb, ata100, 7200rpm, 16mb cache, 8.9ms - 3 years warranty
3.5" S-ATA / S-ATA2	
Seagate	
HD-S80S8	seagate barracuda 7200.9 st380811as , 80gb, s-ata2 , 7200rpm, 8mb cache - 3 years warrenty
HD-S160S8	seagate barracuda 7200.9 st3160811as , 160gb, s-ata2 , 7200rpm, 8mb cache - 3 years warrenty
HD-S250S8	seagate barracuda 7200.10 st3250310as , 250gb, s-ata2 , 7200rpm, 8mb cache, 8.5/10ms - 3 years warrenty
HD-S250S16	seagate barracuda 7200.10 st3250620/410as , 250gb, s-ata2 , 7200rpm, 16mb cache, 8.5/10ms - 3 years warrenty
HD-S250S8SV	seagate barracuda SV35.3 ST3250310SV , 200gb, s-ata2 , 7200rpm, 8mb cache, designed for 24x7 digital video surveillance , designed for 24x7 business-critical applications (NAS , video surveillance … ETC) - 5 years warrenty
HD-S250SR32	seagate barracuda ES2 ST3250310NS , 250gb, s-ata2 , 7200rpm, 32mb cache, 8.5/9.5ms , built-in Error Recovery Control, workload management, power management, rotational vibration feed forward, one-step microcode download, Write-same, Signal Integrity analysis, power and thermal profiling, rotational vibration analysis, and performance benchmarking ; designed for 24x7 business-critical applications (NAS , video surveillance … ETC) - 5 years warrenty
HD-S320S16	seagate barracuda 7200.11 st3320613as , 320gb, s-ata2 , 7200rpm, 16mb cache, 8.5/9.5ms - 3 years warrenty
HD-S500S16	seagate barracuda 7200.12 st3500418as , 500gb, s-ata2 , 7200rpm, 16mb cache, 8.5/9.5ms - 3 years warrenty
HD-S500S32	seagate barracuda 7200.11 st3500320as , 500gb, s-ata2 , 7200rpm, 32mb cache, 8.5/9.5ms - 3 years warrenty
HD-S500S32SV	seagate barracuda SV35.3 ST3500320SV , 500gb, s-ata2 , 7200rpm, 32mb cache, designed for 24x7 digital video surveillance , designed for 24x7 business-critical applications (NAS , video surveillance … ETC) - 5 years warrenty
HD-S500SR32	seagate barracuda ES2 ST3500320NS , 500gb, s-ata2 , 7200rpm, 32mb cache, 8.5/9.5ms , built-in Error Recovery Control, workload management, power management, rotational vibration feed forward, one-step microcode download, Write-same, Signal Integrity analysis, power and thermal profiling, rotational vibration analysis, and performance benchmarking ; designed for 24x7 business-critical applications (NAS , video surveillance … ETC) - 5 years warrenty
HD-S640S32	seagate barracuda 7200.11 st3640323as , 640gb, s-ata2 , 7200rpm, 32mb cache, 8.5/9.5ms - 3 years warrenty
HD-S750S32	seagate barracuda 7200.11 st3750330as , 750gb, s-ata2 , 7200rpm, 32mb cache, 8.5/9.5ms - 3 years warrenty

HD-S750SR32		seagate barracuda ES2 ST3750330NS , 750gb, s-ata2 , 7200rpm, 32mb cache, 8.5/9.5ms , built-in Error Recovery Control, workload management, power management, rotational vibration feed forward, one-step microcode download, Write-same, Signal Integrity analysis, power and thermal profiling, rotational vibration analysis, and performance benchmarking ; designed for 24x7 business-critical applications (NAS , video surveillance … ETC) - 5 years warrenty
HD-S1000S32		seagate barracuda 7200.11 st31000340/33as , 1TB/1000gb, s-ata2 , 7200rpm, 32mb cache, 8.5ms - 3 years warrenty
HD-S1000S32SV		seagate barracuda SV35.3 ST31000340SV , 1TB/1000gb, s-ata2 , 7200rpm, 32mb cache, designed for 24x7 digital video surveillance , designed for 24x7 business-critical applications (NAS , video surveillance … ETC) - 5 years warrenty
HD-S1000SR32		seagate barracuda SV35.3 ST31000340SV , 1TB/1000gb, s-ata2 , 7200rpm, 32mb cache, designed for 24x7 digital video surveillance , designed for 24x7 business-critical applications (NAS , video surveillance … ETC) - 5 years warrenty
HD-S1500S32		seagate barracuda 7200.11 st31500341as , 1.5TB/1500gb, s-ata2 , 7200rpm, 32mb cache, 8.5ms - 3 years warrenty
Western Digital		
HD-W150SVR		Western Digital VelociRaptor WD1500HLFS 150gb, 2.5" hdd with 3.5" heatsink, Sata2 , 10000rpm , 16mb cache, with RAFF , 4.2ms - 5 years warranty
HD-W160S8		Western Digital CAViAR blue SE WD1600JS 160gb, S-ata2 , 7200rpm , 8mb cache, 8.9ms - 3 years warranty
HD-W250S8		Western Digital CAViAR blue WD2500JS 250gb, S-ata2 , 7200rpm , 8mb cache, 8.9ms - 3 years warranty
HD-W250SR16		Western Digital CAViAR RE3 (Raid Edition) WD2502ABYS 250gb, S-ata2 , 7200rpm , 16mb cache, 8.7ms , with TLER , RAFF , locking latch, backplane compatibility, designed for 24x7 business-critical applications - 5 years warranty
HD-W320S8		Western Digital CAViAR blue WD3200JS 320gb, S-ata2 , 7200rpm , 8mb cache, 8.9ms - 3 years warranty
HD-W320S16		Western Digital CAViAR blue WD3200AAKS 320gb, S-ata2 , 7200rpm , 16mb cache, 8.9ms - 3 years warranty
HD-W320SR16		Western Digital CAViAR RE3 (Raid Edition) WD3202ABYS 320gb, S-ata2 , 7200rpm , 16mb cache, 8.7ms , with TLER , RAFF , locking latch, backplane compatibility, designed for 24x7 business-critical applications - 5 years warranty
HD-W300SVR		Western Digital VelociRaptor WD3000HLFS 300gb , 2.5" hdd with 3.5" heatsink , Sata2 , 10000rpm , 16mb cache, with RAFF, 4.2ms - 5 years warranty
HD-W400SR16		Western Digital CAViAR RE2 (Raid Edition) WD4000ABYS 400gb, S-ata2 , 7200rpm , 16mb cache, 8.7ms , with TLER , RAFF , locking latch, backplane compatibility, designed for 24x7 business-critical applications - 5 years warranty
HD-W500S16	N	Western Digital CAViAR blue WD5000AAJB 500gb, S-ata2 , 7200rpm , 8mb cache, 8.9ms - 3 years warranty
HD-W500S16GP		Western Digital CAViAR GP WD5000AACS 500gb, S-ata2 , with intellipower (5400-7200rpm for powersaveing) , 16mb cache, 8.9ms - 3 years warranty
HD-W500S32	N	Western Digital CAViAR black WD5001AALS 500gb, S-ata2 , 7200rpm , 32mb cache, 8.9ms - 5 years warranty
HD-W500SR16		Western Digital CAViAR RE2 (Raid Edition) WD5001ABYS 500gb, S-ata2 , 7200rpm , 16mb cache, 8.7ms , with NCQ, TLER , RAFF , locking latch, backplane compatibility, designed for 24x7 business-critical applications - 5 years warranty

HD-W750S16GP		Western Digital CAViAR GP WD7500AACS 750gb, S-ata2 , with intellipower (5400-7200rpm for powersaveing) , 16mb cache, 8.9ms - 3 years warranty
HD-W750S8AVGP	N	Western Digital CAViAR AV-GP WD7500AAVS 750gb, S-ata2 , with intellipower (5400-7200rpm for powersaveing) designed for 24x7 digital video surveillance , designed for 24x7 business-critical applications (NAS , video surveillance ... ETC) , 8mb cache, 8.9ms - 3 years warranty
HD-W750SR16GP		Western Digital CAViAR RE2-GP WD7500AYPS 750gb , (Raid Edition) , S-ata2 , with intellipower (5400-7200rpm for powersaveing) , 16mb cache, 8.9ms , with NCQ, TLER , RAFF , locking latch, backplane compatibility, designed for 24x7 business-critical applications - 5 years warranty
HD-W1000S32GP		Western Digital CAViAR GP WD10EADS 1000gb/1Tb, S-ata2 , with intellipower (5400-7200rpm for powersaveing) , 32mb cache, 8.9ms - 3 years warranty
HD-W1000S32	N	Western Digital CAViAR black WD1001FALS 1000gb/1Tb, S-ata2 , 7200rpm , 32mb cache, 8.9ms - 5 years warranty
HD-W1000SR16GP		Western Digital CAViAR RE2-GP WD1000FYPS 1000gb/1Tb , (Raid Edition) , S-ata2 , with intellipower (5400-7200rpm for powersaveing) , 16mb cache, 8.9ms , with NCQ, TLER , RAFF , locking latch, backplane compatibility, designed for 24x7 business-critical applications - 5 years warranty
HD-W1000SR32	N	Western Digital CAViAR RE3 (Raid Edition) WD1002ABYS 1Tb/1000gb, S-ata2 , 7200rpm , 16mb cache, 8.7ms , with NCQ, TLER , RAFF , locking latch, backplane compatibility, designed for 24x7 business-critical applications - 5 years warranty
HD-W2000S32GP	N	Western Digital CAViAR GP WD20EADS 2000gb/2Tb, S-ata2 , with intellipower (5400-7200rpm for powersaveing) , 32mb cache, 8.9ms - 3 years warranty
2.5" - PATA notebook drive		
Seagate		http://www.seagate.com/www/en-us/products/laptops/momentus
HD-SN80		seagate momentus 5400.2 st98823a 80gb, 2.5" , ata100, 5400rpm, 8mb cache, 12.5/14.5ms - 3 years warranty
HD-SN160		seagate momentus 5400.3 st9160821a 160gb, 2.5" , ata100, 5400rpm, 8mb cache, 11/13ms - 3 years warranty
Western Digital		http://www.westerndigital.com/en/products/Products.asp?DriveID=102&Language=en
HD-WN120		Western Digital SCORPiO BLUE WD1200VE , 2.5" 9.5mm , 120gb ide , 5400rpm , 8mb cache, 12ms - 3 years warranty
HD-WN160		Western Digital SCORPiO BLUE WD1600BEVE , 2.5" 9.5mm , 160gb ide , 5400rpm , 8mb cache, 12ms - 3 years warranty
HD-WN250		Western Digital SCORPiO BLUE WD2500BEVE , 2.5" 9.5mm , 250gb ide , 5400rpm , 8mb cache, 12ms - 3 years warranty
HD-WN320	N	Western Digital SCORPiO BLUE WD3200BEVE , 2.5" 9.5mm , 320gb ide , 5400rpm , 8mb cache, 12ms - 3 years warranty
2.5" - SATA notebook drive		
accessory - mobile rack		
oT-H2535S	N	icydock MB882 2.5" -> 3.5" sata hdd / SSD converter / housing (work as standard 3.5" hdd) - screwless + anti-vibration + airflow vents design
MR-VARES2	N	Vizo ARES ii , ARS-250 - black , for 2x 2.5" S-ATA HDD / SSD in 1 x 3.5" bay , support raid in 1 x 3.5" bay - ideal for raid in limited space , plastic + aluminum , hot swappable , HDD indicator
MR-i448SR	N	iCYDOCK MB448SR mobile rack , blacK , aulminum , for 1x 2.5" SATA HDD in 3.5" bay , push and eject design with latch lock

EE-i663URS		iCYDOCK MB663UR-1S , Silver , 2.5" external enclosure / mobile rack , ultra slim - 13mm , also comes with mobilerack frame / docking in 3.5" bay , screwless , aluminum , SATA hdd to usb 2.0 ; powered by USB ; with carry bag - also works MB663UR series external enclosure
EE-i663URB		iCYDOCK MB663UR-1SB , Black , 2.5" external enclosure / mobile rack , ultra slim - 13mm , also comes with mobilerack frame / docking in 3.5" bay , screwless , aluminum , SATA hdd to usb 2.0 ; powered by USB ; with carry bag - also works MB663UR series external enclosure
Seagate		
HD-SN120S		seagate momentus 5400.3 st9120822as 120gb, 2.5" , S-ATA , support NCQ , 5400rpm, 8mb cache - 3 years warranty
HD-SN160S		seagate momentus 5400.4/5 , st9160827/310as 160gb, 2.5" , S-ATA2 , support NCQ , 5400rpm, 8mb cache - 3 years warranty
HD-SN160SH		seagate momentus 5400psd Hybrid - with built-in 256mb flash memory + 8mb cache , st91608220as 160gb, 2.5" , S-ATA , support NCQ , 5400rpm - 3 years warranty
HD-SN160SPG		seagate momentus 7200.2 st9160823asg , with G-Force shock protection , 160gb, 2.5" , S-ATA2 , support NCQ , 7200rpm , 8mb cache - 3 years warranty
HD-SN250S		seagate momentus 5400.4 st9250827as 250gb, 2.5" , S-ATA2 , support NCQ , 5400rpm, 8mb cache - 3 years warranty
HD-SN250SP	N	seagate momentus 7200.3 st9250421as 250gb, 2.5" , S-ATA2 , support NCQ , 7200rpm , 16mb cache - 3 years warranty
HD-SN320S		seagate momentus 5400.5 st9320320as 320gb, 2.5" , S-ATA2 , support NCQ , 5400rpm, 8mb cache - 3 years warranty
HD-SN320SP	N	seagate momentus 7200.3 st9320421as 320gb, 2.5" , S-ATA2 , support NCQ , 7200rpm , 16mb cache - 3 years warranty
HD-SN500S	N	seagate momentus 5400.6 st9500325as 500gb, 2.5" , S-ATA2 , support NCQ , 5400rpm, 8mb cache - 3 years warranty
HD-SN500SP	C	seagate momentus 7200.4 st9500420as 500gb, 2.5" , S-ATA2 , support NCQ , 7200rpm , 16mb cache - 3 years warranty
WD		
HD-WN120S		Western Digital SCORPiO WD1200BEVS , 2.5" 9.5mm , 120gb SATA , 5400rpm , 8mb cache, 12ms - 3 years warranty
HD-WN160S		Western Digital SCORPiO WD1600BEVS , 2.5" 9.5mm , 160gb SATA , 5400rpm , 8mb cache, 12ms - 3 years warranty
HD-WN160SPF	N	Western Digital SCORPiO WD1600BJKT , with free-Fall sensor , 2.5" 9.5mm , 160gb SATA , 7200rpm , 16mb cache, 12ms - 3 years warranty
HD-WN250S		Western Digital SCORPiO WD2500BEVS , 2.5" 9.5mm , 250gb SATA , 5400rpm , 8mb cache, 12ms - 3 years warranty
HD-WN250SP	N	Western Digital SCORPiO WD2500BEKT , 2.5" 9.5mm , 250gb SATA , 7200rpm , 16mb cache, 12ms - 3 years warranty
HD-WN320S		Western Digital SCORPiO WD3200BEVT , 2.5" 9.5mm , 320gb SATA-2 , 5400rpm , 8mb cache, 12ms - 3 years warranty
HD-WN320SP	N	Western Digital SCORPiO WD3200BEKT , 2.5" 9.5mm , 320gb SATA , 7200rpm , 16mb cache, 12ms - 3 years warranty
HD-WN320SPF	R	Western Digital SCORPiO WD3200BJKT , with free-Fall sensor , 2.5" 9.5mm , 320gb SATA , 7200rpm , 16mb cache, 12ms - 3 years warranty
HD-WN500S	N	Western Digital SCORPiO WD5000BEVT , 2.5" 9.5mm , 500gb SATA-2 , 5400rpm , 8mb cache, 12ms - 3 years warranty
2.5" - SAS hard disk drive		
Seagate		
HD-SN146SAS	R	seagate Savvio 10K.2 - ST9146802SS 146gb, 2.5" SAS , 10000 rpm, 16mb cache, 3ms - 5 year warrenty

HD-SN146SASP	R	seagate Savvio 10K.2 - ST9146852SS 146gb, 2.5" SAS , 15000 rpm, 16mb cache, 2ms - 5 year warrenty
HD-SN300SAS	R	seagate Savvio 10K.2 - ST9300603SS 300gb, 2.5" SAS , 10000 rpm, 16mb cache, 3ms - 5 year warrenty
3.5" - SCSI hard disk drive		
Seagate		
HD-SS73P		seagate cheetah 15K.5 st373455Lw 73gb, 68pin, u320, 15k rpm, 16mb cache, 3.5/4.0ms - 5 year warrenty
HD-SS73PC		seagate cheetah 15K.5 st373455Lc 73gb, 80pin SCA , u320, 15k rpm, 16mb cache, 3.5/4.0ms - 5 year warrenty
HD-SS146P		seagate cheetah 15K.5 st3146855Lw 146gb, 68pin, u320, 15k rpm, 16mb cache, 3.5/4.0ms - 5 year warrenty
HD-SS146PC		seagate cheetah 15K.5 st3146855Lc 146gb, 80pin SCA , u320, 15k rpm, 16mb cache, 3.5/4.0ms - 5 year warrenty
HD-SS300P	R	seagate cheetah 15K.5 st3300655Lw 300gb, 68pin, u320, 15k rpm, 16mb cache, 3.5/4.0ms - 5 year warrenty
HD-SS300PC	R	seagate cheetah 15K.5 st3300655LC 300gb, 80pin SCA , u320, 15k rpm, 16mb cache, 3.5/4.0ms - 5 year warrenty
3.5" - SAS (Serial Attached SCSI)		
MR-i123iKK	N	iCYDOCK MB123iK-1B , internal mobilerack , blacK , aluminum , for 3.5" SAS or SATA HDD , 40mm rear cooling fan , with keylock
MR-i671iK	N	iCYDOCK MB671iK , screwless + trayless , for 3.5" SAS or S-ATA HDD , silver+black , heavy duty steel + aluminum , 2 segment key-lock , hot swappable , short depth compact size design , 40mm cooling fan
MR-i453iPF	N	iCYDOCK MB453iPF , 3 x hot-swappable in 2 x 5.25" bay - SAS or SATA mobile rack (ideal for raid 0/1/1E/5) , anti-shank design , aluminum , black , latch-lock , with temp. sensor , audio alarm warning , LED indication for Drive activity/overheat/failure + Fan working/failure status ; Interchangeable tray (EE-iA5XiT or MR-iA45XiT) compatiable with external enclosure : MB561S-4S , MB559US , MB559UEA / mobile rack : MB453SPF , MB454SPF , MB455SPF
Seagate		
HD-SAS73P		seagate cheetah 15K.5 - ST373455SS 73gb, SAS , 15000 rpm, 16mb cache, 3.5/4.0ms - 5 year warrenty
HD-SAS146P		seagate cheetah 15K.5 - ST3146855SS 146gb, SAS , 15000 rpm, 16mb cache, 3.5/4.0ms - 5 year warrenty
HD-SAS300P		seagate cheetah 15K.6 - ST3300656SS 300gb, SAS , 15000 rpm, 16mb cache, 3.4/3.9ms - 5 year warrenty
HD-SAS400	R	seagate cheetah NS - ST3400755SS 400gb, SAS , 10000 rpm, 16mb cache, 3.5/4.0ms - 5 year warrenty
HD-SAS450P	R	seagate cheetah 15K.6 - ST3450856SS 450gb, SAS , 15000 rpm, 16mb cache, 3.5/4.0ms - 5 year warrenty
HD-SAS500R32		seagate Barracuda ES.2 - ST3500620SS 500gb , SAS , 7200 rpm , raid edition , 16mb cache, 3.5/4.0ms - 5 year warrenty - designed for 24x7 business-critical applications (NAS , video surveillance ... ETC) - 3 years warrenty
HD-SAS600	R	seagate cheetah NS.2 - ST3600002SS 600gb, SAS , 10000 rpm, 16mb cache, 3.5/4.0ms - 5 year warrenty
HD-SAS1000R32		seagate Barracuda ES.2 - ST31000640SS 1000gb , SAS , 7200 rpm , raid edition , 16mb cache, 3.5/4.0ms - 5 year warrenty - designed for 24x7 business-critical applications (NAS , video surveillance ... ETC) - 5 years warrenty
External HDD accessories		
CB-D18948		Dicota N18948N memory pocket - for 2.5" external hdd - offer extra scratch + shock protection - support hdd upto 145x85x25mm

CB-D17888		Dicota Z17888P baseXX - for 3.5" external hdd - offer extra scratch + shock protection , extra compartments for accessories - support hdd upto 215x160x38mm
MP-WDTV	N	WD TV WDAVP00BE - HD media player , support 1080p HD video , with remote control , 2 x USB port for external usb storage device , video out (RCA + HDMi) , audio out (RCA + optical S/PDiF + HDMi) - 1 year warranty
MP-SFT	C	Seagate STCED101-RK Freeagent Theatermultimedia player , support 1080i HD video , with built-in docking for seagate freeagent Go , remote control , 1x USB port for external usb storage device , video out : RCA+S-video+component ; audio out : RCA+coaxial S/PDiF - 2 years warranty
Maxtor		http://www.maxtorsolutions.com/en/Main/office_biz.html
2.5" portable		
EH-M250PoT4M		Maxtor 250gb Portable OneTouch 4 Mini , STM902503OTD3E1-RK , with 1-touch backup + security software , aluminum , 250gb (2.5", 5400rpm, 8mb cache, 12.5ms), 124x81x15mm, usb 2.0, usb-powered - 5 years warranty
EH-M320PoT4M		Maxtor 320gb Portable OneTouch 4 Mini , STM903203OTD3E1-RK , with 1-touch backup + security software , aluminum , (2.5", 5400rpm, 8mb cache, 12.5ms), 124x81x15mm, usb 2.0, usb-powered - 5 years warranty
3.5"		
EH-M250oT4	N	Maxtor 250gb OneTouch 4 STM302503oTD3E1-RK , with 1-touch backup , (3.5", 7200rpm, 16mb cache), 171x149x63mm , usb 2.0 - 5 years warranty
EH-M1000CA	N	Maxtor 1Tb/1000gb Central Axis STM310005CAD00G-RK , with Password Protection , (3.5", 7200rpm, 32mb cache), 172x63.3x 150.3mm , usb 2.0 + gigabit UTP network ready - 5 years warranty
EH-M1500oT4	C	Maxtor 1.5Tb/1500gb OneTouch 4 STM315005oTD3E1-RK , with 1-touch backup , (3.5", 7200rpm, 16mb cache), 171x149x63mm , usb 2.0 - 5 years warranty
Seagate		
2.5" portable		
EH-SADC		seagate 100521934 Docking station+ Carry case fro Freeagent Go 2E1 series
EH-S250FGS		seagate ST902503FGD2E1-RK Freeagent Go , Silver , 250gb (2.5", 5400rpm, 8mb cache, 12.5ms), 130x80x12.5mm , usb 2.0, usb-powered , with auto-backup software , support optional dock + carry case - 5 years warranty
EH-S250FGK		seagate ST902503FAD2E1-RK Freeagent Go , blacK , 250gb (2.5", 5400rpm, 8mb cache, 12.5ms), 130x80x12.5mm , usb 2.0, usb-powered , with auto-backup software , support optional dock + carry case - 5 years warranty
EH-S250FGM		seagate ST902503FDD2E1-RK Freeagent Go-Mac , (mac ready or for pc) , with extra docking station + carry bag , silver , 250gb (2.5", 5400rpm, 8mb cache, 12.5ms), 137x80x17.5mm , usb 2.0+ieee1394A/B , usb-powered , with auto-backup software - 5 years warranty
EH-S250FT	C	seagate ST902503FGA2E1-RK Freeagent Theater , support 1080i HD video , with FreeAgent Theater multimedia player with remote control + Freeagent Go external hdd + extra docking station , black+silver , 250gb (2.5", 5400rpm, 8mb cache, 12.5ms), 183x180x31mm , front usb 2.0 for usb device , video out : RCA+S-video+component ; audio out : RCA+coaxial S/PDiF - 5 years warranty on hdd / 2 years on dock + player

EH-S320FGS		seagate ST903203FGD2E1-RK Freeagent Go , Silver , 320gb (2.5", 5400rpm, 8mb cache, 12.5ms) , 130x80x12.5mm , usb 2.0, usb-powered , with auto-backup software , support optional dock + carry case - 5 years warranty
EH-S320FGK		seagate ST903203FAD2E1-RK Freeagent Go , blacK , 320gb (2.5", 5400rpm, 8mb cache, 12.5ms) , 130x80x12.5mm , usb 2.0, usb-powered , with auto-backup software , support optional dock + carry case - 5 years warranty
EH-S320FGL		seagate ST903203FBD2E1-RK Freeagent Go , bLue , 320gb (2.5", 5400rpm, 8mb cache, 12.5ms) , 130x80x12.5mm , usb 2.0, usb-powered , with auto-backup software , support optional dock + carry case - 5 years warranty
EH-S320FGR		seagate ST903203FDD2E1-RK Freeagent Go , Red , 320gb (2.5", 5400rpm, 8mb cache, 12.5ms) , 130x80x12.5mm , usb 2.0, usb-powered , with auto-backup software , support optional dock + carry case - 5 years warranty
EH-S320FGM		seagate ST903203FDD2E1-RK Freeagent Go-Mac , (mac ready or for pc) , with extra docking station + carry bag , silver , 320gb (2.5", 5400rpm, 8mb cache, 12.5ms), 137x80x17.5mm , usb 2.0+ieee1394A/B , usb-powered , with auto-backup software - 5 years warranty
EH-S500FGS		seagate ST905003FGD2E1-RK Freeagent Go , Silver , 500gb (2.5", 5400rpm, 8mb cache, 12.5ms) , 130x80x12.5mm , usb 2.0, usb-powered , with auto-backup software , support optional dock + carry case - 5 years warranty
EH-S500FGK		seagate ST905003FAD2E1-RK Freeagent Go , blacK , 500gb (2.5", 5400rpm, 8mb cache, 12.5ms) , 130x80x12.5mm , usb 2.0, usb-powered , with auto-backup software , support optional dock + carry case - 5 years warranty
EH-S500FGM		seagate ST905003FJD105-RK Freeagent Go-Mac , (mac ready or for pc) , with extra docking station + carry bag , silver , 500gb (2.5", 5400rpm, 8mb cache, 12.5ms), 137x80x17.5mm , usb 2.0+ieee1394A/B , usb-powered , with auto-backup software - 5 years warranty
EH-S500FT	C	seagate ST902503FGA2E1-RK Freeagent Theater , support 1080i HD video , with FreeAgent Theater multimedia player with remote control + Freeagent Go external hdd + extra docking station , black+silver , 250gb (2.5", 5400rpm, 8mb cache, 12.5ms), 183x180x31mm , front usb 2.0 for usb device , video out : RCA+S-video+component ; audio out : RCA+coaxial S/PDiF - 5 years warranty on hdd / 2 years on dock + player
3.5"		
EH-S500FDS	N	seagate Freeagent Desktop , Silver , ST305004FDD2E1-RK 500gb (3.5", 7200rpm, 16mb cache), 175x172x34mm (exclude base) , usb 2.0 - 5 years warranty
EH-S500FPUEF		seagate Freeagent Pro ST305004FDD1E3-RK 500gb (3.5", 7200rpm, 16mb cache), 190x162x35mm (exclude base) , usb 2.0+ eSATA+Firewire , with auto-backup software - 5 years warranty
EH-S500FDM	N	seagate Freeagent Desktop for Mac , (mac ready or for pc) , ST305005FJD105-RK , silver , 500gb (3.5", 7200rpm, 16mb cache), 185x152x38mm (exclude base) , usb 2.0+ieee1394B/A , with auto-backup software - 5 years warranty
EH-S1000FDS	N	seagate Freeagent Desktop ST310005FDD2E1-RK , Silver , 1Tb/1000gb (3.5", 7200rpm, 16mb cache), 175x172x34mm (exclude base) , usb 2.0 - 5 years warranty

EH-S1000FPUEF		seagate Freeagent Pro/XTreme , black , 1Tb/1000gb (3.5", 7200rpm, 16mb cache), 175x172x34mm (exclude base) , usb 2.0 + eSATA + Firewire , with auto-backup software - 5 years warranty
EH-S1000FDM	N	seagate Freeagent Desktop Mac , (mac ready or for pc) , ST310005FJD105-RK , silver , 1Tb/1000gb (3.5", 7200rpm, 16mb cache), 185x152x38mm (exclude base) , usb 2.0+ieee1394B/A , with auto-backup software - 5 years warranty
EH-S1000x2NURH	R	seagate BlackArmor® NAS 420 , ST320005SHD10G-RK , with built-in raid (0, 1, 0+1/10 , 5, JBOD - raid 0+1/10, 5 only function when 4 hdd used) + lcd display , 2Tb (2 x Hot-swappable 1TB/1000gb) , 3.5", 7200rpm, 8.9ms , on-board 1.2 GHZ processor, 256mb memory , 4xusb 2.0 + dual gigabit UTP network ready (support wirelees network via additional access point) , with backup software + cooling fan - 3 years warranty
EH-S1000x4NURH	R	seagate BlackArmor® NAS 440 , ST340005SHD10G-RK , with built-in raid (0, 1, 0+1/10 , 5, JBOD) + lcd display , 4Tb (4 x Hot-swappable 1TB/1000gb) , 3.5", 7200rpm, 8.9ms , on-board 1.2 GHZ processor, 256mb memory , 4xusb 2.0 + dual gigabit UTP network ready (support wirelees network via additional access point) , with backup software + cooling fan - 3 years warranty
EH-S1500FD	N	seagate Freeagent Desktop ST315005FDD2E1-RK , silver , 1.5Tb/1500gb (3.5", 7200rpm, 16mb cache), 175x172x34mm (exclude base) , usb 2.0 - 5 years warranty
EH-S1500FXUEF	N	seagate Freeagent XTreme ST315005FPD2E3-RK , black , 1.5Tb/1500gb (3.5", 7200rpm, 16mb cache), 175x172x34mm (exclude base) , usb 2.0 + eSATA + Firewire , with auto-backup software - 5 years warranty
EH-S1500FDM	N	seagate Freeagent Desktop for Mac , (mac ready or for pc) , ST315005FJD105-RK , silver , 1.5Tb/1500gb (3.5", 7200rpm, 16mb cache), 185x152x38mm (exclude base) , usb 2.0+ieee1394B/A , with auto-backup software - 5 years warranty
EH-S1500x4NURH	R	seagate BlackArmor® NAS 440 , ST360005SHD10G-RK , with built-in raid (0, 1, 0+1/10 , 5, JBOD) + lcd display , 6Tb (4 x Hot-swappable 1.5TB/1500gb) , 3.5", 7200rpm, 8.9ms , on-board 1.2 GHZ processor, 256mb memory , 4xusb 2.0 + dual gigabit UTP network ready (support wirelees network via additional access point) , with backup software + cooling fan - 3 years warranty
Western Digital		http://www.westerndigital.com/en/products/index.asp?Cat=5&Language=en
2.5" portable		
EH-W160PB		WD WDME1600 passort essential portable 160gb Portable Black (2.5", 5400rpm, 8mb cache, 12ms), 129x80x15mm, usb 2.0, usb-powered - 2 years warranty
EH-W160PR	N	WD WDMER1600 passort essential portable 160gb Portable Red (2.5", 5400rpm, 8mb cache, 12ms), 129x80x15mm, usb 2.0, usb-powered - 2 years warranty
EH-W160PL	N	WD WDMEB1600 passort essential portable 160gb Portable bLue (2.5", 5400rpm, 8mb cache, 12ms), 129x80x15mm, usb 2.0, usb-powered - 2 years warranty
EH-W250PB		WD WDME2500 passort essential portable 250gb Black (2.5", 5400rpm, 8mb cache, 12ms), 129x80x15mm, usb 2.0, usb-powered - 2 years warranty
EH-W250PR	N	WD WDMER2500 passort essential portable 250gb Red (2.5", 5400rpm, 8mb cache, 12ms), 129x80x15mm, usb 2.0, usb-powered - 2 years warranty
EH-W250PL	R	WD WDMEB2500TE passort essential portable 250gb bLue (2.5", 5400rpm, 8mb cache, 12ms), 129x80x15mm, usb 2.0, usb-powered - 2 years warranty

EH-W250PTE		WD WDML2500 passort elite portable 250gb (2.5", 5400rpm, 8mb cache, 12ms) , with capacity display gauge, automatic backup software , synchronized and secure , remote access , 126x80x15mm, usb 2.0, usb-powered - 5 years warranty
EH-W320PB		WD WDME3200 portable 320gb , Black , (2.5", 5400rpm, 8mb cache, 12ms), 129x80x15mm, usb 2.0, usb-powered - 2 years warranty
EH-W320PR	N	WD WDMER3200 portable 320gb , Red , (2.5", 5400rpm, 8mb cache, 12ms), 129x80x15mm, usb 2.0, usb-powered - 2 years warranty
EH-W320PL	N	WD WDMEB3200 portable 320gb , bLue , (2.5", 5400rpm, 8mb cache, 12ms), 129x80x15mm, usb 2.0, usb-powered - 2 years warranty
EH-W320PTE	R	WD ML3200TE passort elite portable 320gb (2.5", 5400rpm, 8mb cache, 12ms) , with capacity display gauge, automatic backup software , synchronized and secure , remote access , 126x80x15mm, usb 2.0, usb-powered - 5 years warranty
EH-W320PS	N	WD MS3200TE passort Studio portable , (mac ready or for pc) , 320gb (2.5", 5400rpm, 8mb cache, 12ms) , with capacity display gauge , 126x80x15mm, Firewire 1394A + usb 2.0 , usb-powered - 5 years warranty
EH-W500PB	N	WD WDME5000TE portable 500gb , Black , (2.5", 5400rpm, 8mb cache, 12ms), 126x80x15mm, usb 2.0, usb-powered - 2 years warranty
EH-W500PR	N	WD WDMER5000TE portable 500gb , Red , (2.5", 5400rpm, 8mb cache, 12ms), 126x80x15mm, usb 2.0, usb-powered - 2 years warranty
EH-W500PL	N	WD WDMEB5000TE portable 500gb , bLue , (2.5", 5400rpm, 8mb cache, 12ms), 126x80x15mm, usb 2.0, usb-powered - 2 years warranty
EH-W500PEL	N	WD WDML5000 Passort Elite portable 500gb , bLue , (2.5", 5400rpm, 8mb cache, 12ms) , with capacity display gauge, automatic backup software , synchronized and secure , remote access , 126x80x15mm, usb 2.0, usb-powered - 5 years warranty
3.5"		
EH-W320UE		WD MyBook premium ES , WDG1SU3200 , with capacity gauge display , external 320gb (3.5", 7200rpm, 8mb cache, 8.9ms) , usb 2.0 + E-sata - 2 year warranty
EH-W320UEF		WD WDH1CS3200 My Book Home edition + capacity gauge display , auto backup software , 320gb (3.5", 7200rpm, 8.9ms) , black , usb 2.0+e-sata+ieee1394A - 3 years warranty
EH-W320UEFS		WD WDH1Q3200 my book Studio edition (mac ready or for pc) + capacity gauge display , auto backup software , 320gb (3.5", 7200rpm, 8.9ms) , silver , usb 2.0+e-sata+ieee1394A+1394B - 5 years warranty
EH-W500U		WD MyBook essential 2.0 , WDH1U5000 , black , external 500gb (3.5", 7200rpm, 16mb cache, 8.9ms) , usb 2.0 - 2 years warranty
EH-W500Uo		WD MyBook Office , WDH1B5000 , with capacity gauge display , auto backup software , silver , external 500gb (3.5", 7200rpm, 16mb cache, 8.9ms) , usb 2.0 , with extra softwares : backup + MioNet + small business tool - 2 years warranty
EH-W500UEF		WD WDH1CS5000 My Book Home edition + capacity gauge display , auto backup software , 500gb (3.5", 7200rpm, 8.9ms) , black , usb 2.0+e-sata+ieee1394A - 3 years warranty
EH-W500UEFS		WD WDH1Q5000 my book Studio edition (mac ready or for pc) + capacity gauge display , auto backup software , 500gb (3.5", 7200rpm, 8.9ms) , silver , usb 2.0+e-sata+ieee1394A+1394B - 5 years warranty

EH-W500NU		WD WDG1NC5000 mybook world edition , with capacity gauge display , auto backup software , external 500gb (3.5", 7200rpm, 16mb cache, 8.9ms) , usb 2.0 + gigabit UTP network ready - 3 years warranty
EH-W750UEF	N	WD WDH1CS7500 My Book Home edition + capacity gauge display , 750gb (3.5", 7200rpm, 8.9ms) , black , usb 2.0+e-sata+ieee1394A , with backup software - 3 years warranty
EH-W1TU		WD MyBook essential 2.0 , WDH1U10000 , black , external 1Tb/1000gb (3.5", 7200rpm, 16mb cache, 8.9ms) , usb 2.0 - 2 years warranty
EH-W1TUo	N	WD MyBook Office , WDH1B10000 , with capacity gauge display , auto backup software , silver , external 1000gb (3.5", 7200rpm, 16mb cache, 8.9ms) , usb 2.0 , with extra softwares : backup + MioNet + small business tool - 2 years warranty
EH-W1TUEFS		WD WDH1Q10000 my book Studio edition (mac ready or for pc) + capacity gauge display , auto backup software , 1000gb/1TB (3.5", 7200rpm, 8.9ms) , silver , usb 2.0+e-sata+ieee1394A+1394B - 5 years warranty
EH-W1TNU		WD WDG1NC10000 mybook world edition , with capacity gauge display , auto backup software , external 1TB/1000gb (3.5", 7200rpm, 16mb cache, 8.9ms) , usb 2.0 + gigabit UTP network ready - 3 years warranty
EH-W1Tx2UR	N	WD WDH2U20000 mybook mirror edition with built-in raid (0, 1, JBOD) + capacity gauge display , auto backup software , 2TB/2x1000gb (3.5", 7200rpm, 8.9ms) , usb 2.0 - 3 years warranty
EH-W1Tx2UEFRS		WD WDH2Q20000 my book Studio edition (mac ready or for pc) with built-in raid (0, 1, JBOD) + capacity gauge display , auto backup software , 2TB/2x1000gb (3.5", with intellipower 5400-7200rpm for powersaveing , 8.9ms) , silver , usb 2.0+e-sata+ieee1394A+1394B - 5 years warranty
EH-W1Tx2NUR		WD WDG2NC20000 mybook world edition II with built-in raid (0, 1, JBOD) + capacity gauge display , auto backup software , 2TB/2x1000gb (3.5", 7200rpm, 8.9ms) , usb 2.0 + gigabit UTP network ready (support wirelees network via additional access point) - 3 years warranty
EH-W1Tx4NURH	N	WD WDA4NC40000E ShareSpace , with built-in raid (0, 1, 5, JBOD) + capacity gauge display , 4Tb, 4 x Hot-swappable 1TB/1000gb , 3.5", 7200rpm, 8.9ms , with intellipower 5400-7200rpm for powersaveing , 3xusb 2.0 + gigabit UTP network ready (support wirelees network via additional access point) , with backup software + kensington Lock + 120mm cooling fan - 3 years warranty
EH-W2TU	C	WD MyBook essential 2.0 , WDH1U20000 , black , external 2Tb/2000gb (3.5", 7200rpm, 16mb cache, 8.9ms) , usb 2.0 - 2 years warranty
EH-W2TUEF	C	WD WDH1CS20000 My Book Home edition + capacity gauge display , 2Tb/2000gb (3.5", 7200rpm, 8.9ms) , black , usb 2.0+e-sata+ieee1394A , with backup software - 3 years warranty
EH-W2TUEFS	C	WD WDH1Q10000 my book Studio edition (mac ready or for pc) + capacity gauge display , auto backup software , 1000gb/1TB (3.5", 7200rpm, 8.9ms) , silver , usb 2.0+e-sata+ieee1394A+1394B - 5 years warranty

EH-W2Tx4NURH	C	WD WDA4NC80000E ShareSpace , with built-in raid (0, 1, 5, JBOD) + capacity gauge display , 8Tb, 4 x hot-swappable 2TB/2000gb , 3.5", 7200rpm, 8.9ms , with intellipower 5400-7200rpm for powersaveing , 3xusb 2.0 + gigabit UTP network ready (support wirelees network via additional access point) , with backup software + kensington Lock + 120mm cooling fan - 3 years warranty

Optical device		
Dvd Writer		
Dacal		
DS-D016RW	N	dacal powerdrive DC-106RW - cd/dvd library + built-in super-multi dvd writer (8X DVD / 24X CD / 8xDVD±RW / 6X DVD±RDL/ 5X DVD-RAM) , ivory ; upto 100 x DVD , CD , usb interface with 1 x usb downstream hub , support daisychain upto 127 unit - management software bundled
Canon		
DW-CDW100	R	Canon DW-100 , External , support HD (High Definition) or SD (Standard Definition) direct video recording from selected video camera , support HD video playback through selected video camera , DL DVD-R/RW , 3 copy option , USB2.0 - retail pack
Samsung		
DW-S22So		Samsung SH-S223 , 22x , Sata , Oem pack , black , with SAT , super-multi : DL dvd+R , dvd±r/rw + dvd-ram + cd+/-rw ; 2mb
DW-S22S	N	Samsung SH-S223F , 22x , Sata , black , with SAT , super-multi : DL dvd+R , dvd±r/rw + dvd-ram + cd+/-rw ; 2mb - retail pack
DW-S22SL	N	Samsung SH-S223Q , 22x , Sata , Ligh-scribe, black , with SAT, TruDirect real time recording , super-multi : DL dvd+R , dvd±r/rw + dvd-ram + cd+/-rw ; 2mb - retail pack
DW-SE22L	N	Samsung SE-S224q , 22x , Ligh-scribe, black , with SAT, TruDirect real time recording , super-multi : DL dvd+R , dvd±r/rw + dvd-ram + cd+/-rw ; 2mb , USB2.0 - retail pack
sony		
DW-S20Bo	N	sony ad7200a 20x super-multi , IDE , black , DL dvd±R , dvd±r/rw + dvd-ram + cd+/-rw ; 2mb - Oem pack
DW-S20BS	N	sony DRU-V200S , 20x , super-multi , Sata , black , DL dvd±R , dvd±r/rw + dvd-ram + cd+/-rw ; 2mb - retail pack
DW-SE20U		sony DRX-840U external , 20x , blue + mirror front panel , DL dvd±R , dvd±R/RW + DVD-RAM + cd+/-rw , usb2.0 , DL dvd+R , USB , 2mb - retail pack
DW-SE8SU		Sony DRX-S70u external slim (165x152x20mm) , Black , DL dvd±R , dvd±R/RW + DVD-RAM + cd+/-rw , usb2.0 ; 2mb - retail pack
LG		
DW-L22		LG GH22NP20 , 22x , black+beige bezel , support SecurDisc technology (password protection , digital signature , data integrity check , PDF copy protection) , super-multi : DL dvd+R , dvd±r/rw + dvd-ram + cd+/-rw ; 2mb - retail pack
DW-L22L		LG GH22LP20 , 22x , Lightscribe , black+beige bezel , support SecurDisc technology (password protection , digital signature , data integrity check , PDF copy protection) , super-multi : DL dvd+R , dvd±r/rw + dvd-ram + cd+/-rw ; 2mb - retail pack
DW-L22S	N	LG GH22NS30 , 22x , Sata , black+beige bezel , support SecurDisc technology (password protection , digital signature , data integrity check , PDF copy protection) , super-multi : DL dvd+R , dvd±r/rw + dvd-ram + cd+/-rw ; 2mb - retail pack

DW-L22LS		LG GH22LS30 , 22x , Lightscribe , Sata , black+beige bezel , support SecurDisc technology (password protection , digital signature , data integrity check , PDF copy protection) , super-multi : DL dvd+R , dvd±r/rw + dvd-ram + cd+/-rw ; 2mb - retail pack
DW-LE20L		LG GE20LU10 , External . 20x + Lightscribe , with AWS (Auot Write Strategy) , support SecurDisc technology (password protection , digital signature , data integrity check , PDF copy protection) , super-multi : DL dvd+R , dvd±r/rw + dvd-ram + cd+/-rw , USB2.0 ; 2mb - retail pack
DW-LE8SL		LG GSA-E50L/GP08LU10 , External Slim (165x156x21mm) + Lightscribe , mirror finish , support SecurDisc technology (password protection , digital signature , data integrity check , PDF copy protection) , super-multi : DL dvd+R , dvd±r/rw + dvd-ram + cd+/-rw , USB2.0 ; 2mb - retail pack
dvd Writer + blu-ray reader combo drive		
LG		
DW-L16SLB6B	N	LG GGC-H20L , Sata , Lightscribe , black , SATA , 16x DVD+/-RW + 6x Blu-Ray reader + HD DVD reader combo drive - read 50Gb blu-ray disc ; DL dvd±R , dvd±r/rw , dvd-ram , 4mb buffer - retail pack
Blu-Ray Dvd Writer		
BW-LH20L		LG GGW-H20L , black , Dual Layer , Blu-Ray writer (6x) + HD-DVD rom , 50/25/17/8.5/4.7GB : DL BD-RE , DL BD-R , DL dvd+R , dvd±r/rw, dvd-ram ; 150/160/180ms , SATA , 4mb buffer for BD , 2mb buffer for DVD
BW-LE6L	N	LG BE06LU10 External , white+black with blue light , Dual Layer , Blu-Ray writer (6x) + HD-DVD rom , support SecurDisc technology (password protection , digital signature , data integrity check , PDF copy protection) , 50/25/17/8.5/4.7GB : DL BD-RE , DL BD-R , DL dvd+R , dvd±r/rw, dvd-ram ; 150/160/180ms , USB , 4mb buffer for BD , 2mb buffer for DVD
Stiffy Drive		
OT-B35		3.5" to 5.25" mounting bracket
FD-M		Mitsumi 1.44 stiffy drive - beige
FD-SB		sony 1.44 stiffy drive - black
FD-HUB	N	Hp DC361B 1.44 external usb stiffy drive - black
other STorgae		
iomega REV		
ST-iR90ii	R	iOMEGA REV35 drive , 30/90gb internal ide , 3.5" , 25mb/sec , 13ms , bootable , black , include 1 x rev disk + 3.5"->5.25" bracket - 2 years warranty
ST-iR90iS	R	iOMEGA REV35 drive , 30/90gb internal s-ata , 3.5" , black , include 1 x rev disk - 2 years warranty
ST-iR90EU	R	iOMEGA REV35 drive , 30/90gb external USB 2.0 , 25mb/sec , 13ms , black , include 1 x rev disk - 2 years warranty
ST-iR90EF	R	iOMEGA REV35 drive , 30/90gb external firewire ieee1394 , 25mb/sec , 13ms , silver , include 1 x rev disk - 2 years warranty
ST-iR140ii	R	iOMEGA REV70 drive , 70/140gb internal ide , 3.5" , 30mb/sec , 7.1ms , black , include 1 x rev disk + 3.5"->5.25" bracket - 2 years warranty
ST-iR140iiS	R	iOMEGA REV70 drive Server Backup and Disaster Recovery Kit , 70/140gb internal ide , 3.5" , 30mb/sec , 7.1ms , black , include 5 x rev disks + 3.5"->5.25" bracket , CA Solutions CD (1 x Brightstor ARCserve for Small Business Server premium edition + 5 x Brightstor ARCserve for Laptops and Desktops + 5 x eTrust Antivirus for Windows Desktops and Servers) , ONLY for Microsoft Small Business Server - 2 years warranty

ST-iR140iS	R	iOMEGA REV70 drive , 70/140gb internal Sata , 3.5" , 30mb/sec , 7.1ms , black , include 1 x rev disk + 3.5"->5.25" bracket - 2 years warranty
ST-iR140EU	R	iOMEGA REV70 drive , 70/140gb external USB 2.0 , 30mb/sec , 7.1ms , black , include 1 x rev disk - 2 years warranty
ST-iR140EUS	R	iOMEGA REV70 drive Server Backup and Disaster Recovery Kit , 70/140gb External USB , black , include 5 x rev disks , CA Solutions CD (1 x Brightstor ARCserve for Small Business Server premium edition + 5 x Brightstor ARCserve for Laptops and Desktops + 5 x eTrust Antivirus for Windows Desktops and Servers) , ONLY for Microsoft Small Business Server - 2 years warranty
ST-iRL560	R	iOMEGA REV Loader 560 , (8 x slot) , 560/1120gb external usb , 25mb/sec , 7.1ms , include 1 x rev 35/90disk , Kensington lock compatible , with CA BrightStor ARCserve Backup software - 2 years warranty
Di-iR90		iOMEGA REV 35/90gb disk
Di-iR140	R	iOMEGA REV 70/140gb disk
Quantum / Seagate Tape drive		
Travan		
ST-QT40ii	R	Quantum (Seagate) Travan 40 STT3401A-SST , 20/40gb internal ide , 3.5" , 4mb/sec , 8mb buffer , beige , include Yosemite TapeWare XE software , 1 x Travan40 (TR-7) tape , 5.25" mounting kit ; also read Travan20 tape - 2 years warranty
ST-QT40EU	R	Quantum (Seagate) Travan 40 STT6401U2-SSTE , 20/40gb external USB , 4mb/sec , 8mb buffer , black , include Yosemite TapeWare XE software , 1 x Travan40 (TR-7) tape , 5.25" mounting kit ; also read Travan20 tape - 2 years warranty
Di-T40		20/40gb travan tape
DAT		
ST-QD72iS		Quantum (Seagate) DAT-72 CD72LWH-SST , 36/72gb internal 68pin Ultra2 scsi LVD , 5.25" , 16mb buffer , black , include VERITAS Backup Exec software , also read+write DAT-72 , DDS-4 , DDS-3 - 3 years warranty
ST-QD72iSA	N	Quantum (Seagate) DAT-72 CD72SH-SST , 36/72gb internal SAta , 5.25" , 16mb buffer , black , include VERITAS Backup Exec software , also read+write DAT-72 , DDS-4 , DDS-3 - 3 years warranty
ST-QD72ES	R	Quantum (Seagate) DAT-72 CD72LWE-SST , 36/72gb external 68pin Ultra2 scsi LVD , 16mb buffer , black , include VERITAS Backup Exec software , also read+write DAT-72 , DDS-4 , DDS-3 - 3 years warranty
ST-QD72R1U	R	Quantum (Seagate) DAT-72 CD72LW1U-SST , Single unit in 1U rackmount , 36/72gb external 68pin Ultra2 scsi LVD , 16mb buffer , black , include VERITAS Backup Exec software , also read+write DAT-72 , DDS-4 , DDS-3 - 3 years warranty
ST-QD144R1U	R	Quantum (Seagate) DAT-72 CD144LW1U-SST , Dual unit in 1U rackmount , 72/144gb external 68pin Ultra2 scsi LVD , 16mb buffer , black , include VERITAS Backup Exec software , also read+write DAT-72 , DDS-4 , DDS-3 - 3 years warranty
Di-DDS5		36/72gb DDS5 tape
Chassis & accessories		
Chassis Accessories		
CA-Po		2m POwer cable - SABS approved
CA-PoD	N	2m POwer cable - Dedicated
CA-PoE		2m POwer Extension cable - SABS approved
CA-Po2		2 way 2m power cable (for psu + display device) - SABS approved
CA-Po2D	N	2 way 2m power cable (for psu + display device) - Dedicated

CH-EASS		Enermax UC-SST8 Security Screws kit - with 2 type of security screws (8+8) + 2 type of security screw drivers + keys
OT-UL		Sv-tech Usb Lock - with 1 key + 4 locks on usb port - to prevent lost of data from usb port for security - ideal for notebook or office PC
CH-AASP160W		Antec SP160W windowed side panel for p160 chassis
NB-VAS400	N	Vantec nbl-S400 - key security lock for PC / Notebook / Lcd / monitor / projector , with locks on to D-Sub or com/serial port) , length : 200cm - retail pack
NB-VAS450	N	Vantec nbl-S450 - 4 digit combination security lock for PC / Notebook / Lcd / monitor / projector , with locks on to D-Sub or com/serial port) , length : 200cm - retail pack
NB-VAS300	N	Vantec nbl-S300 - detachable key security lock for PC / Lcd / monitor , length : 200cm - retail pack
multi-function panel in 3.5" or 5.25" bay		
CH-LABZU02S	N	Lian-li BZ-U02 Silver , multi-media i/o port with dust cover , 5.25" , 4xusb+ audio in/out+ 1xe-SATA+1x ieee1394 firewire - compatiable with most of case
CH-LABZU02B	N	Lian-li BZ-U02 Black , multi-media i/o port with dust cover , 5.25" , 4xusb+ audio in/out+ 1xe-SATA+1x ieee1394 firewire - compatiable with most of case
CH-AAVE	N	Antec Veris Elite VFD module with MCE (Media Center Edition) remote control + control knob , for 5.25" bay , black , designed by iMON , ideal for upgrading vista home preminum / ultimate to MCE , 58-keys , with bundled microsoft certified MPEG-2 encoder , reatil pack
CH-AAVP	N	Antec Veris Premier VFD module with MCE (Media Center Edition) remote control + 2 x control knob + multimedia buttons , for 2 x 5.25" bay , black , designed by iMON , ideal for upgrading vista home preminum / ultimate to MCE , 58-keys , with bundled microsoft certified MPEG-2 encoder , reatil pack
CH-AAFL		Asus FrontLinker , black - for 5.25" bay , with retractable cables to connect/charge portable device even when pc is off , 1 x usb + 1 x mini-usb + 1 x ieee1394 + 1 x eSATA + 1 x 3.5mm audio-in + 1 x 6.3mm audio-in (for karaoke) + iPoD dock retractable cable + card reader (sd/mmc/CF/MD)
CH-TAH11		thermaltake A1863 Hardcano11 , silver - 5.25" universal HDD cooler (ide/sata/scsi) + multi-function panel - 3 x fan speed controller , aluminum , with redundant hdd fan for quiteness + realibility , 3 temperature probe sensors , with Lcd display + over-heat temp. audio alarm + yellow LED - silver
CH-iA228MGR		iCYDOCK MB228MGR bodyguard , silver - 5.25" universal HDD cooler (ide/sata/scsi) + multi-function panel - 4 x fan speed controller , aluminum , with redundant hdd fan for quiteness + realibility , 3 temperature probe sensors , with Lcd display + over-heat temp. audio alarm + yellow LED - silver
CH-iA228MGC		iCYDOCK MB228MGC bodyguard , silver - 5.25" universal HDD cooler (ide/sata/scsi) + multi-function panel - 2 front USB + 1 x iEEE1394A + 1x fan speed controller , aluminum , with redundant hdd fan for quiteness + realibility , 3 temperature probe sensors , with Lcd display + over-heat temp. audio alarm + yellow LED - silver
CH-EAUCA7W		Enermax multi-function panel UC-A07FATR2W , White , with Lcd , for 5.25" bay , 2 channel fan speed controls (with blue led) + 2 x usb2.0 + 1 x ieee1394 + audio in/out
CH-ZAFM2		Zalman Fan Mate2 - fan speed mini controller , 5-11V output to reduce fan speed and noise - 1 channel
CH-ZAMFC1PS		zalman ZM-MFC1 Plus Silver , 6 channels fan controller with 6 x knobs , aluminum silver , for 5.25" bay

CH-ZAMFC1PB		zalman ZM-MFC1 Plus Black , 6 channels fan controller with 6 x knobs , aluminum black , for 5.25" bay
CH-ZAMFC2		zalman ZM-MFC2, 4 channels (1x PWM fan and 3x standard fans.) fan controller + jog wheel dial + real time display of power consumption , for 5.25"Bay , with Lcd display (animated propeller Images) + over-heat alarm + yellow LED
CH-VAMPB		ViZo MTP-101-BK Master Panel Black , for 5.25" bay , with IDE + eSATA+SATA interface (data cable + power cable included) , with on/off switch
CH-VAMPG		ViZo MTP-101-GR Master Panel Gray , for 5.25" bay , with IDE + eSATA+SATA interface (data cable + power cable included) , with on/off switch
CH-VAMPW		ViZo MTP-101-WH Master Panel White , for 5.25" bay , with IDE + eSATA+SATA interface (data cable + power cable included) , with on/off switch
CH-VAMP2		ViZo MTP-201 Master Panel 2 , Black , for 5.25" bay , with eSATA + usb + iEEE1394 +card reader + 3.5mm audio in/out + RCA Video out + 2 ch fan speed controller with knob
CH-CAM2B		Coolermaster Musketeer 2 Black , 3 x analogue meter for hdd speed + sound pressure , with L+R volume control + 7 adjustable color led for all 3 dial (red, blue, green, yellow, light blue, purple, white and flashing colors) , for 5.25" bay
Vantec		
CH-VTSX300N	N	Vantec TSX-300 , No psu : built-in 2.5" sata mobile rack + card reader , tools free for Pci+3.5"+5.25" ; 2 x front usb + audio in/out + + e-SATA + ieee1394 - upto 4x 5.25", 1x 3.5" , 4x 3.5" hidden (side removable) - 1x front + 1x rear 120mm fan upto 3 - atx
CH-VTSX200N	N	Vantec TSX-200 , No psu , light weight aluminum : built-in 2.5" sata mobile rack + card reader , tools free for Pci+3.5"+5.25" ; 2 x front usb + audio in/out + + e-SATA + ieee1394 - upto 4x 5.25", 1x 3.5" , 4x 3.5" hidden (side removable) - 1x front + 1x rear 120mm fan upto 3 - atx
Asus		
CH-ATMB22N	N	Asus TM-B22 , No psu , black+silver : with foldable front door ; 2 x front usb + audio in/out - 4x 5.25", 1x 3.5", 5x 3.5" hidden - 1 x 80mm fan support upto 2 , with dust filter , lockable side panel - micro-atx
CH-ATAD31N	N	Asus TA-D31 , No psu , black : 2 x front usb + audio in/out - 4x 5.25", 1x 3.5", 6x 3.5" hidden - 1 x 120mm fan support upto 3 , with dust filter , lockable side panel - atx
CH-ATAK21N	N	Asus TA-K21 , No psu , black+silver : 2 x front usb + audio in/out - 4x 5.25", 1x 3.5", 6x 3.5" hidden - 1 x 120mm fan support upto 3 , with dust filter , lockable side panel - atx
CH-ATAM11WN	C	Asus TA-M11 , Windowed meshed side panel , No psu , black : tools free design on pci/3.5"/5.25" ; 2 x front usb + audio in/out - 4/3x 5.25", 0/1x 3.5", 4x 3.5" hidden - 2x blue e-led 120mm + 1x 120mm fan fan upto 4 , with dust filter , lockable side panel - atx
Lian-Li		
XboX moding case		
CH-LXB01	N	Lian-li pc-XB01 modding chase for xbox360 , black , hairline brushed anodized aluminum , support watercooling for modding , tower or desktop , made in Taiwan , extra cooling + quieter cooling
desktop		http://www.lian-li.com/v2/en/product/product04.php?cl_index=1&sc_index=25&ss_index=64

CH-LA01SN	N	Lian-li pc-A01 , Silver , No psu , tower or desktop convertiable , made in Taiwan , hairline brush anodized aluminum , anti-vibration kit ; 1394 firewire + 2 x front usb + audio in/out - 1x 5.25", 2x 3.5", 1x 3.5" hidden - support upto 2 x 80mm fan , adjustable cpu air duct - micro-atx
CH-LA01BN	C	Lian-li pc-A01 , Black , No psu , tower or desktop convertiable , made in Taiwan , hairline brush anodized aluminum , anti-vibration kit ; 1394 firewire + 2 x front usb + audio in/out - 1x 5.25", 2x 3.5", 1x 3.5" hidden - support upto 2 x 80mm fan , adjustable cpu air duct - micro-atx
CH-LC37BN		Lian-li pc-C37 , Black , No psu (support stand psu) , 94mm height slimline desktop , made in Taiwan , hairline brush anodized aluminum , removable drive cage with anti-vibration kit , with support bar ; 1394 firewire + 2 x front usb + audio in/out - 1 x 5.25", 2x 3.5" hidden - 1 x 1500rpm 70mm fan upto 2 - expansion card required to be low-profile - micro-atx
CH-LC39BN	C	Lian-li pc-C39 , Black , No psu (support stand psu) , 94mm height slimline desktop , with wireless MCE remote control + built-in sensor , made in Taiwan , hairline brush anodized aluminum , removable drive cage with anti-vibration kit , with support bar ; 1394 firewire + 2 x front usb + audio in/out - 1 x 5.25", 2x 3.5" hidden - 2x 1500rpm 70mm fan - expansion card required to be low-profile - micro-atx
CH-LC33BN	C	Lian-li pc-C33 , Black , No psu , desktop , made in Taiwan , hairline brush anodized aluminum , with support bar ; e-Sata + 1394 firewire + 4 x front usb + audio in/out - 2/1 x 5.25", 0/1 x 3.5", 4x 3.5" hidden (anti-vibration removable drive cage) - 2 x 1500rpm 120mm fan (position adjustable on support barl) upto 3 fan - atx
CH-LC32SN		Lian-li pc-C32 , Silver , No psu , desktop or rackmount (rackmount kit included) , made in Taiwan , hairline brush anodized aluminum , with support bar ; 1394 firewire + 2 x front usb + audio in/out - 2/1 x 5.25", 0/1 x 3.5", 4x 3.5" hidden (anti-vibration removable drive cage) - 2 x 1500rpm 120mm fan (position adjustable on support bar) upto 3 fan - atx
CH-LC32BN		Lian-li pc-C32 , Black , No psu , desktop or rackmount (rackmount kit included) , made in Taiwan , hairline brush anodized aluminum , with support bar ; 1394 firewire + 2 x front usb + audio in/out - 2/1 x 5.25", 0/1 x 3.5", 4x 3.5" hidden (anti-vibration removable drive cage) - 2 x 1500rpm 120mm fan (position adjustable on support bar) upto 3 fan - atx
CH-LC34FBN	C	Lian-li pc-C34F , Black , No psu , desktop with front lockable hdd cage with sata hotswap backplane kit , with wireless MCE remote control + built-in sensor , made in Taiwan , hairline brush anodized aluminum , with support bar ; e-Sata + 1394 firewire + 4 x front usb + audio in/out - 2/1 x 5.25", 0/1 x 3.5", 4x 3.5" hidden (anti-vibration removable drive cage , front accessed with hotswap backplane kit) - 2 x 1500rpm 120mm fan (position adjustable on support bar) upto 3 fan - atx
mini tower / cube chassis		
CH-LQ07BN	C	Lian-li pc-Q07 mini-itx chassis , No psu (use optional standard psu , with psu bracket , 180 degrees reversable for psu fan facing cpu or side panel) , black , mini size (193x280x208mm) , made in Taiwan , hairline brush anodized aluminum , removable mb side panel ; 2x front usb - 1x 5.25", 1x 3.5" hidden (anti-vibration removable drive cage) - only for mini-itx

CH-LA03BN	C	Lian-li pc-A03 , black , No psu , mini-tower (368x188x447mm) , left sidepanel mb mounting design (for cpu to be positioned away from the psu) , made in Taiwan , hairline brush anodized aluminum , removable front panel with jointer ; 2 x front usb + audio in/out - tool-free 2x 5.25", 1x 3.5", 3x 3.5" hidden (anti-vibration removable drive cage - side accessed) - 1x blue led 120mm + 1x blue led 92mm fan - micro-atx
CH-LA06SN		Lian-li pc-A06 , Silver , No psu (front poistioned) , mini-tower (381x210x490mm) for atx , made in Taiwan , hairline brush anodized aluminum , removable front panel with jointer ; ieee1394 + 2 x front usb + audio in/out - 2x 5.25", 1x 3.5", 3x 3.5" hidden (anti-vibration removable drive cage) - 1 x blue led 120mm + 1x80mm fan upto 3 - atx
CH-LA06BN		Lian-li pc-A06 , Black , No psu (front poistioned) , mini-tower (381x210x490mm) for atx , made in Taiwan , hairline brush anodized aluminum , removable front panel with jointer ; ieee1394 + 2 x front usb + audio in/out - 2x 5.25", 1x 3.5", 3x 3.5" hidden (anti-vibration removable drive cage) - 1 x blue led 120mm + 1x80mm fan upto 3 - atx
CH-LA05NSN	C	Lian-li pc-A05N , Silver , No psu (front poistioned) , mini-tower (381x210x490mm) for atx , made in Taiwan , hairline brush anodized aluminum , removable front panel with jointer ; 2 x front usb + audio in/out - tool-free 2x 5.25", 1x 3.5", 3x 3.5" hidden (anti-vibration removable drive cage) - 2 x 120mm upto 3 - atx
CH-LA05NBN	C	Lian-li pc-A05N , Black , No psu (front poistioned) , mini-tower (381x210x490mm) for atx , made in Taiwan , hairline brush anodized aluminum , removable front panel with jointer ; 2 x front usb + audio in/out - tool-free 2x 5.25", 1x 3.5", 3x 3.5" hidden (anti-vibration removable drive cage) - 2 x 120mm upto 3 - atx
CH-LA05SN		Lian-li pc-A05 , Silver , No psu (front poistioned) , mini-tower (381x210x490mm) for atx , made in Taiwan , hairline brush anodized aluminum , removable front panel with jointer ; ieee1394 + 2 x front usb + audio in/out - 2x 5.25", 1x 3.5", 3x 3.5" hidden (anti-vibration removable drive cage) - 2 x 120mm upto 3 - atx
CH-LA05BN		Lian-li pc-A05 , Black , No psu (front poistioned) , mini-tower (381x210x490mm) for atx , made in Taiwan , hairline brush anodized aluminum , removable front panel with jointer ; ieee1394 + 2 x front usb + audio in/out - 2x 5.25", 1x 3.5", 3x 3.5" hidden (anti-vibration removable drive cage) - 2 x 120mm upto 3 - atx
CH-LA06FBN	C	Lian-li pc-A06F , black , No psu (wit psu bracket , 180 degrees reversable for psu fan facing cpu or side panel) , mini-tower (381x210x490mm) for atx , made in Taiwan , hairline brush anodized aluminum , removable front panel with jointer ; 2 x front usb + audio in/out - tool-free 4x 5.25", 3x 3.5" hidden (anti-vibration removable drive cage - side accessed) - 1x120mm + 1x 140mm upto 3 - atx
CH-LV350SN		Lian-li pc-V350 , Silver , No psu , right/left side-accessed 5.25" device , cube chassis , made in Taiwan , hairline brush anodized aluminum , slide out motherboard tray ; 1394 firewire + 2 x front usb + audio in/out - 2/1x 5.25", 0/1x3.5" , 2x 3.5" hidden (anti-vibration removable drive cage) - 2 x 120mm + 1x 80mm fan upto 4 - micro-atx

CH-LV351SN	C	Lian-li pc-V351 , Silver , No psu , right/left side-accessed 5.25" device , cube chassis , made in Taiwan , hairline brush anodized aluminum , slide out motherboard tray ; 1394 firewire + 2 x front usb + audio in/out - 2/1x 5.25", 0/1x3.5" , 2x 3.5" hidden (anti-vibration removable drive cage) - 2 x 120mm + 1x 80mm fan upto 4 - micro-atx
CH-LV351BN	C	Lian-li pc-V351 , Black , No psu , right/left side-accessed 5.25" device , cube chassis , made in Taiwan , hairline brush anodized aluminum , slide out motherboard tray ; 1394 firewire + 2 x front usb + audio in/out - 2/1x 5.25", 0/1x3.5" , 2x 3.5" hidden (anti-vibration removable drive cage) - 2 x 120mm + 1x 80mm fan upto 4 - micro-atx
CH-LV351RN	C	Lian-li pc-V351 , Red , No psu , right/left side-accessed 5.25" device , cube chassis , made in Taiwan , hairline brush anodized aluminum , slide out motherboard tray ; 1394 firewire + 2 x front usb + audio in/out - 2/1x 5.25", 0/1x3.5" , 2x 3.5" hidden (anti-vibration removable drive cage) - 2 x 120mm + 1x 80mm fan upto 4 - micro-atx
midi tower		http://www.lian-li.com/v2/en/product/product04.php?cl_index=1&sc_index=25&ss_index=62
CH-LA07SN		Lian-li pc-A07 , midi tower , Silver , No psu , made in Taiwan , hairline brush anodized aluminum , anti-vibration kit ; 1394 firewire + 2 x front usb + audio in/out - 4x 5.25", 2x 3.5", 3x 3.5" hidden (anti-vibration removable drive cage - side accessed) - 2 x 120mm fan upto 4 - atx
CH-LA07BN		Lian-li pc-A07 , midi tower , Black , No psu , made in Taiwan , hairline brush anodized aluminum , anti-vibration kit ; 1394 firewire + 2 x front usb + audio in/out - 4x 5.25", 2x 3.5", 3x 3.5" hidden (anti-vibration removable drive cage - side accessed) - 2 x 120mm fan upto 4 - atx
CH-L7PSWN		Lian-li pc-7 Plus , midi tower , Silver , Windowed side panel , No psu , with 25cm blue led fan on side panel , made in Taiwan , hairline brush anodized aluminum , removable front panel with jointer , removable top cover for modding purpose ; 1394 firewire + 2 x front usb + audio in/out - 4x 5.25", 2x 3.5", 3x 3.5" hidden (anti-vibration removable drive cage) - 1x250mm blue led +2 x blue led 120mm fan upto 4 - atx
CH-L7PBWN		Lian-li pc-7 Plus , midi tower , Black , Windowed side panel , No psu , with 25cm blue led fan on side panel , made in Taiwan , hairline brush anodized aluminum , removable front panel with jointer , removable top cover for modding purpose ; 1394 firewire + 2 x front usb + audio in/out - 4x 5.25", 2x 3.5", 3x 3.5" hidden (anti-vibration removable drive cage) - 1x250mm blue led +2 x blue led 120mm fan upto 4 - atx
CH-L60P2SN		Lian-li pc-60Plus II , midi tower , Silver , No psu , made in Taiwan , with extra cpu air duct + vga vent on side panel , hairline brush anodized aluminum , removable front panel with jointer, slide-out motherboard tray ; 1394 firewire + 2 x front usb + audio in/out - 4x 5.25", 2x 3.5", 5x 3.5" hidden (anti-vibration removable drive cage) - 1 x 120mm + 2 x 80mm fan + BS-02 120mm internal pci cooler (position adjustable) - atx
CH-L60P2BN		Lian-li pc-60Plus II , midi tower , Black , No psu , made in Taiwan , with extra cpu air duct + vga vent on side panel , hairline brush anodized aluminum , removable front panel with jointer, slide-out motherboard tray ; 1394 firewire + 2 x front usb + audio in/out - 4x 5.25", 2x 3.5", 5x 3.5" hidden (anti-vibration removable drive cage) - 1 x 120mm + 2 x 80mm fan + BS-02 120mm internal pci cooler (position adjustable) - atx

CH-L60FBN		Lian-li pc-60F , midi tower , Black , No psu (bottom placed design) , made in Taiwan ,with lockable side panel , hairline brush anodized aluminum , removable front panel with jointer , removable top cover for modding purpose ; 1394 firewire + 2 x front usb + audio in/out - 5/4x 5.25" with drive rail , 0/1x 3.5", 4x 3.5" hidden (anti-vibration removable drive cage - side accessed) - 1 x 120mm + 1 x 140mm blue-led fan upto 3 - atx
CH-L60FBWN	N	Lian-li pc-60Fw , midi tower , Black , Windowed side panel , No psu (bottom placed design) , made in Taiwan ,with lockable side panel , hairline brush anodized aluminum , removable front panel with jointer , removable top cover for modding purpose ; 1394 firewire + 2 x front usb + audio in/out - 5/4x 5.25" with drive rail , 0/1x 3.5", 4x 3.5" hidden (anti-vibration removable drive cage - side accessed) - 1 x 120mm + 1 x 140mm blue-led fan upto 3 - atx
CH-L7FWBWN		Lian-li pc-7FW , midi tower , Black , Windowed side panel , No psu (bottom placed design) , made in Taiwan ,with lockable side panel , hairline brush anodized aluminum , removable front panel with jointer , removable top cover for modding purpose ; 1394 firewire + 2 x front usb + audio in/out - 5/4x 5.25" with drive rail , 0/1x 3.5", 4x 3.5" hidden (anti-vibration removable drive cage - side accessed) - 1 x 120mm + 1 x 140mm blue-led fan upto 3 - atx
CH-LA6010BN		Lian-li pc-A6010 , midi tower , Black , No psu , made in Taiwan , hairline brush anodized aluminum , slide out motherboard tray , tool free removable+rotatable drive , removable front panel with jointer , removable top cover for modding purpose ; 1394 firewire + 2 x front usb + audio in/out - 4x 5.25", 1 x 3.5" , 4x 3.5" hidden (anti-vibration removable+rotatable drive cage - inner/side accessed) - 120+140mm speed adjustable fan with washable filter upto 3 - atx
CH-LA17BN		Lian-li pc-A17 , midi tower , Black , No psu , made in Taiwan , hairline brush anodized aluminum , removable motherboard tray , removable front panel with jointer , removable top cover for modding purpose ; e-SATA+1394 firewire + 4x front usb + audio in/out - 9/6x 5.25" with air filter, 0/3x 3.5" hidden (anti-vibration removable drive cage) - 2x120+140mm fan with washable filter upto 4 - atx
CH-L9BN	N	Lian-li pc-9 , midi tower , Black , No psu (bottom placed design) , front accessable 4 x hdd tray with lockable door , sata hot swap backplane kit , made in Taiwan , hairline brush anodized aluminum , removable motherboard tray , removable front panel with jointer , removable top cover for modding purpose ; e-SATA+1394 firewire + 4x front usb + audio in/out - 9/6x 5.25" with air filter, 0/3x 3.5" hidden (anti-vibration removable drive cage) - 2x120mm fan with washable filter upto 3 , with 3-speed fan controller- atx
CH-LP60BWN		Lian-li pc-P60 , midi tower , armorsuit , Black , Windowed panel , No psu , removable lockable front door opened to left or right with lock + 3 x 140mm blue led fan , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , removable top cover + front panel for modding purpose ; e-SATA + 1394 firewire + 4x front usb + audio in/out - 9/6x 5.25" , 0/3x 3.5" hidden (anti-vibration removable drive cage) - speed adjustable 4x140mm blue-led + 1x120mm fan upto 6 , 1x 545mm full height washable air filter in front , support optional CH-03 handle - E-atx

CH-LB10BN	**C**	Lian-li pc-B10 , midi tower , Black , No psu (bottom placed design) , lockable front door , noise reduction foam on panels ; tool-less pci/pci-e mounting module , made in Taiwan , hairline brush anodized aluminum , removable motherboard tray , removable front panel with jointer ; 2x front usb + audio in/out - tool-free 5x 5.25" , 4x 3.5" hidden (anti-vibration removable drive cage - side accessed) - 2x120mm+ 1x140mm fan with washable filter upto 4 - atx
CH-LB25BN	**N**	Lian-li pc-B25B blue ring , midi tower , Black with cold blue ring design , No psu , front door opened to left or right with lock , made in Taiwan , hairline brush anodized aluminum , dual -layer side panel with sound dimmer structure , removable motherboard tray , removable front panel with jointer , removable top cover for modding purpose ; 1394 firewire + 2x front usb + audio in/out - 3x 5.25" , 1x3.5" , 5x 3.5" hidden (anti-vibration removable drive cage - side accessed) - 3x120mm fan with washable filter upto 4 - atx
CH-LV1010SN		Lian-li pc-v1010 , midi tower , Silver , No psu (bottom placed design) , dual chamber design , with wheels, made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , tool free removable drive cage with anti-vibration kit , with support bar+card holder , anti-vibration spring kit ; e-SATA + 1394 firewire + 4x front usb + audio in/out - 5x 5.25" , 6x 3.5" hidden (anti-vibration drive cage - side accessed) - speed adjustable 140mm + 2x120mm fan with washable filter upto 4 - E-atx
CH-LV1010BN		Lian-li pc-v1010 , midi tower , Black , No psu (bottom placed design) , dual chamber design , with wheels, made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , tool free removable drive cage with anti-vibration kit , with support bar+card holder , anti-vibration spring kit ; e-SATA + 1394 firewire + 4x front usb + audio in/out - 5x 5.25" , 6x 3.5" hidden (anti-vibration drive cage - side accessed) - speed adjustable 140mm + 2x120mm fan with washable filter upto 4 - E-atx
CH-LV1000ZBWN		Lian-li pc-V1000Z , midi tower , Black , Windowed side panel , No psu (bottom placed design) , dual chamber design , with wheels , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder , anti-vibration spring kit ; e-SATA + 1394 firewire + 4x front usb + audio in/out - 5x 5.25" , 6x 3.5" hidden with drive rail (anti-vibration hdd cage with sata hotswap backplane kit - side accessed) - speed adjustable 120+1x140mm fan with washable filter + 1x BS-03 120mm internal pci cooler upto 4 - E-atx
CH-LV1110SN		Lian-li pc-v1110 , midi tower , Silver , No psu (bottom placed design) , front door with lock , dual chamber design , with wheels, made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , tool free removable drive cage with anti-vibration kit , with support bar+card holder , anti-vibration spring kit ; e-SATA + 1394 firewire + 4x front usb + audio in/out - 5x 5.25" , 6x 3.5" hidden (anti-vibration drive cage - side accessed) - speed adjustable 140mm + 2x120mm fan with washable filter upto 4 - E-atx

CH-LV1110BN		Lian-li pc-v1110 , midi tower , Black , No psu (bottom placed design) , front door with lock , dual chamber design , with wheels, made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , tool free removable drive cage with anti-vibration kit , with support bar+card holder , anti-vibration spring kit ; e-SATA + 1394 firewire + 4x front usb + audio in/out - 5x 5.25" , 6x 3.5" hidden (anti-vibration drive cage - side accessed) - speed adjustable 140mm + 2x120mm fan with washable filter upto 4 - E-atx
CH-LA10SN	N	Lian-li pc-A10 , Silver , midi tower , No psu (bottom placed design , support upto 2 psu) , with lockable front door , dual chamber design , made in Taiwan , hairline brush anodized aluminum , lockable side panel , slide-out motherboard tray, with support bar+card holder , anti-vibration spring kit , removable front panel with jointer ; 1394 firewire + 2x front usb + audio in/out - 7/6x 5.25" with drive rail , 0/1 x 3.5" , 5x 3.5" hidden (anti-vibration removable drive cage - side accessed) - 3x120mm speed adjustable fan with washable filter + 1 x BS-03 120mm internal pci cooler upto 5 - E-atx
CH-LA10BN	N	Lian-li pc-A10 , Black , midi tower , No psu (bottom placed design , support upto 2 psu) , with lockable front door , dual chamber design , made in Taiwan , hairline brush anodized aluminum , lockable side panel , slide-out motherboard tray, with support bar+card holder , anti-vibration spring kit , removable front panel with jointer ; 1394 firewire + 2x front usb + audio in/out - 7/6x 5.25" with drive rail , 0/1 x 3.5" , 5x 3.5" hidden (anti-vibration removable drive cage - side accessed) - 3x120mm speed adjustable fan with washable filter + 1 x BS-03 120mm internal pci cooler upto 5 - E-atx
CH-LA20BN		Lian-li pc-A20 , midi tower , Black , No psu (bottom placed design , support upto 2 psu) , dual chamber design , front door opened to left or right with lock , made in Taiwan , hairline brush anodized aluminum , with support bar+card holder , removable front panel with jointer , removable top cover for modding purpose ; 1394 firewire + e-SATA + 4 x front usb + audio in/out - 7x 5.25", 8x 3.5" hidden (anti-vibration removable drive cage - side accessed) - 2x140+3x120mm speed adjustable fan with washable filter upto 6 - E-atx
CH-LX500BN		Lian-li pc-X500 , midi tower , Black , No psu (bottom placed design) , right/left side-accessed 3.5"+5.25" device , dual chamber + 380mm short depth design , made in Taiwan , hairline brush anodized aluminum , dual -layer side panel with sound dimmer structure , removable front panel with jointer ; 1394 firewire + e-SATA + 4 x front usb + audio in/out - 2x 5.25", 1x3.5" , 4x 3.5" hidden (anti-vibration drive cage - side accessed) - 4x120mm speed adjustable fan upto 5 , 1 x 585mm full height washable air filter in front - atx
full tower		http://www.lian-li.com/v2/en/product/product04.php?cl_index=1&sc_index=25&ss_index=61
CH-LA70SN		Lian-li pc-A70 , Silver , No psu (bottom placed design , support upto 2 psu) , full tower , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder , removable front panel with jointer , removable top cover for modding purpose ; 1394 firewire + 2x front usb + audio in/out - 5x 5.25" , 10x 3.5" hidden (anti-vibration drive cage - side accessed) - 6x120mm fan with washable filter upto 7 - E-atx

CH-LA71SN	Lian-li pc-A71 , Silver , No psu (bottom placed design , support upto 2 psu) , full tower , with lockable front door , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder , removable front panel with jointer , removable top cover for modding purpose ; 1394 firewire + 2x front usb + audio in/out - 5x 5.25" , 10x 3.5" hidden (anti-vibration drive cage - side accessed) - 6x120mm fan with washable filter upto 7 - E-atx
CH-LA71BN	Lian-li pc-A71 , Black , No psu (bottom placed design , support upto 2 psu) , full tower , with lockable front door , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder , removable front panel with jointer , removable top cover for modding purpose ; 1394 firewire + 2x front usb + audio in/out - 5x 5.25" , 10x 3.5" hidden (anti-vibration drive cage - side accessed) - 6x120mm fan with washable filter upto 7 - E-atx
CH-LA77SN	Lian-li pc-A77 , Silver , No psu (bottom placed design , support upto 2 psu) , full tower , with smart fan controller lcd on front panel , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder , removable front panel with jointer , removable top cover for modding purpose ; e-SATA + 1394 firewire + 4x front usb + audio in/out - 12/6x 5.25" , 0/9x 3.5" hidden (3 in anti-vibration removable drive cage) - speed adjustable 4x120mm fan with washable filter upto 7 - E-atx
CH-LA77BN	Lian-li pc-A77 , Black , No psu (bottom placed design , support upto 2 psu) , full tower , with smart fan controller lcd on front panel , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder , removable front panel with jointer , removable top cover for modding purpose ; e-SATA + 1394 firewire + 4x front usb + audio in/out - 12/6x 5.25" , 0/9x 3.5" hidden (3 in anti-vibration removable drive cage) - speed adjustable 4x120mm fan with washable filter upto 7 - E-atx
CH-LA7010BN	Lian-li pc-A7010 , Black , No psu (bottom placed design , support upto 2 psu) , full tower ,made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder , anti-vibration spring kit , removable front panel with jointer , removable top cover for modding purpose ; 1394 firewire + e-SATA + 4 x front usb + audio in/out - 5/4x 5.25", 0/1 x 3.5" , 10x 3.5" hidden (7 x with sata hotswap backplane kit with anti-vibration hdd cage - side accessed + 3 in 1 x removable hdd cage) - 6 x 120mm speed adjustable fan with washable filter upto 7 - E-atx
CH-LA7110BN	Lian-li pc-A7110 , Black , No psu (bottom placed design , support upto 2 psu) , full tower , removable front door opened to left or right with lock , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder , anti-vibration spring kit , removable front panel with jointer , removable top cover for modding purpose ; 1394 firewire + e-SATA + 4 x front usb + audio in/out - 5/4x 5.25", 0/1 x 3.5" , 10x 3.5" hidden (7 x with sata hotswap backplane kit with anti-vibration hdd cage - side accessed + 3 in 1 x removable hdd cage) - 6 x 120mm speed adjustable fan with washable filter upto 7 - E-atx

CH-LV2010SN		Lian-li pc-V2010 , full tower , Silver , No psu (bottom placed design , support upto 2 psu) , dual chamber design , with wheels , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder ; 1394 firewire + e-SATA + 4 x front usb + audio in/out - 7x 5.25", 8x 3.5" hidden (anti-vibration drive cage - side accessed) - 1x140+2x120mm speed adjustable fan with washable filter upto 4 - E-atx
CH-LV2010BN		Lian-li pc-V2010 , full tower , Black , No psu (bottom placed design , support upto 2 psu) , dual chamber design , with wheels , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder ; 1394 firewire + e-SATA + 4 x front usb + audio in/out - 7x 5.25", 8x 3.5" hidden (anti-vibration drive cage - side accessed) - 1x140+2x120mm speed adjustable fan with washable filter upto 4 - E-atx
CH-LV2110SN		Lian-li pc-V2110 , full tower , Silver , No psu (bottom placed design , support upto 2 psu) , front door with lock , dual chamber design , with wheels , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder , anti-vibration spring kit ; 1394 firewire + e-SATA + 4 x front usb + audio in/out - 7x 5.25", 8x 3.5" hidden (anti-vibration drive cage - side accessed) - 1x140+2x120mm speed adjustable fan with washable filter upto 4 - E-atx
CH-LV2110BN		Lian-li pc-V2110 , full tower , Black , No psu (bottom placed design , support upto 2 psu) , front door with lock , dual chamber design , with wheels , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder , anti-vibration spring kit ; 1394 firewire + e-SATA + 4 x front usb + audio in/out - 7x 5.25", 8x 3.5" hidden (anti-vibration drive cage - side accessed) - 1x140+2x120mm speed adjustable fan with washable filter upto 4 - E-atx
CH-LB70BN	**C**	Lian-li pc-B70 , Black , No psu (bottom placed design with bracket , 180 degrees reversable , support 2nd psu when hdd cage removed) , full tower , noise reduction foam on panels , tool-less pci/pci-e mounting module , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder , anti-vibration spring kit , removable front panel with jointer ; 1394 firewire + e-SATA + 4 x front usb + audio in/out - tool-free 5/4x 5.25", 0/1 x 3.5" , 10x 3.5" hidden (7 x side accessed + 3 in hdd cage) - 2 x blue 140mm + 2 x 120mm speed adjustable fan upto 5 - E-atx
CH-LB71BN	**C**	Lian-li pc-B71 , Black , No psu (bottom placed design with bracket , 180 degrees reversable , support 2nd psu when hdd cage removed) , full tower , front accessable 7 x hdd tray with lockable door , noise reduction foam on panels , tool-less pci/pci-e mounting module , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder , anti-vibration spring kit , removable front panel with jointer ; 1394 firewire + e-SATA + 4 x front usb + audio in/out - tool-free 5/4x 5.25", 0/1 x 3.5" , 10x 3.5" hidden (7 x front accessed with hotswap backplane kit + 3 in hdd cage) - 2 x blue 140mm + 2 x 120mm speed adjustable fan upto 5 - E-atx

CH-LP80BN		Lian-li pc-P80 , full tower , armorsuit , Black , No psu , removable lockable front door opened to left or right with lock + 3 x 140mm blue led fan , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder , removable top cover for modding purpose ; e-SATA + 1394 firewire + 4x front usb + audio in/out - 12/6x 5.25" , 0/6x 3.5" hidden (2 x anti-vibration removable drive cage) - speed adjustable 4x140mm blue-led + 1x120mm fan upto 7 , 1x 633mm full height washable air filter in front , support optional CH-03 handle - E-atx
CH-LP80RWN		Lian-li pc-P80R , ati crossfire-x edition , full tower , armorsuit , Red , spider Windowed side panel , No psu , removable lockable front door opened to left or right with lock + 3 x 140mm blue led fan , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray , with support bar+card holder , removable top cover for modding purpose ; e-SATA + 1394 firewire + 4x front usb + audio in/out - 12/6x 5.25" , 0/6x 3.5" hidden (2 x anti-vibration removable drive cage) - speed adjustable 4x140mm red-led + 1x120mm fan upto 7 , 1x 633mm full height washable air filter in front , support optional CH-03 handle - E-atx
CH-LX2000BN		Lian-li pc-X2000 , full tower , Black , No psu (bottom placed design) , right/left side-accessed 3.5"+5.25" device , tripple chamber design , made in Taiwan , hairline brush anodized aluminum , removable motherboard tray , dual -layer side panel with sound dimmer structure , removable front panel with jointer ; 1394 firewire + e-SATA + 4 x front usb + audio in/out - 2x 5.25", 1x3.5" , 6x 3.5" hidden with drive rail (anti-vibration hdd cage with sata hotswap backplane kit - side accessed) - 3x140+1x120+2x80mm speed adjustable fan upto 7 , 1 x 680mm full height washable air filter in front - E-atx
CH-L888LWN	C	Lian-li pc-888 , full tower , bLue , Windowed side panel , No psu , tripple chamber design , made in Taiwan , hairline brush anodized aluminum , lockable side panel , removable motherboard tray ; built-in card reader + e-SATA + 1394 firewire + 4x front usb + audio in/out - 4x 5.25" , 4x 3.5" hidden (side accessed with sata hot swap backplane kit) - speed adjustable 2x blue 140mm + 1xblue 120mm fan - atx
Lian-li chassis accessories		
PS-LAiL		Lian-li interlink cable for psu - for use of 2 psu in 1 x case ….
CH-LAMF20	N	Lian-li MF-20 - 2x 3.5" hdd extension kit - compatiable with most of case - include Y-power adapter
CH-LAMF30	N	Lian-li MF-30 - 3x 3.5" hdd extension kit - compatiable with most of case - include Y-power adapter
CH-LAEX33N1		Lian-li EX-33N1 , aluminum hdd cage , internal , with anti-vibration kit - for 3x hdd in 3x5.25" bay , no fan - compatiable with most of case
CH-LAEX33N		Lian-li EX-33N , aluminum hdd cage , internal , with 120mm fan + anti-vibration kit - for 3x hdd in 3x5.25" bay - compatiable with most of case
CH-LAEX23NB	N	Lian-li EX-23N , Black , aluminum hdd cage , with external meshed front panel , with 80mm fan with air filter+anti-vibration rubber ring - for 3x hdd in 2x5.25" bay - compatiable with most of case
CH-LAEX23NS	N	Lian-li EX-23N , Silver , aluminum hdd cage , with external meshed front panel , with 80mm fan with air filter+anti-vibration rubber ring - for 3x hdd in 2x5.25" bay - compatiable with most of case

CH-LAEXH22B	N	Lian-li EX-H22 , Black , hdd expansion kit , aluminum hdd cage with lock + sata raid 0/1 ready hot swap backplane kit + drive rail , with external meshed front panel , with 1500rpm 80mm fan+ air filter+ anti-vibration kit - for 2x hdd in 2x5.25" bay - compatiable with most of case
CH-LAEXH22S	N	Lian-li EX-H22 , Silver , hdd expansion kit , aluminum hdd cage with lock + sata raid 0/1 ready hot swap backplane kit + drive rail , with external meshed front panel , with 1500rpm 80mm fan+ air filter+ anti-vibration kit - for 2x hdd in 2x5.25" bay - compatiable with most of case
CH-LAEX33B	N	Lian-li EX-33 , Black , aluminum hdd cage , with external meshed front panel , with 120mm fan with air filter+anti-vibration kit - for 3x hdd in 3x5.25" bay - compatiable with most of case
CH-LAEX33S	N	Lian-li EX-33 , Silver , aluminum hdd cage , with external meshed front panel , with 120mm fan with air filter+anti-vibration kit - for 3x hdd in 3x5.25" bay - compatiable with most of case
CH-LAEX34NB		Lian-li EX-34N , Black , aluminum hdd cage , with external meshed front panel , with 120mm fan with air filter+anti-vibration rubber ring - for 4x hdd in 3x5.25" bay - compatiable with most of case
CH-LAEX34NS	N	Lian-li EX-34N , Silver , aluminum hdd cage , with external meshed front panel , with 120mm fan with air filter+anti-vibration rubber ring - for 4x hdd in 3x5.25" bay - compatiable with most of case
CH-LAEXH33B		Lian-li EX-H33 , Black , hdd expansion kit , , aluminum hdd cage with lock + sata raid 0/1/5 ready hot swap backplane kit + drive rail , with external meshed front panel , with 1000rpm 120mm fan+ air filter+ anti-vibration kit - for 3x hdd in 3x5.25" bay - compatiable with most of case
CH-LAEXH33S	N	Lian-li EX-H33 , Silver , hdd expansion kit , , aluminum hdd cage with lock + sata raid 0/1/5 ready hot swap backplane kit + drive rail , with external meshed front panel , with 1000rpm 120mm fan+ air filter+ anti-vibration kit - for 3x hdd in 3x5.25" bay - compatiable with most of case
CH-LAEXH34B	N	Lian-li EX-H34 , Black , hdd expansion kit , , aluminum hdd cage with lock + sata raid 0/1/5/0+1/10 ready hot swap backplane kit + drive rail , with external meshed front panel , with 1000rpm 120mm fan+ air filter+ anti-vibration kit - for 4x hdd in 3x5.25" bay - compatiable with most of case
CH-LAEXH34S	N	Lian-li EX-H34 , Silver , hdd expansion kit , , aluminum hdd cage with lock + sata raid 0/1/5/0+1/10 ready hot swap backplane kit + drive rail , with external meshed front panel , with 1000rpm 120mm fan+ air filter+ anti-vibration kit - for 4x hdd in 3x5.25" bay - compatiable with most of case
CH-LAWB01		Lian-li WB-01 aluminum wheel stand with brake function
CH-LAAD02		Lian-li AD-02 , air duct for cpu , 120mm fan - compatiable with most of case
CH-LABS03		Lian-li BS-03 internal pci cooler - positioned on top of 7 pci slot , 1x120mm fan , 1500rpm , 53CFM , 25.6dBA , 1.51mm-H2O - for selected chassis only
CH-LABS02		Lian-li BS-02 internal pci cooler- positioned on top of 7 pci slot , 1x 120mm position adjustable fan , 1500rpm , 53CFM , 25.6dBA , 1.51mm-H2O - for selected chassis only
CH-LABS06	N	Lian-li BS-06 internal pci cooler - positioned on top of 7 pci slot , 1x140mm fan , 900rpm - for selected chassis only
CH-LABS09	N	Lian-li BS-09 external pci cooler - positioned outside of 3 pci slot , 1x140mm fan , 1180rpm - compatiable with most of case

FA-LBS08	N	Lian-li BS-08 internal pci fan card , aluminum - require 2 x pci slot , 2x120mm fan , 100rpm , pull hot air through expansion slot - compatiable with most of case
CH-LAC02B	N	Lian-li C-02 Black aluminum bezel for 5.25" optical drive with eject button - only compatible with Lian-Li case
CH-LAC02S	N	Lian-li C-02 Silver aluminum bezel for 5.25" optical drive with eject button - only compatible with Lian-Li case
CH-LABZ502B		Lian-li BZ-502 Black , intake cooling kit , aluminum front panel , use 3x 5.25" with 1x 120mm fan + air filter - compatiable with most of case
CH-LABZ502S		Lian-li BZ-502 Silver , intake cooling kit , aluminum front panel , use 3x 5.25" with 1x 120mm fan + air filter - compatiable with most of case
CH-LABZU02S		Lian-li BZ-U02 Silver , multi-media i/o port with dust cover , 5.25" , 4xusb+ audio in/out+ 1xe-SATA+1x ieee1394 firewire - compatiable with most of case
CH-LABZU02B		Lian-li BZ-U02 Black , multi-media i/o port with dust cover , 5.25" , 4xusb+ audio in/out+ 1xe-SATA+1x ieee1394 firewire - compatiable with most of case
CH-LAT713B	N	Lian-li T-713 Black top cover - with mesh opening for 3x120mm fan , ideal for liquid cooling system - for pc-A71 , pc-A7110 series
CH-LAT713S	N	Lian-li T-713 Silver top cover - with mesh opening for 3x120mm fan , ideal for liquid cooling system - for pc-A71 , pc-A7110 series
CH-LAT703B	N	Lian-li T-703 Black top cover - with mesh opening for 3x120mm fan , ideal for liquid cooling system - for pc-A70 , pc-A7010 series
CH-LAT703S	N	Lian-li T-703 Silver top cover - with mesh opening for 3x120mm fan , ideal for liquid cooling system - for pc-A70 , pc-A7010 series
CH-LAW65B		Lian-li W-65 Black windowed side panel - for middle tower of pc-6x series (pc-60Plus II, pc-A6010) / pc-7x series (pc-7AYCF)
CH-LAW65S		Lian-li W-65 Silver windowed side panel - for middle tower of pc-6x series (pc-60Plus II, pc-A6010) / pc-7x series (pc-7AYCF)
CH-LAW65PB		Lian-li W-65P Black windowed side panel with VGA vent - for middle tower of pc-6x series (pc-60Plus II, pc-A6010) / pc-7x series (pc-7AYCF)
CH-LAW65PS		Lian-li W-65P Silver windowed side panel with VGA vent - for middle tower of pc-6x series (pc-60Plus II, pc-A6010) / pc-7x series (pc-7AYCF)
CH-LAWV1010B	N	Lian-li W-V1010 Black windowed side panel - for middle tower of PC-V1010/1110
CH-LAWV1010S	N	Lian-li W-V1010 Silver windowed side panel - for middle tower of PC-V1010/1110
CH-LAW75B		Lian-li W-75 Black windowed side panel - for full tower of pc-A7x series
CH-LAW75S		Lian-li W-75 Silver windowed side panel - for full tower of pc-A7x series
CH-LAW75PB	N	Lian-li W-75P Black windowed side panel with VGA vent - for full tower of pc-A7x series , pc-P80
CH-LAW75PS	N	Lian-li W-75P Silver windowed side panel with VGA vent - for full tower of pc-A7x series
CH-LAWV2010S	N	Lian-li W-V2010 Silver windowed side panel - for full tower of PC-V2010/2110
CH-LAWV2010B	N	Lian-li W-V2010 Black windowed side panel - for full tower of PC-V2010/2110

Coolermaster

coolermaster chassis accessories

CH-CASWN1	N	Coolermaster RA-1000-SWN1 - windowed side panel - silver , for coolermaster cosmos RC-1000 , RC-1010
CH-CAKWN1	N	Coolermaster RA-1100-KWN1 - windowed side panel - black , for coolermaster cosmos-S RC-1100
CH-CASTB3T4B1	N	Coolermaster STB-3T4-B1 internal 4-in3 device module , oem pack - for 4 x 3.5" HDD in 3 x 5.25" bay +120mm fan
CH-CASTB3T4E3		Coolermaster STB-3T4-E3 external 4-in3 device module , with front door , retail pack - for 4 x 3.5" HDD in 3 x 5.25" bay + 120mm blue led fan , for CM stacker 83X / centurion 590 / CM690 - retail pack
CH-CASTFB01E1		Coolermaster STF-B01-E1 cross flow fan , with fan speed controller , 50x50x336mm , 1400/1800/2500rpm , 25/32/46CFM - for CM stacker , CM stacker 830
Elite		
CH-CE340N		Coolermaster RC-340 , Elite 340 , silver+black , No psu : 2 x front usb + audio in/out - 2x 5.25", 2x 3.5", 2x 3.5" hidden - support upto 2 x 120mm fan - micro-atx
CH-CE341N		Coolermaster RC-341 , Elite 341 , black , No psu : 2 x front usb + audio in/out - 2x 5.25", 2x 3.5", 2x 3.5" hidden - 1 120mm fan support upto 3 - micro-atx
CH-CE341		Coolermaster RC-341 , Elite 341 , black , with thermal master 420w psu : 2 x front usb + audio in/out - 2x 5.25", 2x 3.5", 2x 3.5" hidden - 1 120mm fan support upto 3 - micro-atx
CH-CE360N	C	Coolermaster RC-360 , Elite 360 , No psu (front positioned) , mini tower for atx mb , tower / desktop convertiable , 43.9x14.8x36cm : tools free ; 2 x front usb + audio in/out - 2x 5.25", 1x 3.5", 1x 3.5" hidden - 1 x 120mm fan support upto 2 - atx
CH-CE330N	N	Coolermaster RC-330 , Elite 330 , silver+black , No psu : tools free ; 2 x front usb + audio in/out - 4x 5.25", 1x 3.5", 5x 3.5" hidden - 1 x 120mm fan support upto 2 - atx
CH-CE330	N	Coolermaster RC-330 , Elite 330 , silver+black , with thermal master 350w psu : tools free ; 2 x front usb + audio in/out - 4x 5.25", 1x 3.5", 5x 3.5" hidden - 1 x 120mm fan support upto 2 - atx - 1 year warranty - no power cord
CH-CE331N	N	Coolermaster RC-331 , Elite 331 , silver+black , No psu : tools free ; 2 x front usb + audio in/out - 4x 5.25", 2x 3.5", 5x 3.5" hidden - 1 x 120mm fan support upto 2 - atx
CH-CE331	N	Coolermaster RC-331 , Elite 331 , silver+black , with thermal master 350w psu : tools free ; 2 x front usb + audio in/out - 4x 5.25", 2x 3.5", 5x 3.5" hidden - 1 x 120mm fan support upto 2 - atx - 1 year warranty - no power cord
CH-CE332N	N	Coolermaster RC-332 , Elite 332 , silver+black , No psu : tools free ; 2 x front usb + audio in/out - 4x 5.25", 1x 3.5", 5x 3.5" hidden - 1 x 120mm fan support upto 2 - atx - 1 year warranty - no power cord
CH-CE332	N	Coolermaster RC-332 , Elite 332 , silver+black , with thermal master 350w psu : tools free ; 2 x front usb + audio in/out - 4x 5.25", 1x 3.5", 5x 3.5" hidden - 1 x 120mm fan support upto 2 - atx - 1 year warranty - no power cord
CH-CE333N	N	Coolermaster RC-333 , Elite 333 , silver+black , No psu : tools free ; 2 x front usb + audio in/out - 4x 5.25", 2x 3.5", 5x 3.5" hidden - 1 x 120mm fan support upto 2 - atx - 1 year warranty - no power cord
CH-CE333	N	Coolermaster RC-333 , Elite 333 , silver+black , with thermal master 350w psu : tools free ; 2 x front usb + audio in/out - 4x 5.25", 2x 3.5", 5x 3.5" hidden - 1 x 120mm fan support upto 2 - atx - 1 year warranty - no power cord

CH-CE334WN	N	Coolermaster RC-334 , Elite 334 , Windowed side panel , No psu , black : tools free ; 2 x front usb + audio in/out - 4x 5.25", 1x 3.5", 5x 3.5" hidden - 1 x 120mm fan support upto 2 - atx
CH-CE334	N	Coolermaster RC-334 , Elite 334 , with thermal master 350w psu : tools free ; 2 x front usb + audio in/out - 4x 5.25", 1x 3.5", 5x 3.5" hidden - 1 x 120mm fan support upto 2 - atx - 1 year warranty - no power cord
CH-CE335WN	N	Coolermaster RC-335 , Elite 335 , Windowed side panel , No psu , black : tools free ; 2 x front usb + audio in/out - 4x 5.25", 1x 3.5", 6x 3.5" hidden - 1 x 120mm fan support upto 2 - atx
Centurion		
CH-CC590N		Coolermaster RC-590 , Centurion 590 , No psu (bottom placed psu design) : tools free for Pci+3.5"+5.25" ; 2 x front usb + audio in/out + ieee1394 - upto 9x 5.25", 1/0 x 3.5" , upto to 12x 3.5" hidden (1 x 4-in-3 device module include - take 3 x 5.25" bay) - 1 x front blue-led fan + 1 x rear 120mm fan upto 8 - atx
CH-CC590WN		Coolermaster RC-590 , Centurion 590 , Windowed side panel , No psu (bottom placed psu design) : tools free for Pci+3.5"+5.25" ; 2 x front usb + audio in/out + ieee1394 - upto 9x 5.25", 1/0 x 3.5" , upto to 12x 3.5" hidden (1 x 4-in-3 device module include - take 3 x 5.25" bay) - 1 x front blue-led fan + 1 x rear 120mm fan upto 7 - atx
Gladiator		
CH-CG600N	C	Coolermaster RC-600 , gladiator600 , No psu (bottom placed psu design) : tools free for Pci+3.5"+5.25" ; 1xesata + 2 x front usb + audio in/out - 5/4x 5.25", 0/1x 3.5" , 5x 3.5" hidden (side accessed) - 1x front blue-led fan (with led on/off switch) + 1x top 140mm fan upto 5 - atx
CM690		
CH-C690N		Coolermaster RC-690 , CM690 , No psu (bottom placed psu design) : tools free for Pci+3.5"+5.25" ; 2 x front usb + audio in/out + ieee1394 - 4/5x 5.25", 1/0 x 3.5" , 5x 3.5" hidden (hdd side removable) - 1 x front blue-led fan + 1 x rear 120mm fan + 1 x side 120mm fan upto 7 - atx
CH-C690WN		Coolermaster RC-690 , CM690 + Windowed side panel , No psu (bottom placed psu design) : tools free for Pci+3.5"+5.25" ; 2 x front usb + audio in/out + ieee1394 - 4/5x 5.25", 1/0 x 3.5" , 5x 3.5" hidden (hdd side removable) - 1 x front blue-led fan + 1 x rear 120mm fan + 1 x side 120mm fan upto 7 - atx
CH-C690NWN	N	Coolermaster RC-690 , NV-690C-KWN1-GP , CM690 - Nvidia edition + Windowed side panel , No psu (bottom placed psu design) : with green highlight , tools free for Pci+3.5"+5.25" ; 2 x front usb + audio in/out + ieee1394 - 4/5x 5.25", 1/0 x 3.5" , 5x 3.5" hidden (hdd side removable) - 1 x front blue-led fan + 1 x rear 120mm fan + 1 x side 120mm fan upto 7 - atx
AMMO		
CH-CA533WN		Coolermaster RC-533-SWN1 , AMMo 533 , black , meshed side panel , No psu , top handle design + stylish power switch design : tools free for Pci+3.5"+5.25" ; 2 x front usb + 1 x ieee1394 + audio in/out - 5x 5.25", 1x 3.5", 4x 3.5" hidden - 1x blue led 120mm fan upto 2 - atx
Mystique		
CH-CM631SWN		Coolermaster RC-631-SWN1 , Mystique 631 , Silver , Windowed side panel , No psu : aluminum (light weight 6.3Kg) , convertible front door open to left or right , rear retaining hole for water cooling cooling kit , tools free for Pci+3.5"+5.25" ; 2 x front usb + 1 x ieee1394 + audio in/out - 4x 5.25", 2x 3.5", 4x 3.5" hidden - 1x blue led 120mm + 1 x 120mm fan - atx

CH-CM631BWN		Coolermaster RC-631-KWN1 , Mystique 631 , Black , Windowed side panel , No psu : aluminum (light weight 6.3Kg) , convertible front door open to left or right , rear retaining hole for water cooling cooling kit , tools free for Pci+3.5"+5.25" ; 2 x front usb + 1 x ieee1394 + audio in/out - 4x 5.25", 2x 3.5", 4x 3.5" hidden - 1x blue led 120mm + 1 x 120mm fan - atx
CH-CM632BN		Coolermaster RC-632-KWN1 , Mystique 632 , Black , No psu : with front door , rear retaining hole for water cooling cooling kit ; 2 x front usb + 1 x ieee1394 + audio in/out - 4x 5.25", 2x 3.5", 4x 3.5" hidden , slide-out hdd trays - 1x blue led 120mm + 1 x 120mm fan - atx
CH-CM632BWN		Coolermaster RC-632s-SWN1 , Mystique 632 , Silver , Windowed side panel , No psu , with front door , rear retaining hole for water cooling cooling kit ; 2 x front usb + 1 x ieee1394 + audio in/out - 4x 5.25", 2x 3.5", 4x 3.5" hidden , slide-out hdd trays - 1x blue led 120mm + 1 x 120mm fan - atx
CH-CM632SWN		Coolermaster RC-632-SWN1 , Mystique 632 , Silver , Windowed side panel , No psu , with front door , rear retaining hole for water cooling cooling kit ; 2 x front usb + 1 x ieee1394 + audio in/out - 4x 5.25", 2x 3.5", 4x 3.5" hidden , slide-out hdd trays - 1x blue led 120mm + 1 x 120mm fan - atx
i-Tower		
CH-CiT930N		Coolermaster RC-930-SKN2 , iTower930 , Silver , No psu : built-in 4 x sata HDD hot-swap function , double-in-door design (separate fronto door for hdd hot-swap baty) , washable air filters, rear retaining hole for water cooling cooling kit ; 4 x front usb + 1 x ieee1394 + audio in/out - 6x 5.25", 4x 3.5"- (sata hot-swapable) , 1x 120mm + 1 x 92mm fan - atx
HAF		
CH-CHAF932WN	N	Coolermaster RC-932 HAF932 , Windowed side panel , No psu (bottom placed psu design) , with Easy access to liquid coolant fill port on top , black , SECC+plastic - removable motherboard tray ; 1 x eSATA + 4 x front usb + 1 x ieee1394 + audio in/out - 6x 5.25" , 5x 3.5" hidden with drive rail - 1 x 230mm red-led fan + 2 x 230mm fan + 1 x 140mm fan upto 9 - support upto E-ATX
Storm series		
CH-CSN	N	Coolermaster storm series - Sniper , No psu (bottom placed psu design) , meshed side panel , built-in StormGuard cable security lock for various prepherials , built-in fan control knob with led on/off switch , black , SECC+plastic - 1 x eSATA + 4 x front usb + 1 x ieee1394 + audio in/out - 5/4x 5.25" , 0/1 x 3.5" , 5x 3.5" hidden with drive rail - 2 x 200mm blue-led fan + 2 x 120mm fan upto 8 - ATX
CH-CSDWN	N	Coolermaster storm series - Sniper amd Dragon platform edition , Windowed side panel with amd+ati logos , No psu (bottom placed psu design) , meshed side panel , built-in StormGuard cable security lock for various prepherials , built-in fan control knob with led on/off switch , black , SECC+plastic - 1 x eSATA + 4 x front usb + 1 x ieee1394 + audio in/out - 5/4x 5.25" , 0/1 x 3.5" , 5x 3.5" hidden with drive rail - 2 x 200mm blue-led fan + 2 x 120mm fan upto 8 - ATX
CM stacker		

CH-CS830ESN		Coolermaster RC-830-SSN2 , CM Stacker 830 Evo- NVIDIA SLI certified chassis for Dual GeForce 8800 GTX Silver + black mesh , No psu , meshed side panel , front door open to left or right , removable motherboard tray , ; 4 x front usb + 1 x ieee1394 + audio in/out - 9x 5.25" (with 1 x 4-in-3 3.5" hdd module) , 1x 3.5" hidden - 2x120mm blue led fan upto 9 (side panel fan tray support combination of 60/80/92/120/140mm fan or cross flow fan) , with bottom air Inlet - support upto E-ATX + Pico-BTX
CH-CS830EBN	N	Coolermaster RC-830-SKN2 , CM Stacker 830 Evo- NVIDIA SLI certified chassis for Dual GeForce 8800 GTX black + meshed side panel , No psu , meshed side panel , front door open to left or right , removable motherboard tray , ; 4 x front usb + 1 x ieee1394 + audio in/out - 9x 5.25" (with 1 x 4-in-3 3.5" hdd module) , 1x 3.5" hidden - 2x120mm blue led fan upto 9 (side panel fan tray support combination of 60/80/92/120/140mm fan or cross flow fan) , with bottom air Inlet - support upto E-ATX + Pico-BTX
CH-CS830NBN		Coolermaster NV-830-KKN4 , CM Stacker 830 Nvidia Edition Black , No psu - NVIDIA SLI certified chassis for Dual GeForce 8800 GTX , meshed side+front panel , front door open to left or right , removable motherboard tray , ; 4 x front usb + 1 x ieee1394 + audio in/out - 9x 5.25" (with 1 x 4-in-3 3.5" hdd module) , 1x 3.5" hidden - 2x120mm blue led fan upto 9 (side panel fan tray support combination of 60/80/92/120/140mm fan or cross flow fan) , with bottom air Inlet - support upto E-ATX + Pico-BTX
ATCS series		
CH-CATCS840SN	N	Coolermaster RC-840-SSN1-GP , ATCS840 , Silver , no psu (bottom placed psu , support 2) , removable slide-out mb tray , external VGA duct ; 4 x front usb + +1x e-sata + 1 x ieee1394 + audio in/out - 6/5x 5.25" , 0/1x3.5" , 6x 3.5" hidden (side-accessed) - 3x23cm+1x120mm fan upto 8 , with bottom air Inlet - support upto E-ATX
CH-CATCS840BN	N	Coolermaster RC-840-KKN1-GP , ATCS840 , Black , no psu (bottom placed psu , support 2) , removable slide-out mb tray , external VGA duct ; 4 x front usb + +1x e-sata + 1 x ieee1394 + audio in/out - 6/5x 5.25" , 0/1x3.5" , 6x 3.5" hidden (side-accessed) - 3x23cm+1x120mm fan upto 8 , with bottom air Inlet - support upto E-ATX
COSMOS series		
CH-CC1000N		Coolermaster Cosmos RC-1000 , No psu (bottom placed psu design) , silver + black , steel + aluminum - removable wind tunnel for graphic card , front door open to left or right , removable motherboard tray ; 1 x eSATA + 4 x front usb + 1 x ieee1394 + audio in/out - 5x 5.25" , 6x 3.5" hidden - 4 x 120mm fan upto 6 (with bottom air Inlet + air filter) - support upto E-ATX
CH-CC1000WN	N	Coolermaster Cosmos RC-1000 , Windowed side panel , No psu (bottom placed psu design) , silver + black , steel + aluminum - removable wind tunnel for graphic card , front door open to left or right , removable motherboard tray ; 1 x eSATA + 4 x front usb + 1 x ieee1394 + audio in/out - 5x 5.25" , 6x 3.5" hidden - 4 x 120mm fan upto 6 (with bottom air Inlet + air filter) - support upto E-ATX

CH-CC1010N	**N**	Coolermaster Cosmos RC-1010 , nVidia ESA ready - with additional thermal control board for 4 thermal sensors , No psu (bottom placed psu design) , silver + black , steel + aluminum - removable wind tunnel for graphic card , front door open to left or right , removable motherboard tray ; 1 x eSATA + 4 x front usb + 1 x ieee1394 + audio in/out - 5x 5.25" , 6x 3.5" hidden - 4 x 120mm fan upto 6 (with bottom air Inlet + air filter) - support upto E-ATX
CH-CCS1100N		Coolermaster Cosmos S RC-1100 , meshed side panel , No psu (bottom placed psu design) , with concealable I/O panel + a built-in touch sensor , silver + black , aluminum - removable motherboard tray ; 1 x eSATA + 4 x front usb + 1 x ieee1394 + audio in/out - 7x 5.25" , 4x 3.5" hidden - 3 x 120mm fan + 1 x 200mm fan upto 6 (with bottom air Inlet + air filter) - support upto E-ATX
CH-CC1000BLW	**N**	Coolermaster Cosmos RC-1000 Black label Limited edition with Windowed side panel + 850w realpower pro + Hyper Z600 black edition cpu cooler - with unique serial number steel + aluminum - removable wind tunnel for graphic card , front door open to left or right , removable motherboard tray ; 1 x eSATA + 4 x front usb + 1 x ieee1394 + audio in/out - 5x 5.25" , 6x 3.5" hidden - 2x120mm + 2 x 140mm fan upto 6 (with bottom air Inlet + air filter) - support upto E-ATX
Antec		http://www.antec.com/us/pro_enclosures.html
BTX series		
CH-ABK640B		Antec BK640B micro BTX - 380watt Neo HE psu , silver - 2x 5.25", 2x 3.5", 2x 3.5" hidden , with BTX SRM , with front luminated blue led , front usb+ ieee1394 + audio in/out - 3 years warranty on PSU
Skeleton series		
CH-ASKN	**N**	Antec SKeleton , No psu , open to air design with handle , chassis air guide on side panel , 0.8mm cold-rolled steel construction , 2 front usb+ieee1394+eSATA + audio in/out ; 2x 5.25", 2x internal 3.5" upto 6 ; 1x250mm+ 1x 92mm fan - atx
VERiS HTPC series		
CH-AAVC		Antec AV cooler - stackable , ideal for HTPC or other AV equipment , carbon-glass structure with aluminum top deck , 4.6x43x36cm , with 2 1200/1600rpm fans , 5.5/8.0CFM , 22.5/28.7dBA
CH-AFRSN		Antec Fusion Remote , Silver front panel + black body , No psu , with built-in IR receiver + 56keys MCE remote control , desktop HTPC chassis with triple-chamber structure + LCD Display module + volumn control knob ; chassis air guide on side panel , 0.8mm cold-rolled steel construction , 2 front usb+ieee1394 + audio in/out ; 1x 5.25", 2x internal 3.5" ; 2 x Tricool 120mm side fan , lockable - 3 years warranty on PSU - micro atx only
CH-AFRBN		Antec Fusion Remote , Black front panel + black body , No psu , with built-in IR receiver + 56keys MCE remote control , desktop HTPC chassis with triple-chamber structure + LCD Display module + volumn control knob ; chassis air guide on side panel , 0.8mm cold-rolled steel construction , 2 front usb+ieee1394 + audio in/out ; 1x 5.25", 2x internal 3.5" ; 2 x Tricool 120mm side fan , lockable - 3 years warranty on PSU - micro atx only

CH-AMFR350	N	Antec Micro Fusion Remote 350 , with built-in IR receiver + MCE remote control , 12cm height slim design , black+silver , desktop HTPC chassis with LCD Display module , dual chamber design with side placed psu (away from cpu) ; antec 80plus 350w psu , chassis air guide on side panel , 0.8mm cold-rolled steel construction , 2 front usb+eSATA+ audio in/out ; 1x 5.25", 1x internal 3.5" in removable hdd cage ; 2 x Tricool 80mm side fan - 3 years warranty on PSU - micro atx only - expansion card required to be low-profile
CH-AFV2		Antec Fusion V2 with built-in IR receiver , Silver front panel + black body , desktop HTPC chassis with triple-chamber structure + VFD (Vacuum Fluorescent Display) module + volumn control knob ; antec HE 430w psu , chassis air guide on side panel , 0.8mm cold-rolled steel construction , 2 front usb+ieee1394 + audio in/out ; 1x 5.25", 2x internal 3.5" ; 2 x Tricool 120mm side fan , lockable - 3 years warranty on PSU - micro atx only
CH-AFRMBN	N	Antec Fusion Remote Max , Black , No psu , with built-in IR receiver + 56keys MCE remote control , desktop / 4U design HTPC chassis with LCD Display module + volumn control knob , Tripple chamber design with side placed psu (away from cpu) , chassis air guide on side panel , 0.8mm cold-rolled steel construction , 2 front usb+eSATA+iEEE1394 firewire + audio in/out ; 1x 5.25", 4x internal 3.5" in removable hdd cage ; 1x 140mm+ 1x 120mm side fan upto 3 - 3 years warranty on PSU - atx
Life style & Speciality		
CH-AMiN350	N	antec minuet 350 - lifestyle slimline micro atx , desktop or vertical , piano black + chrome front part - 80plus certrified 350w psu ; 2 x front usb + 1 x ieee1394 + audio in/out ; 1x 5.25", 1x 3.5", 1x 3.5" hidden , 1 x tricool 80mm fan+ 1x 40mm fan optional , with cooling vent for vga & cpu ; front audio + usb + e-SATA - expansion card required to be low-profile
CH-ASLWN		Antec Super Lanboy , Windowed side panel , No psu , aluminum (4Kg light weight) , semi-transparent front panel with blue e-led - 3x 5.25", 2x 3.5", 4x hidden 3.5" , slide-out hdd trays with rubber grommets to absorb hard drive vibrations , 2 x front usb + audio in/out , 2 x 120mm fan with damper kit + pci expansion slot protective cover + anti-dust front door + nylon carrying strap
CH-ASN		Antec Solo , No PSU , silver + piano black mirror finish , dual-layer panels with sound-deadening Vinyl dampening + removable front panel for easier access of HDD bays and washable air filters , Integrated cable organizers , advanced screwless HDD suspension system 2 x front usb + 1 x ieee1394 + audio in/out - 5.25"/3.5"/3.5" hidden : 3/1/4 or 4/0/4 - 1 x tricool fan upto 3 , drive rail kits , 2 x lock @ removable side panel
CH-AP150		Antec performance one p150 , white+silver , antec Neo HE 430w psu with ACM (advance cable management , only connect cables to psu that needed) , panels with sound-deadening Vinyl dampening + removable front panel for easier access of HDD bays and washable air filters , Integrated cable organizers , advanced screwless HDD suspension system 2 x front usb + 1 x ieee1394 + audio in/out - 5.25"/3.5"/3.5" hidden : 3/1/4 or 4/0/4 - 1 x tricool fan upto 3 , drive rail kits , 2 x lock @ removable side panel

CH-ASoEN	**N**	antec lifestyle series SOnata Elite No psu , piano black finish , dual layers sound-deadening panels , double hinge door design (allows the door to open up to 270º) , 3/2x 5.25", 0/1x 3.5", 4x 3.5" hidden ; 2 x front usb + eSATA + HD audio in/out , 3.5" drive rail, double hinge door design (allows the door to open up to 270º) , with washable air filter; 1x 120mm rear fan + 1 x 120mm slot cooler, designed to run ultra quiet
CH-ASo3		antec lifestyle series SOnata3 - earthwatts 500watt psu (80Plus certrified) , piano black finish , double hinge door design (allows the door to open up to 270º) , 3x 5.25", 2x 3.5", 4x 3.5" hidden ; 2 x front usb + eSATA + HD audio in/out , 3.5" drive rail, double hinge door design (allows the door to open up to 270º) , lockable front door with washable air filter; support 1x 120mm fan upto 2 , hdd trays with rubber grommets to absorb hard drive vibrations, designed to run ultra quiet - 3 years warranty on PSU
CH-ASoD500		Antec lifestyle series SOnata Designer 500 , white+silver with blue highlight - (orange/ green/ pink/ white panel optional) , antec Neo earthwatt 500w psu (80Plus certrified) , panels with sound-deadening Vinyl dampening + removable front panel for easier access of HDD bays and washable air filters , Integrated cable organizers , advanced screwless HDD suspension system 2 x front usb + 1 x ieee1394 + audio in/out - 5.25"/3.5"/3.5" hidden : 3/1/4 or 4/0/4 - 1 x tricool fan upto 3 , drive rail kits , 2 x lock @ removable side panel
CH-ASoP550		Antec lifestyle series SOnata Plus 550 , pianon black with orange highlight - (green/ pink/ white panel optional) , antec Neo He 550w psu with modular cable management (80Plus certrified) , panels with sound-deadening Vinyl dampening + removable front panel for easier access of HDD bays and washable air filters , Integrated cable organizers , advanced screwless HDD suspension system 2 x front usb + 1 x ieee1394 + audio in/out - 5.25"/3.5"/3.5" hidden : 3/1/4 or 4/0/4 - 1 x tricool fan upto 3 , drive rail kits , 2 x lock @ removable side panel
CH-AAFP-G		Antec 761345-30134 front panel with Green highlight for SOnata Designer 500 / sonata plus / solo / P150
CH-AAFP-o		Antec 761345-30132 front panel with Orange highlight for SOnata Designer 500 / sonata plus / solo / P150
CH-AAFP-P		Antec 761345-30135 front panel with Pink highlight for SOnata Designer 500 / sonata plus / solo / P150
CH-A300N	**N**	Antec 300 (Three Hundred) , black , no psu , bottom placed PSU ; 2 x front usb+ audio in/out - 3 x 5.25", 6 x 3.5" hdd , 2 front loaded HDD cages - top-mounted 140mm tri-cool fan + 1 x rear 120mm tri-cool fan upto 5
CH-A900WN		Antec 900 (Nine Hundred) with windowed side panel , black , no psu , bottom placed PSU ; 2 x front usb + audio in/out - 3/6 x 5.25", 6/3 x 3.5" hdd , 2 front loaded HDD cages - top-mounted 200mm tri-cool fan + 2 x front 120mm tricool blue led fan + 1 x rear 120mm tri-cool fan upto 6 , quick-release drive cages with rubber grommets , with accessories tray on top
CH-A900TWN	**N**	Antec 900 Two (Nine Hundred Two) with windowed side panel , black , no psu , bottom placed PSU ; 2 x front usb + 1 x eSATA + audio in/out - 3/6/9 x 5.25", 6/3/0 x 3.5" hdd , 2 front loaded HDD cages - top-mounted 200mm tri-cool blue fan + 2 x front 120mm blue + 1 x rear 120mm blue + 1x top 200mm blue tri-cool fan upto 6 , quick-release drive cages with rubber grommets , with accessories tray on top

CH-A1200WN	**N**	Antec 1200 (Twelve Hundred) with windowed side panel , black , no psu , bottom placed PSU ; 2 x front usb + 1 x e-sata + audio in/out - 3 x 5.25", 9 x internal 3.5" hdd , built-in 4 x rear switched fan controller + 2 x front fan speed controller knob on the chassis ; top-mounted 200mm tri-cool fan + 3 x front 120mm tricool blue led fan + 2 x rear 120mm tri-cool fan upto 8 , quick-release drive cages with rubber grommets , with accessories tray on top
CH-AMP180BN		antec performance one Mini P180 , Black , No psu , for micro atx , with external fan speed controller , stainless steel panel with black interior , 3 layers (aluminum/ plastic/ aluminum) sound-deadening panels , bottom separated ducted chamber for PSU and hdd (silicone rubber grommets) , double hinge door design (allows the door to open up to 270º), built-in cable management system , front access to washable fan filters , damping materials at panel contact points to reduce vibration noise ; 2 x front usb + e-SATA + HD audio in/out - 3x 5.25", 1x 3.5", 5x 3.5" hidden - 2 x tricool fan upto 4 , 1 x lock @ front panel , quick-release drive cages with rubber grommets
CH-AMP180WN		antec performance one Mini P180 , White , No psu , for micro atx , with external fan speed controller , stainless steel panel with black interior , 3 layers (aluminum/ plastic/ aluminum) sound-deadening panels , bottom separated ducted chamber for PSU and hdd (silicone rubber grommets) , double hinge door design (allows the door to open up to 270º), built-in cable management system , front access to washable fan filters , damping materials at panel contact points to reduce vibration noise ; 2 x front usb + e-SATA + HD audio in/out - 3x 5.25", 1x 3.5", 5x 3.5" hidden - 2 x tricool fan upto 4 , 1 x lock @ front panel , quick-release drive cages with rubber grommets
CH-AP180SN		antec performance one p180 , silver , no psu , 3 layers (aluminum/plastic/aluminum) sound-deadening panels , bottom separated ducted chamber (with 120mm fan in middle) for PSU and 4 hdd (silicone rubber grommets) , 2 x air ducting system for VGA/CPU fresh air intake , double hinge door design (allows the door to open up to 270º) , front access to washable fan filters , damping materials at panel contact points to reduce vibration noise ; 2 x front usb + 1 x ieee1394 + audio in/out - 4x 5.25", 1x 3.5", 6x 3.5" hidden - 3 x tricool fan upto 5 , 1 x lock @ front panel , quick-release drive cages with rubber grommets
CH-AP180BN		antec performance one p180 , black , no psu , 3 layers (aluminum/plastic/aluminum) sound-deadening panels , bottom separated ducted chamber (with 120mm fan in middle) for PSU and 4 hdd (silicone rubber grommets) , 2 x air ducting system for VGA/CPU fresh air intake , double hinge door design (allows the door to open up to 270º) , front access to washable fan filters , damping materials at panel contact points to reduce vibration noise ; 2 x front usb + 1 x ieee1394 + audio in/out - 4x 5.25", 1x 3.5", 6x 3.5" hidden - 3 x tricool fan upto 5 , 1 x lock @ front panel , quick-release drive cages with rubber grommets

CH-AP182BN		antec performance one P182 , Black , No psu , with external fan speed controller + pipe hole for external water cooling system , stainless steel panel with black interior , 3 layers (aluminum/ plastic/ aluminum) sound-deadening panels , bottom separated ducted chamber (with 120mm fan in middle) for PSU and 4 hdd (silicone rubber grommets) , double hinge door design (allows the door to open up to 270º), built-in cable management system , front access to washable fan filters , damping materials at panel contact points to reduce vibration noise ; 2 x front usb + 1 x ieee1394 + HD audio in/out - 4x 5.25", 1x 3.5", 6x 3.5" hidden - 3 x tricool fan upto 6 , 1 x lock @ front panel , quick-release drive cages with rubber grommets
CH-AP182SESN		antec performance one P182SE special edition , stainless steel exterior with real mirror finish , No psu , with external fan speed controller + pipe hole for external water cooling system , stainless steel silver panel with black interior , 3 layers (aluminum/ plastic/ aluminum) sound-deadening panels , bottom separated ducted chamber (with 120mm fan in middle) for PSU and 4 hdd (silicone rubber grommets) , double hinge door design (allows the door to open up to 270º), built-in cable management system , front access to washable fan filters , damping materials at panel contact points to reduce vibration noise ; 2 x front usb + 1 x ieee1394 + HD audio in/out - 4x 5.25", 1x 3.5", 6x 3.5" hidden - 3 x tricool fan upto 5 , 1 x lock @ front panel , quick-release drive cages with rubber grommets
CH-AP183BN	**C**	antec performance one P183 , Black , No psu , with external fan speed controller + pipe hole for external water cooling system , stainless steel panel with black interior , 3 layers (aluminum/ plastic/ aluminum) sound-deadening panels , bottom separated ducted chamber (with 120mm fan in middle) for PSU and 4 hdd (silicone rubber grommets) , double hinge door design (allows the door to open up to 270º), built-in cable management system , front access to washable fan filters , damping materials at panel contact points to reduce vibration noise ; 2 x front usb + 1 x eSATA + HD audio in/out - 4x 5.25", 1x 3.5", 6x 3.5" hidden - 3 x tricool fan upto 6 , 1 x lock @ front panel , quick-release drive cages with rubber grommets
CH-AP193BN	**C**	antec performance one P193 , Black , No psu , support 12'x13" eATX mb , external fan speed controller + pipe hole for external water cooling system , 2 layers (aluminum/plastic) sound-deadening panels , bottom separated ducted chamber (with 120mm fan in middle) , double hinge door design (allows the door to open up to 270º) , front access to washable fan filters , damping materials at panel contact points to reduce vibration noise ; 2 x front usb + 1 x eSATA + HD audio in/out - 4x 5.25", 1x 3.5", 6x 3.5" hidden - 5 x system fan (3 with external fan controller) upto 7 , 1 x lock @ front panel , quick-release drive cages with rubber grommets

CH-AP190B		antec performance one P190 , Black , neo-link 1200w psu (dual psu : truepower3 650w+550w) , support 12'x13" eATX mb , with internal flexible snake light , external fan speed controller + pipe hole for external water cooling system , 2 layers (aluminum/plastic) sound-deadening panels , bottom separated ducted chamber (with 120mm fan in middle) for 2 x PSU and 4 hdd (silicone rubber grommets) , double hinge door design (allows the door to open up to 270º) , front access to washable fan filters , damping materials at panel contact points to reduce vibration noise ; 2 x front usb + 1 x ieee1394 + HD audio in/out - 4x 5.25", 1x 3.5", 6x 3.5" hidden - 5 x system fan (3 with external fan controller) , 1 x lock @ front panel , quick-release drive cages with rubber grommets
VAR II series		http://www.antec.com/us/pro_en_varii.html
CH-AS1000N		antec var ii series sx1000ii full tower , beige - 4x 5.25", 2x 3.5", 4x 3.5" hidden - no PSU; with lockable side panel, 2 x 8cm fan upto 5, with front washable air filter, quick release drive bays with lever, snap-in fan mounts drive rails for 5.25" devices, removable 3.5" hdd cages + anti-dust front door (lockable) ; front usb+ieee1394
Solution series		http://www.antec.com/us/pro_en_solution.html
CH-ASS2650BN		Antec solution series SLK2650BQE , Quiet Black , No psu , chassis air guide on side panel ; drive rails for 5.25” drives , 2 front usb + audio in/out , removable Drive Cages ; 4 x 5.25", 2x 3.5" , 2 x internal 3.5" with rubber grommets ; 1x120mm rear fan upto 3 , pci expansion slot protective cover
CH-ASS3000BN		Antec solution series SLK3000B , Black , NO psu , chassis air guide on side panel , drive rails for 5.25” drives , 2 x front usb + audio in/out ; removable drive cages for 3.5” drives; 4x 5.25", 2x 3.5" , 5x internal 3.5" with rubber grommets ; 1x 120mm rear fan upto 3 , lockable front door with washable air filter
New Solution series		http://www.antec.com/us/pro_en_newsolution.html
CH-ANSK1380		Antec New Solution series NSK1380 ; micro-atx cube case , antec HE 350w psu , 3 layers side panel (aluminum, plastic, aluminum) dampens system generated noise , with soft blue illumination , accepts standard MicroATX , with 4 full-height PCI expansion ; 300watt, 1x120mm+1xcyclone vga cooler ; 1 x 5.25", 3 x 3.5" hidden ; front usb+ audio in/out
CH-ANSK1480	N	Antec New Solution series NSK1480 - slimline micro atx - desktop or vertical , dual chamber design with bottom placed psu (away from cpu) , black + silver , 12cm height slim design , 80plus certrified 350w psu , 2 front usb + audio in/out + e-sata ; 1x 5.25", 2x internal 3.5" in removable hdd cage ; 3 x tricool 80mm top/side fan , lockable - 3 years warranty on PSU - micro atx only - expansion card required to be low-profile
CH-ANSK2480		Antec New Solution series NSK2480 , desktop chassis with triple-chamber structure , black + silver , antec earthwatt 380w psu , chassis air guide on side panel , 0.8mm cold-rolled steel construction , 2 front usb + audio in/out ; 2x 5.25", 2x internal 3.5" ; 2 x Tricool 120mm side fan , lockable - 3 years warranty on PSU - micro atx only
CH-ANSK3480		Antec New Solution series NSK3480 , with dual-chamber structure , black + silver , antec 380w HE SFX active PFC psu , chassis air guide on side panel , 0.8mm cold-rolled steel construction , 2 front usb + audio in/out + ieee1394 ; 2x 5.25", 1x 3.5", 1x internal 3.5" ; 1 x Tricool 120mm rear fan upto 3 - 3 years warranty on PSU - for micro atx only

CH-ANSK4000N		Antec New Solution series NSK4000 , No psu , black + silver , chassis air guide on side panel , 0.8mm cold-rolled steel construction , 2 front usb ; 3x 5.25", 2x 3.5", 3x internal 3.5" ; 1 x Tricool 120mm rear fan upto 3 - 3 years warranty on PSU
CH-ANSK4000BiiN	N	Antec New Solution series NSK400Bii , No psu , black , chassis air guide on side panel , 0.8mm cold-rolled steel construction , 2 front usb ; 3x 5.25", 2x 3.5", 3x internal 3.5" ; 1 x Tricool 120mm rear fan upto 2
CH-ANSK4480		Antec New Solution series NSK4480 , black + silver , antec earthwatts 380w psu (80Plus certrified) , chassis air guide on side panel , 0.8mm cold-rolled steel construction , 2 front usb ; 3x 5.25", 2x 3.5", 3x internal 3.5" ; 1 x Tricool 120mm rear fan upto 3
CH-ANSK4480B		Antec New Solution series NSK4480 , black , antec earthwatts 380w psu (80Plus certrified) , chassis air guide on side panel , 0.8mm cold-rolled steel construction , 2 front usb ; 3x 5.25", 2x 3.5", 3x internal 3.5" ; 1 x Tricool 120mm rear fan upto 3
CH-ANSK6000N		Antec New Solution series NSK6000 , No psu , black + silver , chassis air guide on side panel , 0.8mm cold-rolled steel construction , 2 front usb + audio in/out + ieee1394 ; 4x 5.25" (with 1 x 5.25" to 3.5" bracket+front panel) , 5x internal 3.5" ; 1 x Tricool 120mm rear fan upto 4 - 3 years warranty on PSU
CH-ANSK6580		Antec New Solution series NSK6580 , black + silver , antec earthwatt 430w psu , chassis air guide on side panel , 0.8mm cold-rolled steel construction , 2 front usb + audio in/out + ieee1394 ; 4x 5.25" (with 1 x 5.25" to 3.5" bracket+front panel) , 5x internal 3.5" ; 1 x Tricool 120mm rear fan upto 4 - 3 years warranty on PSU
CH-ANSK6580B		Antec New Solution series NSK6580 , black + silver , antec earthwatt 430w psu , chassis air guide on side panel , 0.8mm cold-rolled steel construction , 2 front usb + audio in/out + ieee1394 ; 4x 5.25" (with 1 x 5.25" to 3.5" bracket+front panel) , 5x internal 3.5" ; 1 x Tricool 120mm rear fan upto 4 - 3 years warranty on PSU
Titan series		
CH-ATN		Antec titan server chasis , no PSU , black , support 12'x13" eATX mb - double hinge door design (allows the door to open up to 270º) - 4x 5.25" , 6x internal 3.5" front accessable individually ; lockable swing out side panel with handle, 1x 120mmm fan upto 3 , quick release drive bays with lever , snap-in fan mounts , front usb+ieee1394 - support E-ATX
Rackmount		
RA-A2U20550		antec 2U20ATX550XR 20" depth 2U rackmount case , 550w psu - 1 x 5.25" + 1 x 3.5" + 3x 3.5" hidden + 1x 60mm fan + 1 x 80mm fan + 2 slot pci riser card , with lockable drive access panel , atx - black
RA-A2U26550	N	Antec 2U26ATX550XR 26" depth 2U rackmount case , 550w psu - 1 x 5.25" + 1 x 3.5" + 5x 3.5" hidden + 1x 60mm fan + 3 x 80mm fan + 2 slot pci riser card , with lockable drive access panel , support E-ATX - black
RA-A3U25E650		Antec 3U25EPS650-XR 19" width , 25" depth 3U rackmount case , 650w EPS12V psu - 4 x 5.25" + 2 x 3.5" + 4x 3.5" hidden + 1x 80mm fan + 3 x 92mm fan - support 7 full hight pci card , with lockable drive access panel , support E-ATX - black
RA-AT3E650		Antec TAKE3+650 , 20" depth 3U rackmount case , Neopower 650w psu - 2 x 5.25" + 1 x 3.5" + 3x 3.5" hidden + 1x 92mm fan + 1 x 120mm fan - support 7 full hight pci card , rubber grommets for HDD , separate air duct to keep heat from psu away from system , from usb + ieee1394 - black

RA-A4U22E550		Antec 4U22EPS550-2 19" width , 22" depth 4U rackmount case , 550w EPS12V psu - 3 or 6 x 5.25" + 3 x 3.5" + 7 or 3 x 3.5" hidden + 1x 120mm fan + 2 x 80mm fan - support 7 full hight pci card , with front usb , lockable drive access panel , support E-ATX - black
RA-AT4450		Antec TAKE4+450 , 20" depth 4U rackmount case , smart power2 450w psu - 2 x 5.25" + 2 x 3.5" + 4x 3.5" hidden + 1x 92mm fan + 1 x 120mm fan - support 7 full hight pci card , rubber grommets for HDD , separate air duct to keep heat from psu away from system , from usb + ieee1394 - black
RA-AT4E650		Antec TAKE4+650 , 20" depth 4U rackmount case , Neopower 650w psu - 2 x 5.25" + 2 x 3.5" + 4x 3.5" hidden + 1x 92mm fan + 1 x 120mm fan - support 7 full hight pci card , rubber grommets for HDD , separate air duct to keep heat from psu away from system , from usb + ieee1394 - black
RA-A4U22E650		Antec 4U22EPS650-2 19" width , 22" depth 4U rackmount case , 650w EPS12V psu - 3 or 6 x 5.25" + 3 x 3.5" + 7 or 3 x 3.5" hidden + 1x 120mm fan + 2 x 80mm fan - support 7 full hight pci card , with front usb , lockable drive access panel , support E-ATX - black
RA-AA6P		antec 6 pci back panel for 2u case
RA-AAS20		antec sliding rail kit for 20" rackmount chasis
RA-AAS26		antec sliding rail kit for 26" rackmount chasis
Zalman		http://www.zalman.com/ENG/product/CategorySecond_Pic.asp?categoryname=Cases&categorySecond=
accessories		
CH-ZAHS100	N	Zalman ZM-HS100 3 x SATA hot-swap backplan PCB kit for GS1000 - support upto raid 0/1/5
gaming chassis		
CH-ZGS1000BN		Zalman GS1000 Black gaming chassis , No psu , 2 front usb + ieee1394 + audio in/out ; 4/2x 5.25", 0/2x 3.5", 8x internal 3.5" (3 external hot-swapable upto 6) , support 2 x optional SATA hot-swap backplan PCB kit ; 2 x 120mm upto 5 - upto e-ATX
CH-ZGS1000TN		Zalman GS1000 Titanium (silver+black) gaming chassis , No psu , 2 front usb + ieee1394 + audio in/out ; 4/2x 5.25", 0/2x 3.5", 8x internal 3.5" (3 external hot-swapable upto 6) , support 2 x optional SATA hot-swap backplan PCB kit ; 2 x 120mm upto 5 - upto e-ATX
CH-ZFN		Zalman fc-ze1 Fatal1ty champ1on gaming chassis , No psu , black , with laser-etched exterior graphics , with windowed side panel (screwless) , 4-5mm anodized aluminum , 2 front usb + ieee1394 + audio in/out ; 4x 5.25", 1x 3.5", 3x internal 3.5" (tool free) ; blue LED accented power + reset buttons , 2 x 92mm + 1 x 120mm fan with red led - for atx
CH-ZGT900BN		Zalman GT900 Black gaming chassis , No psu , with windowed side panel (screwless) , 4-5mm anodized aluminum , 2 front usb + ieee1394 + audio in/out ; 4x 5.25", 1x 3.5", 6x internal 3.5" (tool free) ; blue LED accented power + reset buttons , 2 x 92mm + 1 x 120mm fan with red led - for atx
CH-ZGT1000TN		Zalman GT1000 Titanium gaming chassis , No psu , with windowed side panel (screwless) , 4-5mm anodized aluminum , 2 front usb + ieee1394 + audio in/out ; 4x 5.25", 1x 3.5", 6x internal 3.5" (tool free) ; blue LED accented power + reset buttons , 2 x 92mm + 1 x 120mm fan with blue led - for atx
CH-ZGT1000BN		Zalman GT1000 Black gaming chassis , No psu , with windowed side panel (screwless) , 4-5mm anodized aluminum , 2 front usb + ieee1394 + audio in/out ; 4x 5.25", 1x 3.5", 6x internal 3.5" (tool free) ; blue LED accented power + reset buttons , 2 x 92mm + 1 x 120mm fan with red led - for atx

CH-ZLQ1000	N	Zalman LQ1000 , chassis , No psu , built-in watercooling system (automatic/manual control modes with control knob , dual Analog Gage for fan speed + flowrate , FND Display (internal temperature, water temperature, water level and mode) , cpu water block included + optional vga , northbridge waterblock , passive heatsink side panel (screwless) , 5mm anodized aluminum , 2 front usb + ieee1394 + audio in/out ; 4x 5.25", 1x 3.5", 5x internal 3.5" (tool free) ; 1 x 220mm fan with blue led (550-850rpm) - for atx
HTPC DESKTOP		
CH-ZHD160PBN		zalman HD-160 Plus Black No psu - HTPC chassis with FFSTN Lcd module , volumn control knob , built-in card reader - ideal multimedia center in living room + MCE ready remote control ; 460x435x160mm , trure aluminum , 5x3.5" (int) ; 1x5.25"(ext) , 2 x 80mm fan upto 4 , front usb+ieee1394+audio in/out - NO Psu
CH-ZHD160PSN		zalman HD-160 Plus Silver No psu - HTPC chassis with FFSTN Lcd module , volumn control knob , built-in card reader - ideal multimedia center in living room + MCE ready remote control ; 460x435x160mm , trure aluminum , 5x3.5" (int) ; 1x5.25"(ext) , 2 x 80mm fan upto 4 , front usb+ieee1394+audio in/out - NO Psu
CH-ZHD135SN		zalman HD-135 Silver HTPC chassis with VFD module - ideal multimedia center in living room + MCE ready remote control ; 435x425x135mm , trure aluminum , 1x 5.25", 1x 3.5", 4 x internal 3.5" , 2 x 80mm fan , front usb+ieee1394+audio in/out - NO Psu
CH-ZHD135BN		zalman HD-135 Black HTPC chassis with VFD module - ideal multimedia center in living room + MCE ready remote control ; 435x425x135mm , trure aluminum , 1x 5.25", 1x 3.5", 4 x internal 3.5" , 2 x 80mm fan , front usb+ieee1394+audio in/out - NO Psu
CH-ZHD160XTPSN		zalman HD-160XT Plus Silver , No psu , HTPC chassis with 7" Touch-screen LCD + volumn control knob + built-in card reader + fan speed control software + iMoN MCE ready remote control - ideal multimedia center in living room ; 460x435x160mm , trure aluminum , 5x3.5" (int) with sliding tray ; 1x5.25" (ext) with sliding tray , 4 x system fan , front usb+ieee1394+audio in/out
CH-ZHD160XTPBN		zalman HD-160XT Plus Black , No psu , HTPC chassis with 7" Touch-screen LCD + volumn control knob + built-in card reader + fan speed control software + iMoN MCE ready remote control - ideal multimedia center in living room ; 460x435x160mm , trure aluminum , 5x3.5" (int) with sliding tray ; 1x5.25" (ext) with sliding tray , 4 x system fan , front usb+ieee1394+audio in/out
TNN (Totally No Noise) series		
CH-ZT3		zalman TNN300B - micro atx , for intel s478 or Amd s462/754/939 - ideal multimedia center in living room + MCE ready remote control (with joystick mouse) , totally no noiseless computer case - with heatpipe technology, HSC (Heat Source Contact) power technology, a high capacity extrusion technique, and FMS (Flexible Mounting Structure) design technology , with EMI interception blocks , antitheft lock ; 1x3.5" (int) ; 1x5.25"(ext) - with fanless 350W PSU , built-in card reader for multimedia center
		motherboard and vga recommendation : http://www.zalman.co.kr/eng/product/view.asp?idx=178&code=020
intel server chassis		http://www.intel.com/products/server/chassis/index.htm
pedestal		configuration tool

CH-iSC5299DP		intel SC5299DP Pilot Point 4 server chasis , 5U rackmount convertible , 550w PSU , black - 2x 5.25" , 1x 3.5" , 6 x internal 3.5" , upgradable to 6 x hot-swap SATA/SAS bay , 1 x 120m system fan , front usb+serial , support optional Intel local control panel
CH-iSC5299WS		intel SC5299WS Pilot Point 4 server chasis , 5U rackmount convertible , 670w PSU , black - 2x 5.25" , 1x 3.5" , 6 x internal 3.5" , upgradable to 6 x hot-swap SATA/SAS bay , 2 x 120m system fan , front usb+serial , support optional Intel local control panel
CH-iSC5299BRP		intel SC5299BRP Pilot Point 4 server chasis , 5U rackmount convertible , 650w PSU support optional redundant psu , black - 2x 5.25" , 1x 3.5" , 6 x internal 3.5" , upgradable to 6 x hot-swap SATA/SAS bay , 1 x 120m system fan , front usb+serial , support optional Intel local control panel
CH-iSC5400B	R	intel SC5400BASE RiGGiNS 2 , BASE server chasis , 5U rackmount convertible , 670w PSU , black - 3x 5.25" , 6x internal 3.5" upgradable to 6 x hot-swap SATA/SAS/SCSI bay , 2 high-flow fans with air duct , lockable side panel , lockable front bezel , front usb + serial , support optional Intel local control panel
CH-iSC5400BRP		intel SC5400BRP RiGGiNS 2 server chasis , 5U rackmount convertible , 830w PSU support optional redundant psu , black - 3x 5.25" , 6x internal 3.5" upgradable to 10 x hot-swap SATA/SAS/SCSI bay , 2 high-flow fans with air duct , lockable side panel , lockable front bezel , front usb + serial , support optional Intel local control panel
CH-iSC5400LX	R	intel SC5400LX RiGGiNS 2 , BASE server chasis , 5U rackmount convertible , 830w PSU support optional redundant psu , black - 3x 5.25" , 6x internal 3.5" upgradable to 10 x hot-swap SATA/SAS/SCSI bay , 4 x redundant 120mm fans , lockable side panel , lockable front bezel , front usb + serial , support optional Intel local control panel
CH-iAAXX4DRV3G	R	intel AXX4DRV3G - 4 SATA/SAS hot-swap hdd cage (non-expanded) , require 4 x SATA or 4 x SAS port from mb/controller - for SC5400BRP/ SC5400LX / SC5600
CH-iAAXX4DRV3GE	R	intel AXX4DRV3GEXP - 4 SATA/SAS hot-swap hdd cage with port expander (4 x SATA / 2 x SAS) , require 2 x SAS port from mb/controller - for SC5400BRP/ SC5400LX / SC5600
CH-iAAPP3HSDBK	R	intel APP3HSDBKIT - hot-swap adapter bracket for use of AXX6DRV3G / AXX6DRV3GEXP with all SC5299-E and SC5295 chassis
CH-iAAXX6DRV3G		intel AXX6DRV3G - 6 SATA/SAS hot-swap hdd cage (non-expanded) , require 6 x SATA or 6 x SAS port from mb/controller - for SC5299 / SC5400 / SC5600 series - require APP3HSDBKIT in sc5299 chassis
CH-iAAXX6DRV3GE	R	intel AXX6DRV3GEXP - 6 SATA/SAS hot-swap hdd cage with port expander (6 x SATA / 4 x SAS) , require 2 x SAS port from mb/controller - for SC5299 / SC5400LX / SC5600 series - require APP3HSDBKIT in sc5299 chassis
CH-iAAXX4SCSiDB	R	intel AXX4SCSIDB - 4 x SCSI hot-swap hdd cage - for SC5400BRP/ SC5400LX
CH-iAAXX6SCSiDB	R	intel AXX6SCSIDB - 6 x SCSI hot-swap hdd cage - for SC5400 series
CH-iAFXX830WPSU		intel FXX830WPSU - 2nd 830w redundant psu - required for PSU redundance for SC5400BRP, SC5400LX
CH-iAAXXLCPPED		intel AXXLCPPED - intel local control panel
CH-iAAPP3RACKIT	R	intel APP3RACKIT - 5U rackmount conversion kit for SC5295/SC5299 series

CH-iAARIGRACK		intel ARIGRACK - 5U rackmount conversion kit for SC5300 / SC5400 / SC5600 series
Power Supply		
PSU Accessories		
CA-Po		2m power cable - SABS approved
CA-PoE		2m POwer Extension cable - SABS approved
CA-Po2		2 way 2m power cable (for psu + display device) - SABS approved
PS-EA246		2x4pin to 6pin (for pci-express vga card) converter - bulk pack
PS-EA68		6pin to 8pin converter for cpu - bulk pack
PS-ZA43		Zalman ZM-MC1 - 4pin (5/12v from psu) to 3pin power connectors for cpu fan or system fan - retail pack
PS-AA4PS	N	asus 4Pin molex to Sata power converter
PS-EA2024		Enermax 20pin to 24pin converter - bulk pack
PS-EA24E24G		Enermax 24pin EPS 12v (intel) to 24pin GES (AMD) converter - bulk pack
PS-LAiL	N	Lian-li interlink cable for psu - for use of 2 psu in 1 x case ….
PS-VAVD		vantec vdk-psu Vibration Dampener kit for psu - ultra-light silica gel to reduce noises
PS-VACR		vantec CSK-80UV-RD cable sleeving kit , UV Red : include sleevings , tie wraps , Heatshrink Tubings
PS-VACY		vantec CSK-80UV-YL cable sleeving kit , UV Yellow : include sleevings , tie wraps , Heatshrink Tubings
PS-VACG		vantec CSK-80UV-GR cable sleeving kit , UV Green : include sleevings , tie wraps , Heatshrink Tubings
PS-VACL		vantec CSK-80-bL bLue cable sleeving kit : include sleevings , tie wraps , Heatshrink Tubings
PS-VACK		vantec CSK-80-BK cable sleeving kit , blacK : include sleevings , tie wraps , Heatshrink Tubings
PS-VAMG		Vantec MCK-iOUV-GR , EZ-Grip Molex Connector Kit - UV reactive Green ; 10 molex connector with one molex remover
PS-VAMK		Vantec MCK-iOUV-BK , EZ-Grip Molex Connector Kit - UV reactive blacK ; 10 molex connector with one molex remover
PS-VAMR		Vantec MCK-iOUV-RD , EZ-Grip Molex Connector Kit - UV reactive Red ; 10 molex connector with one molex remover
PS-VAMY		Vantec MCK-iOUV-YL , EZ-Grip Molex Connector Kit - UV reactive Yellow ; 10 molex connector with one molex remover
PS-VAML		Vantec MCK-iOUV-BL , EZ-Grip Molex Connector Kit - UV reactive bLue ; 10 molex connector with one molex remover
Vantec		http://www.vantectw.com/front/product/index/18
iON-C series		http://www.vantectw.com/front/product/pro_list/75
PS-V460CE	N	Vantec ioN2+C van-460C 460w power supply (12v: 312w) , EPS12V , ATX 12V V2.2 , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , dual 12V rail , 2 x SATA + 1x6 PCI-E power connectors , 1x 135mm pwm fan with intelligent fan speed control ; with OCP, OVP , SCP - 2 years warranty
PS-V520CE	N	Vantec ioN2+C van-520C 520w power supply (12v: 384w) , EPS12V , ATX 12V V2.2 , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , dual 12V rail , 2 x SATA + 1x6 PCI-E power connectors , 1x 135mm pwm fan with intelligent fan speed control ; with OCP, OVP , SCP - 2 years warranty
PS-V620CE	N	Vantec ioN2+C van-620C 620w power supply (12v: 444w) , EPS12V , ATX 12V V2.2 , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , dual 12V rail , 2 x SATA + 1x6 PCI-E power connectors , 1x 135mm pwm fan with intelligent fan speed control ; with OCP, OVP , SCP - 2 years warranty
iON-N series		http://www.vantectw.com/front/product/pro_list/72

PS-V500NE	N	Vantec ioN2+N van-500N 500w power supply (12v: 384w) , EPS12V , ATX 12V V2.2 , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , dual 12V rail , 4 x SATA + 2x6 or 1x6+1x8pin PCI-E power connectors , 1x 135mm pwm fan with intelligent fan speed control ; with OCP, OVP , SCP - 2 years warranty
PS-V600NE	N	Vantec ioN2+N van-600N 600w power supply (12v: 432w) , EPS12V , ATX 12V V2.2 , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , dual 12V rail , 4 x SATA + 2x6 or 1x6+1x8pin PCI-E power connectors , 1x 135mm pwm fan with intelligent fan speed control ; with OCP, OVP , SCP - 2 years warranty
iON-A series		http://www.vantectw.com/front/product/pro_list/43
PS-V600ASEM	N	Vantec ioN2+AS van-600AS , EPS12V+ Modular cable management , 80PLUS certified for energy saving , 600w power supply (12v: 432w) , ATX 12V V2.3 , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , dual 12V rail , 6 x SATA + 2x6 or 2x8pin PCI-E power connectors , 1x 135mm pwm fan with intelligent fan speed control ; with OCP, OVP , SCP - 3 years warranty
PS-V700ASEM	N	Vantec ioN2+AS van-700AS , EPS12V+ Modular cable management , 80PLUS certified for energy saving , 700w power supply (12v: 612w) , ATX 12V V2.3 , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , dual 12V rail , 6 x SATA + 2x6 or 2x8pin PCI-E power connectors , 1x 135mm pwm fan with intelligent fan speed control ; with OCP, OVP , SCP - 3 years warranty
PS-V700AEM	C	Vantec ioN2+AS van-700A , EPS12V+ Modular cable management , 80PLUS certified for energy saving , 700w power supply (12v: 680w) , ATX 12V V2.3 , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , quad 12V rail , 6 x SATA + 2x6 or 2x8pin PCI-E power connectors , 1x 135mm pwm fan with intelligent fan speed control ; with OCP, OVP , SCP - 3 years warranty
PS-V800AEM	N	Vantec ioN2+AS van-800A , EPS12V+ Modular cable management , 80PLUS certified for energy saving , 800w power supply (12v: 780w) , ATX 12V V2.3 , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , quad 12V rail , 6 x SATA + 2x6 or 2x8pin PCI-E power connectors , 1x 135mm pwm fan with intelligent fan speed control ; with OCP, OVP , SCP - 3 years warranty
PS-V1000AEM	C	Vantec ioN2+AS van-1000A , EPS12V+ Modular cable management , 80PLUS certified for energy saving , 1000w power supply (12v: 984w) , ATX 12V V2.3 , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , quad 12V rail , 6 x SATA + 2x6 or 2x8pin PCI-E power connectors , 1x 135mm pwm fan with intelligent fan speed control ; with OCP, OVP , SCP - 3 years warranty
Corsair		http://www.corsair.com/products/power_supplies.aspx
PS-C400CXE	N	Corsair CX400W , Eps12V , ATX 12V V2.2 - 400w (12v : 360w) , 80PLUS certified for energy saving , 24pin (4pin detachable) , with active-PFC , 6pin PCI-E power , 1x 120mm thermal controled fan - 3 years warranty
PS-C450VXE		Corsair VX450W , Eps12V , ATX 12V V2.2 - 450w (12v : 396w) , 80PLUS certified for energy saving , 24pin (4pin detachable) , with active-PFC , 6pin PCI-E power , 1x 120mm thermal controled fan ; with OCP, OVP, OPP, SCP, UVP - 5 years warranty
PS-C450HXEM	N	Corsair HX450W , Eps12V + Modular cable management , ATX 12V V2.2 - 520w (12v : 480w) , nvidia SLi ready , 80PLUS certified for energy saving , 24pin (4pin detachable) , with active-PFC , 2 x 8pin (2+6) PCI-E power connectors , 1x 120mm thermal controled fan - 7 years warranty

PS-C520HXEM		Corsair HX520W , Eps12V + Modular cable management , ATX 12V V2.2 - 520w (12v : 480w) , nvidia SLi ready , 80PLUS certified for energy saving , Tripple 12V rail , 24pin (4pin detachable) , with active-PFC , 2 x 6pin PCI-E power connectors , 1x 120mm thermal controled fan ; with OCP, OVP, OPP, SCP, UVP - 5 years warranty
PS-C550VXE	N	Corsair VX550W , Eps12V , ATX 12V V2.2 - 550w (12v : 492w) , 80PLUS certified for energy saving , 24pin (4pin detachable) , with active-PFC , 6pin PCI-E + 1x8pin (6+2) PCI-E power connectors , 1x 120mm thermal controled fan ; with OCP, OVP, OPP, SCP, UVP - 5 years warranty
PS-C620HXEM		Corsair HX620W , Eps12V + Modular cable management , ATX 12V V2.2 - 620w (12v : 600w) , nvidia SLi ready , 80PLUS certified for energy saving , Tripple 12V rail , 24pin (4pin detachable) , with active-PFC , 2 x 6pin PCI-E power connectors , 1x 120mm thermal controled fan ; with OCP, OVP, OPP, SCP, UVP - 5 years warranty
PS-C650TXE		Corsair TX650W , Eps12V , ATX 12V V2.2 - 620w (12v : 624w) , nvidia SLi ready , 80PLUS certified for energy saving , 24pin (4pin detachable) , with active-PFC , 2 x 8pin (2+6) PCI-E power connectors , 1x 120mm thermal controled fan ; with OCP, OVP, OPP, SCP, UVP - 5 years warranty
PS-C750TXE		Corsair TX750W , Eps12V , ATX 12V V2.2 - 750w (12v : 720w) , nvidia SLi ready , 80PLUS certified for energy saving , 24pin (4pin detachable) , with active-PFC , 4 x 8pin (2+6) PCI-E power connectors , 1x 140mm thermal controled fan ; with OCP, OVP, OPP, SCP, UVP - 5 years warranty
PS-C850TXE	N	Corsair TX850W , Eps12V , ATX 12V V2.2 - 850w (12v : 840w) , nvidia SLi ready , 80PLUS certified for energy saving , 24pin (4pin detachable) , with active-PFC , 4 x 8pin (2+6) PCI-E power connectors , 1x 140mm thermal controled fan ; with OCP, OVP, OPP, SCP, UVP - 5 years warranty
PS-C1000HXEM	N	Corsair HX1000W , Eps12V + Modular cable management , ATX 12V V2.2 - 1000w (12v : 980w) , nvidia SLi ready , 80PLUS certified for energy saving , dual 12V rail , 24pin (4pin detachable) , with active-PFC , 6 x 8pin (2+6) PCI-E power connectors , 1x 140mm thermal controled fan ; with OCP, OVP, OPP, SCP, UVP - 5 years warranty
Zalman		http://www.zalman.co.kr/eng/product/code_list.asp?code=015
PS-Z360E		zalman ZM360B-APS : 360w (12v : 312w) , with EPS12V support , ultra quiet , 2 x 12V rail , 1 x 120mm fan auto control cooling fan , one Multi-connector for Fan ; Active PFC ; with OCP , OVP , SCP , OTP , UVP - 3 years warranty
PS-Z460E		zalman ZM460B-APS : 460w (12v : 408w) , with EPS12V support , ultra quiet , 2 x 12V rail , 1 x 120mm fan auto control cooling fan , one Multi-connector for Fan ; Active PFC ; with OCP , OVP , SCP , OTP , UVP - 3 years warranty
PS-Z500EML		zalman ZM500-HP : 500w (12v : 408w) , with EPS12V support + heat-pipe technology , with modular cable management , blue E-Led , 2 x 12V rail , active PFC , 1 x 120mm auto control cooling fan , one Multi-connector for Fan ; Active PFC ; with OCP , OVP , SCP , OTP , UVP - 3 years warranty
PS-Z600ML		zalman ZM600-HP : 600w (12v : 504w) + heat-pipe technology , with modular cable management , blue E-Led , quad 12V rail , active PFC , 1x6pin + 1x8pin (6+2) PCI-E power connectors , 1 x 120mm auto control cooling fan , one Multi-connector for Fan ; Active PFC ; with OCP , OVP , SCP , OTP , UVP - 3 years warranty

PS-Z660EML	C	zalman ZM660-XT : 660w (12v : 636w) , with EPS12V support + heat-pipe technology , with modular cable management , quad 12V rail , active PFC , 1x6pin + 1x8pin (6+2) PCI-E power connectors , 1 x 140mm auto control cooling fan with blue E-Led , one Multi-connector for Fan ; Active PFC ; with OCP , OVP , SCP , OTP , UVP - 3 years warranty
PS-Z750EML		zalman ZM750-HP : 750w (12v : 720w) , with EPS12V support + heat-pipe technology , 80PLUS certified for energy saving , with modular cable management , blue E-Led , quad 12V rail , active PFC , 1 x 120mm auto control cooling fan , one Multi-connector for Fan ; Active PFC ; with OCP , OVP , SCP , OTP , UVP - 3 years warranty
PS-Z770EML	C	zalman ZM770-XT : 770w (12v : 720w) , with EPS12V support + heat-pipe technology , 80PLUS certified for energy saving , with modular cable management , quad 12V rail , active PFC , 1 x 140mm auto control cooling fan with blue E-Led , one Multi-connector for Fan ; Active PFC ; with OCP , OVP , SCP , OTP , UVP - 3 years warranty
PS-Z850EM		zalman ZM850-HP : 850w (12v : 768w) , with EPS12V support + dual heat-pipe technology + dual engine system , 80PLUS certified for energy saving , with modular cable management , with 5v standby noise filter switch , 6 x 12V rail , active PFC , 2x6pin + 2x8pin (6+2) PCI-E power connectors , 1 x 140mm auto control cooling fan , one Multi-connector for Fan ; Active PFC ; with OCP , OVP , SCP , OTP , UVP - 3 years warranty
PS-Z1000EM		zalman ZM1000-HP : 1000w (12v : 960w) , with EPS12V support + dual heat-pipe technology + dual engine system , 80PLUS certified for energy saving , with modular cable management , with 5v standby noise filter switch , 6 x 12V rail , active PFC , 2x6pin + 2x8pin (6+2) PCI-E power connectors , 1 x 140mm auto control cooling fan , one Multi-connector for Fan ; Active PFC ; with OCP , OVP , SCP , OTP , UVP - 3 years warranty
Antec		http://www.antec.com/us/pro_powerSupply.html
speciality		
PS-AMT350		Antec MT350 - 350w SFX psu (150x 55x 83mm) for Minuet , 24pin , 1x 80mm fan - 3 years warranty
PS-ASU300		Antec SU300 - 300w SFX psu (125x 55x 100mm) for NSK3300 , 24pin , 1x 80mm fan - 3 years warranty
PS-AAR350		Antec AR300 - 350w L-shape dedicated psu for antec ARIA / NSK1300 , 24pin , 1x 120mm fan - 3 years warranty
PS-ANP650R		Antec Neo-Power 650R - 650w EPS12V psu for Take4 , 4U22EPS650XR
PS-ANP650XR		Antec Neo-Power 650XR - 650w EPS12V psu - AC + DC at the same side - for Take3 , 3U25EPS650XR
PS-ANL550		Antec Neo-Link 550 - 550w EPS12V psu for P190
PS-ANL650		Antec Neo-Link 650 - 650w EPS12V psu for P190
Basiq		http://www.antec.com/us/pro_p_Basiq.html
PS-A550BEM		Antec Basiq BP550 plus , Eps12v + Module cable management , 500w (12v : 348w) , 24pin (4pin detachable) , with active-PFC , 1x6+1x8pin PCI-E power connectors PCI-E power connectors , Tripple 12V rail , 1x 120mm fan - 1 year warranty
Earthwatts		http://www.antec.com/us/pro_p_EarthWatts.html
PS-A380EA		Antec EA-380 , 80PLUS certified for energy saving - 380w , 24pin (4pin detachable) , with active-PFC , 6pin PCI-E power , dual 12V rail , 1x 80mm thermal controled fan ; with OVP, OPP, SCP, UVP - 3 years warranty , SABS approved

PS-A430EA		Antec EA-430 , 80PLUS certified for energy saving - 430w , 24pin (4pin detachable) , with active-PFC , 6pin PCI-E power , dual 12V rail , 1x 80mm thermal controled fan ; with OVP, OPP, SCP, UVP - 3 years warranty , SABS approved
PS-A500EA		Antec EA-500 , 80PLUS certified for energy saving - 500w , 24pin (4pin detachable) , with active-PFC , 2 x 6pin PCI-E power , dual 12V rail , 1x 80mm thermal controled fan ; with OVP, OPP, SCP, UVP - 3 years warranty , SABS approved
PS-A650EAE		Antec EA-650 , 80PLUS certified for energy saving , with EPS12V - 650w , 24pin (4pin detachable) , with active-PFC , 2x6 or 1x6+1x8pin PCI-E power connectors , Tripple 12V rail , 1x 80mm thermal controled fan ; with OVP, OPP, SCP, UVP - 3 years warranty , SABS approved
PS-A750EAEM	**C**	Antec EA-750 , 80PLUS certified for energy saving , with EPS12V + Modular cable management - 750w , 24pin (4pin detachable) , with active-PFC , 2x6 or 2x6+2x8(6+2)pin PCI-E power connectors , quad 12V rail , 1x 140mm thermal controled fan ; with OVP, OCP, SCP - 3 years warranty , SABS approved
CP		
PS-A850CPEM	**C**	Antec CP-850 , 850w , with EPS12V v2.91 + Modular cable management , nVidia SLi certificated - 24pin (4pin detachable) , Quad 12V rail + antec Low noise technology ; 2 x 6pin PCI-E 1.0 power connectors + 2x 8 (6+2) pin PCI-E 2.0 power connectors , 1x 120mm double ball bearing fans with advanced thermal control ; with OVP, OCP, SCP safety standard , 80PLUS certified for energy saving - 5 years warranty
TruePower		
PS-A430T3		Antec TruePower Trio 430w (12v : 384w) , 24pin (4pin detachable) , dedicated output circuits for 3.3V, 5V, Tripple 12V rail + voltage feedback detection + antec Low noise technology ; 1 x 6pin PCI-E 1.0 power connectors , 1x 120mm double ball bearing fans with advanced thermal control ; with OVP, OPP, SCP, UVP safety standard - 5 years warranty , SABS approved
PS-A650T3E		Antec TruePower Trio 650w (12v : 624w) , with EPS12V , nVidia SLi certrified - 650w , 24pin (4pin detachable) , dedicated output circuits for 3.3V, 5V, Tripple 12V rail + voltage feedback detection + antec Low noise technology ; 2 x 6pin PCI-E 1.0 power connectors , 1x 120mm double ball bearing fans with advanced thermal control ; with OVP, OPP, SCP, UVP safety standard - 5 years warranty , SABS approved
PS-A750TBEM	**C**	Antec TruePower Blue 750w , with EPS12V v2.91 + Modular cable management , nVidia SLi certrified - 24pin (4pin detachable) , dedicated output circuits for 3.3V, 5V, Quad 12V rail + voltage feedback detection + antec Low noise technology ; 2 x 6pin PCI-E 1.0 power connectors + 2 x 8pin PCI-E 2.0 power connectors , 1x blue E-led 120mm PWM fans with advanced thermal control ; with OVP, OCP, SCP, UVP safety standard , 80PLUS certified for energy saving - 5 years warranty , SABS approved
PS-A850T4EM		Antec TruePower Quattro 850w , with EPS12V v2.91 + Modular cable management - 24pin (4pin detachable) , dedicated output circuits for 3.3V, 5V, Quad 12V rail + voltage feedback detection + antec Low noise technology ; 2 x 6pin PCI-E 1.0 power connectors + 2 x 8pin PCI-E 2.0 power connectors , 1x 80mm double ball bearing fans with advanced thermal control ; with OVP, OCP, SCP, UVP safety standard , 80PLUS certified for energy saving - 5 years warranty , SABS approved

PS-A1000T4EM	Antec TruePower Quattro 1000w , with EPS12V v2.91 + Modular cable management - 24pin (4pin detachable) , dedicated output circuits for 3.3V, 5V, Quad 12V rail + voltage feedback detection + antec Low noise technology ; 2 x 6pin PCI-E 1.0 power connectors + 2 x 8pin PCI-E 2.0 power connectors , 1x 80mm double ball bearing fans with advanced thermal control ; with OVP, OCP, SCP, UVP safety standard , 80PLUS certified for energy saving - 5 years warranty , SABS approved
Neo series	http://www.antec.com/us/pro_p_NeoHE.php
PS-A380NHM	antec NEO HE 380w (12v : 336w) , with Modular cable management , High Efficiency (85%) , active PFC , 1 x 6pin PCI-E power connector , dedicated output circuits for 3.3V, 5V, and tripple 12V circut + voltage feedback detection + antec Low noise technology ; 1x 80mm low noise fans with advanced thermal control , with OCP , OVP , OPP , SCP , UVP - 5 years warranty
PS-A430NHM	antec NEO HE 430w (12v : 384w) , with Modular cable management , High Efficiency (85%) , active PFC , 1 x 6pin PCI-E power connector , dedicated output circuits for 3.3V, 5V, and tripple 12V circut + voltage feedback detection + antec Low noise technology ; 1x 80mm low noise fans with advanced thermal control , with OCP , OVP , OPP , SCP , UVP - 5 years warranty
PS-A500NHEM	antec NEO HE 500w (12v : 456w) , with EPS12V + Modular cable management , SLi certrified , High Efficiency (85%), active PFC , with 4 or 8pin 12v , 2 x 6pin PCI-E power connectors , dedicated output circuits for 3.3V, 5V, and tripple 12V circut + voltage feedback detection + antec Low noise technology ; 1x 80mm low noise fans with advanced thermal control , with OCP , OVP , OPP , SCP , UVP - 5 years warranty
PS-A650NPEM	antec NeoPower 650 , 650w , with EPS12V , with Modular Cable Management , SLi certrified , High Efficiency (85%) , active PFC , with 4 or 8pin 12v , 2 x 6pin + 2 x 8pin PCI-E power connectors , dedicated output circuits for 3.3V, 5V, tripple 12V circut + voltage feedback detection + antec Low noise technology ; 1x 80mm low noise fan with advanced thermal control , with OPP , OVP , SCP , UVP - 5 years warranty
PS-A650NPBEM	antec NeoPower 650 Blue , 650w , with Blue led , with EPS12V , with Modular Cable Management , SLi certrified , High Efficiency (85%) , active PFC , with 4 or 8pin 12v , 2 x 6pin + 2 x 8pin PCI-E power connectors , dedicated output circuits for 3.3V, 5V, tripple 12V circut + voltage feedback detection + antec Low noise technology ; 1x 120mm low noise fan with blue led , with OPP , OVP , SCP , UVP - 5 years warranty
Signature	http://www.antec.com/us/pro_p_Signature.php
PS-A650SEM	Antec Signature 650 , 650w , with EPS12V) , with Modular Cable Management , 80 PLUS® Bronze Certified , SLi certrified , High Efficiency (85% , active PFC , with 4 or 8pin 12v , 1 x 6pin + 1 x 8(6+2)pin PCI-E power connectors , dedicated output circuits for 3.3V, 5V, tripple 12V circut + voltage feedback detection ; 1x 80mm PWM fan , with OTP , OVP , SCP , OCP - 5 years warranty
PS-A850SEM	Antec Signature 850 , 850w , with EPS12V) , with Modular Cable Management , 80 PLUS® Bronze Certified , SLi certrified , High Efficiency (85%) , active PFC , with 4 or 8pin 12v , 2 x 6pin + 2 x 8(6+2)pin PCI-E power connectors , dedicated output circuits for 3.3V, 5V, Quad 12V circut + voltage feedback detection ; 1x 80mm PWM fan , with OTP , OVP , SCP , OCP, OPP - 5 years warranty
Enermax	
Noisetaker series	http://www.enermax.co.uk/index.php?id=55&cat=11&subcat=64&L=0

PS-EN600E	Enermax Noisetaker2 DXX 600w (12v : 420w) , all-in-1 for ATX,EPS12V,BTX , nVidia SLi certificated , external fan speed control knob , corrosion resistant , High Efficiency , ring core technology for EMI shielding , active PFC , 20/24pin + 4 or 8pin 12v AUX , 2x6 or 1x6+1x8pin PCI-E power connectors , 8+9cm auto+manual thermal controled smart fan (after PC shuts down, fans keep running for 2 mins to cool down parts and hardware inside PSU and PC case) , dual 12V rails ; with OCP , OVP , OPP, OTP , SCP , UVP protection - 3 years warranty
Liberty series	http://www.enermax.co.uk/index.php?id=55&cat=11&subcat=63&L=0
PS-EL500EM	Enermax Liberty DXX 500w (12v : 384w) , all-in-1 for ATX,EPS12V,BTX , High Efficiency , with modular cables + storage bag , active PFC , 20/24pin + 2x4 or 1x8pin 12v AUX , 2x6 or 1x6+1x8pin PCI-E power connectors , 12cm thermal controled fan , support upto 18 drives , EMI shielding , dual 12V rails ; with OCP , OLP , OVP , OTP , SCP , UVP protection - 3 years warranty
PS-EL620EM	Enermax Liberty DXX 620w (12v : 432w) , all-in-1 for ATX,EPS12V,BTX , High Efficiency , with modular cables + storage bag , active PFC , 20/24pin + 2x4 or 1x8pin 12v AUX , 2x6 or 1x6+1x8pin PCI-E power connectors , 12cm thermal controled fan , support upto 18 drives , EMI shielding , dual 12V rails ; with OCP , OLP , OVP , OTP , SCP , UVP protection - 3 years warranty
Pro82+ series	http://www.enermax.co.uk/index.php?id=55&cat=11&subcat=165&L=0
PS-E425P82E	Enermax Pro82+ 425w (12v : 396w) , 84-88% Efficiency 80 PLUS certified , all-in-1 for ATX12V v2.3, EPS12V, BTX , active PFC , 20/24pin + 2x4 or 1x8pin 12v AUX , 2x6 or 1x6+1x8pin PCI-E power connectors , 12cm thermal controled fan , support upto 11 drives , EMI shielding , tripple 12V rails ; with OCP , OLP , OVP , OTP , SCP , UVP protection - 3 years warranty
PS-E625P82E	Enermax Pro82+ 625w (12v : 600w) , 84-88% Efficiency 80 PLUS certified , all-in-1 for ATX12V v2.3, EPS12V, BTX , active PFC , 24pin + 2x4 or 1x8pin 12v AUX , 4x6 or 2x6+2x8pin PCI-E power connectors , 12cm thermal controled fan , support upto 14 drives , EMI shielding , tripple 12V rails ; with OCP , OLP , OVP , OTP , SCP , UVP protection - 3 years warranty
Modu82+ series	http://www.enermax.co.uk/index.php?id=55&cat=11&subcat=164&L=0
PS-E425M82EM	Enermax Modu82+ 425w (12v : 396w) , with modular cables + storage bag , 84-88% Efficiency 80 PLUS certified , all-in-1 for ATX12V v2.3, EPS12V, BTX , active PFC , 20/24pin + 2x4 or 1x8pin 12v AUX , 2x6 or 8pin PCI-E power connectors , 12cm thermal controled fan , support upto 12 drives , EMI shielding , tripple 12V rails ; with OCP , OLP , OVP , OTP , SCP , UVP protection - 3 years warranty
Infiniti series	http://www.enermax.co.uk/index.php?id=55&cat=11&subcat=120&L=0

PS-Ei650EM	Enermax Infiniti 650w (12v : 624w) , with CoolGuard (psu + system fans continue running after system shut down until heat out of the chassis) , with PowerGuard - 4 alarm mode monitoring led , 80PLUS certified for energy saving , designed for 24x7 @ 40° , all-in-1 for ATX,EPS12V,BTX , High Efficiency , with Modular cables + storage bag , active PFC , 24pin + 2x4 or 1x8pin 12v AUX , 3x6 or 2x6+1x8pin PCI-E power connectors , 13.5cm thermal controled fan , support upto 18 drives , EMI shielding , Tripple 12V rails ; with OCP , OLP , OVP , OTP , SCP , UVP protection - 3 years warranty
PS-Ei720EM	Enermax Infiniti 720w (12v : 672w) , with CoolGuard (psu + system fans continue running after system shut down until heat out of the chassis) , with PowerGuard - 4 alarm mode monitoring led , 80PLUS certified for energy saving , designed for 24x7 @ 40° , all-in-1 for ATX,EPS12V,BTX , High Efficiency , with Modular cables + storage bag , active PFC , 24pin + 2x4 or 1x8pin 12v AUX , 3x6 or 2x6+1x8pin PCI-E power connectors , 13.5cm thermal controled fan , support upto 18 drives , EMI shielding , Tripple 12V rails ; with OCP , OLP , OVP , OTP , SCP , UVP protection - 3 years warranty
Galaxy series	http://www.enermax.co.uk/index.php?id=55&cat=11&subcat=62&L=0
PS-EG1000E	Enermax Galaxy DXX 1000w (12v : 408w + 492w) , ATX/EPS12V SSi with Quad CPU support , High Efficiency , dedicated 5x 12V rail , tripple transformer design , 4 mode alert powerguard with reset function , with modular cables + storage bag , active PFC , 24pin + 2x4pin + 1x8pin + 2x2pin 12v AUX , 3x6 or 1x6+2x8pin PCI-E power connectors , 2 x thermal controled fan (8.5+13.5cm) , support upto 24 drives ; with OCP , OLP , OVP , OTP , SCP , UVP protection - 3 years warranty
Coollermaster	
eXtreme power	
PS-C390X	Coolermaster RS-390-PCAR eXtreme power 390w , ATX 12V V2.01, dual 12V rail , 2 x SATA , 24pin , 1x 80mm fan ; with OCP , OVP , OPP - 2 years warranty
PS-C460X	Coolermaster RS-460-PCAR eXtreme power plus 460w , ATX 12V V2.3 , 2 x SATA , 24pin , 1x 120mm fan ; with OCP , OVP , OPP , SCP - 2 years warranty
PS-C500X	Coolermaster RS-500-PCAR eXtreme power 500w , ATX 12V V2.01 , dual 12V rail , 3 x SATA + 6pin PCI-E power , 24pin (4 pin detachable) , 1x 120mm fan ; with OVP , OPP , SCP - 2 years warranty
PS-C550X	Coolermaster RP/RS-550-PCAR eXtreme power 550w , ATX 12V V2.01 , dual 12V rail , 3 x SATA + 1 x 6pin PCI-E power , 24pin (4 pin detachable) , 1x 120mm fan ; with OVP , OPP , SCP - 2 years warranty
PS-C600X	Coolermaster RP/RS-600-PCAR eXtreme power 600w , ATX 12V V2.01 , dual 12V rail , 3 x SATA + 2 x 6pin PCI-E power , 24pin (4 pin detachable) , 1x 120mm fan ; with OVP , OPP , SCP - 2 years warranty
PS-C650X	Coolermaster RP/RS-650-PCAR eXtreme power 650w , ATX 12V V2.01 , dual 12V rail , 3 x SATA + 2 x 6pin PCI-E power , 24pin (4 pin detachable) , 1x 120mm pwm fan with intelligent fan speed control ; with OVP , OPP , SCP - 2 years warranty
Real power	

PS-C400RE	**N**	Coolermaster RS400-ASAAD3 Real power pro 400w (12v: 300w) , EPS12V V2.91 + SSi + ATX 12V V2.31 , active PFC , 2 x 12V rail , 4 x SATA , 1x6 pin PCI-E power connectors , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 120mm fan with intelligent fan speed control ; with OVP, UVP, OTP, OCP, OPP, SCP ; 80 PLUS certified - 5 years warranty
PS-C460RE	**N**	Coolermaster RS460-ASAAD3 Real power pro 460w (12v: 384w) , EPS12V V2.91 + SSi + ATX 12V V2.31 , active PFC , 2 x 12V rail , 4 x SATA , 1x6 pin PCI-E power connectors , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 120mm fan with intelligent fan speed control ; with OVP, UVP, OTP, OCP, OPP, SCP ; 80 PLUS certified - 5 years warranty
PS-C550RELD		Coolermaster RS-550-ACLY Real power 550w , EPS12V V2.1 + SSi + ATX 12V V2.01 + bLue led fan + 3.5" Display for power consumpation - quad SLi + quad CPU ready , multiple protection circuit , active PFC , 3 x 12V rail , 3 x SATA + 2 x 6pin PCI-E power , 20/24pin + 4 or 8pin 12v AUX , 1x 120mm blue led fan with intelligent fan speed control ; with OVP , UVP , OTP , OCP , OLP , SCP - 3 years warranty
PS-C550RE		Coolermaster RS-550-ACAA Real power pro 550w (12v: 432w) , EPS12V V2.91 + SSi + ATX 12V V2.2 , SLi ready , multiple protection circuit , active PFC , 3 x 12V rail , 6 x SATA , 2x6 pin PCI-E power connectors , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 120mm fan with intelligent fan speed control ; with OVP, UVP, OTP, OCP, OLP, OPP, SCP ; 80 PLUS certified - 5 years warranty
PS-C520REM		Coolermaster RS-520-ASAA Real power 520w (12v: 408w) , EPS12V V2.91 + SSi + ATX 12V V2.3 , Modular cable manafgement , with piano finish, active PFC , 3 x 12V rail , 2x6 or 1x6+1x8pin PCI-E power connectors , 24pin + 4 or 8pin 12v AUX , 1x 120mm fan with intelligent fan speed control ; with OVP, OTP, OCP, OLP - 5 years warranty
PS-C650RE		Coolermaster RS-650-ACAA Real power pro 650w (12v: 540w) , EPS12V V2.91 + SSi + ATX 12V V2.2 , SLi ready , multiple protection circuit , active PFC , 3 x 12V rail , 6 x SATA , 2x6 pin PCI-E power connectors , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 120mm fan with intelligent fan speed control ; with OVP, UVP, OTP, OCP, OLP, OPP, SCP ; 80 PLUS certified - 5 years warranty
PS-C620REM		Coolermaster RS-620-ASAA Real power 620w (12v: 516w) , EPS12V V2.91 + SSi + ATX 12V V2.3 , Modular cable manafgement , active PFC + 2x6 or 1x6+1x8pin PCI-E power connectors (8 pin for for pci-e 2.0 vga card) , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 120mm fan with intelligent fan speed control ; with OVP , OTP , OCP , OLP , SCP - 3 years warranty
PS-C700REM		Coolermaster RS-700-ASAA Real power 700w (12v: 624w) , EPS12V V2.91 + SSi + ATX 12V V2.3 , Modular cable manafgement , active PFC , 4 x 12V rail , 2x6pin + 2x8(6+2) pin PCI-E power connectors, 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 120mm fan with intelligent fan speed control ; with OVP , OTP , OCP , OLP , SCP - 5 years warranty
PS-C750RE		Coolermaster RS-750-ACAA Real power pro 750w (12v: 684w) , EPS12V V2.91 + SSi + ATX 12V V2.2 , SLi ready , multiple protection circuit , active PFC , 4 x 12V rail , 6 x SATA + 2x6pin + 2x8(6+2) pin PCI-E power connectors , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 120mm fan with intelligent fan speed control ; with OVP, UVP, OTP, OCP, OLP, OPP, SCP ; 80 PLUS certified - 5 years warranty

PS-C850RE		Coolermaster RS-850-EMBA Real power pro 850w (12v: 768w) , EPS12V V2.91 + SSi + ATX 12V V2.2 , quad SLi + quad CPU ready , multiple protection circuit , active PFC , 6 x 12V rail , 8 x SATA , 4x6pin + 2x8(6+2) pin PCI-E power connectors , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 135mm fan with intelligent fan speed control ; with OVP , UVP , OTP , OCP , OLP , SCP ; 80 PLUS certified - 5 years warranty
PS-C850REM		Coolermaster RS-850-ESBA Real power M850 850w (12v: 768w) , EPS12V V2.91 + SSi + ATX 12V V2.2 , Modular cable manafgement , quad SLi + quad CPU ready , multiple protection circuit , active PFC , 6 x 12V rail , 6 x SATA , 4x6pin + 2x8(6+2) pin PCI-E power connectors , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 135mm fan with intelligent fan speed control ; with OVP , UVP , OTP , OCP , OLP , SCP ; 80 PLUS certified - 5 years warranty
PS-C1000RE		Coolermaster RS-A00-EMBA Real power 1000w (12v: 960w) , EPS12V V2.92 + SSi + ATX 12V V2.3 , quad SLi + quad CPU ready , multiple protection circuit , active PFC , 6 x 12V rail , 8 x SATA + 4 x 6pin PCI-E power + 2 x 8pin PCI-E power connector , 24pin + 4 or 8pin 12v AUX , 1x 135mm PWM fan ; with OVP, UVP, OTP, OCP, OPP ; 80 PLUS certified - 5 years warranty
PS-C1000REM		Coolermaster RS-A00-ESBA Real power 1000w (12v: 960w) , EPS12V V2.91 + SSi + ATX 12V V2.2 , Modular cable manafgement , quad SLi + quad CPU ready , multiple protection circuit , active PFC , 6 x 12V rail , 6 x SATA + 4 x 6pin PCI-E power + 2 x 8pin PCI-E power connector , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 135mm fan with intelligent fan speed control ; with OVP , UVP , OTP , OCP , OLP , SCP ; 80 PLUS certified - 5 years warranty
PS-C1000REE	N	Coolermaster RS-A00-EFAM Real power 1000w nVidia ESA ready , (12v: 960w) , EPS12V V2.92 + SSi + ATX 12V V2.3 , quad SLi + quad CPU ready , multiple protection circuit , active PFC , 6 x 12V rail , 8 x SATA + 4 x 6pin PCI-E power + 2 x 8pin PCI-E power connector , 24pin + 4 or 8pin 12v AUX , 1x 120mm PWM fan ; with OVP, UVP, OTP, OCP, OPP ; 80 PLUS certified - 5 years warranty
PS-C1250RE		Coolermaster RS-C50-EMBA Real power 1250w (12v: 1125w) , EPS12V V2.91 + SSi + ATX 12V V2.2 , quad SLi + quad CPU ready , multiple protection circuit , active PFC , 6 x 12V rail , 8 x SATA + 6 x 6pin PCI-E power + 3 x 8pin PCI-E power connector , 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 135mm fan with intelligent fan speed control ; with OVP , UVP , OTP , OCP , OLP , SCP ; 80 PLUS certified - 5 years warranty
silent pro series		
PS-C500SEM	N	Coolermaster RS-500-AMBA Silent power pro 500w , EPS12V V2.91 + SSi + ATX 12V V2.3 , Modular cable manafgement , copper+aluminum heatsink , anti-vibration silicon pads , active PFC , 2x8(6+2) pin PCI-E power connectors, 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 135mm fan with intelligent fan speed control ; with OVP , OTP , OCP , OLP , SCP - 5 years warranty
PS-C600SEM	N	Coolermaster RS-600-AMBA Silent power pro 600w , EPS12V V2.91 + SSi + ATX 12V V2.3 , Modular cable manafgement , copper+aluminum heatsink , anti-vibration silicon pads , active PFC , 2x8(6+2) pin PCI-E power connectors, 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 135mm fan with intelligent fan speed control ; with OVP, UVP, OTP, OCP, OPP, OLP, SCP - 5 years warranty

PS-C700SEM	N	Coolermaster RS-700-AMBA Silent power pro 700w , EPS12V V2.91 + SSi + ATX 12V V2.3 , Modular cable manafgement , copper+aluminum heatsink , anti-vibration silicon pads , active PFC , 2x8(6+2) pin PCI-E power connectors, 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 135mm fan with intelligent fan speed control ; with OVP , OTP , OCP , OLP , SCP - 5 years warranty
Ultimate series		
PS-C700UE	N	Coolermaster RS-700-AAAA-A3 , UCP 700w , high efficiency VRM module 88% effciency , EPS12V V2.92 + SSi + ATX 12V V2.3 , active PFC , 4 x 12V rail , 2x6pin + 2x8(6+2) pin PCI-E power connectors, 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 120mm fan with intelligent fan speed control ; with OVP, OTP, OCP, OPP, UVP , SCP - 5 years warranty
PS-C900UE	N	Coolermaster RS-900-AAAA-A3 , UCP 900w , high efficiency VRM module 88% effciency , EPS12V V2.92 + SSi + ATX 12V V2.3 , active PFC , 4 x 12V rail , 2x6pin + 2x8(6+2) pin PCI-E power connectors, 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 120mm fan with intelligent fan speed control ; with OVP, OTP, OCP, OPP, UVP , SCP - 5 years warranty
PS-C1100UE	N	Coolermaster RS-B00-AAAA-A3 , UCP 1100w , high efficiency VRM module 88% effciency , EPS12V V2.92 + SSi + ATX 12V V2.3 , active PFC , 6 x 12V rail , 2x6pin + 2x8(6+2) pin PCI-E power connectors, 24pin (4 pin detachable) + 4 or 8pin 12v AUX , 1x 120mm fan with intelligent fan speed control ; with OVP, OTP, OCP, OPP, UVP , SCP - 5 years warranty
Case Fan		
Accessories		
CH-ZAFM2		Zalman Fan Mate2 - fan speed mini controller , 5-11V output to reduce fan speed and noise - 1 channel
FA-ZASC	N	Zalman Silent Connector - ZM-RC56 - 3pin fan resistor for fan to run in silent mode , reduce 12V fan to 7v to reduce fan speed and noise - 1 channel
FA-VV60		vantec vdk-60 60mm system fan vibration dampener kit - ultra-light silica gel to reduce noises
FA-VV80		vantec vdk-80 80mm system fan vibration dampener kit - ultra-light silica gel to reduce noises
FA-VV92		vantec vdk-92 92mm system fan vibration dampener kit - ultra-light silica gel to reduce noises
FA-VV120		vantec vdk-120 120mm system fan vibration dampener kit - ultra-light silica gel to reduce noises
Thermalright		
FA-120TFDB1000	N	Thermalright TR-FDB-1000 , FDB (Fluid Dynamic Bearing) , 120mm quiet fan : 1000rpm , 15.8db, 38.9CFM
FA-120TFDB1300	N	Thermalright TR-FDB-1300 , FDB (Fluid Dynamic Bearing) , 120mm quiet fan : 1300rpm , 24.1db, 50CFM
FA-120TFDB1600	N	Thermalright TR-FDB-1600 , FDB (Fluid Dynamic Bearing) , 120mm quiet fan : 1600rpm , 28db, 63.7CFM
FA-120TFDB2000	N	Thermalright TR-FDB-2000 , FDB (Fluid Dynamic Bearing) , 120mm quiet fan : 2000rpm , 38db, 80CFM
Lian-Li		
FA-140LK	N	Lian-li BS-05 140mm cooling kit , with dust filter + fan guard/grill , double-ball bearing - 1200rpm, 0.66mm-H2O , 60.42CFM , 20.9dBA
FA-140LL	N	Lian-li CF-1412 140mm fan with bLue led , with dust filter fan guard/grill , double-ball bearing , 1200rpm, 0.66mm-H2O , 72.88CFM , 29.65dBA , 900rpm

CH-LABS03	N	Lian-li BS-03 internal pci cooler - positioned on top of 7 pci slot , 1x120mm fan , 1500rpm , 53CFM , 25.6dBA , 1.51mm-H2O - for selected chassis only
CH-LABS02	N	Lian-li BS-02 internal pci cooler- positioned on top of 7 pci slot , 1x 120mm position adjustable fan , 1500rpm , 53CFM , 25.6dBA , 1.51mm-H2O - for selected chassis only
CH-LABS06	N	Lian-li BS-06 internal pci cooler - positioned on top of 7 pci slot , 1x140mm fan , 900rpm - for selected chassis only
CH-LABS09	N	Lian-li BS-09 external pci cooler - positioned outside of 3 pci slot , 1x140mm fan , 1180rpm - compatiable with most of case
FA-LBS08	N	Lian-li BS-08 internal pci fan card , aluminum - require 2 x pci slot , 2x120mm fan , 100rpm , pull hot air through expansion slot - compatiable with most of case
Zalman		
FA-ZSC100	C	Zalman ZM-SC100 pci Fan Card - , powered by pci slot , fan card with blue Led - 92x92x15mm , double ball-bearing , 3 level 1400-2300rpm , 25-39 dBa
FA-80ZoP1		Zalman ZM-OP1 80mm ultra slim fan + fan grill ; 80x80x15mm, 1400/2800rpm- as system fan or optional fan for zalman vga cooler ZM80C-HP/ZM80D-HP
FA-80ZF1P	N	Zalman ZM-F1 Plus - 80mm quiet fan : 1700/2800rpm , 20/32db - with anti-vibration silicone pin instead of screw
FA-80ZBL		Zalman ZM-F1BL 80mm Blue Led , 80x80x25mm , 1500-2500rpm , 20-35dBA , with anti-vibration silocone pins - 1 year warranty
FA-80ZGL		Zalman ZM-F1GL 80mm Green Led , 80x80x25mm , 1500-2500rpm , 20-35dBA , with anti-vibration silocone pins - 1 year warranty
FA-80ZRL		Zalman ZM-F1RL 80mm Red Led , 80x80x25mm , 1500-2500rpm , 20-35dBA , with anti-vibration silocone pins - 1 year warranty
FA-92ZF2		Zalman ZM-F2 92mm quiet fan : 1600/2800rpm , 20 / 36.1db
FA-92ZF2P	N	Zalman ZM-F2 Plus - 92mm quiet fan : 1500/2800rpm , 20/36db - with anti-vibration silicone pin instead of screw
FA-92Z123		Zalman FB123 92mm fan with adjustable extention bracket : 1600/2800rpm , 20 / 36db - can attach upto 3 fans (80 , 92 or 120mm)
FA-92ZBL		Zalman ZM-F2BL 92mm Blue Led , 92x92x25mm , 1500-2800rpm , 20-35dBA , with anti-vibration silocone pins - 1 year warranty
FA-92ZGL		Zalman ZM-F2GL 92mm Green Led , 92x92x25mm , 1500-2800rpm , 20-35dBA , with anti-vibration silocone pins - 1 year warranty
FA-92ZRL		Zalman ZM-F2RL 92mm Red Led , 92x92x25mm , 1500-2800rpm , 20-35dBA , with anti-vibration silocone pins - 1 year warranty
FA-120ZF3		Zalman ZM-F3 120mm quiet fan : 900/1800rpm , 20 / 34db - with silcon pin instead of screw
FA-120ZBL		Zalman ZM-F3BL 120mm Blue Led , 120x120x25mm , 1000-1800rpm , 20-32dBA , with anti-vibration silocone pins - 1 year warranty
FA-120ZGL		Zalman ZM-F3GL 120mm Green Led , 120x120x25mm , 1000-1800rpm , 20-32dBA , with anti-vibration silocone pins - 1 year warranty
FA-120ZRL		Zalman ZM-F3RL 120mm Red Led , 120x120x25mm , 1000-1800rpm , 20-32dBA , with anti-vibration silocone pins - 1 year warranty
Enermax		
FA-80EM		Enermax TC-8CAS-NL 80mm multi-color led fan with built-in fan speed control Knob - access fan speed control outside of the chassis , 80x80x25mm , sleeve , 900-1700rpm , 66.2CFM , 19.2-33.1dBA - 1 year warranty

FA-80EG		Enermax UC-8ABS-B 80mm fan with fan guard + built-in fan speed control Knob - access fan speed control outside of the chassis , 80x80x25mm , double ball bearing , 1200-2800rpm , 40.5CFM , 21-26dBA - 1 year warranty
FA-92EL		Enermax TC-9CAS-BL 92mm blue led fan with built-in fan speed control Knob - access fan speed control outside of the chassis , 92X92x25mm , sleeve , 1200-2500rpm , 43.3CFM max , 17-30.28dBA max - 1 year warranty
FA-92EW		Enermax Warp series 92mm fan , UC-9AEBS-B , with auto-restart function (prevent system damage), with built-in fan speed control Knob - access fan speed control outside of the chassis , 80x80x25mm , enlobal bearing (magnetic-barometric design), 1000-2500rpm , 9-49.8CFM , 15-32dBA - 1 year warranty
FA-120EM		Enermax TC-12CAS-NL 120mm multi-color led fan with built-in fan speed control Knob - access fan speed control outside of the chassis , 120x120x25mm , sleeve , 900-1700rpm , 66.2CFM , 19.2-33.1dBA - 1 year warranty
Vizo / Vantec		
FA-VFCPS	N	ViZO PCL-101 Fan Card Propeller Single - fan card with blue UV Led - 65x65x15mm , 1500rpm , 5.34 CFM , 20 dBa - pull hot air out through expansion slot
FA-VFCPD		ViZO PCL-201 Fan Card Propeller Dual - fan card with blue UV Led , adjustable fan speed - 70x70x15mm x2 , 2700-4800rpm , 20-36.5 CFM , 30.7-45 dBa - to be use on Pci / Pci-E / AGP slot
FA-60VTF		vantec 60mm thermoflow TF6025 + temp. sensor , 60x60x25mm , double ball bearing , 1900/4200rpm , 9.9/24.2 CFM, 19/33.5dBA - 1 year warranty
FA-80VUo		vantec 80mm sp8025uv-OR spectrum UV fan - Orange , 80x80x25mm , 2900rpm , 39CFM , 34dBA - 1 year warranty
FA-80VUG		vantec 80mm sp8025uv-GR spectrum UV fan - Green , 80x80x25mm , 2900rpm , 39CFM , 34dBA - 1 year warranty
FA-80VLL		vizo 80mm sp80uvled-BL UV+Led fan - bLue , 80x80x25mm , 2900rpm , 36CFM , 34dBA - 1 year warranty
FA-80VLG		vizo 80mm sp80uvled-GR UV+Led fan - Green, 80x80x25mm , 2900rpm , 36CFM , 34dBA - 1 year warranty
FA-80VLo		vizo 80mm sp80uvled-OR UV+Led fan - Orange, 80x80x25mm , 2900rpm , 36CFM , 34dBA - 1 year warranty
FA-80VLGo		vizo/vantec 80mm sp80uvled-GO UV+Led fan - Green+Orange, 80x80x25mm , 2900rpm , 36CFM , 34dBA - 1 year warranty
FA-80VLLG		vizo 80mm sp80uvled-BG UV+Led fan - bLue+Green , 80x80x25mm , 2900rpm , 36CFM , 34dBA - 1 year warranty
FA-80VSM	N	Vizo Super Muffle SF8025 , ultra quiet with magnetic long-life bearing , 80x80x25mm , 1500rpm , 24.5CFM , 17dBA - 1 year warranty
FA-80VS	N	Vantec Stealth SF8025L , ultra quiet with double ball bearing , 80x80x25mm , 2050rpm , 27CFM , 21dBA - 1 year warranty
FA-80VF	N	Vizo Freezer FZ8025 + temp. sensor , with magnetic long-life bearing , 80x80x25mm , 1900/3000rpm, 28.5/44.3 CFM, 20.5/34.5dBA - 1 year warranty
FA-92VLGo		vantec 92mm sp92uvled-Go UV+Led fan - Green+Orange , 92x92x25mm , 2600rpm , 46CFM , 33dBA - 1 year warranty
FA-92VLG		vantec 92mm sp92uvled-GR UV+Led fan - Green , 92x92x25mm , 2600rpm , 46CFM , 33dBA - 1 year warranty
FA-92VLLG		vantec 92mm sp92uvled-BG UV+Led fan - bLue+Green , 92x92x25mm , 2600rpm , 46CFM , 33dBA - 1 year warranty
FA-92VLo		vantec 92mm sp92uvled-OR UV+Led fan - Orange , 92x92x25mm , 2600rpm , 46CFM , 33dBA - 1 year warranty
FA-92VS	N	Vantec Stealth SF9225L , ultra quiet with double ball bearing , 92x92x25mm , 1750rpm , 28CFM , 20dBA - 1 year warranty

FA-92VTF		vantec 92mm thermoflow TF9225 + temp. sensor, 92x92x25mm, double ball bearing, 1850/3100rpm, 34.8/58.5 CFM, 34.8/58.5dBA- 1 year warranty
FA-92VW	N	Vizo 92mm Windstorm WS9238h , 92x92x38mm , double ball bearing , 4800rpm , 110CFM, 55dBA - 1 year warranty
FA-120VLL		vizo 120mm sp12uvled-BL UV+Led fan - bLue , 120x120x25mm , 1800rpm , 63CFM , 31dBA - 1 year warranty
FA-120VLo		vizo 120mm sp12uvled-OR UV+Led fan - Orange , 120x120x25mm , 1800rpm , 63CFM , 31dBA - 1 year warranty
FA-120VLG		vizo 120mm sp12uvled-GR UV+Led fan - Green , 120x120x25mm , 1800rpm , 63CFM , 31dBA - 1 year warranty
FA-120VLLG		vizo 120mm sp12uvled-BG UV+Led fan - bLue+Green , 120x120x25mm , 1800rpm , 63CFM , 31dBA - 1 year warranty
FA-120VLGo		vizo 120mm sp12uvled-Go UV+Led fan - Green+Orange , 120x120x25mm , 1800rpm , 63CFM , 31dBA - 1 year warranty
FA-120VSM	N	Vizo Super Muffle SF12025 , ultra quiet with magnetic long-life bearing, 120x120x25mm, 1200rpm, 38.4CFM, 17dBA - 1 year warranty
FA-120VS	N	Vantec Stealth SF12025L , ultra quiet with double ball bearing , 120x120x25mm , 1500rpm , 53CFM , 28dBA - 1 year warranty
FA-120VF	N	Vizo Freezer FZ12025 + temp. sensor , with magnetic long-life bearing , 120x120x25mm , 1350/2100rpm, 43.5/64.3 CFM, 20/32.5dBA - 1 year warranty
Coolermaster		
FA-80CLL		Coolermaster neon led fan , TLF-S82-EB uv+Led bLue - 80x80x25mm , sleeve bearing , 1800rpm , 22.84CFM , 22dBA - 1 year warranty
FA-80CLLx2		Coolermaster , R4-L8S-182b-GB , 80mm bLue led fan x 2 (twin pack) - 80x80x25mm , sleeve bearing , 1800rpm , 17.16CFM , 21dBA - 1 year warranty
FA-80CLG		Coolermaster neon led fan TLF-S82-EG uv+Led Green - 80x80x25mm , sleeve bearing , 1800rpm , 22.84CFM , 22dBA - 1 year warranty
FA-80CP		Coolermaster R4-P8B-25AK , Pwm fan - 80x80x25mm , ball bearing , 900-2500rpm , 28.77CFM , 12.84dBA - 1 year warranty
FA-80Cx6		Coolermaster SAF-S83-E1 , 6 pack , sleeve bearing - 80x80x25mm , 2000rpm , 28.89CFM , 24.4dBA - 1 year warranty
FA-92CP		Coolermaster P9B-22AK-GP pwn fan - 92x92x25mm , 850-2250rpm , 39.3CFM , 11.95dBA - 1 year warranty
FA-120CLR	N	Coolermaster neon led fan , TLF-S12-ER uv+Led Red- 120x120x25mm , sleeve bearing , 1220rpm , 42.73CFM , 22dBA - 1 year warranty
FA-120CLL		Coolermaster neon led fan , TLF-S12-EB uv+Led bLue - 120x120x25mm , sleeve bearing , 1220rpm , 42.73CFM , 22dBA - 1 year warranty
FA-120CLLx2		Coolermaster 120mm bLue led fan x 2 (twin pack) , R4-L2S-122B - 120x120x25mm , sleeve bearing , 1200rpm , 39.77CFM , 19.3dBA - 1 year warranty
FA-120CLG		Coolermaster neon led fan , TLF-S12-EG uv+Led Green - 120x120x25mm , sleeve bearing , 1220rpm , 42.73CFM , 22dBA - 1 year warranty
FA-120CP		Coolermaster R4-P2B-12AK , Pwm fan - 120x120x25mm , ball bearing , 900-1200rpm , 44CFM , 13.8dBA - 1 year warranty
FA-120CBx4	N	Coolermaster R4-S2B-124K-GP , 120mm fan x 4 (quad pack) - 120x120x25mm , double Ball bearing , 1200rpm , 44.03CFM , 19.8dBA - 1 year warranty
FA-140CK	N	Coolermaster R4-S4S-10AK , silent fan - 140x140x25mm , sleeve bearing , 1000rpm , 60.9CFM , 16dBA - 1 year warranty

FA-140CL	N	Coolermaster led fan , R4-L4S-10AB-GP , uv+Led bLue , 140x140x25mm , sleeve bearing , 1000rpm , 60.9CFM , 16dBA - 1 year warranty
FA-200CL	C	Coolermaster megaflow led fan , R4-LUS-07AB-GP , uv+ bLue led , 200x200x30mm , sleeve bearing , 700rpm , 110CFM , 19dBA - 1 year warranty
FA-200CR	C	Coolermaster megaflow led fan , R4-LUS-07AR-GP , uv+ Red led , 200x200x30mm , sleeve bearing , 700rpm , 110CFM , 19dBA - 1 year warranty

Antec

FA-ASCB	antec supercyclone blower - 3 level fan speed , take 2 expansion slot , pull hot air through expansion slot -1500 / 2000 / 2600rpm , 20 / 24.5 / 37.5 CFM , 24 / 32 / 39 dBA - 3 years warranty
FA-AVC	antec VCool with Blue LED + Extension duct - 3 level fan speed , take 2 expansion slot , pull hot air out through expansion slot -2500 / 3000 / 3500rpm , 11.5 / 13.6 / 15.9 CFM , 29.3 / 35.5 / 37 dBA - 3 years warranty
FA-ASC	Antec Spot Cool with Blue LED , mounted onto motherboard/chassis standard screw mounting , flexabile and angle adjustable for any place on the motherboard area - 3 level fan speed -2000 / 2500 / 3000rpm , 15 / 18 / 22 CFM , 23 / 27 / 33 dBA
FA-40AK	antec 40x40x20mm , 2 ball bearing, 4550rpm, 28dba - for antec 1u rackmount , minuet case … etc
FA-80AUo	antec 80 mm UV fan - Orange : 80x80x25mm , double ball bearing , 2600rpm , 34CFM , 30dba - 3 years warranty
FA-80ALL	antec 80mm LED fan - bLue , 3 x Led : 80x80x25mm , double ball bearing , 2600rpm , 34CFM , 30dba - 3 years warranty
FA-80ATC	antec 80mm TriCool Led - Clear(no color) : 3 speed switch (manual) , 80x80x25mm , double ball bearing , 1500/2000/2600rpm , 20/26/34 CFM , 18/24/30dba - 3 years warranty
FA-80ATCLG	antec 80mm TriCool Led - Green : 3 speed switch (manual) , 80x80x25mm , double ball bearing , 1500/2000/2600rpm , 20/26/34 CFM , 18/24/30dba - 3 years warranty
FA-80ATCLL	antec 80mm TriCool Led - bLue : 3 speed switch (manual) , 80x80x25mm , double ball bearing , 1500/2000/2600rpm , 20/26/34 CFM , 18/24/30dba - 3 years warranty
FA-80ATCLR	antec 80mm TriCool Led - Red : 3 speed switch (manual) , 80x80x25mm , double ball bearing , 1500/2000/2600rpm , 20/26/34 CFM , 18/24/30dba - 3 years warranty
FA-80ATT	antec 80mm TriCool Trilight (red+green+blue) : 3 speed switch (manual) , 80x80x25mm , double ball bearing , 1500/2000/2600rpm , 20/26/34 CFM , 18/24/30dba - 3 years warranty
FA-80ASC	antec 80mm SmartCool + temperature sensor; 1650~2850RPM, 24--41CFM, 21-34 dba; Double ball bearing - 3 years warranty
FA-92ATC	antec 92mm TriCool - clear (no color) ; double Ball Bearing; 3 speed switch (manual) , 92x92x25mm , double ball bearing , 1200/1600/2200rpm , 21/28/38 CFM , 14/21/27dba - 3 years warranty
FA-92ASC	antec 92mm SmartCool + temperature sensor ; 1450~2070 RPM, 28--40CFM, 23.5-31.2 dba; Double ball bearing
FA-120ATCLG	antec 120mm TriCool Led - Green ; 3 speed switch (manual) , 120x120x25mm , double ball bearing , 1200/1600/2000rpm , 39/56/79 CFM , 25/28/30dba - 3 years warranty

FA-120ATCLR		antec 120mm TriCool Led - Red ; 3 speed switch (manual) , 120x120x25mm , double ball bearing , 1200/1600/2000rpm , 39/56/79 CFM , 25/28/30dba - 3 years warranty
FA-120ATCLL		antec 120mm TriCool Led - bLue ; 3 speed switch (manual) , 120x120x25mm , double ball bearing , 1200/1600/2000rpm , 39/56/79 CFM , 25/28/30dba - 3 years warranty
FA-120ATC		antec 120mm TriCool Led - clear (no color) ; 3 speed switch (manual) , 120x120x25mm , double ball bearing , 1200/1600/2000rpm , 39/56/79 CFM , 25/28/30dba - 3 years warranty
FA-120ATT		antec 120mm TriCool Trilight (red+green+blue) ; 3 speed switch (manual) , 120x120x25mm , double ball bearing , 1200/1600/2000rpm , 39/56/79 CFM , 25/28/30dba - 3 years warranty
FA-120ASC		antec 120mm SmartCool + temperature sensor; 980~1720 RPM, 34-60CFM, 20-32 dba; Double ball bearing - 3 years warranty
FA-200ABB	N	antec 200mm Big-Boy - 3 speed switch (manual) ; 980~1720 RPM, 34-60CFM, 20-32 dba; Double ball bearing - 3 years warranty
Cpu Cooler		
Accessories		
CC-AATG		Antec Thermal Grease - silicone compounds , 3 packets , 3x1g
CC-AASTC		Antec Silver Thermal compound - thermal compound ; 99% pure micronized silver , 3.5g , 350,000 W/m²ºC , temperature limit : -50°C to 180°C
CC-ZATG2	N	Zalman ZM-TG2 Thermal Grease - non-curing compound , 6.5g , specific gravity : 2.60 ; thermal conductivity : 1.2W/mK
CC-ZASTG1		Zalman ZM-STG1 Super Thermal Grease - non-curing compound , 3.5g , specific gravity : 2.42 ; thermal conductivity : 4W/mK
CC-CAHTK002		Coolermaster HTK-002 thermal grease , specific gravity @ 25°C : 2.37 , thermal conductivity - watts/meter°C : 0.8 , thermal resistance°C-cm /W@40psi - 0.02
CC-CAPTK002		Coolermaster PTK-002 thermal grease , specific gravity @ 25°C : 2.63 , thermal conductivity - watts/meter°C : 4.5 , thermal resistance°C-cm /W@40psi - 0.02
CC-CANF		Coolermaster PTK-003 NanoFusion thermal grease , specific gravity @ 25°C : 3.25 , thermal conductivity , thermal resistance°C-cm /W@40psi - 0.065
CC-CAiF	N	Coolermaster IceFusion thermal grease , specific gravity @ 25°C : 2.5 , thermal conductivity - watts/meter°C : 1.0 - 40g
CC-CATF400	N	Coolermaster Thermal Fusion 400 thermal grease , specific gravity @ 25°C : 3.5 , thermal conductivity - watts/meter°C : 2.89 , thermal resistance°C-cm /W@40psi - 0.032 - 4g
CH-ZAFM2		Zalman Fan Mate2 - fan speed mini controller , 5-11V output to reduce fan speed and noise - 1 channel
CC-CA1366	N	coolermaster RR-ACC-1366-GP - LGA1366 clip support for V8, Hyper Z600, Hyper Z600R, Hyper N620, Hyper N520, Hyper 212, GeminII S, GeminII
CC-TA1366	N	Thermalright LGA1366 clip support for all Ultra series / HR-01 Plus / HR-01 4U / HR-01 3U / Ultima 90 / AXP140
CC-ZA1366	N	zalman ZM-CS4A - LGA1366 clip support for cnps9500 , cnps9700 series
CC-ZACS1		zalman ZM-CS1 LGA775 clip support for CNPS7000 - include thermal grease , clip support, clip support installation bolts , cooler installation bolts , 4 nipples , 1 set of Washers
CC-ZAoC1		zalman ZM-oC1 Optional Clip support for AMD AM2 , socket-F (1207) , socket-L1 (1207) - for all CNPS9500 series
CC-ZAEC1		Zalman ZM-EC1 - 720mm 3 pin power extension cable for cpu fan or system fan

PS-ZA43		Zalman ZM-MC1 - convert 4pin (5/12v from psu) to 3pin power connectors for cpu fan or system fan - retail pack
Vantec		
CC-VAF9225	N	vantec aeroflow fx92 vaf-9225 , copper base+ aluminum fin with 3x 8mm heatpipes , Fluid Magnetic Bearing 92mm PWM fan with vibration dampener, 1200-2800rpm , 39-54.6CFM , 23-35dba - for intel LGA478/775 , amd s754/939/940/AMx/socket-F(1207)
CC-VAF1225	N	vantec aeroflow fx120 vaf-1225 , copper base+ aluminum fin with 3x 8mm heatpipes , Fluid Magnetic Bearing 120mm PWM fan with vibration dampener , 1000-2200rpm , 72.1-99.6CFM , 20-32dba - for intel LGA478/775 , amd s754/939/940/AMx/socket-F(1207)
ASUS		
CC-AT85		Asus Triton 85 , 4 x copper heatpipe + copper base + aluminum fin , vapo bearing 2300rpm 120mm PWM fan , 49.04CFM , 22dBa - for intel LGA775 , AMD socket754/939/940/AMx/1207
CC-AAS		Asus Arctic Square , 4 x copper heatpipe + copper base + aluminum fin , vapo bearing 2300rpm 92mm PWM fan with blue led , 36.5CFM - for intel LGA775 , AMD socket754/939/940/AMx/1207
CC-ASSE		Asus Silent Square Evo , 5 x copper heatpipe + copper base + aluminum fin , vapo bearing 2300rpm 92mm PWM fan with blue led , 36.5CFM , 22dBa - for intel LGA775 , AMD socket754/939/940/AMx/1207
CC-ASK2		Asus Silent Knight 2 , 6 x copper heatpipe + copper base and fin , sleeve bearing 2300rpm 92mm fan fan with blue led , 52.25CFM , 25dBa - for intel LGA775 , AMD socket939/940/AMx/1207
Coolermaster		
CC-CXD4		Coolermaster X Dream 4 , aluminum , sleeve bearing 92mm fan , 2200rpm , 33.75CFM , 17dba - for intel LGA775
CC-CXDK640	N	Coolermaster X Dream K640 , RR-KIF-L9E1 , copper base+ aluminum fin , Rifle bearing 92mm fan , 800-2800rpm , 69.59CFM , 19.5dba - for amd s754/939/940/AMx/socket-F(1207)
CC-CV752	N	Coolermaster Vortex 752 RR-CCH-P911/2-GP , copper base+ aluminum fin with 2 heatpipes , sleeve bearing 92mm PWM fan , 800-2200rpm , 51.04CFM , 18dba - for intel LGA775 , amd s754/939/940/AMx/socket-F(1207)
CC-CHTX2		Coolermaster Hyper TX2 , RR-CCH-L9U1-GP , copper base+ aluminum fin with 3 heatpipes , sleeve bearing 92mm PWM fan , 1800rpm , 41.76CFM , 22dba - for intel LGA775 , amd s754/939/940/AMx/socket-F(1207)
CC-CGS		Coolermaster Geminll S , RR-CCH-PBJ1-GP , wide area cooling for both cpu + mb component , position adjustable fan bracket for upto 2 x fan , copper base+ aluminum fin with 5 heatpipes , 1 x sleeve bearing 120mm PWM fan support upto 2 x 80/92mm , 1000-2000rpm , 69.69CFM , 17-21dba - for intel 478/LGA775 , AMD s754/939/940/AMx/socket-F(1207)
CC-CG		Coolermaster Geminll , RR-CCH-ANU2-GP , wide area cooling for both cpu + mb component , position adjustable fan bracket for 2 x optional 120mm fan , copper base+ aluminum fin with 6 heatpipes - for intel 478/LGA775 , AMD s754/939/940/AMx/socket-F(1207)
CC-CH212	N	Coolermaster Hyper 212 , RR-CCH-LB12-GP , copper base+ aluminum fin with 4 heatpipes , 1 x 120mm blue-led fan support upto 2 , sleeve bearing , 2000rpm , 69.69CFM max. , 19dba - for intel LGA775 , AMD s754/939/940/AMx/socket-F(1207)

CC-CMS		Coolermaster CM Sphere , RR-CCZ-LL12-GP , pure copper (base+fin) with 4 heatpipes , gliding fan duct to cool surrounding component , sleeve bearing 68mm PWM fan with blue E-led , 2200rpm , 84.7CFM max. , 22dba - for intel LGA775 , AMD s754/939/940/AMx/socket-F(1207)
CC-CMSB		Coolermaster CM Sphere Black , RR-CCZ-LL11-GP , pure copper (base+fin) with 4 heatpipes , gliding fan duct to cool surrounding component , sleeve bearing 68mm PWM fan with blue E-led , 2200rpm , 84.7CFM max. , 22dba - for intel LGA775 , AMD s754/939/940/AMx/socket-F(1207)
CC-CHN520	N	Coolermaster Hyper N520 , RR-920-N520-GP , copper base+ aluminum fin with 5 heatpipes , 2 x 92mm blue-led pwm fan , sleeve bearing , 1800rpm , 43.8CFM, 19dba - for intel LGA775/1366 , AMD s754/940/AMx/socket-F(1207)
CC-CHZ600	N	Coolermaster Hyper Z600 , RR-600-NNU1-GP , copper base+ aluminum fin with 6 heatpipes , support upto 2 x optional fan - for intel LGA775 , AMD s940/AMx/socket-F(1207)
CC-CHN620	N	Coolermaster Hyper N620 , RR-B20-N620-GP , copper base+ aluminum fin with 6 heatpipes , 2 x 120mm blue-led pwm fan , rifle bearing , 800-2000rpm , 83.6CFM, 16-28dba - for intel LGA775/1366 , AMD s754/940/AMx/socket-F(1207)
CC-CV8		Coolermaster V8 , RR-UV8-XBU1-GP , copper base+ aluminum fin with 8 heatpipes , fan speed controller @ pci slot , rifle bearing 120mm PWM fan , 800-1800rpm , 69.69CFM max. , 17-21dba - for intel LGA775 , AMD s940/AMx/socket-F(1207)
CC-CV10	C	Coolermaster V10 , RR-B2P-UV10-GP , copper base+ aluminum fin with 10 heatpipes , 3 sets of heatsink modular , 2x rifle bearing 120mm PWM fan (1 with red led) , 800-2400rpm , 90CFM max. , 17-21dba - for intel LGA775/1366 , AMD s940/AMx/socket-F(1207)
Zalman		
CC-Z65BC		Zalman CNPS6500B-Cu : pure copper FHS + FB-123 (detached 92mm fan at desired location ; reducing fan vibration to the CPU) + fan mate2 , 1300/2500rpm , double ball bearing , noise 20/32db - for intel s478 p4
CC-Z70CAC	N	Zalman CNPS7000C-AlCu : support silent mode with no noise/vibration ; aluminum+copper FHS + 92mm fan + fan mate2 , 1350/2600rpm , double ball bearing , noise 18/27db - for Amd 754/939/940/AMx/1207 , Intel LGA775 cpu
CC-Z70CACL	N	Zalman CNPS7000C-AlCu Led : support silent mode with no noise/vibration ; aluminum+copper FHS + 92mm blue led fan + fan mate2 , 1350/2600rpm , double ball bearing , noise 18/27db - for Amd 754/939/940/AMx/1207 , Intel LGA775 cpu
CC-Z70BC		Zalman CNPS7000B-Cu : pure copper FHS + 92mm fan + fan mate2 , 1350/2600rpm , double ball bearing , noise 18/27db - for Amd 462/754/939/940 , Intel cpu (LGA775 p4 require CC-ZACS1 / ZM-CS1)
CC-Z70CC	N	Zalman CNPS7000C-Cu : support silent mode with no noise/vibration ; pure copper + 92mm fan + fan mate2 , 1350/2600rpm , double ball bearing , noise 18/27db - for Amd 754/939/940/AMx/1207 , Intel LGA775 cpu
CC-Z70BCL		Zalman CNPS7000B-Cu Led : pure copper FHS + 92mm blue led fan + fan mate2 : 1350/2600rpm , double ball bearing , noise 18/27db - for Amd 462/754/939/940 , Intel cpu (LGA775 p4 require CC-ZACS1 / ZM-CS1)
CC-Z70CCL	N	Zalman CNPS7000C-Cu Led : support silent mode with no noise/vibration ; pure copper + 92mm blue led fan + fan mate2 , 1350/2600rpm , double ball bearing , noise 18/27db - for Amd 754/939/940/AMx/1207 , Intel LGA775 cpu

CC-Z75ACoi		Zalman CNPS7500-AlCu Oem : aluminum+copper FHS + 110mm Fan : 1150/2300rpm , double ball bearing , noise 17/32db - for Intel cpu
CC-Z75ACL		Zalman CNPS7500-AlCu Led : aluminum+copper FHS + 110mm blue-led Fan + Fan mate2 : 1150/2300rpm , double ball bearing , noise 17/32db - for Amd 754/939/940/AMx , all Intel cpu
CC-Z75CL		Zalman CNPS7500-Cu Led : copper FHS + 110mm blue-led Fan + Fan mate2 : 1150/2300rpm , double ball bearing , noise 17/32db - for Amd 754/939/940/AMx , all Intel cpu
CC-Z77Aoi		Zalman CNPS7700-Al Oem pack for Intel lga775 : aluminum FHS + 120mm Fan : 1200/2200rpm , double ball bearing , noise 18/27db - for intel Lga775
CC-Z77ACoi		Zalman CNPS7700-AlCu Oem pack for Intel lga775 : aluminum+copper FHS + 120mm Fan : 1200/2200rpm , double ball bearing , noise 18/27db - for intel Lga775
CC-Z77AC		Zalman CNPS7700-AlCu : aluminum+copper FHS + 120mm Fan + Fan mate2 : 1200/2200rpm , double ball bearing , noise 18/27db - for Amd 754/939/940 , all Intel cpu
CC-Z77C		Zalman CNPS7700-Cu : pure copper FHS+ 120mm Fan+ Fan mate2 : 1000/2000rpm, double ball bearing, noise 20/32db - for Amd 754/939/940 , all Intel cpu
CC-Z80		Zalman CNPS8000 low profile cpu cooler : aluminum + 4 copper heatpipe + 92mm Fan + Fan mate2 : 1350/2600rpm , double ball bearing , noise 18/30db - for Amd 754/939/940 , intel LGA775 cpu
CC-Z87L		Zalman CNPS8700 Led low profile cpu cooler : 2 x copper heatpipe + 0.2mm ultra thin copper fin + 110mm bLue led Fan+ Fan mate2 : 1150-2300rpm , double ball bearing, noise 17.5/33db - for Amd 754/939/940/AMx/1207 , LGA775 Intel cpu
CC-Z87NT		Zalman CNPS8700NT low profile cpu cooler with with Nickel plate : 2 x copper heatpipe + 0.2mm ultra thin copper fin in silver color + 110mm bLue led PWM Fan : 1150-2100rpm , double ball bearing, noise 17.5/30db - for Amd 754/939/940/AMx/1207 , LGA775 Intel cpu
CC-Z93AT		Zalman CNPS9300AT : 407g light weight compact size , 3 x 8-shape bending design copper heatpipe with 0.2mm ultra thin copper fin , aero-dynamically tunnel , 92mm fan with PWM control + auto restart : 1500/2400rpm , superflo ball bearing , noise 20/30db - for Amd 754/939/940/AMx/1207 / intel LGA775
VC-ZVF2000L	C	Zalman VF2000-Led Hybrid cooler for VGA or CPU - low-profile , with fan mate2 - copper base + quad heat pipes + 0.3mm ultra slim aluminum fin, 8 x vga memory heatsink included , support silend/ normal mode ; 2 ball bearing 92mm fan with blue Led ; speed: 1400/ 2350 rpm ; noise level : 19/29dB , weight : 290g - support ati/nvidia vga or intel/amd cpu
CC-Z95o		Zalman CNPS9500 Oem pack - heatsink and fan only - require optional clip mounting for AM2/1207/LGA775 : 3 x 8-shape bending design copper heatpipe with 0.2mm ultra thin copper fin , aero-dynamically tunnel , 92mm fan : 1300/2600rpm , double ball bearing , noise 18/27.5db
CC-Z95ATo		Zalman CNPS9500AT Oem pack - heatsink and fan only - require optional clip mounting for AM2/1207/LGA775 : 3 x 8-shape bending design copper heatpipe with 0.2mm ultra thin copper fin , aero-dynamically tunnel , 92mm fan with PWM control + auto restart : 1300/2600rpm , double ball bearing , noise 18/27.5db

CC-Z95Lo		zalman CNPS9500LED Oem pack - heatsink and fan only - require optional clip mounting : 3 x 8-shape bending design copper heatpipe with 0.2mm ultra thin copper fin , aero-dynamically tunnel , 92mm opaque fan with blue led : 1300/2600rpm , double ball bearing , noise 18/27.5db
CC-Z95AT		Zalman CNPS9500AT : 3 x 8-shape bending design copper heatpipe with 0.2mm ultra thin copper fin , aero-dynamically tunnel , 92mm fan with PWM control + auto restart : 1300/2600rpm , double ball bearing , noise 18/27.5db - intel LGA775 / AMD AM2/1207 (AM2/1207 require ZM-oC1 optional clip support)
CC-Z95AM2		zalman CNPS9500-AM2 : 3 x 8-shape bending design copper heatpipe with 0.2mm ultra thin COPPER fin (in silver color) , aero-dynamically tunnel , 92mm opaque fan with green led + Fan mate2 : 1350/2600rpm , double ball bearing , noise 18/27.5db - for Amd 754/939/940/AMx/1207 / intel LGA775 (via optional clip)
CC-Z95AL	N	zalman CNPS9500A-LED : 3 x 8-shape bending design copper heatpipe with 0.2mm ultra thin copper fin , aero-dynamically tunnel , 92mm opaque fan with blue led + Fan mate2 : 1300/2600rpm , double ball bearing , noise 18/27.5db - for all Intel cpu ; Amd 754/939/940/AM2/1207
CC-Z97L		zalman CNPS9700LED : 3 x 8-shape bending design copper heatpipe with 0.2mm ultra thin copper fin , aero-dynamically tunnel , 110mm opaque fan with blue led + Fan mate2 + ZM-STG1 super thermal grease : 1250/2800rpm , double ball bearing , noise 18/27.5db - for Amd 754/939/940/AMx/1207 , LGA775 Intel cpu
CC-Z97NT		zalman CNPS9700-NT : 3 x 8-shape bending design copper heatpipe with 0.2mm ultra thin COPPER fin (in silver color) , aero-dynamically tunnel , 110mm opaque green led fan with PWM control + auto restart ; include ZM-STG1 super thermal grease : 1250/2800rpm , double ball bearing , noise 18/27.5db - for Amd 754/939/940/AMx/1207 , LGA775 Intel cpu
CC-Z99L	N	zalman CNPS9900LED : 6 x circle copper heatpipe with dual heatsink + with 0.2mm ultra thin copper fin , aero-dynamically tunnel with UV activated fan protection cover , 120mm opaque high-intensity blue-led fan with PWM control + auto restart ; include ZM-STG1 super thermal grease : 1000/2000rpm , double ball bearing , noise 19.5/38db - for Amd 754/939/940/AMx/1207 , LGA775/1366 Intel cpu
Thermalright		http://www.thermalright.com/product_default.htm
CC-THR013U	N	thermalright HR-01 3U , aluminum fins with 4 copper heatpipes to copper base ; for Amd AM2/1207 ; for intel xeon socket 603/604/771 , 110x60x110mm , 374g - heatsink only ; with clip for optional 60mm fan
CC-THR014U	N	thermalright HR-01 4U , aluminum fins with 4 copper heatpipes to copper base ; for Amd AM2/1207 ; for intel xeon socket 603/604/771 , 110x60x145mm , 489g - heatsink only ; with clip for optional 92mm fan
CC-THR01X		thermalright HR-01 X , aluminum fins with 6 copper heatpipes to copper base ; for intel xeon socket 603/604/771 , 110x60x159.5mm , 600g - heatsink only ; with clip for optional 120mm fan
CC-TiFX10		thermalright iFX-10 , backside cooler , aluminum fins with 2 copper heatpipes to copper base (to be mounted underneath the MB) ; for Amd 939/AM2/1207 ; intel LGA775 , 130g - heatsink only ; with clip for optional 80mm fan

CC-TXP120		thermalright XP-120 , aluminum fins with 5 copper heatpipes to copper base ; for Amd 754/939/940 , 110x125x63mm , 370g - heatsink only ; with clip for optional 120mm fan
CC-TSi128SE		thermalright Si-128SE , aluminum fins with 4 mega-sized 8mm copper heatpipes to copper base ; for Amd AM2/1207 ; intel LGA775 , 125x145x91.5mm , 510g - heatsink only ; with clip for optional 120mm fan
CC-THR01P		thermalright HR-01 Plus , aluminum fins with 6 copper heatpipes to copper base ; for Amd AM2/1207 ; intel LGA775 / LGA1366 via optional bracket , 110x60x159.5mm , 600g - heatsink only ; with clip for optional 120/140mm fan
CC-TU120X		thermalright Ultra-120 eXtreme , aluminum fins with 6 copper heatpipes to copper base ; for Amd AM2/1207 ; intel LGA775 / LGA1366 via optional bracket , 63.5x132x160.5mm , 790g - heatsink only ; with clip for optional 120mm fan
CC-TU120TB		thermalright Ultra-120 True Black , aluminum fins with 6 copper heatpipes to copper base ; for Amd AM2/1207 ; intel LGA775 / LGA1366 via optional bracket, 63.5x132x160.5mm , 790g - heatsink only ; with clip for optional 120mm fan
CC-TAXP140	N	thermalright AXP-140 , low-profile , aluminum fins with 6 mega-sized 8mm copper heatpipes to copper base ; for intel LGA775 / / LGA1366 via optional bracket , 145x147x70mm , 550g - heatsink only ; with clip for optional 120mm fan
CC-TiFX14		thermalright iFX-14 , tripple heatsink system , aluminum fins with 4 x mega-sized 8mm copper heatpipes to copper base (for cpu) + back-side dual copper heatpipe heatsink (to be mounted underneath the MB) ; for Amd AM2/1207 ; intel LGA775 , 790g+130g - heatsink only ; with clip for optional 2 x 120/140mm fan (for cpu heatsink) + 80mm fan (for back-side heatsink)
CC-TU120XAM2RT	N	thermalright Ultra-120 eXtreme AM2 RT , retail pack with FDB fan , aluminum fins with 6 copper heatpipes to copper base ; for AMD AM2/AM2+/1207 , 38x133x156mm , 790g , 120mm 1600rpm FDB fan
CC-TU120X775RT	N	thermalright Ultra-120 eXtreme 775 RT , retail pack with FDB fan , aluminum fins with 6 copper heatpipes to copper base ; for intel LGA775 , 38x133x156mm , 790g , 120mm 1600rpm FDB fan
CC-TU120X1366RT	N	thermalright Ultra-120 eXtreme 1366 RT , retail pack with FDB fan , aluminum fins with 6 copper heatpipes to copper base ; for intel LGA1366 , 38x133x156mm , 790g , 120mm 1600rpm FDB fan
CC-TU120TC	N	thermalright Ultra-120 True Copper , copper fins with 6 copper heatpipes ; for Amd AM2/1207 ; intel LGA775 / LGA1366 via optional bracket , 38x133x156mm , 1900g - heatsink only ; with clip for optional 120mm fan

Water Cooling

Coolermaster

WC-CADV		Coolermaster Aquagate Duo Viva , RL-M4A-E7E3-GP , with internal aluminum radiator for 3.5" , 5.25" , side panel or pci slot (175x75x44mm + 2x70mm 1000~4800 RPM fan) + Dual copper-based water block for vga or SLi/crossfire ; noise level : 20-37.7dBa , 33.948CFM , blue coolant - cpu support AMD 754/939/940/AM2/F/1207 ; VGA support upto 8800GTS / HD3870

WC-CAM		Coolermaster Aquagate Max , nVidia ESA ready , front display (2 x 5.25" bay) for water level+water flow , internal aluminum radiator for 2 x 5.25" bay (300x142x71mm + 2 x 120mm 850-2400rpm green Led fan) , 1 x cpu water block ; noise level : 22dBa , 71.81CFM , green coolant ; for Intel LGA775 + all AMD 754/939/940/AM2/F/1207 cpu
WC-CAG9200		Coolermaster RL-VNA-FNU2-GP Glacier 9200 vga water block , aluminum - for nVidia geforece 8800GT/8800GTS , 197x125x13.8mm
WC-CANC1B		Coolermaster RL-ACL-NNUB-GP Aquagate NC-1 Blue coolant
WC-CANC1G		Coolermaster RL-ACL-NNUG-GP Aquagate NC-1 Green coolant
Zalman		
WC-ZRP		Zalman Reserator 1 Plus , BLACK - fanless water cooling , with external anodized aluminum radiator + ZM- WB3 Gold (cpu water block) + ZM-GWB2 (vga water block) , support optional vga memory + northbridge waterblock , blue coolant ; for Intel s478/LGA775 + AMD 754/939/940 cpu
WC-ZR1V2		Zalman Reserator 1 V2 , silver - fanless water cooling , with external anodized aluminum radiator + ZM- WB4 Gold (cpu water block) + ZM-GWB3 (vga water block) , support optional vga memory + northbridge waterblock , blue coolant ; for Intel s478/LGA775 + AMD 754/939/940 cpu
WC-ZR2		Zalman Reserator 2 - fanless water cooling , with external anodized aluminum radiator + ZM- WB4 Gold (cpu water block) + ZM-GWB3 (vga water block) , support optional vga memory + northbridge waterblock , blue coolant ; for Intel s478/LGA775 + AMD 754/939/940/AM2/F/1207 cpu
WC-ZRXTB		Zalman Reserator XT , Black , fanless water cooling - external anodized aluminum radiator , automatic/manual control modes with control knob , dual Analog Gage (for fan speed + flowrate) , FND Display (internal temperature, water temperature, water level and mode) , active/passive hybrid Cooling Design , 140mm fan , warning & alarm system for coolant flow + coolant level monitoring , with ZM- WB5 (cpu water block) , support optional vga memory + northbridge waterblock , blue coolant ; Compatible CPUs - Intel (Socket 478, 775), - AMD (Socket A462/754/939/940/AM2)
WC-ZRXTS		Zalman Reserator XT , Silver , fanless water cooling - external anodized aluminum radiator , automatic/manual control modes with control knob , dual Analog Gage (for fan speed + flowrate) , FND Display (internal temperature, water temperature, water level and mode) , active/passive hybrid Cooling Design , 140mm fan , warning & alarm system for coolant flow + coolant level monitoring , with ZM- WB5 (cpu water block) , support optional vga memory + northbridge waterblock , blue coolant ; Compatible CPUs - Intel (Socket 478, 775), - AMD (Socket A462/754/939/940/AM2)
CH-ZLQ1000	N	Zalman LQ1000 chassis , No psu , built-in watercooling system (automatic/manual control modes with control knob , dual Analog Gage for fan speed + flowrate , FND Display (internal temperature, water temperature, water level and mode) , cpu water block included + optional vga , northbridge waterblock , passive heatsink side panel (screwless) , 5mm anodized aluminum , 2 front usb + ieee1394 + audio in/out ; 4x 5.25", 1x 3.5", 5x internal 3.5" (tool free) ; 1 x 220mm fan with blue led (550-850rpm) - for atx
WC-ZARF1		Zalman ZM-RF1 add-on fan duct for Reserator 1 Plus / V2 - 140x140x25mm fan with blue Led + fan-mate2
WC-ZAG200		Zalman ZM-G200 - Anti-corrosion coolant , 500ml

WC-ZAWB5		Zalman ZM-WB5 - CPU water block , pure copper , silver , 160g - for intel 775 , AMD 754/939/940/AM2/1207
WC-ZAWB5P	N	Zalman ZM-WB5 Plus - CPU water block , pure copper , silver , 154g - for intel 775/1366 , AMD 754/939/940/AMx/1207
WC-ZANWB1		Zalman ZM-NWB1 - water block for north bridge , anodized aluminum , 43x30.5mm , 48g
WC-ZARWB1		Zalman ZM-RWB1 - water block for VGA RAM (memory) , anodized aluminum , to work with ZM-GWB3 VGA water block - only compatiable with ATi X1800 and up / nForce 7800 and up (except 7800GS / 7950GX2)
WC-ZAGWB3		Zalman ZM-GWB3 - additional water block for SLi VGA , anodized aluminum , 60x60x30mm - don't support nvidia 6600agp/7800GS + ati 9550 / 9600
WC-ZAGWB88GTS		Zalman ZM-GWB8800 GTS - water block for nVidia geforece 8800GTS GPU, RAM, FET, i/o , dimple-type processing technology for light weight , anodized aluminum , 93x183x31mm
WC-ZAGWB88GTX		Zalman ZM-GWB8800 Ultra/GTX - water block for nVidia geforece 8800GTX GPU, RAM, FET, i/o , dimple-type processing technology for light weight , anodized aluminum , 93x183x31mm
WC-ZAGWB88G92	N	Zalman ZM-GWB8800GT/GTS(G92) - water block for nVidia geforece G92 - 8800GT/8800GTS 512mb GPU, RAM, FET, i/o , dimple-type processing technology for light weight , anodized aluminum , 93x183x31mm
WC-ZAGWB38	N	Zalman ZM-GWB38050/3870 - water block for Ati HD3850 / HD3870 GPU, RAM, FET, i/o , dimple-type processing technology for light weight , anodized aluminum , 85x117x31mm
HDD Cooler		
Vantec		
HC-V3502		vantec hcp-3502a - plastic , 2 x 3800rpm 60mm fan , 28cfm - for 3.5" HDD in 3.5" bay
HC-V5252		vantec hcp-5252a - plastic , 2 x 3800rpm 60mm fan , 28cfm - for 3.5" HDD in 5.25" bay
HC-VV2		Vizo Voyager 2 , HCL-102 - 1 fan hdd cooler , silver , 2900rpm 50mm fan , 13.1cfm , 22.5dBA - for 3.5" HDD in 3.25" bay
HC-V701K		vantec iceberq HDC-701A-bK hdd cooler - blacK ; 2800rpm 70mm fan , 22.3 cfm , 26dBA , 26 dbafor 3.5" HDD in 3.5" bay
HC-Vo		Vizo Orbiter HCL-101 - 1 fan hdd cooler with blue E-LED , 3200rpm 60mm fan , 11.6cfm , 20dBAfor 3.5" HDD in 3.5" bay
HC-VV	N	Vizo Voyager HCL-201 - 2 fan hdd cooler , silver , 2 x 4000rpm 50mm fan , 9.21cfm , 23.19dBAfor 3.5" HDD in 3.5" bay
HC-VV2S		vantec vortex2 hard drive cooling system - silver ; easy access air flter + fan speed contrl knob , adjustable fan speed 0~3700rpm crossflow blower , 0~30cfm , 0~38dba , with rubber dampeners - for 3.5" HDD in 5.25" bay
HC-VVS	N	vantec vortex vtx-c01-sL hard drive cooling system - silver ; Lcd + 3 filters + 3 levels adjustable 2000~3700rpm crossflow blower , 16~30cfm , 26~38dba , with rubber dampeners - for 3.5" HDD in 5.25" bay
Zalman		
HC-ZHC		zalman ZM-2HC2, HDD cooler; fanless HDD cooler ; aluminum + copper, with rubber dampeners - for 5.25" bay or in the case
VGA Cooler		
Vantec		
VC-VVP		Vantec iceberq4 pro CCB-A4P vga cooler, 4 vga memory heatsink+ 6000rpm 45x45x10mm blue e-led ball bearing fan - for nvidia only
VC-VVP5		Vantec iceberq5 CCB-A5C , vga cooler, 8 copper vga memory heatsink , 2500rpm 60x60x12mm fan with blue e-led - - for nvidia or Ati

VC-VVP6		Vantec iceberq6 CCB-A6C , vga cooler, full copper heatsink , 2700rpm 45x45x15mm fan
Coolermaster		
VC-CCVG1		Coolermaster CoolViva G1 VGA cooler , RV-UAA-L6U1-GP , aluminum , 4 vga memory heatsink + 3300rpm 60x60x10mm blue e-led - sleeve bearing fan , noise level : 23dBa , 11.78CMF- support upto nvidia 8600gt , Ati HD2600
VC-CCVZ1		Coolermaster CoolViva Z1 VGA cooler RV-UCH-NNU1-GP , with reverse cool , RV-UCH-NNU1-GP ; copper base with 2 heatpipes ; fanless design ; support optional 80mm fan ; include 8 x vga memory heatsinks , 286g - support upto nvidia 8600GTS , Ati 1800XL
VC-CCVPSE		Coolermaster CoolViva Pro SE vga cooler , RV-UCH-P7U2-GP ; copper base with 3 heatpipes ; include 8 x vga memory heatsinks ; sleeve bearing 74mm fan ; speed: 1800 rpm ; noise level : 20dBa , 11CMF , 290g - support upto nvidia 8800GTS , Ati hd3870
Thermalright - please check website for compatiability list of vga cards		
VC-THR11		Thermalright HR-11 vga backside cooler (only for the back side of VGA card) , support 2 unit for SLi ; copper base + aluminum fin with 2 heatpipes , with memory heatsink ; fanless design ; support optional 80mm fan , 150g
VC-TV1U		Thermalright V1 Ultra vga cooler - reverse cool fanless VGA cooler (heatsink at the back of PCB , closer to cpu fan) ; copper base + aluminum fin with 3 heatpipes , with memory heatsink ; 1 x 80mm fan support upto 2 , 310g
VC-TV2		Thermalright V2 Ultra vga cooler - all copper with 4 heatpipes , with memory heatsink ; fanless design ; support optional 80mm fan , 290g - support upto nvidia 9800GTX / Ati x1900 / ATi HD4870
VC-THR03		Thermalright HR-03 (rev. a) vga cooler - copper base + aluminum fin with 4 heatpipes , with memory heatsink ; fanless design ; support optional 80/92mm fan , 350g , support upto nvidia 9800GTX / Ati x1900 / ATi HD4870
VC-THR03P		Thermalright HR-03 Plus vga cooler - copper base + aluminum fin with 6 heatpipes , with memory heatsink ; fanless design ; support optional 80/92mm fan , 410g - support upto nVidia 8800GTS/GTX/ULTRA
VC-THR03GT		Thermalright HR-03 GT vga cooler - double sided copper base (for front or reverse cool) , (SLi/Crossfire will require front + reverse cool) , aluminum fin with 6 heatpipes , with memory heatsink ; fanless design ; support optional 80/92mm fan , 410g - support upto nvidia 9800GTX / Ati x1900 / ATi HD4870
VC-THR03GTX	**N**	Thermalright HR-03 GTX vga cooler - double sided copper base (for front or reverse cool) , (SLi/Crossfire will require front + reverse cool) , aluminum fin with 6 heatpipes , with VRM/memory/HSi heatsink ; require optional 80/92mm fan , 410g - for nvidia GTX260 / GTX280 only
VC-TTRAD2	**N**	Thermalright T-RAD2 - 25mm ultra slim vga cooler designed for SLi or Crossfire - double sided copper base (for front or reverse cool) , (SLi/Crossfire will require front + reverse cool) , aluminum fin with 6 copper heatpipes , with memory heatsink ; fanless design ; support optional 2x92 or 1x120mm fan , 410g - support upto nvidia9800GTX / Ati HD4870
Zalman		
VC-ZVM		zalman ZM-RHS1; VGA RAM heat sink; material: aluminum ; 4 (13x13x13mm) + 4 (13x13x6mm) vga memory heat sink
VC-ZRHS50	**N**	zalman ZM-RHS50 - FET (Field Effect Transistor) heat sink for ati 3850/4850 series

VC-ZRHS70	**N**	zalman ZM-RHS70 - FET (Field Effect Transistor) heat sink for ati 4870 series
VC-ZVHS1		zalman ZM-VHS1; VGA chipset heat sink - for nvidia GeForce 6600/6600GT AGP Series or chipset with 43mm heatsink mounting holes , ideal to user together with VF700 series vga cooler
VC-ZM80C		zalman ZM80C-HP; fanless VGA cooler; single copper heatpipes + aluminum heatsink ; fanless design ; support optional ZM-OP1 fan
VC-ZM80D		zalman ZM80D-HP; fanless VGA cooler; dual copper heatpipes + aluminum heatsink ; fanless design ; include 8 x vga memory heatsinks ; support optional ZM-OP1 fan
VC-ZVF902o		Zalman VF902-CU Oem pack - all copper fin + dual heat pipes with 120 x 0.2mm ultra slim copper fin , support silend/ normal mode ; 2 ball bearing 80mm fan ; speed: 2000rpm ; noise level : 18.5/28.5dB , weight : 170g - pls note : not to be used with Matrox , radeon 9600/9550series , nvidia 6600 agp
VC-ZVF7AC		zalman VF700 AlCu - aluminum + copper fin + 8 x vga memory heatsink included , support silend/ normal mode ; 2 ball bearing 80mm fan ; speed: 1350/ 2650 rpm ; noise level : 18.5/ 28.5dB , 180g - pls note : not to be used with Matrox
VC-ZVF7ACL		zalman VF700 AlCu Led - aluminum + copper fin + 8 x vga memory heatsink included , support silend/ normal mode ; 2 ball bearing 80mm fan with blue Led ; speed: 1350/ 2650 rpm ; noise level : 18.5/ 28.5dB , 180g - pls note : not to be used with Matrox
VC-ZVF7C		zalman VF700-Cu - all copper fin + 8 x vga memory heatsink included , support silend/ normal mode ; 2 ball bearing 80mm fan ; speed: 1350/ 2650 rpm ; noise level : 18.5/ 28.5dB , 270g - pls note : not to be used with Matrox
VC-ZVF7CL		zalman VF700-Cu Led - all copper fin + 8 x vga memory heatsink included , support silend/ normal mode ; 2 ball bearing 80mm fan with blue Led ; speed: 1350/ 2650 rpm ; noise level : 18.5/ 28.5dB , 270g - pls note : not to be used with Matrox
VC-ZVNF100		zalman VNF100 reverse cool fanless VGA cooler (heatsink at the back of PCB , closer to cpu fan) ; tripple copper heatpipes + 0.4mm thin aluminum heatsink ; fanless design ; include 8 x vga memory heatsinks
VC-ZVF900o		Zalman VF900-CU Oem pack - all copper fin + dual heat pipes with 162 x 0.2mm ultra slim copper fin , support silend/ normal mode ; 2 ball bearing 80mm fan ; speed: 2000 rpm ; noise level : 18.5/25dB , weight : 187g - pls note : not to be used with Matrox , radeon 9600/9550series , nvidia 6600 agp
VC-ZVF900		Zalman VF900-CU + fan mate2 - all copper fin + dual heat pipes with 162 x 0.2mm ultra slim copper fin , 8 x vga memory heatsink included , support silend/ normal mode ; 2 ball bearing 80mm fan ; speed: 1350/ 2400 rpm ; noise level : 18.5/25dB , weight : 187g - pls note : not to be used with Matrox , radeon 9600/9550series , nvidia 6600 agp
VC-ZVF900L	**N**	Zalman VF900-CU Led + fan mate2 - all copper fin + dual heat pipes with 162 x 0.2mm ultra slim copper fin , 8 x vga memory heatsink included , support silend/ normal mode ; 2 ball bearing 80mm fan ; speed: 1350/ 2400 rpm ; noise level : 18.5/25dB , weight : 187g - pls note : not to be used with Matrox , radeon 9600/9550series , nvidia 6600 agp

VC-ZVF2000L	C	Zalman VF2000-Led Hybrid cooler for VGA or CPU - low-profile , with fan mate2 - copper base + quad heat pipes + 0.3mm ultra slim aluminum fin, 8 x vga memory heatsink included , support silend/ normal mode ; 2 ball bearing 92mm fan with blue Led ; speed: 1400/ 2350 rpm ; noise level : 19/29dB , weight : 290g - support ati/nvidia vga or intel/amd cpu
VC-ZVF1000L		Zalman VF1000-Led + fan mate2 - all copper fin + quad heat pipes with 0.3mm ultra slim copper fin with blue E-LED , 8 x vga memory heatsink included , support silend/ normal mode ; 2 ball bearing 80mm fan with blue Led ; speed: 1400/ 2500 rpm ; noise level : 18/28dB , weight : 380g - support upto 8800 series when using ZM-RHS88
VC-ZGV1000R	N	Zalman GV1000 with Red led + fan mate2 - all copper fin in silver color + quad heat pipes with 0.3mm ultra slim copper fin with red E-LED , 8 x vga memory heatsink included , support silend/ normal mode ; 2 ball bearing 80mm fan with Red Led ; speed: 1650/ 3600 rpm ; noise level : 20/36dB , weight : 380g - support upto 8800 series when using ZM-RHS88
VC-ZRHS88		zalman ZM-RHS88; VGA chipset+memory heatsink - for nvidia GeForce 8800GTS/GTX/Ultra - to be used only together with VF1000-Led vga cooler
Memory Cooler		
MC-VMA		vizo DDR-ALM SDR/DDR/DDR2 memory heat spreader - Aluminum
MC-VMAT	N	vizo DDR-ALM-TW SDR/DDR/DDR2 memory heat spreader - Aluminum - Twin pack
MC-VMC		Vizo DDR-CPR SDR/DDR/DDR2 memory heat spreader - Copper
MC-VMCT	N	vizo DDR-CPR-TW SDR/DDR/DDR2 memory heat spreader , Copper - Twin pack
MC-V201	N	Vizo armada 2 RCL-201 dual-fan memory cooler with blue led , for SDR/DDR/DDR2 , 2 x 40x40mm blue led fan , 4500rpm , 20dbn , 13.86x2 CFM
MC-V301		Vizo armada RCL-301 tri-fan memory cooler with blue led , for SDR/DDR/DDR2 , 3 x 40x40mm blue led fan , 4500rpm , 27.98dbn , 13.86x3 CFM
MC-CMXAF1		Corsair CMXAF1 memory cooler with 3 x 40x40mm fan - with extra height - ideal for Corsair Dominator memory
MC-THR07		Thermalright HR-07 - memory cooler , 150x27x86mm - copper heatsink + 2 copper heatpipes - 150g , support optional 72/80/92mm fan
MC-THR07DL		Thermalright HR-07 Duo type-H - Dual Highrise memory cooler , 128x19x85.28mm - copper heatsink + 2x2 copper heatpipes
MC-THR07DH		Thermalright HR-07 Duo type-L - Dual Low-rise memory cooler , 128x19x56.28mm - copper heatsink + 2x2 copper heatpipes
Other Cooler		
oC-ViCA		vizo nbc-101-alu , Copper chipset or vga cooling kit with 40mm fan , 5600rpm , 51.2x59x14.2mm
oC-ViCC		vizo nbc-101-cpr , Copper chipset or vga cooling kit with 40mm fan , 5600rpm , 51.2x59x14.2mm
oC-ZN4		zalman ZM-NB47J, north bridge heat sink - aluminum ; 37x37x47mm; weight 54g
oC-ZN4F		zalman ZM-NBF47 , north bridge heat sink , flower type - aluminum ; 81x37x47mm; weight 57g
oC-CBiP		Coolermaster Blue Ice Pro , RT-NCW-L4E1 , north bridge cooler , copper heatsink : 43x43x30mm , 40mm 4500rpm fan with blue-led , 4.5CFM , 22-26dBa , weight 90g
oC-CBi		Coolermaster CM Blue Ice , RT-UCL-L4U1 , north bridge cooler , copper base + copper heatpipe + aluminum fin : 60x47x69mm , 40mm 4500rpm fan with blue-led , 4.5CFM , 22-26dBa , weight 90g

oC-THR09U		Thermalright HR-09U Type1 , Upright MoSFET heatsink - copper base + aluminum fin ; 84x32x48mm ; weight 90g - pls check website for compatibility mb list
oC-THR09S		Thermalright HR-09S Type1 , Slant MoSFET heatsink - copper base + aluminum fin ; 84x32x48mm ; weight 90g - pls check website for compatibility mb list
oC-THR09UT2		Thermalright HR-09U Type2 , Upright MoSFET heatsink - copper base + aluminum fin ; 84x17x48mm ; weight 90g - pls check website for compatibility mb list
oC-THR09ST2		Thermalright HR-09S Type2 , Slant MoSFET heatsink - copper base + aluminum fin ; 84x32.3x48mm ; weight 90g - pls check website for compatibility mb list
oC-THR09T4	N	Thermalright HR-09U Type4 , Upright MoSFET heatsink , IFX designed fins with 6mm heatpipe , copper base + aluminum fin ; 61x12x44.25mm ; weight 45g - pls check website for compatibility mb list
oC-THR05		Thermalright HR-05 , chipset heatsink - copper base + 2 copper heatpipes + aluminum fin ; 78x30x105mm , weight 145g - support optional 80mm fan
oC-THR05i		Thermalright HR-05-ifx , chipset heatsink - copper base + 2 copper heatpipes + aluminum fin ; 85x30x105mm , weight 110g - support optional 80mm fan
oC-THR05S		Thermalright HR-05-Sli , chipset heatsink - copper base + 2 copper heatpipes + aluminum fin ; 78x62x105mm , weight 124g - support optional 80mm fan
oC-THR05Si		Thermalright HR-05 Sli/ifx , chipset heatsink , L-shape design with extra space to support upto SLi - copper base + 2 copper heatpipes + aluminum fin ; 87x62x105mm , weight 125g - support optional 80mm fan
Chassis cable		
Floppy Rounded Cable		
CA-VF10L		vantec 25cm (10") rounded fdd cable with pull tab - 2 connectors - Blue pvc pipe
CA-VF10R		vantec 25cm (10") rounded fdd cable with pull tab - 2 connectors - Red pvc pipe
CA-VF10Y		vantec 25cm (10") rounded fdd cable with pull tab - 2 connectors - yellow pvc pipe
CA-VF10S		vantec 25cm (10") rounded fdd cable with pull tab - 2 connectors - clear pvc with silver braid
CA-VF18R		vantec 45cm (18") rounded fdd cable with pull tab - 2 connectors - red pvc pipe
CA-VF18Y		vantec 45cm (18") rounded fdd cable with pull tab - 2 connectors - yellow pvc pipe
CA-VF18S		vantec 45cm (18") rounded fdd cable with pull tab - 2 connectors - clear pvc with silver braid
CA-VF18C		vantec 45cm (18") rounded fdd cable with pull tab - 2 connectors - clear pvc with copper braid
CA-VF18F		vantec 45cm (18") rounded fdd cable with pull tab - 2 connectors - fluorescent pvc with silver braid
IDE Rounded Cable		
CA-Vi10Y2		vantec 25cm (10") rounded ata133 ide cable with pull tab - Yellow pvc pipe - 2 connectors only
CA-Vi10R2		vantec 25cm (10") rounded ata133 ide cable with pull tab - Red pvc pipe - 2 connectors only
CA-Vi10K2		vantec 25cm (10") rounded ata133 ide cable with pull tab - blacK pvc pipe - 2 connectors only
CA-Vi10L2		vantec 25cm (10") rounded ata133 ide cable with pull tab - bLue pvc pipe - 2 connectors only

CA-Vi10C2	vantec 25cm (10") rounded ata133 ide cable with pull tab - clear pvc with Copper braid - 2 connectors only
CA-Vi10S2	vantec 25cm (10") rounded ata133 ide cable with pull tab - clear pvc with Silver braid - 2 connectors only
CA-Vi10F2	vantec 25cm (10") rounded ata133 ide cable with pull tab - fluorescent pvc with silver braid - 2 connectors only
CA-Vi18Y2	vantec 45cm (18") rounded ata133 ide cable with pull tab - Yellow pvc pipe - 2 connectors only
CA-Vi18K2	vantec 45cm (18") rounded ata133 ide cable with pull tab - blacK pvc pipe - 2 connectors only
CA-Vi18L2	vantec 45cm (18") rounded ata133 ide cable with pull tab - bLue pvc pipe - 2 connectors only
CA-Vi18R2	vantec 45cm (18") rounded ata133 ide cable with pull tab - Red pvc pipe - 2 connectors only
CA-Vi18S2	vantec 45cm (18") rounded ata133 ide cable with pull tab - clear pvc with Silver braid - 2 connectors only
CA-Vi18F2	vantec 45cm (18") rounded ata133 ide cable with pull tab - fluorescent pvc with silver braid - 2 connectors only
CA-Vi18C2	vantec 45cm (18") rounded ata133 ide cable with pull tab - clear pvc with copper braid - 2 connectors only
CA-Vi18Y	vantec 45cm (18") rounded ata133 ide cable with pull tab - 3 connectors - yellow pvc pipe
CA-Vi18R	vantec 45cm (18") rounded ata133 ide cable with pull tab - 3 connectors - red pvc pipe
CA-Vi18F	vantec 45cm (18") rounded ata133 ide cable with pull tab - 3 connectors - fluorescent pvc with silver braid
CA-Vi18S	vantec 45cm (18") rounded ata133 ide cable with pull tab - 3 connectors - clear pvc with silver braid
CA-Vi18C	vantec 45cm (18") rounded ata133 ide cable with pull tab - 3 connectors - clear pvc with copper braid
CA-Vi24K2	vantec 60cm (24") rounded ata133 ide cable with pull tab - blacK pvc pipe - 2 connectors only
CA-Vi24R2	vantec 60cm (24") rounded ata133 ide cable with pull tab - Red pvc pipe - 2 connectors only
CA-Vi24Y2	vantec 60cm (24") rounded ata133 ide cable with pull tab - Yellow pvc pipe - 2 connectors only
CA-Vi24L2	vantec 60cm (24") rounded ata133 ide cable with pull tab - bLue pvc pipe - 2 connectors only
CA-Vi24F2	vantec 60cm (24") rounded ata133 ide cable with pull tab - fluorescent pvc with silver braid - 2 connectors only
CA-Vi24S2	vantec 60cm (24") rounded ata133 ide cable with pull tab - clear pvc with silver braid - 2 connectors only
CA-Vi24C2	vantec 60cm (24") rounded ata133 ide cable with pull tab - clear pvc with Copper braid - 2 connectors only
CA-Vi24Y	vantec 60cm (24") rounded ata133 ide cable with pull tab - 3 connectors - yellow pvc pipe
CA-Vi24R	vantec 60cm (24") rounded ata133 ide cable with pull tab - 3 connectors - red pvc pipe
CA-Vi24F	vantec 60cm (24") rounded ata133 ide cable with pull tab - 3 connectors - fluorescent pvc with silver braid
CA-Vi24C	vantec 60cm (24") rounded ata133 ide cable with pull tab - 3 connectors - clear pvc with copper braid
CA-Vi24S	vantec 60cm (24") rounded ata133 ide cable with pull tab - 3 connectors - clear pvc with silver braid
CA-Vi36Y	vantec 90cm (36") rounded ata133 ide cable with pull tab - 3 connectors - yellow pvc pipe
CA-Vi36S	vantec 90cm (36") rounded ata133 ide cable with pull tab - 3 connectors - clear pvc with silver braid

CA-Vi36F		vantec 90cm (36") rounded ata133 ide cable with pull tab - 3 connectors - fluorescent pvc with silver braid
CA-Vi36C		vantec 90cm (36") rounded ata133 ide cable with pull tab - 3 connectors - clear pvc with copper braid
S-ATA Cable		
CA-VS60L		Vizo SA-60 60cm (24") UV s-ata cable - bLue
CA-VS60Y		Vizo SA-60 60cm (24") UV s-ata cable - Yellow
CA-VS60G		Vizo SA-60 60cm (24") UV s-ata cable - Green
CA-VS60R		Vizo SA-60 60cm (24") UV s-ata cable - Red
CA-VSES		Vizo external SATA converter - from SATA on motherboard to External SATA in pci bracket - 30cm
CA-VSEES		Vizo external SATA converter - from SATA on motherboard to External E-SATA in pci bracket - 45cm
EE-iAH		Icydock Hybrid external e-SATA + ac power connector on pci bracket - from SATA on motherboard to External E-SATA + 4pin molex from psu to power connector - for icydock external enclosure
CA-VSESES		Vizo E-SATA to E-SATA cable - 100cm
CA-VSESES2	N	Vizo E-SATA to E-SATA cable - 200cm
CA-VSESEES		Vizo external SATA to external E-SATA cable - 100cm
Mobile Rack (internal swappable storage)		
Vi-Power		http://en.vipower.com/products01.php?CID=121&PageID=118
for IDE hdd		
MR-ViiL		Vi-Power VP-10LSFU-133 , ide to ide , Latchlock , 40mm fan - for 5.25"
MR-ViiLK		Vi-Power VP-10LSFU-133-black , ide to ide , Latchlock , 40mm fan , blacK - for 5.25"
MR-ViiL2T		Vi-Power VPQ-10LS2FU-133, ide to ide, Latch, 2 x 40mm Fan, Transparent with 3 color Led fan- for 5.25"; usb expansion capability
MR-ViiK2		Vi-Power VP-10KP2FU-133 , ide to ide , Keylock , 2 x 40mm fan - for 5.25" ; usb expansion capability
MR-ViiK2K		Vi-Power VP-10KP2FU-133-black , ide to ide , Keylock , 2 x 40mm fan , blacK - for 5.25" ; usb expansion capability
MR-ViUHL		Vi-Power VP-1028LSF , ide to Usb2.0 , Hotswapable , Latchlock , 40mm fan , No need to turn off pc - for 5.25"
MR-ViUHLB		Vi-Power VP-1028B , ide to Usb2.0, Hotswapable, Latchlock, 40mm fan with 1-touch button for Back-up / Restore , beige , no need to turn off pc ; with software to allow you to choose files, directories, source, destination ; ideal for pure backup , or backup on 1 pc and restore to another PC
MR-ViUHLBK		Vi-Power VP-1028B, ide to Usb2.0, Hotswapable, Latchlock, 40mm fan with 1-touch button for Back-up / Restore , blacK, no need to turn off pc ; with software to allow you to choose files, directories, source, destination ; ideal for pure backup , or backup on 1 pc and restore to another PC
MR-ViUHL2A		Vi-Power VP-4128LS2F , ide to Usb2.0 , Hotswapable , Latchlock , 2 x 40mm Fan , A , Aluminum , No need to turn off pc - for 5.25"
MR-ViSHL		Vi-Power VP-1001LSF , ide to S-ata . Hotswapable , Latchlock , 40mm Fan , No need to turn off pc - for 5.25"
MR-VA15		Vi-Power VP-15-133 , ide inner tray (cartridge) , plastic - for all VP-10xxx , VP-410xx
MR-VA15FK		Vi-Power VP-15F-133-black , ide inner tray (cartridge) , plastic , with 1 x 40mm fan - for all VP-10xxx , VP-410xx
for SATA hdd		
MR-VSSHL2		Vi-Power VPP-2010LS2F , S-ata to S-ata . Hotswapable , Latchlock , 2 x 40mm fan , No need to turn off pc - for 5.25"
MR-VSSHK2K		Vi-Power VPP-2010KP2F-black , S-ata to S-ata . Hotswapable , Keylock , 2 x 40mm fan , blacK , No need to turn off pc - for 5.25"

MR-VSSHLA		Vi-Power VP-5010LSF , S-ata to S-ata , Hotswapable , Latchlock , 40mm fan, Aluminum , No need to turn off pc - for 5.25"
MR-VSSHLAK		Vi-Power VP-5010LSF , S-ata to S-ata , Hotswapable , Latchlock , 40mm fan, Aluminum , blacK , No need to turn off pc - for 5.25"
MR-VSSHL2AK		Vi-Power VPA-5010LS2F-black , S-ata to S-ata , Hotswapable , Latchlock , 2 x 40mm fan, Aluminum , blacK , No need to turn off pc - for 5.25"
MR-VSSHKAK		Vi-Power VPA-5010KPF-blacK , S-ata to S-ata , Hotswapable , Keylock , 40mm fan, Aluminum , No need to turn off pc - for 5.25" , also support external enclosure - VPMA-75211R , VPMA-75189 , VPMA-752189 , VPMA-75511R
MR-VSSHK2AK		Vi-Power VPA-5010KP2F-blacK , S-ata to S-ata , Hotswapable , Keylock , 2 x 40mm fan, Aluminum , No need to turn off pc - for 5.25"
MR-VSSHK2A		Vi-Power VPA-5010KP2F , S-ata to S-ata , Hotswapable , Keylock , 2 x 40mm fan, Aluminum , No need to turn off pc - for 5.25"
MR-VA9101P		Vi-Power VP-9101P - external Ac-Adapter + S-ATA cable - connect S-ATA inner tray or S-ATA HDD to external S-ATA port - recommend to use together external S-ATA add on card (eg. AC-V9601A , AC-VSP200 , AC-V9701)
MR-VA5015A		Vi-Power VP-5015 , S-ata inner tray (cartridge) , aluminum , with 1 x 40mm fan - for VP-5010LSF series
MR-VA5015AK		Vi-Power VP-5015-black , S-ata inner tray (cartridge) , aluminum , with 1 x 40mm fan - for VP-5010LSF series
VANTEC / ViZO		
for IDE hdd		
MR-V103		vantec (oem by icydock) EZ-Swap MRK-103F, beige, aluminum , for IDE HDD , 40mm rear cooling fan, keylock, hdd access/power indicator- 3 years warranty - inner tray compatiable with iCYDOCK MB452UK
MR-V103C		vantec (oem by icydock) EZ-Swap MRK-103F, beige, aluminum inner tray tray , for IDE HDD - compatiable with iCYDOCK MB452UK
MR-V102		vantec (oem by icydock) EZ-Swap MRK-102FD , beige , aluminum , for IDE HDD , 40mm rear cooling fan , with keylock , with LCD (hdd access , alarm , fan failure , overheating , hdd master/slave) - 3 years warranty - inner tray compatiable with iCYDOCK MB452UK , MB123AK , MB122AKGF
MR-V102C		vantec (oem by icydock) EZ-Swap MRK-102FD , beige , aluminum inner tray with LCD (hdd access , alarm , fan failure , overheating , hdd master/slave) , for IDE HDD - compatiable with iCYDOCK MB452UK , MB123AK , MB122AKGF
for SATA hdd		
EE-V250ST	N	Vantec mrk-250st nexstar ex , black , 2.5" external enclosure / mobile rack , also comes with mobilerack frame / docking in 3.5" or 5.25" bay , screwless , aluminum , 2.5" SATA hdd to usb 2.0(as external enclosure) or sata (as internal mobile rack) ; powered by USB ; with carry bag
MR-VARES2	N	Vizo ARES ii , ARS-250 - black , for 2x2.5" S-ATA HDD in 1 x 3.5" bay , plastic + aluminum , hot swappable , HDD indicator
MR-V100ST	N	Vantec mrk-100st ez-swap3 , black , for 3.5" S-ATA HDD , plastic+aluminum , trayless design hot swappable , with power, HDD indicator
MR-VARES	N	Vizo ARES ARS-525 (oem by icydock) black+silver , for 3.5" S-ATA HDD , plastic + aluminum , key-lock , hot swappable , with power , HDD indicator

MR-V200SK	N	vantec EZ-Swap MRK-200ST black , for 3.5" S-ATA HDD , plastic + aluminum , key-lock , hot swappable , blue backlight LCD display for temperature , power , HDD indicator - inner tray compatiable with iCYDOCK MB452MK , MB123SK
MR-V200SKC		vantec EZ-Swap MRK-200ST black , 3.5" S-ATA hdd inner tray (cartridge) with LCD display - for vantec MR-V200SK , iCYDOCK MB452MK , MB123SK
ICYDOCK		http://www.cremax.com.tw/english/index_eng.html
EE-iA883	N	Icydock MB883 - leather carry bag for hdd inner tray (EE-iA5XiTW , EE-iA5XiTB or MR-iA45XiT)
MR-iA45XiT		iCYDOCK removable inner tray , SATA , black - for MP453/454/455SPF mobile rack or MB559/561 series external enclosure
EE-iA5XiTW		iCYDOCK removable inner tray , SATA , White - for icydock MB559/561 series enclosure or MP453/454/455SPF mobile rack
EE-iA5XiTB	N	iCYDOCK removable inner tray , SATA , Black - for icydock MB559/561 series enclosure or MP453/454/455SPF mobile rack
for IDE hdd		
MR-i123AK		iCYDOCK MB123AK , beige , aluminum , for IDE HDD , 40mm rear cooling fan , with keylock - inner tray compatiable with iCYDOCK MB452UK , Vantec MRK-102FD
MR-i123AKK		iCYDOCK MB123AK-B , blacK , aluminum , for IDE HDD , 40mm rear cooling fan , with keylock - inner tray compatiable with iCYDOCK MB452UK , Vantec MRK-102FD
MR-i122AKGF		iCYDOCK MB122AKGF , beige , aluminum , with LCD (hdd access , alarm , fan failure , overheating , hdd master/slave) , for IDE HDD , 40mm rear cooling fan , with keylock - inner tray compatiable with iCYDOCK MB452UK , Vantec MRK-102FD
for SATA hdd		
MR-i448SR		iCYDOCK MB448SR mobile rack , blacK , aulminum , for 2.5" SATA HDD in 3.5" bay , push and eject design with latch lock
EE-i663URS		iCYDOCK MB663UR-1S , Silver , 2.5" external enclosure / mobile rack , ultra slim - 13mm , also comes with mobilerack frame / docking in 3.5" bay , screwless , aluminum , SATA hdd to usb 2.0 ; powered by USB ; with carry bag - also works MB663UR series external enclosure
EE-i663URB		iCYDOCK MB663UR-1SB , Black , 2.5" external enclosure / mobile rack , ultra slim - 13mm , also comes with mobilerack frame / docking in 3.5" bay , screwless , aluminum , SATA hdd to usb 2.0 ; powered by USB ; with carry bag - also works MB663UR series external enclosure
EE-i663UBS		iCYDOCK MB663UB-1S , Silver , 2.5" external enclosure , ultra slim - 13mm , screwless , aluminum , for 2.5" SATA hdd , usb 2.0 ; powered by USB ; with carry bag - also works as innternal tray for MB663UR series external enclosure / mobile rack
EE-i663UBB		iCYDOCK MB63UB-1SB , Black , 2.5" external enclosure , ultra slim - 13mm , screwless , aluminum , for 2.5" SATA hdd , usb 2.0 ; powered by USB ; with carry bag - also works as innternal tray for MB663UR series external enclosure / mobile rack
MR-i123SK		iCYDOCK MB123SK , beige , aluminum , for 3.5" SATA HDD , 40mm rear cooling fan , with keylock - inner tray compatiable with iCYDOCK MB452MK , Vantec MRK-200ST
MR-i123SKK		iCYDOCK MB123SK-B , blacK , aluminum , for 3.5" SATA HDD , 40mm rear cooling fan , with keylock - inner tray compatiable with iCYDOCK MB452MK , Vantec MRK-200ST
MR-i123iKK		iCYDOCK MB123iK-1B , blacK , aluminum , for 3.5" SAS or SATA HDD , with key-lock , 40mm rear cooling fan , with keylock

MR-i671SK		iCYDOCK MB671SK-B , screwless + trayless , for 3.5" S-ATA HDD , silver+black , heavy duty steel + aluminum , 2 segment key-lock , hot swappable , short depth compact size design , 40mm cooling fan
MR-i671SKK	N	iCYDOCK MB671SK-B , blacK , screwless + trayless , for 3.5" S-ATA HDD , heavy duty steel + aluminum , 2 segment key-lock , hot swappable , short depth compact size design , 40mm cooling fan
MR-i671iK		iCYDOCK MB671iK , screwless + trayless , for 3.5" SAS or S-ATA HDD , silver+black , heavy duty steel + aluminum , 2 segment key-lock , hot swappable , short depth compact size design , 40mm cooling fan
MR-i672SKGF		iCYDOCK MB672SKGF-B , screwless + trayless , with blue backlight LCD display for temperature + power + HDD indicator , with visual + audio alarm , for 3.5" S-ATA HDD , silver+black , heavy duty steel + aluminum , 2 segment key-lock , hot swappable , short depth compact size design , 40mm cooling fan
MR-i672SKGFK	N	iCYDOCK MB672SKGF-BB , blacK , screwless + trayless , with blue backlight LCD display for temperature + power + HDD indicator , with visual + audio alarm , for 3.5" S-ATA HDD , heavy duty steel + aluminum , 2 segment key-lock , hot swappable , short depth compact size design , 40mm cooling fan
MR-i122SKGF		iCYDOCK MB122SKGF , for 3.5" S-ATA HDD , blk , plastic + aluminum , with key-lock , hot swappable , blue backlight LCD display for temperature + power + HDD indicator , with visual + audio alarm , 40mm cooling fan - inner tray compatiable with iCYDOCK MB452MK , MB123SK , vantec MRK-200ST
MR-i673SPF		iCYDOCK MB673SPF , 3 x hot-swappable in 2 x 5.25" bay , screwless + trayless - SATA mobile rack (ideal for raid 0/1/1E/5) , anti-shank design , aluminum , black , latch-lock , with temp. sensor, LED indication for Drive activity/overheat/failure + Fan working/failure status
MR-i674SPF		iCYDOCK MB673SPF , 4 x hot-swappable in 3 x 5.25" bay , screwless + trayless - SATA mobile rack (ideal for raid 0/1/0+1/1E/5/10) , anti-shank design , aluminum , black , latch-lock , with temp. sensor, LED indication for Drive activity/overheat/failure + Fan working/failure status
MR-i451SPF	C	iCYDOCK MB876SK , 1 x hot-swappable in 1 x 5.25" bay - SATA mobile rack , anti-shank design , aluminum , black , key-lock , with temp. sensor , audio alarm warning , LED indication for Drive activity/overheat/failure + Fan working/failure status ; Interchangeable tray (EE-iA5XiT or MR-iA45XiT) compatiable with external enclosure : MB561S-4S , MB559US , MB559UEA / mobile rack : MB453SPF , MB454SPF , MB455SPF
MR-i453SPF		iCYDOCK MB453SPF , 3 x hot-swappable in 2 x 5.25" bay - SATA mobile rack (ideal for raid 0/1/1E/5) , anti-shank design , aluminum , black , latch-lock , with temp. sensor , audio alarm warning , LED indication for Drive activity/overheat/failure + Fan working/failure status ; Interchangeable tray (EE-iA5XiT or MR-iA45XiT) compatiable with external enclosure : MB561S-4S , MB559US , MB559UEA / mobile rack : MB453SPF , MB454SPF , MB455SPF
MR-i453iPF		iCYDOCK MB453iPF , 3 x hot-swappable in 2 x 5.25" bay - SAS or SATA mobile rack (ideal for raid 0/1/1E/5) , anti-shank design , aluminum , black , latch-lock , with temp. sensor , audio alarm warning , LED indication for Drive activity/overheat/failure + Fan working/failure status ; Interchangeable tray (EE-iA5XiT or MR-iA45XiT) compatiable with external enclosure : MB561S-4S , MB559US , MB559UEA / mobile rack : MB453SPF , MB454SPF , MB455SPF

MR-i454SPF		iCYDOCK MB454SPF , 4 x hot-swappable in 3 x 5.25" bay - SATA mobile rack (ideal for raid 0/1/1E/0+1/10/5/5EE/6) , anti-shank design , aluminum , black , latch-lock , with temp. sensor , audio alarm warning , LED indication for Drive activity/overheat/failure + Fan working/failure status ; Interchangeable tray (EE-iA5XiT or MR-iA45XiT) compatiable with external enclosure : MB561S-4S , MB559US , MB559UEA / mobile rack : MB453SPF , MB454SPF , MB455SPF
MR-i455SPF		iCYDOCK MB455SPF , 5 x hot-swappable in 3 x 5.25" bay - SATA mobile rack (ideal for raid 0/1/1E/0+1/10/5/5EE/6) , anti-shank design , aluminum , black , latch-lock , with temp. sensor , audio alarm warning , LED indication for Drive activity/overheat/failure + Fan working/failure status ; Interchangeable tray (EE-iA5XiT or MR-iA45XiT) compatiable with external enclosure : MB561S-4S , MB559US , MB559UEA / mobile rack : MB453SPF , MB454SPF , MB455SPF
MR-i810SKF		iCYDOCK MB810SKF , 5 x hot-swappable in 3 x 5.25" bay , with key-lock front panel - SATA mobile rack (ideal for raid 0/1/1E/0+1/10/5/5EE/6) , anti-shank design , aluminum , beige , audio alarm warning , LED indication for Drive activity/overheat/failure + Fan working/failure status ; Interchangeable tray (stainless steel plate)
External Enclosure		
accessories		
CA-VSES		Vizo external SATA converter - from SATA on motherboard to External SATA in pci bracket - 30cm
CA-VSEES		Vizo external e-SATA converter - from SATA on motherboard to External E-SATA in pci bracket - 45cm
EE-VAPoWSA	N	Vizo 10w ac-adpter for 2.5" external enclosure
EE-iAH		Icydock Hybrid external e-SATA + ac power connector on pci bracket - from SATA on motherboard to External E-SATA + 4pin molex from psu to power connector - for icydock external enclosure
EE-iA884W	C	Icydock MB884U-C , White , optional clip-on fan for external enclosure , 120mm fan , 2000rpm, usb power , 138x122x68mm, 24dBA
EE-iA884B	C	Icydock MB884U-CB , Black , optional clip-on fan for external enclosure , 120mm fan , 2000rpm, usb power , 138x122x68mm, 24dBA
CA-VSESES		Vizo E-SATA to E-SATA cable - 100cm
CA-VSESES2		Vizo E-SATA to E-SATA cable - 200cm
CA-VSESEES		Vizo external SATA to external E-SATA cable - 100cm
CB-D18948		Dicota N18948N memory pocket - for 2.5" external hdd - offer extra scratch + shock protection - support hdd upto 145x85x25mm
CB-D17888		Dicota Z17888P baseXX - for 3.5" external hdd - offer extra scratch + shock protection , extra compartments for accessories - support hdd upto 215x160x38mm
iC-V9218		Vi-power VP-9218 interface converter - USB2.0 to External eSATA smart dongle
iC-ViSU	N	Vantec CB-iSATAU2 Interface Converter - USB to IDE + SATA interface , for 44pin 2.5" ide / 40pin 3.5" IDE / 40pin 5.25" IDE / 3.5" SATA / external SATA / external e-SATA (require SATA to eSATA cable) , ide + 1 x sata can be used at the same time , include power cable for IDE/SATA device - retail pack
hdd docking for 2.5" + 3.5" sata drive		
Vantec		

EE-VD100U		Vantec nexstar hard drive dock , nst-d100-s2 , 2.5" or 3.5" sata to Usb2.0 hdd dock , pearl white , with eject button for easy removal of hard drive
EE-VD100UK	N	Vantec nexstar hard drive dock , nst-d100-s2 , 2.5" or 3.5" sata to Usb2.0 hdd dock , blacK , with eject button for easy removal of hard drive
EE-VD100SU		Vantec nexstar hard drive dock , nst-d100-su , 2.5" or 3.5" sata to e-Sata + Usb2.0 hdd dock , white , with eject button for easy removal of hard drive
EE-VD100SUF		Vantec nexstar hard drive dock , nst-d100-ufs , 2.5" or 3.5" sata to e-Sata + Usb2.0 + Firewire (ieee1394a) hdd dock , white , with eject button for easy removal of hard drive
EE-VD200SU	N	Vantec nexstar dual hdd hard drive dock , nst-d200-su , 2x bay for 2.5" or 3.5" sata to e-Sata + Usb2.0 hdd dock , pearl white , with eject button for easy removal of hard drive
ICYDOCK		
EE-i881US	N	Icydock MB881US-1S-1 ez-dock - 2.5" or 3.5" sata to e-Sata + Usb2.0 hdd dock / enclosure , white - with desk top stan dfor 2.5" or 3.5" sata hdd , with carry case for 2.5" hdd to make it as ultra portable 2.5" extrenal hdd , bundled external e-Sata adapter (connect from on board s-ata to pci back plate) , support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)
for 2.5" IDE notebook drive		
Magnetox		
VR-MV120		Magnetox V120 Video Recorder + bundled stackable B200 usb enclosure for 2.5" IDE hdd with schedule recording up to 100 events , hardware MPEG4 recording , silver + pearl white , mini size : 116 x 116 x 29mm , with remote control + SD/SDHC card reader , video/audio/picture output to TV, PC, iPoD, PSP, GBM, PMP, PDA, Smart Phone, & Mobile Phone ; video recorded to SD or external usb hdd , video support format DivX / XviD / AVi / VoB, MPG ; audio support format : MP3, WAV, WMA, AAC ; AV in/out , tuner input , mini usb
Asus		
EE-AWH		Asus WL-HDD2.5 external enclosure for 2.5" ide HDD (upto 160gb) , usb 2.0 + 10/100 UTP + wireless (802.11b/g 54mbps , 64/128bit WEP) ; support auto-copy (when connect with Flash Drive) - max. 6 users at one time
Coolermaster		
EE-C250iBL	N	Coolermaster , RX-250-U2B1 , X Craft 250 Lite , Ide , Black , anodized aluminum , high qulaity mesh design for heat dissipation , with blue led , usb 2.0 for 2.5" ide hdd ; powered by USB ; 136x81x19mm ; 140g ; with carry bag
Vi-Power		
EE-V1828B		Vi-Power VPP-1828B 1.8" external enclosure with 1-touch button for Back-up or Restore , eye-pattern approved , IDE hdd to usb 2.0 ; powered by USB ; 85 x 72 x 12mm ; with software to allow you to choose files, directories, source, destination ; ideal for pure backup , or backup on 1 pc and restore to another PC
EE-V2528B		Vi-Power VPP-2528B 1.8"/2.5" external enclosure with 1-touch button for Back-up or Restore , eye-pattern approved , IDE hdd to usb 2.0 ; powered by USB ; 128 x 72 x 12mm ; with software to allow you to choose files, directories, source, destination ; ideal for pure backup , or backup on 1 pc and restore to another PC

EE-V25289A		Vi-Power VPA-25289 1.8"/2.5" external enclosure , aluminum , eye-pattern approved , IDE hdd to usb 2.0+ieee1394A (400mb/sec) ; powered by usb or firewire , include usb cable + firewire cable (4 or 6 pin)
EE-V25289BA		Vi-Power VPA-25289B-800 1.8"/2.5" external enclosure , aluminum , eye-pattern approved , IDE hdd to usb 2.0+ieee1394A+ieee1394B (800mb/sec) ; powered by usb or firewire , include usb cable + firewire cable (6-6/4 pin)
vizo		
EE-VSi		ViZO Shuttle SHE-250 external enclosure , aluminum , usb 2.0 , for 2.5" ide hdd ; powered by USB (support optional 10w ac-adapter for high power consumption HDD) ; 127x79x17mm ; 90g ; with carry bag
EE-VPBL		ViZO Paragon + Backup button - bLue , aluminum , 2.5" ide external enclosure , with 1-touch button for Back-up or Restore : usb 2.0 , with carry bag
EE-VPBK		ViZO Paragon + Backup button - blacK , aluminum , 2.5" ide external enclosure , with 1-touch button for Back-up or Restore : usb 2.0 , with carry bag
EE-VPBW		ViZO Paragon + Backup button - White , aluminum , 2.5" ide external enclosure , with 1-touch button for Back-up or Restore : usb 2.0 , with carry bag
EE-VoCA		Vizo Opera CAR ADAPTER
Vantec		
EE-V260iUFK	N	Vantec nexstar3 , nst-260uf-bk , 2.5" Ide to Usb2.0+Firewire (ieee1394A) external enclosure , blacK , aluminum with mirror finish , usb powered , with carry bag
EE-V260iUKS	N	Vantec nexstarDS , nst-260ds-bk , 2.5" Ide to Usb2.0 external enclosure , blacK , with Security keys + 64bit hardware encryption + audio alarm , also works as OTG device (One-Touch-Go : pc-free backup/copy directly from other usb device - ie digital camera / flash drive ... etc) , aluminum with mirror finish , usb or 4xAA battery powered for OTG , with carry bag
for 1.8" , 2.5" SATA notebook drive		
Pc winner		
EE-PEC258S	N	Pc winner EC258S , Silver , 2.5" external enclosure with fingerprint 256bit AES protection , for 2.5" SATA hdd , usb 2.0 ; powered by USB
Magnetox		
EE-MP210		Magnetox P210 2.5" external enclosure + multimedia player (video , music , photo) , aluminum , SATA hdd to usb 2.0 + Audio out + video out (rca + s-video) headphone output , with remote control
ICYDOCK		
EE-i663UBS		iCYDOCK MB663UB-1S , Silver , 2.5" external enclosure , ultra slim - 13mm , screwless , aluminum , for 2.5" SATA hdd , usb 2.0 ; powered by USB ; with carry bag - also works as innternal tray for MB663UR series external enclosure / mobile rack
EE-i663UBB		iCYDOCK MB663UB-1SB , Black , 2.5" external enclosure , ultra slim - 13mm , screwless , aluminum , for 2.5" SATA hdd , usb 2.0 ; powered by USB ; with carry bag - also works as innternal tray for MB663UR series external enclosure / mobile rack
EE-i663URS	N	iCYDOCK MB663UR-1S , Silver , 2.5" external enclosure / mobile rack , ultra slim - 13mm , also comes with mobilerack frame / docking in 3.5" bay , screwless , aluminum , SATA hdd to usb 2.0 ; powered by USB ; with carry bag - also works MB663UR series external enclosure

EE-i663URB	N	iCYDOCK MB663UR-1SB , Black , 2.5" external enclosure / mobile rack , ultra slim - 13mm , also comes with mobilerack frame / docking in 3.5" bay , screwless , aluminum , SATA hdd to usb 2.0 ; powered by USB ; with carry bag - also works MB663UR series external enclosure
Vi-Power		
EE-V25018		Vi-Power VPA2-25018 1.8"/2.5" external enclosure , aluminum , SATA hdd to usb 2.0 ; powered by USB
EE-V25118		Vi-Power VPA2-25118 1.8"/2.5" external enclosure , aluminum , SATA hdd to usb 2.0+eSATA ; powered by USB
EE-V25218R	N	Vi-Power VPA-25218R 2x 2.5" hdd dock or external enclosure , aluminum , with backup button + built-in raid system (raid 0, 1, JBOD) , OS independent SteelVine Storage Processor , 1 x fan , 2xSATA hdd to eSATA or usb
Coolermaster		
EE-C250SUB		Coolermaster X Craft 250 Lite , SATA , Black , RX-250-SUB , anodized aluminum with mirror finish , high qulaity mesh design for heat dissipation , with blue led , usb 2.0 for 2.5" SATA hdd ; powered by USB ; 136x81x19mm ; 140g ; with carry bag
EE-C250SUS	N	Coolermaster X Craft 250 Lite , SATA , Silver , RX-250-SUS , anodized aluminum with mirror finish , high qulaity mesh design for heat dissipation , with blue led , usb 2.0 for 2.5" SATA hdd ; powered by USB ; 136x81x19mm ; 140g ; with carry bag
EE-C250SSUBB	N	Coolermaster X Craft 250 Lite RX-250-STB1-GP , SATA to eSata+Usb , with back-up button , Black , anodized aluminum , high qulaity mesh design for heat dissipation , with blue led , usb 2.0 + e-SATA for 2.5" SATA hdd ; powered by USB ; 136x81x19mm ; 140g ; with carry bag
EE-C250SSUBS	C	Coolermaster X Craft 250 Lite RX-250-STS1-GP , SATA to eSata+Usb , with back-up button , Black , anodized aluminum , high qulaity mesh design for heat dissipation , with blue led , usb 2.0 + e-SATA for 2.5" SATA hdd ; powered by USB ; 136x81x19mm ; 140g ; with carry bag
vizo		
EE-VSS		ViZO Shuttle SHE-250SA external enclosure , aluminum , usb 2.0 , for 2.5" SATA hdd ; powered by USB (support optional 10w ac-adapter for high power consumption HDD) ; 131x79x15.5mm ; 90g ; with carry bag
EE-VS250BK		ViZO sat-250 Saturno + dual Backup button - blacK , aluminum , 3G 2.5" SATA external enclosure , with dual 1-touch button for Back-up or Restore (only for USB2.0 connection) , USB powered , usb 2.0+eSATA , with carry bag , e-SATA cable , usb cable , external eSATA adapter (connect from on board s-ata to pci back plate as eSATA)
EE-VS250BL		ViZO sat-250 Saturno + dual Backup button - bLue , aluminum + mirror finish , 3G 2.5" SATA external enclosure , with dual 1-touch button for Back-up or Restore (only for USB2.0 connection) , USB powered , usb 2.0+eSATA , with carry bag , e-SATA cable , usb cable , external eSATA adapter (connect from on board s-ata to pci back plate as eSATA)
EE-VS250BW		ViZO sat-250 Saturno + dual Backup button - White , aluminum + mirror finish , 3G 2.5" SATA external enclosure , with dual 1-touch button for Back-up or Restore (only for USB2.0 connection) , USB powered , usb 2.0+eSATA , with carry bag , e-SATA cable , usb cable , external eSATA adapter (connect from on board s-ata to pci back plate as eSATA)
Vantec		

EE-V250ST	N	Vantec mrk-250st , black , 2.5" external enclosure / mobile rack , also comes with mobilerack frame / docking in 3.5" or 5.25" bay , screwless , aluminum , 2.5" SATA hdd to usb 2.0(as external enclosure) or sata (as internal mobile rack) ; powered by USB ; with carry bag
EE-V200SUK	N	Vantec nexstar-cx , nst-200s2 , 2.5" Sata to Usb2.0 external enclosure , blacK , aluminum , usb powered , 135x82x13mm
EE-V200SSUK	N	Vantec nexstar-cx , nst-200su , 2.5" Sata to e-Sata+Usb2.0 external enclosure , blacK , aluminum , usb powered , 135x82x13mm
EE-V285SUK	N	Vantec nexstar-lite nst-285s2-bk , 2.5" Sata to Usb2.0 external enclosure , blacK , aluminum with mirror finish , usb powered , 128x73x12mm , 60g , with carry bag
EE-V285SUS	N	Vantec nexstar-lite nst-285s2-sl , 2.5" Sata to Usb2.0 external enclosure , Silver , aluminum with mirror finish , usb powered , 128x73x12mm , 60g , with carry bag
EE-V260SUK	N	Vantec nexstar3 nst-260s2-bk , 2.5" Sata to Usb2.0 external enclosure , blacK , with OTB , aluminum with mirror finish , usb powered , 132x80x15mm , 60g , with carry bag
EE-V260SUL	N	Vantec nexstar3 nst-260s2-bl , 2.5" Sata to Usb2.0 external enclosure , bLue , with OTB , aluminum with mirror finish , usb powered , 132x80x15mm , 60g , with carry bag
EE-V260SSUK	N	Vantec nexstar3 nst-260su-bk , 2.5" Sata to e-SATA+Usb2.0 external enclosure , blacK , with OTB , aluminum with mirror finish , usb powered , with carry bag
EE-VAVoX101S2	N	Vantec AVoX jukebox , avox-101S2 , 2.5" Sata to Usb2.0 external enclosure with OTB , also works as multi-media storage , R+L Audio out + video out (rca + s-video) , aluminum
for 3.5" HDD		
Antec		
EE-AMX100		Antec MX100 , Black , external enclosure for 3.5" SATA hdd , aluminum , usb 2.0
EE-AMX1		Antec MX1 , Black , external enclosure for 3.5" SATA hdd , carbon-glass filled frame to reinforce the strength of the enclosure , 2 layers material design + built-in silicone pad to reduce hdd noise , with blower fan : e-SATA + usb 2.0 - also comes with e-SATA adapter (connect from on board s-ata to pci back plate)
Enermax		
EE-EGB		Enermax Glory Black , EB306U , 1.5mm aluminum 3.5" external enclosure with 3 x 1-touch buttons for OS , Data or Custom back-up , IDE to usb 2.0
EE-EGS		Enermax Glory Silver , EB306U , 1.5mm aluminum 3.5" external enclosure with 3 x 1-touch buttons for OS , Data or Custom back-up , IDE to usb 2.0
Lian-Li		
EE-LEX20	C	Lian-Li EX-20 , 2 bay (support , raid 0/1/JBoD) external enclosure , front door with lock + filter , with sata hot-swap backplane kit , black , aluminum , 2x 3.5" Sata to Usb2.0+e-SATA , 60mm fan
EE-LEX30	C	Lian-Li EX-30 , 3 bay (support raid 0/1/JBoD) external enclosure , front door with lock + filter , with sata hot-swap backplane kit , black , aluminum , 3x 3.5" Sata to Usb2.0+e-SATA , 80mm fan
D-Link		
EE-DNS323		D-Link DNS-323 network storage with built-in usb printer server , for 2 x SATA HD with raid0/1 , 1 gigabit utp + 1 usb port for extra USB external HDD , USB flash drive or USB printer , built-in FTP server to access files over the Internet , support wireless when connect to wireless AP/router

EE-DNS343		D-Link DNS-343 network storage with built-in usb printer server , for 4 x SATA HD with raid0/1/5 , OLED Display Screen, 1 gigabit utp + 1 usb port for extra USB external HDD , USB flash drive or USB printer , built-in FTP server to access files over the Internet , support wireless when connect to wireless AP/router
Promise		
EE-PNS2300N	N	Promise smartstor NS2300N network storage with built-in usb printer server , 2 x front-access SATA/SAS hot-swapable HD with raid0/1 , with OTB (One-Touch-Backup button) , 1 gigabit utp + usb port for extra USB external HDD , USB flash drive or USB printer , built-in FTP server to access files over the Internet , support wireless when connect to wireless AP/router
EE-PNS4300N	C	Promise smartstor NS4300N network storage with built-in usb printer server , 4 x front-access SATA/SAS hot-swapable HD with raid0/1/0+1/10/5 , with OTB (One-Touch-Backup button) , 1 gigabit utp + usb port for extra USB external HDD , USB flash drive or USB printer , built-in FTP server to access files over the Internet , support image snapshot , nas to nas replication ; support wireless when connect to wireless AP/router
ICYDOCK		
EE-iAH		Icydock Hybrid external e-SATA + ac power connector on pci bracket - from SATA on motherboard to External E-SATA + 4pin molex from psu to power connector - for icydock external enclosure
EE-iA883	N	Icydock MB883 - leather carry bag for hdd inner tray (EE-iA5XiTW , EE-iA5XiTB or MR-iA45XiT)
EE-iA5XiTW		iCYDOCK removable inner tray , SATA , White - for icydock MB559/561 series enclosure or MP453/454/455SPF mobile rack
EE-iA5XiTB	N	iCYDOCK removable inner tray , SATA , Black - for icydock MB559/561 series enclosure or MP453/454/455SPF mobile rack
MR-iA45XiT		iCYDOCK removable inner tray , SATA , black - for MP453/454/455SPF mobile rack or MB559/561 series external enclosure
EE-iA884W	C	Icydock MB884U-C , White , optional clip-on fan for external enclosure , 120mm fan , 2000rpm, usb power , 138x122x68mm, 24dBA
EE-iA884B	C	Icydock MB884U-CB , Black , optional clip-on fan for external enclosure , 120mm fan , 2000rpm, usb power , 138x122x68mm, 24dBA
EE-i452iU		iCYDOCK MB452UK , multi-drive exchangeability with hot-swapable removable inner tray , Ide to Usb 2.0 , 3.5" external enclosure , aluminum , silver+black , built-in stand , key-lock ; compatiable inner hdd tray : MB123AK , MB122AKGF ; compatiable mobile rack : Vantec MRK-102FD ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)
EE-i452SU	N	iCYDOCK MB452UK-1SB , multi-drive exchangeability with hot-swapable removable inner tray , sata to Usb 2.0 , (also works with ide inner tray) , 3.5" external enclosure , aluminum , silver+black , built-in stand , key-lock ; compatiable inner hdd tray : MB123AK , MB122AKGF ; compatiable mobile rack : Vantec MRK-102FD , MRK-200ST ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)

EE-i452SUSS	**N**	iCYDOCK MB452MK-S , multi-drive exchangeability with hot-swapable removable inner tray , SATA to Usb 2.0+eSATA , 3.5" external enclosure , aluminum , silver+black , built-in stand , key-lock , bundled with external e-SATA adapter (connect from on board s-ata to pci back plate) ; compatiable inner hdd tray : iCYDOCK MB123SK , MB122SKGF / Vantec MRK-200ST ; compatiable mobile rack : Vantec MRK-200ST ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)
EE-i452SUSK		iCYDOCK MB452MK-K , multi-drive exchangeability with hot-swapable removable inner tray , SATA to Usb 2.0+eSATA , 3.5" external enclosure , aluminum , silver+black , built-in stand , key-lock , bundled with external e-SATA adapter (connect from on board s-ata to pci back plate) ; compatiable inner hdd tray : iCYDOCK MB123SK , MB122SKGF / Vantec MRK-200ST ; compatiable mobile rack : Vantec MRK-200ST ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)
EE-i559SUS		iCYDOCK MB559US-1S , pearl white + silver , multi-drive exchangeability with hot-swapable removable inner tray , ultra-thin (194x142.6x42.6mm) + anti-shank design , SATA to Usb 2.0+eSATA , 3.5" external enclosure , aluminum , built-in stand , latch-lock , with security slot for cable lock , bundled with external e-SATA adapter (connect from on board s-ata to pci back plate) ; Interchangeable tray compatiable with external enclosure : MB561S-4S , MB559US , MB559UEA / mobile rack : MB453SPF , MB454SPF , MB455SPF ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)
EE-i559SUSK		iCYDOCK MB559US-1SB , blacK , multi-drive exchangeability with hot-swapable removable inner tray , ultra-thin (194x142.6x42.6mm) + anti-shank design , SATA to Usb 2.0+eSATA , 3.5" external enclosure , aluminum , built-in stand , latch-lock , with security slot for cable lock , bundled with external e-SATA adapter (connect from on board s-ata to pci back plate) ; Interchangeable tray compatiable with external enclosure : MB561S-4S , MB559US , MB559UEA / mobile rack : MB453SPF , MB454SPF , MB455SPF ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)
EE-i559SUSMB		iCYDOCK MB559US-1SMB , black with Mirror finish , multi-drive exchangeability with hot-swapable removable inner tray , ultra-thin (194x142.6x42.6mm) + anti-shank design , SATA to Usb 2.0+eSATA , 3.5" external enclosure , aluminum , built-in stand , latch-lock , with security slot for cable lock , bundled with external e-SATA adapter (connect from on board s-ata to pci back plate) ; Interchangeable tray compatiable with external enclosure : MB561S-4S , MB559US , MB559UEA / mobile rack : MB453SPF , MB454SPF , MB455SPF ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)
EE-i559SUF		iCYDOCK MB559UEA-1S , pearl white + silver , multi-drive exchangeability with hot-swapable removable inner tray , ultra-thin (194x142.6x42.6mm) + anti-shank design , SATA to Usb 2.0+Firewire ieee1394A (400mb/sec) , 3.5" external enclosure , aluminum , built-in stand , latch-lock , with security slot for cable lock ; Interchangeable tray compatiable with external enclosure : MB561S-4S , MB559US , MB559UEA / mobile rack : MB453SPF , MB454SPF , MB455SPF ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)

EE-i559SUFK		iCYDOCK MB559UEA-1SB , blK , multi-drive exchangeability with hot-swapable removable inner tray , ultra-thin (194x142.6x42.6mm) + anti-shank design , SATA to Usb 2.0+Firewire ieee1394A (400mb/sec) , 3.5" external enclosure , aluminum , built-in stand , latch-lock , with security slot for cable lock ; Interchangeable tray compatiable with external enclosure : MB561S-4S , MB559US , MB559UEA / mobile rack : MB453SPF , MB454SPF , MB455SPF ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)
EE-i559SUFBK		iCYDOCK MB559UEB-1S , blacK , multi-drive exchangeability with hot-swapable removable inner tray , ultra-thin (194x142.6x42.6mm) + anti-shank design , SATA to Usb 2.0+Firewire ieee1394A/1394B(800mb/sec) , 3.5" external enclosure , aluminum , silver+white , built-in stand , latch-lock , with security slot for cable lock ; Interchangeable tray compatiable with external enclosure : MB561S-4S , MB559US , MB559UEA / mobile rack : MB453SPF , MB454SPF , MB455SPF ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)
EE-i664SUS		iCYDOCK MB664US-1S , pearl white + silver , multi-drive exchangeability with hot swappable screw-less design , ultra-thin (134x32x190mm) + anti-shank design , SATA to Usb 2.0+eSATA , 3.5" external enclosure , aluminum , built-in stand , latch-lock , with security slot for cable lock , bundled with external e-SATA adapter (connect from on board s-ata to pci back plate) ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)
EE-i664SUSK		iCYDOCK MB664US-1SB , black , multi-drive exchangeability with hot swappable screw-less design , ultra-thin (134x32x190mm) + anti-shank design , SATA to Usb 2.0+eSATA , 3.5" external enclosure , aluminum , built-in stand , latch-lock , with security slot for cable lock , bundled with external e-SATA adapter (connect from on board s-ata to pci back plate) ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)
EE-i664SUF		iCYDOCK MB664UEA-1S , pearl white + silver , multi-drive exchangeability with hot swappable screw-less design , ultra-thin (134x32x190mm) + anti-shank design , SATA to Usb 2.0+FirewireA (400mb/sec) , 3.5" external enclosure , aluminum , built-in stand , latch-lock , with security slot for cable lock ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)
EE-i664SUFK		iCYDOCK MB664UEA-1SB , blacK , multi-drive exchangeability with hot swappable screw-less design , ultra-thin (134x32x190mm) + anti-shank design , SATA to Usb 2.0+FirewireA (400mb/sec) , 3.5" external enclosure , aluminum , built-in stand , latch-lock , with security slot for cable lock ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)
EE-i664SUFB	C	iCYDOCK MB664UEB-1S , pearl white + silver , multi-drive exchangeability with hot swappable screw-less design , ultra-thin (134x32x190mm) + anti-shank design , SATA to Usb 2.0+FirewireB (800mb/sec) , 3.5" external enclosure , aluminum , built-in stand , latch-lock , with security slot for cable lock ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)

EE-i664SUFBK	C	iCYDOCK MB664UEB-1SB , blacK , multi-drive exchangeability with hot swappable screw-less design , ultra-thin (134x32x190mm) + anti-shank design , SATA to Usb 2.0+FirewireB (800mb/sec) , 3.5" external enclosure , aluminum , built-in stand , latch-lock , with security slot for cable lock ; support icydock Hybrid external adapter (e-SATA + ac power connector on pci bracket)
EE-i662SUS	C	iCYDOCK MB662US-2S , dual bay (JBoD , raid 0/1/BiG/safe33/safe50) external enclosure , multi-drive exchangeability with trayless design , pearl white + silver , with security slot for cable lock , aluminum , 2x 3.5" Sata to Usb2.0+e-SATA , 40mm fan , slicom 5744 chipset
EE-i662SUFB	C	iCYDOCK MB662UEAB-2S , dual bay (JBoD , raid 0/1/BiG) external enclosure , multi-drive exchangeability with trayless design , pearl white + silver , with security slot for cable lock , aluminum , 2x 3.5" Sata to Usb2.0+iEEE1394A+iEEE1394B , 40mm fan , Oxford924DSB chipset
EE-i561S4S		iCYDOCK MB561S-4S , multi-drive exchangeability with 4 x hot-swapable removable inner tray , pearl white + silver , anti-shank design , 4 x SATA hdd to 4xeSATA , 3.5" external enclosure , aluminum , latch-lock , with security slot for cable lock , bundled with 2 x 2 port external e-SATA adapter (connect from on board s-ata to pci back plate) ; Interchangeable tray (EE-iA5XiT or MR-iA45XiT) compatiable with external enclosure : MB561S-4S / mobile rack : MB453SPF , MB454SPF , MB455SPF
EE-i561S4SB		iCYDOCK MB561S-4SB , multi-drive exchangeability with 4 x hot-swapable removable inner tray , Black , anti-shank design , 4 x SATA hdd to 4xeSATA , 3.5" external enclosure , aluminum , latch-lock , with security slot for cable lock , bundled with 2 x 2 port external e-SATA adapter (connect from on board s-ata to pci back plate) ; Interchangeable tray (EE-iA5XiT or MR-iA45XiT) compatiable with external enclosure : MB561S-4S / mobile rack : MB453SPF , MB454SPF , MB455SPF
EE-i561S1S1U	N	iCYDOCK MB561US-4S , multi-drive exchangeability with 4 x hot-swapable removable inner tray , pearl white + silver , anti-shank design , 4 x SATA hdd to 1xeSATA or 1xUsb , 3.5" external enclosure , aluminum , latch-lock , with security slot for cable lock ; Interchangeable tray (EE-iA5XiT or MR-iA45XiT) compatiable with external enclosure : MB561S-4S / mobile rack : MB453SPF , MB454SPF , MB455SPF
EE-i561S1S1U+C	N	iCYDOCK MB561US-4SC , with bundled Port Multiplier eSATA pci-e card , multi-drive exchangeability with 4 x hot-swapable removable inner tray , pearl white + silver , anti-shank design , 4 x SATA hdd to 1xeSATA or 1xUsb , 3.5" external enclosure , aluminum , latch-lock , with security slot for cable lock ; Interchangeable tray (EE-iA5XiT or MR-iA45XiT) compatiable with external enclosure : MB561S-4S / mobile rack : MB453SPF , MB454SPF , MB455SPF
EE-i561S1S1UB+C	C	iCYDOCK MB561US-4SBC , with bundled Port Multiplier eSATA pci-e card , multi-drive exchangeability with 4 x hot-swapable removable inner tray , Black , anti-shank design , 4 x SATA hdd to 1xeSATA or 1xUsb , 3.5" external enclosure , aluminum , latch-lock , with security slot for cable lock ; Interchangeable tray (EE-iA5XiT or MR-iA45XiT) compatiable with external enclosure : MB561S-4S / mobile rack : MB453SPF , MB454SPF , MB455SPF

Vi-Power

EE-V3528AB	Vi-Power VPA-3528B aluminum 3.5" external enclosure with blue e-led , 1-touch button for Back-up or Restore , eye-pattern approved , IDE to usb 2.0 ; with software to allow you to choose files, directories, source, destination ; ideal for pure backup , or backup on 1 pc and restore to another PC
EE-V35018A	Vi-Power VPA-35018 , silver , aluminum 3.5" external enclosure with blue e-led , eye-pattern approved , SATA hdd to USB
EE-V35011A	Vi-Power VPA-35011 aluminum 3.5" external enclosure with blue e-led , eye-pattern approved , SATA to eSATA
EE-V35018PA	Vi-Power VPA-35018 Plus (VPA-35011 + VP-9218) , silver , aluminum 3.5" external enclosure with blue e-led , eye-pattern approved , SATA hdd to eSATA or USB (via USB to eSATA converter included)
EE-V35118A	Vi-Power VPA-35118 , silver , aluminum 3.5" external enclosure with blue e-led , eye-pattern approved , SATA hdd to eSATA or USB or SATA (via USB to SATA converter inlcuded)
EE-V6248MT	Vi-Power VPM-6248T external enclosure with 3.5" mobile rack , true Metal , with thermal controlled fan , eye-pattern approved , usb2.0
EE-V8258P	Vi-Power VP-8258Plus - SmartDock external enclosure - include Vp-15-133 inner tray , ac-adapter , 2 x 40pin ide interface board (for 3.5"/5.25" ide device) , 1 x 44pin 2.5" ide interface board (for notebook drive) , usb 2.0 - support all inner tray or stand alone 2.5" , 3.5" or 5.25" ide device outside of a PC
EE-V75211R	Vi-Power VPMA-75211R - external enclosure with 2 x 3.5" SATA hot-swappable mobile rack (VPA-5010KPF) , aluminum , with built-in raid system (raid 0, 1, JBOD) , OS independent SteelVine Storage Processor , 2xSATA hdd to eSATA or usb 2.0 (via e-SATA to usb adapter)
EE-V75511R	Vi-Power VPMA-75511R - external enclosure with 5 x 3.5" SATA hot-swappable mobile rack (VPA-5010KPF) , aluminum , with built-in raid system (raid 0, 1, 0+1, 10, JBOD) , OS independent SteelVine Storage Processor , 5xSATA hdd to eSATA or usb 2.0 (via e-SATA to usb adapter)
Vizo	
EE-VLASK	ViZO Luxon Advanced Sd , blacK , LUS-360-BK , aluminum , usb2.0 external enclosure for 3.5" SATA hdd
EE-VLASL	ViZO Luxon Advanced Sd , bLue , LUS-360-BL , aluminum , usb2.0 external enclosure for 3.5" SATA hdd
EE-VLASG	ViZO Luxon Advanced Sd , Grey/Silver , LUS-360-GY , aluminum , usb2.0 external enclosure for 3.5" SATA hdd
EE-VLAEK	ViZO Luxon Advanced Ed , blacK , LUE-360-BK , aluminum , external enclosure : e-SATA + Usb 2.0 , for 3.5" SATA hdd - also comes with e-sata cable , usb cable
EE-VLAEL	ViZO Luxon Advanced Ed , bLue , LUE-360-BL , aluminum , external enclosure : e-SATA + Usb 2.0 , for 3.5" SATA hdd - also comes with e-sata cable , usb cable
EE-VLAEG	ViZO Luxon Advanced Ed , Grey , LUE-360-GY , aluminum , external enclosure : e-SATA + Usb 2.0 , for 3.5" SATA hdd - also comes with e-sata cable , usb cable
EE-VU350BK	ViZO Uranus URA350SA-BK + dual Backup button (only work with usb2.0 connection) , blacK , aluminum , 3G external enclosure : eSATA + USB 2.0 , for 3.5" SATA hdd - bundled with eSATA cable , usb cable , external eSATA adapter (connect from on board s-ata to pci back plate)

EE-VU350BL		ViZO Uranus URA350SA-BL + dual Backup button (only work with usb2.0 connection) , bLue , aluminum , 3G external enclosure : eSATA + USB 2.0 , for 3.5" SATA hdd - bundled with eSATA cable , usb cable , external eSATA adapter (connect from on board s-ata to pci back plate)
EE-VU350BG		ViZO Uranus URA350SA-GY + dual Backup button (only work with usb2.0 connection) , Gray , aluminum , 3G external enclosure : eSATA + USB 2.0 , for 3.5" SATA hdd - bundled with eSATA cable , usb cable , external eSATA adapter (connect from on board s-ata to pci back plate)
EE-VLA350K		ViZO Luxon Advanced LXE-350-BK , black , aluminum , external enclosure : e-SATA + Usb 2.0 , for 3.5" IDE or SATA hdd - also comes with e-sata cable , usb cable , external e-Sata adapter (connect from on board s-ata to pci back plate)
EE-VLA350L		ViZO Luxon Advanced LXE-350-BL , bLue , aluminum , external enclosure : e-SATA + Usb 2.0 , for 3.5" IDE or SATA hdd - also comes with e-sata cable , usb cable , external e-Sata adapter (connect from on board s-ata to pci back plate)
EE-VLA350G		ViZO Luxon Advanced LXE-350-GY , Grey , aluminum , external enclosure : e-SATA + Usb 2.0 , for 3.5" IDE or SATA hdd - also comes with e-sata cable , usb cable , external e-Sata adapter (connect from on board s-ata to pci back plate)
EE-VM		Vizo Milano , MiP-100 3.5" IDE HDD external enclosure + multimedia player (video , music , photo) , with control bottoms + remote control , support HDTV 1080i : usb 2.0 ; video output : RCA+component YPbPr+svideo , audio output : RCA+optical SPiDiF
EE-VMSi	N	Vizo Milano Si , MiP-100-Si 3.5" IDE or SATA HDD external enclosure + multimedia player (video , music , photo) , with control bottoms + remote control , support HDTV 1080i : usb 2.0 ; video output : RCA+component YPbPr+svideo , audio output : RCA+optical SPiDiF
Vantec		
EE-V370GX		Vantec Nexstar GX NST-370GX , white , external enclosure with blue LED , 3 x downstream usb hub , passive cooling + temperature controlled fan + security lock , stackable : usb 2.0, for 3.5" hdd
EE-V360iUKB	N	Vantec nexstar3 , nst-360u2-bk-otb , 3.5" Ide to Usb2.0 external enclosure , blacK , with Backup button , aluminum with sand coating
EE-V355UF		Vantec Nexstar2 NST-355-UF external encloure with blue e-led , usb 2.0+firewire , for 3.5" hdd ; 210 x 135 x 40 mm
EE-V360iUNK	N	Vantec nexstar Ls , nst-360ls-bk , 3.5" Ide to Usb2.0+Network (utp/rj-45) external enclosure , blacK , aluminum with mirror finish
EE-V300SUK	N	Vantec nexstar-cx , nst-300S2 , 3.5" Sata to Usb2.0 external enclosure , blacK , aluminum
EE-V300SSUK	N	Vantec nexstar-cx , nst-300SU , 3.5" Sata to e-Sata + Usb2.0 external enclosure , blacK , aluminum
EE-V360SUK		Vantec nexstar3 , nst-360s2-bk , 3.5" Sata to Usb2.0 external enclosure , blacK , aluminum with mirror finish
EE-V360SUL		Vantec nexstar3 , nst-360s2-bl , 3.5" Sata to Usb2.0 external enclosure , bLue , aluminum with mirror finish
EE-V360SUWP		Vantec nexstar3i , nst-360s2i-Wh , 3.5" Sata to Usb2.0 external enclosure , White , with Power management (saves power + extends hard drive lifetime) , aluminum with mirror finish
EE-V360SSUK		Vantec nexstar3 , nst-360su-bk , 3.5" Sata to e-Sata + Usb2.0 external enclosure , blacK , aluminum with mirror finish

EE-V360SSUR		Vantec nexstar3 , nst-360su-rd , 3.5" Sata to e-Sata + Usb2.0 external enclosure , Red , aluminum with mirror finish
EE-V360SSUFK	N	Vantec nexstar3 , nst-360ufs , 3.5" Sata to e-Sata + Usb2.0 + Firewire 1394A external enclosure , blacK , aluminum with mirror finish
EE-V360SSUFBK	N	Vantec nexstar3 , NST-360FBSU-BK , 3.5" Sata to e-Sata + Usb2.0 + Firewire 1394A+1394B (800mb/sec) external enclosure , blacK , aluminum with mirror finish
EE-V400MXS2	N	Vantec nexstar-mx , nst-400mx-S2 , dual bay (JBoD) , 2x 3.5" Sata to Usb2.0 external enclosure , blacK , aluminum
EE-V400MXSR	N	Vantec nexstar-mx , nst-400mx-SR , dual bay (JBoD , raid 0/1) , 2x 3.5" Sata to Usb2.0+e-SATA external enclosure , , blacK , aluminum
EE-VAVoX200S2	N	Vantec AVoX jukebox , avox-200s2 , 3.5" Sata to Usb2.0 external enclosure with OTB , also works as multi-media storage , with built-in control panel + remote control , R+L Audio out + video out (rca + s-video) , aluminum
Coolermaster		
EE-C350iS		Coolermaster RX-3HU-LES1 , X Craft 350 , Ide to Usb , Silver + Hub + Back-up : built-in 2 port USB 2.0 Hub with MultiTRAK - stackable , with back-up button , anodized aluminum with mirror finish , high qulaity mesh design for heat dissipation , stackable design , with blue led , usb 2.0 ; 225x120x38mm ; 438g
EE-C350SUB		Coolermaster RX-3SB-SEB1 , X Craft Lite 350 , Sata to Usb , Black : anodized aluminum with mirror finish , high qulaity mesh design for heat dissipation , stackable design , with blue led , usb 2.0 ; 225x120x38mm ; 438g
EE-C350SUS		Coolermaster RX-3SB-SES1 , X Craft Lite 350 , Sata to Usb , Silver : anodized aluminum with mirror finish , high qulaity mesh design for heat dissipation , stackable design , with blue led , usb 2.0 ; 225x120x38mm ; 438g
EE-C350SSUBB	N	Coolermaster RX-3SB-SEB1-GP , X Craft Lite 350 , Sata to Usb+eSata , with Back-up button , Black : anodized aluminum with mirror finish , high qulaity mesh design for heat dissipation , stackable design , with blue led , usb 2.0 ; 225x120x38mm ; 438g
EE-C350SiSUB	N	Coolermaster RX-3Si-SUS1 , X Craft Lite 350 , Sata or Ide to eSata or Usb , Blk : anodized aluminum with mirror finish , high qulaity mesh design for heat dissipation , stackable design , with blue led , usb 2.0 ; 225x120x38mm ; 438g
EE-C350SiSUS	N	Coolermaster RX-3Si-SUS1 , X Craft Lite 350 , Sata or Ide to eSata or Usb , Silver : anodized aluminum with mirror finish , high qulaity mesh design for heat dissipation , stackable design , with blue led , usb 2.0 ; 225x120x38mm ; 438g
5.25" - optical		
vi-power - (also support 3.5" hdd or hdd mobilerack)		
EE-V6228MT		Vi-Power VPM-6228T 3.5" / 5.25" external enclosure , true Metal , IDE to USB 2.0, 40mm thermal controlled fan - support 5.25" or 3.5" device (with front panel + mounting bracket for 3.5" ide hdd) - also work with Vi-Power ide mobile rack
EE-V6228MH		Vi-Power VPM-6228H 3.5" / 5.25" Device Enclosure , true Metal + 3 port down stream hub , USB 2.0, 40mm thermal controlled fan - support 5.25" or 3.5" device (with front panel + mounting bracket for 3.5" ide hdd) - also work with Vi-Power ide mobile rack
EE-V62289M		Vi-Power VPM-62289 3.5" / 5.25" Device Enclosure , true Metal , IDE to USB 2.0+1394 firewire , 40mm thermal controlled fan - support 5.25" or 3.5" device (with front panel + mounting bracket for 3.5" ide hdd)

EE-V7500UD		Vi-Power VPM-7500UD standalone , built-in PSU , support 4 x 5.25" IDE device (optical drive , 3.5" IDE or mobile rack) , built-in PSU , with audio (RCA) out , USB 2.0
Vantec		
EE-V530S2	N	vantec Nexstar DX NST-530S2 , sata 5.25" to usb2.0 external enclosure with audio port , aluminum , black , 40mm cooling fan
EE-V525UF		vantec Nexstar2 NST-525UF , 5.25" external Enclosure , plastic/perspx , white , USB 2.0 + firewire ieee1394a , 40mm cooling fan
iCYDOCK CD/DVD duplicator tower		
EE-i556AP9		iCYDOCK MB566AP-9 duplicator tower , for 1 x optional duplication controller + 8 x 5.25" IDE device with removable drive tray , 2 fan , 300w psu
CCFL / Lighting peripherals		
VANTEC		
LT-VCG		vantec Green CCFL light tube, Inverter not included : to be used with vantec NXP301&305 or existing ac-inverter
LT-VCP		vantec Purple CCFL light tube, Inverter not included : to be used with vantec NXP301&305 or existing ac-inverter
ViZo		
LT-VSB		ViZo starlet CCFL DUAL light tube + AC-Inverter - Blue
LT-VSR		ViZo starlet CCFL DUAL light tube + AC-Inverter - Red
LT-VSG		ViZo starlet CCFL DUAL light tube + AC-Inverter - Green
LT-VSU		ViZo starlet CCFL DUAL light tube + AC-Inverter - UV
LT-VSRC		ViZo starlet Crystal Neon Light tube - with liquid, waving and rippling effect , with AC-Inverter - Red
LT-VSRGBC		ViZo starlet Crystal Neon Light tube - with liquid, waving and rippling effect , with AC-Inverter - Red+Green+Blue
ANTEC		
LT-AER		antec external LED light tube (30cm) - Red - sound activation with sensitivity control - usb powered
LT-AEB		antec external LED light tube (30cm) - bLue - sound activation with sensitivity control - usb powered
LT-AEMB		antec external LED , 2 x mini light tube (16cm) - blue- sound activation with sensitivity control - usb powered
LT-AEM7		antec external LED , 2 x mini light tube (16cm) - 7 colors - sound activation with sensitivity control - usb powered
LT-AiB		antec internal blue led light stick (16cm) - with external lighted switch + sound activation with sensitivity control
LT-AiU		antec internal UV led light stick (16cm) - with external lighted switch + sound activation with sensitivity control
Card Reader		
external		
CR-VMB	N	ViZO MirrorBox CR MiR-521 , 52-in-1 usb card reader with piano black mirror finish - MS , MS Micro (m2) , SDm miniSD , MicroSDHC , MMC , CF , MD , XD, SM ….
CR-V935	N	Vantec go 2.0 , UGT-CR935 , black , external usb card reader , 27x15mm ultra compact design (micro usb flash drive type design) , for MicroSD upto 4Gb
CR-V925	N	Vantec go 2.0 , UGT-CR925 , Green , 19-in-1 external usb card reader , retractable USB connector , 73x25x14.5mm compact design , for MS , MS Micro (m2) , SDHC, miniSD , MicroSDHC , MMC
CR-V920	N	Vantec go 2.0 , UGT-CR920 , Green , external 58-in-1 usb card reader , 104x58x9mm ultra slim design , for MS , MS Micro (m2) , SDHC miniSD , MicroSDHC , MMC , CF , MD , XD, SM ….

CR-V605	N	Vantec go 2.0 , UGT-MH605-BK , external 58-in-1 usb card reader with piano black mirror finish + vertical stand , 100x51x17mm ultra slim design , for MS , MS Micro (m2) , SDHC miniSD , MicroSDHC , MMC , CF , MD , XD, SM ….
CR-KMRB		Kingston FCR-MRB Black - usb card reader for miCro-SD/SDHC - mini size - 32.9x15.3x7.7mm (usb drive type)
CR-KML9		Kingston FCR-ML MobileLite 9-in-1 usb card reader for SD, SDHC, MMC, MMCplus, MMCmobile, RS-MMC, microSD, and miniSD, MMCmicro - 77.3x29.5x15.3mm
CR-KML19		Kingston FCR-HS219/1 MobileLite 19-in-1 usb card reader for CF, MD, SDHC, miniSD, microSD, MMC, microMMC , RS-MMC, MMCplus, MS, Ms pro, MS pro Duo, SM ; 91.7x69x20mm
internal		
CR-SECR4400U		Sunix ECR4400U card reader , expresscard 34 (for 34 or 54 slot) , for SD , SDHC , miniSD , miniSDHC , MMC , rs-MMC , XD , Memory Stick, Duo, Memory Stick PRO , M2
CR-GiR100		Greenpower iR-100 , 3.5" internal card reader - CF, SD/SDHC/MMC , SM, micro SD , MS/ Ms Pro Duo - black
CR-FCRV01	N	Foxconn CR-V01 , 3.5" internal 39in1 card reader - CF, SD/SDHC/MMC , SM, micro SD , MS/ Ms Pro Duo/ M2 - black
CR-SMRW620	N	Sony MRW620 3.5" internal 17in1 card reader - CF, SD/SDHC/MMC , SM, micro SD , MS/ Ms Pro Duo/ M2 - black
CR-V905i	N	Vantec ugt-cr905 , internal 58-in-1 card reader with 1 USB downstream port for 3.5" or 5.25" bay- CF, SD, SDHC, SM, MMC, MS, Ms Duo, XD - retail pack
CR-VA900SF		Vantec silver face plate for ugt-cr900 3.5" internal IDE card reader
Software		
Games		
SF-GLP		Lost Planet , pc-dvd - oem pack - to be bundled with xfx products only
SF-GARMA		ARMed Assualt , PC-DVD - compact retail pack
SF-G007QS		Activision 007 Quantum Of Solace , PC-DVD - compact retail pack
SF-GBFTB		Activision world series of poker 2008 - Battle For The Bracelets , PC-DVD - compact retail pack
SF-GCoDWAW		Activision Call Of Duty - World At War- PC-DVD - compact retail pack
SF-GD3		Activision Doom 3 - PC-CD - compact retail pack
SF-GETQW		Activision Enemy Territory Quake Wars , PC-DVD - compact retail pack
SF-GETQWC		Activision Enemy Territory Quake Wars Collector's edition , PC-DVD - compact retail pack - include extra bonus card + extra dvd
SF-GHDRR		Activision Harley-Davidson Race to the Rally , PC-CD - compact retail pack
SF-GMADE2A		Activision MADagascar Escape 2 Africa , PC-DVD - compact retail pack
SF-GMUA		Activision Marvel Ultimate Alliance PC-DVD - compact retail pack
SF-GSM3		Activision Spider-Man 3 , PC-DVD - compact retail pack
SF-GTF		Activision TransFormers the game - PC-DVD - compact retail pack
SF-GUA		Altar Ufo Afterlight , PC-DVD - compact retail pack
SF-GL		Altar Legendary , PC-DVD - compact retail pack
SF-GTTT		Ascaron Tortuga Two Treasures , PC-DVD - compact retail pack
SF-GAC1		Ascaron Collection vol1 - 3 games (patrician iii + port royale + tortuga - pirates of the new world) , PC-DVD - compact retail pack

SF-GAC2		Ascaron Collection vol2 - 3 games (darkstar one + scared gold + port royale 2) , PC-DVD - compact retail pack
SF-GS2		Ascaron Sacred2 - fallen angel , PC-DVD - compact retail pack
SF-GAiTD		Atari Alone In The Dark , PC-DVD - compact retail pack
SF-GCPCW	N	Atari codename:panzers cold war , PC-DVD - compact retail pack
SF-GEoSE	N	Atari Eve Online Special Edition , PC-DVD - compact retail pack
SF-GNWN2SoZ		Atari NeverWinter Nights 2 - Storm Of Zehir- expansion pack , PC-DVD - compact retail pack
SF-GPoTC		Bethsoft Pirates Of The Carribbean - Legend Of Jack Sparrow , PC-CD - compact retail pack
SF-GD2		Blizzard Diablo 2 , PC-CD - compact retail pack
SF-GD2E		Blizzard Diablo 2 Expansion set , PC-CD - compact retail pack
SF-GSC		Blizzard StarCraft + with extra Expansion set , PC-CD - compact retail pack
SF-GWC3		Blizzard WarCraft 3 , PC-CD - compact retail pack
SF-GWC3E		Blizzard WarCraft 3 Expansion set - frozen throne , PC-CD - compact retail pack
SF-GWoW		Blizzard World Of Warcraft , PC-DVD - lite retail pack
SF-GWoWEBC		Blizzard World Of Warcraft Expansion set - Burning Crusade , PC-CD - lite retail pack
SF-GWoWEWLK		Blizzard World Of Warcraft Expansion set - Wrath of the Lich King , require burning crusade expension set , PC-DVD - compact retail pack
SF-GWoWGC		Blizzard World Of Warcraft Game Card (60days prepaid) - lite retail pack
SF-GWoWBC		Blizzard World Of Warcraft Battle Chest - World Of Warcraft + burning crusade expansion set + strategy guide - full retail pack
SF-GEM		Cenega El Matador , PC-DVD - compact retail pack
SF-GMKA		Deepsilver Mage Kinght : Apocalypse , PC-DVD - compact retail pack
SF-GSCS		Deepsilver Stalker Clear Sky , PC-DVD - compact retail pack
SF-GWFTP		Digital reality War Front Turning Point , PC-DVD - compact retail pack
SF-GWoVUH1		G5 software : Whirlwind Of Vietnam : UH-1 , PC-DVD - compact retail pack
SF-GEFMi		Lucasarts Escape From Monkey Island , PC-CDROM - compact retail pack
SF-GGF		Lucasarts Grim Fandango , PC-CDROM - compact retail pack
SF-GLIJ		Lucasarts Lego Indiana Jones , PC-CDROM - compact retail pack
SF-GSWEAW		Lucasarts Star Wars Empire At War , PC-CDROM - compact retail pack
SF-GSWR		Lucasarts Starwars Racer , PC-CDROM - compact retail pack
SF-GAoEC		Microsoft Age Of Empires Collector's edition , include 4 games - age of empire + age of empire 2 + the rise of rome expansion pack + conquerors expansion pack , PC-DVD - compact retail pack
SF-GAoEG		Microsoft Age Of Empires Gold edition , include 2 games - age of empire + age of empire der aufstleg roms expansion pack , PC-DVD - compact retail pack
SF-GAoE3		Microsoft Age Of Empires 3 , PC-DVD - compact retail pack
SF-GAoE3WC		Microsoft Age Of Empires the WarChiefs - expansion pack , PC-DVD - compact retail pack
SF-GAoE3AD		Microsoft Age Of Empires the Asian Dynasties - expansion pack , PC-DVD - compact retail pack
SF-GAoE3G		Microsoft Age Of Empires Goled edition - (Age Of Empires 3 + the WarChiefs expansion pack) , PC-DVD - compact retail pack
SF-GAoMG		Microsoft Age Of Mythology Gold edition - age of mythology + the titan expansion pack , PC-CD - compact retail pack

SF-GCFS2		Microsoft Combat Flight Simulator 2 - Wwii pacific theater , PC-cdrom - compact retail pack
SF-GCFS3		Microsoft Combat Flight Simulator 3 - battle for europe , PC-DVD - compact retail pack
SF-GFS2		Microsoft Flight Simulator 2002 , PC-cdrom - compact retail pack
SF-GFS4		Microsoft Flight Simulator 2004 - Century of Flight , PC-cdrom - compact retail pack
SF-GFSXS		Microsoft Flight Simulator X Standard , 18 airplanes , 40 airports , 28 cities , 30+ structured missions , PC-DVD - compact retail pack
SF-GFSXD		Microsoft Flight Simulator X Delux , 24 airplanes , 45 airports , 38 cities , 50+ structured missions , with more high detail cities + airport , more airplanes included , enhanced multi-player , PC-DVD - compact retail pack
SF-GFSXE		Microsoft Flight Simulator X Expansion pack - with DX10 graphics, multiplayer race mode, new action-packed missions + content- pc-dvd
SF-GFSXG		Microsoft Flight Simulator X Gold edition - include Microsoft Flight Simulator X Delux + acceleration expansion pack
SF-GFO3		Microsoft FallOut3 , PC-DVD - compact retail pack
SF-GGoW		Microsoft Gear Of Wars , PC-DVD - compact retail pack
SF-GH2		Microsoft Halo2 for windows vista , PC-DVD - compact retail pack
SF-GRoNG		Microsoft Rise Of Nation Gold edition - Rise of Nation + thrones and patriots expansion pack , PC-CD - compact retail pack
SF-GZTCC		Microsoft Zoo Tycoon Complete Collection , include extra Endamgered Species + strategy guide , PC-DVD - compact retail pack
SF-GZT2MM		Microsoft Zoo Tycoon 2 Marine Mania - expansion pack , PC-CD - retail pack
SF-GZT2EA	**N**	Microsoft Zoo Tycoon 2 Extinct Animals - expansion pack , PC-CD - retail pack
SF-GZT2ZKC		Microsoft Zoo Tycoon 2 Zoo Keeper Collection (include Zoo Tycoon 2 + Endangered Species + African Adventure) - compact retail pack
SF-GZT2U		Microsoft Zoo Tycoon 2 Ultimate collection - include all 4 expansion set (marine mania + endangered species + extinct animals + African Adventure) - pc-DVD
SF-GGWEoTN		Ncsoft Guild Wars Eye Of The North - expansion pack , PC-DVD - retail pack
SF-GBSE		rockstargames Bully - Scholarship Edition , PC-DVD - compact retail pack
SF-GGTAiV		rockstargames Grand Theft Autio IV , PC-DVD - compact retail pack
SF-GXRX		Techland Xpand Rally Xtreme , PC-DVD - compact retail pack
SF-GAC		Ubisoft Assassins Creed , PC-DVD - compact retail pack
SF-GBA		Ubisoft Blazing Angels : squadrons of WWII , PC-DVD - compact retail pack
SF-GBA2		Ubisoft Blazing Angels 2 : secret missions of WW II , PC-DVD - compact retail pack
SF-GBGAE		Ubisoft Beyond Good And Evil , PC-DVD - compact retail pack
SF-GBiA		Ubisoft Brothers In Arms , Road To Hill 30 , PC-DVD - compact retail pack
SF-GCM9		Ubisoft Chess Master 9000 , PC-DVD - compact retail pack
SF-GCMG		Ubisoft Chess Master Grandmaster edition , PC-DVD - compact retail pack
SF-GCSi		Ubisoft CSi , PC-DVD - compact retail pack
SF-GCSi2DM		Ubisoft CSi 2 Dark Motive , PC-DVD - compact retail pack

SF-GCSi3DoM		Ubisoft CSi 3 Dimensions Of Murder , PC-DVD - compact retail pack
SF-GCSiHE		Ubisoft CSi 3 Hard Evidence , PC-DVD - compact retail pack
SF-GCSiNY		Ubisoft CSi New York , PC-DVD - compact retail pack
SF-GDMC3		Ubisoft Devil May Cry 3 - dante's awakening special edition , PC-DVD - compact retail pack
SF-GD+C		Ubisoft petz series - DogZ + CatZ - 2 games , PC-CD - compact retail pack
SF-GEW+HS	N	Ubisoft tom clancy's EndWar , PC-DVD - compact retail pack + bundled genius HS-05 gaming headset
SF-GFC		Ubisoft FarCry , PC-CD - compact retail pack
SF-GFC2		Ubisoft FarCry 2 , PC-DVD - compact retail pack
SF-GGRAW		Ubisoft Ghost Recon Advanced Warfighter , PC-DVD - compact retail pack - support Ageia Phyx PPU add on card
SF-GGRAW2		Ubisoft Ghost Recon Advanced Warfighter 2 , PC-DVD - compact retail pack - support Ageia Phyx PPU add on card
SF-GHAWX	N	Ubisoft tom clancy's H.A.W.X , PC-DVD - compact retail pack
SF-GHoMM5ToE		Ubisoft Heroes of might and magic 5 - Tribes Of the East - expansion pack , PC-DVD - compact retail pack
SF-GHoMM5G		Ubisoft Heroes of might and magic 5 Gold edition , with extra expansion set Tribes Of the East - PC-DVD - compact retail pack
SF-GiL2SFB		Ubisoft iL2 Sturmovik Forgotten Battles , PC-DVD - compact retail pack
SF-GKK		Ubisoft peter jackson's King Kong , PC-CDROM - compact retail pack
SF-Go3		Ubisoft Onimusha 3 , PC-DVD - compact retail pack
SF-GoS		Ubisoft Open Season , PC-DVD - compact retail pack
SF-GPOPTTT		Ubisoft Prince Of Persia The Two Thrones , PC-DVD - compact retail pack
SF-GPoPT		Ubisoft Prince Of Persia Trilogy (the 2 thrones + the sands of time + warrior within 3 games in one) , PC-DVD - compact retail pack
SF-GPoP4		Ubisoft Prince Of Persia 4 , PC-DVD - compact retail pack
SF-GR6V		Ubisoft Rainbow Six Vegas , PC-DVD - compact retail pack
SF-GR6V2		Ubisoft Rainbow Six Vegas 2 , PC-DVD - compact retail pack
SF-GRRR		Ubisoft Rayman Raving Rabbids , PC-DVD - compact retail pack
SF-GRE4		Ubisoft Resident Evil 4 , PC-DVD - compact retail pack
SF-GSCCT		Ubisoft Splinter Cell : Chaos Theory , PC-DVD - compact retail pack
SF-GSCPT		Ubisoft Splinter Cell : Pandora Tomorrow , PC-DVD - compact retail pack
SF-GSCDA		Ubisoft Splinter Cell : Double Agent , PC-DVD - compact retail pack
SF-GSCT		Ubisoft Splinter Cell Trilogy , PC-DVD - compact retail pack
SF-GSH3		Ubisoft Silent Hunter 3 , PC-DVD - compact retail pack
SF-GSH4		Ubisoft Silent Hunter 4 - wolves of the pacific , PC-DVD - compact retail pack
SF-GSi7		Ubisoft Scrabble Interactive 2007 , PC-DVD - compact retail pack
SF-GSTL		Ubisoft Star Trek Legacy , PC-DVD - compact retail pack
SF-GSU		Ubisoft Surf's UP , PC-DVD - compact retail pack
SF-GTMNT		Ubisoft Teenage Mutant Ninja Turtles , PC-DVD - compact retail pack
SF-GTSRoAE		Ubisoft The Settlers - Rise Of An Empire , include eastern realm mission pack , PC-DVD - compact retail pack
Microsoft		
os - windows XP		
SF-MDWXH		Microsoft Dsp Windows XP Home edition with SP2/3
SF-MDWXP		Microsoft Dsp Windows XP Professional edition with SP2/3
SF-MDWXP64		Microsoft Dsp Windows XP Professional 64bit edition

os - windows Vista	
SF-MDVSP1	Microsoft Dsp Vsita Service Pack1 on dvd
SF-MDVHB32	Microsoft Dsp windows Vista Home Basic 32bit - support 1 cpu , upto 4gb memory - with intelligent search, parent control, windows defender, ready drive, ready boost, windows media player 11, photo gallery, windows meeting space (view only), remote access desktop (only as client) - DVD
SF-MDVHB64	Microsoft Dsp windows Vista Home Basic 64bit - support 1 cpu , upto 8gb memory - with intelligent search, parent control, windows defender, ready drive, ready boost, windows media player 11, photo gallery, windows meeting space (view only), remote access desktop (only as client) - DVD
SF-MVHBU	Microsoft windows Vista Home Basic Upgrade (32bit + 64bit) , retail pack - DVD
SF-MVHB	Microsoft windows Vista Home Basic (32bit + 64bit) , retail pack - DVD
SF-MDVHP32	Microsoft Dsp windows Vista Home Premium 32bit - support 2 cpu , upto 4gb memory - with aero effect, intelligent search, parent control, windows defender, ready drive, ready boost, windows media player 11, windows media center, windows movie maker, windows DVD maker, photo gallery, windows meeting space (view only), remote access desktop - support tablet PC - DVD
SF-MDVHP64	Microsoft Dsp windows Vista Home Premium 64bit - support 2 cpu , upto 16gb memory - with aero effect, intelligent search, parent control, windows defender, ready drive, ready boost, windows media player 11, windows media center, windows movie maker, windows DVD maker, photo gallery, windows meeting space (view only), remote access desktop - support tablet PC - DVD
SF-MVHPUA	Microsoft windows Vista Home Premium Upgrade Academic Edition 32bit , retail pack - DVD
SF-MVHPU	Microsoft windows Vista Home Premium Upgrade 32bit , retail pack - DVD
SF-MVHP	Microsoft windows Vista Home Premium 32bit , retail pack - DVD
SF-MDVB32	Microsoft Dsp windows Vista Business 32bit - support 2 cpu , upto 4gb memory - with aero effect, intelligent search, windows defender, ready drive, ready boost, windows meeting space, remote access desktop - support tablet PC - DVD
SF-MDVB64	Microsoft Dsp windows Vista Business 64bit - support 2 cpu , upto 128gb memory - with aero effect, intelligent search, windows defender, ready drive, ready boost, windows meeting space, remote access desktop - support tablet PC - DVD
SF-MVBU	Microsoft windows Vista Business Upgrade (32bit + 64bit) , retail pack - DVD
SF-MVB	Microsoft windows Vista Business (32bit + 64bit) , retail pack - DVD
SF-MDVU32	Microsoft Dsp windows Vista Ultimate 32bit - support 2 cpu , upto 4gb memory - with aero effect, intelligent search, parent control, windows defender, ready drive, ready boost, windows media player 11, windows media center, windows movie maker, windows DVD maker, photo gallery, windows meeting space, remote access desktop - support tablet PC , multi-language interface - DVD

SF-MDVU64		Microsoft Dsp windows Vista Ultimate 64bit - support 2 cpu , upto 128gb memory - with aero effect, intelligent search, parent control, windows defender, ready drive, ready boost, windows media player 11, windows media center, windows movie maker, windows DVD maker, photo gallery, windows meeting space, remote access desktop - support tablet PC , multi-language interface - DVD
SF-MVUU		Microsoft windows Vista Ultimate Upgrade (32bit + 64bit) , retail pack - DVD
SF-MVU		Microsoft windows Vista Ultimate (32bit + 64bit) , retail pack - DVD
os - windows Server		
SF-MDWHS		Microsoft Dsp Windows Home Server
SF-MDWS3	R	Microsoft Dsp Windows Server 2003 with 5 users CAL - 32bit
SF-MDWS364	R	Microsoft Dsp Windows Server 2003 with 5 users CAL - 64bit
SF-MD5CWS3D	R	Microsoft Dsp 5 CAL for Windows Server 2003 - Devices - for same people's license on mutiple devices
SF-MD5CWS3U		Microsoft Dsp 5 CAL for Windows Server 2003 - Users
SF-MDWS8W		Microsoft Dsp Windows Server 2008 Web edition - 32/64bit
SF-MDWS8		Microsoft Dsp Windows Server 2008 with 5 users CAL - 32/64bit
SF-MD1CWS8U		Microsoft Dsp 1 CAL for Windows Server 2008 - users
SF-MD5CWS8U		Microsoft Dsp 5 CAL for Windows Server 2008 - Users
SF-MD5CWS8D	R	Microsoft Dsp 5 CAL for Windows Server 2008 - Devices - for same people's license on mutiple devices
SF-MDSBS3S		Microsoft Dsp Small Business Server 2003 standard - with 5 users CAL ; with windows server 2003 and exchange server 2003
SF-MDSBS3P		Microsoft Dsp Small Business Server 2003 Premium - with 5 users CAL ; with windows server 2003 and exchange server 2003 , SQL server 2000 and ISA server 2000
SF-MD5CSBS3D	R	Microsoft Dsp 5 CAL for Windows SBS (Small Business Server) 2003 - Devices - for same people's license on mutiple devices
SF-MD5CSBS3U		Microsoft Dsp 5 CAL for Windows SBS (Small Business Server) 2003 - Users
SF-MDSBS8S	N	Microsoft Dsp Small Business Server 2008 standard - with 5 users CAL - support upto 4 cpu
SF-MD5CSBS8SD	R	Microsoft Dsp 5 CAL for Windows SBS (Small Business Server) 2008 Standard - Devices - for same license on mutiple devices
SF-MD5CSBS8SU	N	Microsoft Dsp 5 CAL for Windows SBS (Small Business Server) 2008 Standard - User
SF-MDSBS8P	C	Microsoft Dsp Small Business Server 2008 Premium - with 5 users CAL - support upto 4 cpu
SF-MD5CSBS8PD	R	Microsoft Dsp 5 CAL for Windows SBS (Small Business Server) 2008 Premium - Devices - for same license on mutiple devices
SF-MD5CSBS8PU	R	Microsoft Dsp 5 CAL for Windows SBS (Small Business Server) 2008 Premium - User
application		
SF-MDWP8		Microsoft Dsp Works Plus 2008 - Microsoft works 9 + Word2003
SF-MViSiOS7		Microsoft Visio Standard 2007 - retail pack
SF-MViSiOP7		Microsoft Visio Professional 2007 - retail pack
SF-MPJ7S		Microsoft ProJect 2007 Standard - retail pack
SF-MPJ7P		Microsoft ProJect 2007 Professional - retail pack
ms office		
SF-MDoHS7		Microsoft Dsp Office Home and Student 2007 - include word, excel, powerpoint, onenote - license only - require Media Kit
SF-MoHS7		Microsoft Office Home and Student 2007 , retail pack - include word, excel, powerpoint, onenote - licensed for noncommerical use on upto 3 home PCs - CD

SF-MDoB7		Microsoft Dsp Office Basic 2007 - include word , excel , outlook - license only - require Media Kit
SF-MoS7A		Microsoft Office Standard 2007 Academic Edition , retail pack - include word , excel , outlook , powerpoint - CD
SF-MoS7U		Microsoft Office Standard 2007 Upgrade retail pack - include word , excel , outlook , powerpoint - CD
SF-MoS7		Microsoft Office Standard 2007 retail pack - include word , excel , outlook , powerpoint - CD
SF-MDoSB7		Microsoft Dsp Office Small Business 2007 - include word, excel, powerpoint , publisher , outlook with Business Contact Manager - license only - require Media Kit
SF-MoSB7U		Microsoft Office Small Business 2007 Upgrade , retail pack - include word, excel, powerpoint , publisher , outlook with Business Contact Manager - CD
SF-MoSB7		Microsoft Office Small Business 2007 , retail pack - include word, excel, powerpoint , publisher , outlook with Business Contact Manager - CD
SF-MDOP7S	N	Microsoft Dsp Office Professional 2007 prepaid - Starter Edition - 6 Months (initial pack)
SF-MDOP7S3	N	Microsoft Dsp Office Professional 2007 prepaid - 3 months renew
SF-MDoP7		Microsoft Dsp Office Prefessional 2007 - include word, excel, powerpoint , publisher , outlook with Business Contact Manager , access - license only - require Media Kit
SF-MoP7A		Microsoft Office Prefessional 2007 Academic Edition , retail pack - include word, excel, powerpoint , publisher , outlook with Business Contact Manager , access - CD
SF-MoP7U		Microsoft Office Prefessional 2007 Upgrade , retail pack - include word, excel, powerpoint , publisher , outlook with Business Contact Manager , access - CD
SF-MoP7		Microsoft Office Prefessional 2007 , retail pack - include word, excel, powerpoint , publisher , outlook with Business Contact Manager , access - CD
SF-MoU7A		Microsoft Office Ultimate 2007 Academic Edition , retail pack - include word, excel, powerpoint, publisher, outlook with Business Contact Manager, access, info path, communicator, groove, onenote, enterprise content management, electronic forms … ETC - DVD
SF-MoU7U		Microsoft Office Ultimate 2007 Upgrade , retail pack - include word, excel, powerpoint, publisher, outlook with Business Contact Manager, access, info path, communicator, groove, onenote, enterprise content management, electronic forms … ETC - DVD
SF-MoU7		Microsoft Office Ultimate 2007 , retail pack - include word, excel, powerpoint, publisher, outlook with Business Contact Manager, access, info path, communicator, groove, onenote, enterprise content management, electronic forms … ETC - DVD
Kaspersky		
SF-KoAV		Kaspersky Oem pack Anti-Virus 7.0 , with 3 new protection against new and unknown threats : hourly automated database updates + reliminary behavior analysis + On-going behavior analysis- oem pack
SF-KAV		Kaspersky Anti-Virus 7.0 , with 3 new protection against new and unknown threats : hourly automated database updates + reliminary behavior analysis + On-going behavior analysis- reatil pack

SF-KoAV3	N	Kaspersky Oem pack Anti-Virus 7.0 - 3 users pack , with 3 new protection against new and unknown threats : hourly automated database updates + reliminary behavior analysis + On-going behavior analysis
SF-KAV3		Kaspersky Anti-Virus 7.0 - 3 users pack , with 3 new protection against new and unknown threats : hourly automated database updates + reliminary behavior analysis + On-going behavior analysis- reatil pack
SF-KoiS		Kaspersky Oem pack Internet Security 7.0 , with 3 new protection against new and unknown threats : hourly automated database updates + reliminary behavior analysis + On-going behavior analysis ; Personal firewall with an IDS / IPS system ; Parental Control ; Protection from leaks of confidential data - oem pack
SF-KiS		Kaspersky Internet Security 7.0 , with 3 new protection against new and unknown threats : hourly automated database updates + reliminary behavior analysis + On-going behavior analysis ; Personal firewall with an IDS / IPS system ; Parental Control ; Protection from leaks of confidential data - reatil pack
SF-KoiS3	N	Kaspersky Oem pack Internet Security 7.0 3 users pack , with 3 new protection against new and unknown threats : hourly automated database updates + reliminary behavior analysis + On-going behavior analysis ; Personal firewall with an IDS / IPS system ; Parental Control ; Protection from leaks of confidential data
SF-KiS3		Kaspersky Internet Security 7.0 3 users pack , with 3 new protection against new and unknown threats : hourly automated database updates + reliminary behavior analysis + On-going behavior analysis ; Personal firewall with an IDS / IPS system ; Parental Control ; Protection from leaks of confidential data - reatil pack
symantec		
oem pack		
SF-SONAV		Symantec Oem pack - Norton Anti-Virus 2009 for windows Vista - only sold with hardware
SF-SONiS		Symantec Oem pack - Norton Internet Security 2009 for windows Vista - with antivirus , personal firewall , privacy control antispam , parental control - only sold with hardware
SF-SON360V2	N	Symantec Oem pack - Norton360 V2 all-in-one security , with 2GB of secured online storage , pc security + transcation security + backup and restore + PC tuneup ; for up to 3 household PCs - retail pack - for up to 3 household PCs
retail pack		
SF-SNG		Symantec Norton Ghost 14.0 - advanced backup and recovery for your PC - retail pack
SF-SNAV93	N	Symantec Norton Anti-Virus 2009 , 3 users pack - reatil pack
SF-SNiS83U		Symantec Norton Internet Security 2008 Upgrade , 3 users pack - with antivirus , personal firewall , antispyware , antiphishing , 2-way firewall , rootkit detection , intrusion prevention - retail pack
SF-SNiS83		Symantec Norton Internet Security 2008 , 3 users pack - with antivirus , personal firewall , antispyware , antiphishing , 2-way firewall , rootkit detection , intrusion prevention - retail pack
SF-SNiS93U	N	Symantec Norton Internet Security 2009 Upgrade , 3 users pack - with antivirus , personal firewall , antispyware , antiphishing , 2-way firewall , rootkit detection , intrusion prevention - retail pack
SF-SNiS93	N	Symantec Norton Internet Security 2009 , 3 users pack - with antivirus , personal firewall , antispyware , antiphishing , 2-way firewall , rootkit detection , intrusion prevention - retail pack

SF-SN360V2U		Symantec Norton360 V2 Upgrade - all-in-one security , with 2GB of secured online storage , pc security + transcation security + backup and restore + PC tuneup ; for up to 3 household PCs - retail pack - for up to 3 household PCs
SF-SN360V3	N	Symantec Norton360 V3 all-in-one security , with 2GB of secured online storage , pc security + transcation security + backup and restore + PC tuneup ; for up to 3 household PCs - retail pack - for up to 3 household PCs
SF-SN360V2P		Symantec Norton360 V2 Premier all-in-one security , with 10GB of secured online storage pc security + transcation security + backup and restore + PC tuneup ; for up to 3 household PCs - retail pack - for up to 3 household PCs
SF-SEP5	N	Symantec EndPoint 11.0 , 5 users , with antivirus, antispyware, firewall, intrusion prevention, device control , for desktops and servers - reatil pack
SF-SEP10	N	Symantec EndPoint 11.0 , 10 users , with antivirus, antispyware, firewall, intrusion prevention, device control , for desktops and servers - reatil pack
SF-SEP25	R	Symantec EndPoint 11.0 , 25 users , with antivirus, antispyware, firewall, intrusion prevention, device control , for desktops and servers - reatil pack
KeyBoard / numeric KEypad		
Vizo		
KE-VMK	N	Vizo Master Keypad MKD-100 usb numeric keypad with extra dual 0 keys
ASUS		
KE-AKM631	N	Asus KM-631 keyboard+mouse desktop , Black , keyboard (ps2/usb) , 3 button 1000dpi optical mouse (usb)
Belkin		
KE-BN52TE		Belkin (designed by Razer) N52TE gaming keypad : adjustable soft-touch wrist pad , easily toggle between 3 keymap states , programmable 8-way thumb pad with removable joystick , 15 fully programmable keys , blue backlit led
Targus		
KE-TAKP01EU	N	Targus AKP01EU wireless stow-n-go numeric keypad
KE-TPAKP003E		Targus PAKE003E wireless numeric keypad + mini wireless optical mouse
Enermax		
KE-EAB		Enermax Aurora aluminum kb , Black , heavy duty with audio in/out for headset , 2 x usb downstream hub , hairline brushed aluminum design , leading responsive scissors keys , blue LED indicator , ultra-flat , zero-degree tilt , extended wrist rest , polish towel included - usb
KE-EAS		Enermax Aurora aluminum kb , Silver , heavy duty with audio in/out for headset , 2 x usb downstream hub , hairline brushed aluminum design , leading responsive scissors keys , blue LED indicator , ultra-flat , zero-degree tilt , extended wrist rest , polish towel included - usb
Razer		
KE-RABB	C	Razer Arctosa Black+Black text print gaming keyboard , with touch control media keys , programmable keys with macro capability , on-board memory for 10 different On-the-fly gaming profile , 1000Hz Ultrapolling , 1ms response time , detachable palmrest
KE-RABS		Razer Arctosa Black+Silver text print gaming keyboard , with touch control media keys , programmable keys with macro capability , on-board memory for 10 different On-the-fly gaming profile , 1000Hz Ultrapolling , 1ms response time , detachable palmrest

KE-RL		Razer Lycosa gaming keyboard , with non-slip rubber finish , blue backlight Illumination on all keys with WASD , touch control media keys , programmable keys with macro capability , on-board memory for 10 different On-the-fly gaming profile , 1000Hz Ultrapolling , 1ms response time , detachable palmrest , with headphone-out + mic-in audio jacks , 1 x usb downstream port
KE-RLM		Razer Lycosa Mirror special edition gaming keyboard , with High gloss mirror finish keytop , non-slip rubber finish , blue backlight Illumination on all keys with WASD , touch control media keys , programmable keys with macro capability , on-board memory for 10 different On-the-fly gaming profile , 1000Hz Ultrapolling , 1ms response time , detachable palmrest , with headphone-out + mic-in audio jacks , 1 x usb downstream port
KE-RPT		Razer Pro|Type keyboard , pearl white with universal iPod dock , 10 programmable gaming hot keys , with image buttons (rotate , zoom in/out , 100%) + multimedia buttons , with Headphone-out and microphone-in jacks , 2 x usb downstream port
KE-RT		Razer Tarantula gaming keyboard , with 32kb on-board memory for 5 different On-the-fly gaming profile (upto 100 customable profiles) , 10 programmable gaming hot keys (50 combination in 5 different gaming profile) , include 10 custom FPS keys (with logo) + keys removal tool (for u to place custom key wherever you like on keyboard) , with image buttons (rotate , zoom in/out , 100%) + multimedia buttons , with Headphone-out and microphone-in jacks , 2 x usb downstream port , with battledock for add-on accessories (battleeye , battlelight .. etc)
KE-RABL	N	Razer Battle Light - add on blue E-led module for Razer Tarantula , swivelable
Zboard		http://www.zboard.com/us/index.html
KE-ZMS	N	Zboard MERC stealth gaming keyboard ; 3 color (red, blue, purple) illumination on all keys with levels of brightness (subtle, ambient, intense, off) , with audio jacks for headsets and microphones , 13 multimedia keys + 34 gaming keys (butterfly layout + 11 degree ergonomic layout) , phantom-keys elimination capabilities delivers up to 7 simultaneous keystrokes
KE-ZKCS		Zboard limited edition gaming keyset for CounterStrike
KE-ZKBF2142		Zboard limited edition gaming keyset for Battle Field 2142
KE-ZKGWF		Zboard limited edition gaming keyset for GuildWars Faction or GuildWars
KE-ZKBME2		Zboard limited edition gaming keyset for the lord of the ring ; Battle for Middle Earth 2
KE-ZKAoE3		Zboard limited edition gaming keyset for Age Of Empire 3
KE-ZKCoD2		Zboard limited edition gaming keyset for Call Of Duty 2
KE-ZKBF2		Zboard limited edition gaming keyset for Battle Field 2
KE-ZKEQ2		Zboard limited edition gaming keyset for Ever Quest 2
KE-ZKDM3		Zboard limited edition gaming keyset for Doom 3
KE-ZKMoH		Zboard limited edition gaming keyset for Medal Of Honor : pacific assault
KE-ZKMW		Zboard keyset for Microsoft Word , 112 labeled Microsoft® Word default shortcuts , color coded, pre-programmed shortcuts , 12 Bar Lock keys for key Microsoft® Word commands , 16 Pad Lock keys for additional Microsoft® Word commands
KE-ZKME		Zboard keyset for Microsoft Excel , 104 labeled Microsoft® Excel default shortcuts , color coded, pre-programmed shortcuts , 17 Bar Lock keys for key Microsoft® Excel commands , 12 Pad Lock keys for additional Microsoft® Excel commands

KE-ZKMo		Zboard keyset for Microsoft Office , 55 labeled Microsoft® Office default shortcuts , color coded, pre-programmed shortcuts , 12 Bar Lock keys for key Microsoft® Office commands , 16 Pad Lock keys for additional Microsoft® Office commands
KE-ZKPS		Zboard keyset for photoshop , 109 default labeled Adobe® Photoshop® default commands , color coded, pre-programmed shortcuts , 12 Bar Lock commands for main actions , 16 Pad Lock commands for quick and easy Layers control
KE-ZK3S		Zboard keyset for 3DS MAX, 134 labeled 3ds max™ commands , color coded, pre-programmed shortcuts , 12 Bar Lock keys for Creating commands , 19 Pad Lock keys for Modifiers
KE-ZKMD		Zboard keyset for Macromedia Dreamweaver MX , 143 labeled Macromedia Dreamweaver MX default commands , color coded (Blue - Ctrl+Shift; Red - Ctrl; Green - Ctrl+Alt; Yellow - Shift) , pre-programmed shortcuts , 16 Pad Lock commands for quick and easy Layers control
KE-ZKMF		Zboard keyset for Macromedia Flash MX , 115 labeled Macromedia Flash MX default commands , color coded (Black - Direct; Blue - Ctrl+Shift; Red - Ctrl; Green - Ctrl+Alt) , pre-programmed shortcuts , 12 Bar Lock keys for Creating commands , 18 Pad Lock commands for quick and easy Layers control

Targus		
KE-TPAKP004E		Targus PAKE004E usb numeric keypad with 2 port usb hub
KE-TPAKP003E		Targus PAKE003E wireless numeric keypad + mini wireless optical mouse

Microsoft		http://www.microsoft.com/hardware/mouseandkeyboard/default.mspx
keyboard only		http://www.microsoft.com/hardware/mouseandkeyboard/productlist.aspx?type=Keyboard
KE-M400D	N	Microsoft wired keyboard 400 , ivory , Dsp pack , usb
KE-M400BD	N	Microsoft wired keyboard 400 , Black , Dsp pack , usb
KE-M500BD		Microsoft keyboard 500 , Black , Dsp pack , wired , hotkeys : 5+5 - ps2
KE-M500B		Microsoft keyboard 500 , Black , wired , hotkeys : 5+5 - ps2 - retail pack
KE-M500		Microsoft keyboard 500 , ivory , wired , hotkeys : 5+5 - ps2 - retail pack
KE-M600B	N	Microsoft keyboard 600 , Black , wired , 5 hotkeys - usb - retail pack
KE-MCC2D	N	Microsoft Comfort Curve keyboard 2000 Dsp , comfort curve design keys , ultra thin profile - black , usb
KE-MCC2		Microsoft Comfort Curve keyboard 2000 , comfort curve design keys , ultra thin profile - black , usb - retail pack
KE-MDM3000	N	Microsoft Digital Media 3000 keyboard , zoom slider , windows Flip 3D Key , hotkeys : 7+15 - black + silver , ps2+usb - retail pack
KE-MNE4		Microsoft Natural Ergonomic 4000 , reverse slope for more rest on wrist , cushioned palmrest , comfort curve design keys , zoom slider , hotkeys : 4+12 - black + silver , usb - retail pack
KE-MRECLUSA		Microsoft Reclusa gaming keyboard powered by Razer , with blue ambient backlighting keys , 32kb on-board memory for 5 different On-the-fly gaming profile , 6 programmable gaming hot keys + two 360 degree jog-dials, 2 x usb downstream port , detachable palm rest , smart cabling management system
KE-MSX6D	N	Microsoft Sidewinder X6 gaming keyboard , Dsp , with detachable numeric keypad / gaming keypad (positioned at right or left side of the kb) , 30/90 programmable gaming hot keys + two 360 degree jog-dials

KE-MSX6	N	Microsoft Sidewinder X6 gaming keyboard , with detachable numeric keypad / gaming keypad (positioned at right or left side of the kb) , 30/90 programmable gaming hot keys + two 360 degree jog-dials - retail pack
desktop - cord		http://www.microsoft.com/hardware/mouseandkeyboard/productlist.aspx?type=Keyboard&AdditionalType=Sets
KE-MBBVPD		Microsoft Basic Black Value Pack , Dsp , hotkeys : 3 , ps2 multimedia keyboard , 3 button optical mouse (ps2+usb)
KE-MCC2VPD		Microsoft Comfort Curve 2000 Value Pack DSP , black , hotkeys : 4+6 - multimedia keyboard (usb) + wheel mouse optical (usb)
KE-MBVPD		Microsoft Black Value Pack , Dsp , zoom slider , hotkeys : 3+12 , ps2+usb digital media keyboard , 3 button optical mouse (ps2+usb)
KE-MBHP		Microsoft Business Hardware Pack , zoom slider , hotkeys : 3+12 , ps2+usb digital media keyboard , 5 button intelli mouse optical (ps2+usb)
KE-MEVPD		Microsoft Ergonomic Value Pack , DSP , reverse slope for more rest on wrist , cushioned palmrest , comfort curve design keys , zoom slider , 3 button ps2+usb optical mouse with 4way tilt wheel - black + silver , ps2+usb - dsp pack
desktop - cordless		http://www.microsoft.com/hardware/mouseandkeyboard/productlist.aspx?type=Keyboard&AdditionalType=Sets
KE-MWoD700D		Microsoft Wireless Optical Desktop 700 , Dsp , 3 buttons wireless mouse , hotkeys : 4+6 - black , usb
KE-MWoD700	N	Microsoft Wireless Optical Desktop 700 , 3 buttons wireless mouse , hotkeys : 4+6 - black , usb - retail pack
KE-MWoD1		Microsoft Wireless Optical Desktop 1000 , 3 buttons wireless mouse (400dpi / 6000fps) , hotkeys : 8+9 - black , usb - retail pack
KE-MWMD1	N	Microsoft Wireless Media Desktop 1000 , 3 buttons wireless mouse (1000dpi / 6000fps) , hotkeys : 7+12 - black , usb - retail pack
KE-MWoD2		Microsoft Wireless Optical Desktop 2000 , comfort curve design keys , 3 buttons wireless mouse , hotkeys : 4+5 - black , usb - retail pack
KE-MWoD3D		Microsoft Wireless Optical Desktop 3000 , Dsp , comfort curve design keys , 3 buttons wireless mouse , hotkeys : 4+6 - black , usb
KE-MWoD3	N	Microsoft Wireless Optical Desktop 3000 , comfort curve design keys , 3 buttons wireless mouse , hotkeys : 4+6 - black , usb - retail pack
KE-MWLD5		Microsoft Wireless Laser Desktop 5000 , with bundled microsoft digital home standard software , cushioned palmrest , comfort curve design keys , hotkeys : 6+19 keys , zoom buttoms , 5 buttons wireless mouse with 4-way scrolling + magnifier - black + silver , usb - retail pack
KE-MNWED7		Microsoft Natural Wireless Ergonomic Desktop 7000 , ultra-thin comfort curve design keys , reverse slope for more rest on wrist , cushioned palmrest , hotkeys : 4+11 keys , battery status indicator , 5 buttons laser mouse with 4-way scrolling + magnifier - silver+black , usb - retail pack
KE-MWLD6V2D		Microsoft Wireless Laser Desktop 6000 V2 , Dsp, ultra-thin comfort curve design keys , reverse slope for more rest on wrist , cushioned palmrest , hotkeys : 6+20 keys (with zoom , gadget , windows live call buttons) , battery status indicator , 5 buttons laser mouse with 4-way scrolling + magnifier - silver+black , usb

KE-MWLD6V2		Microsoft Wireless Laser Desktop 6000 V2 , ultra-thin comfort curve design keys , reverse slope for more rest on wrist , cushioned palmrest , hotkeys : 6+20 keys (with zoom , gadget , windows live call buttons) , battery status indicator , 5 buttons laser mouse with 4-way scrolling + magnifier - silver+black , usb - retail pack
KE-MWLD6V3		Microsoft Wireless Laser Desktop 6000 V3 , translucent border Inspired by vista aero effect , with Flip-3D key , ultra-thin comfort curve design keys , reverse slope for more rest on wrist , cushioned palmrest , battery status indicator , 5 buttons laser mouse with 4-way scrolling + magnifier - silver+black , usb - retail pack
KE-MWLD7	N	Microsoft Wireless Laser Desktop 7000 , with recharging station for mouse , comfort curve design keys , hotkeys : 6+14 keys (with 3x touch-sensitive keys) , battery status indicator , 5 buttons rechargable laser mouse with 4-way scrolling + magnifier + Flip 3D - black , usb - retail pack
KE-MWED7		Microsoft Wireless Entertainment Desktop 7000 , bluetooth , black+gray+brushed aluminum , ultra-thin comfort curve design keys , with navigation pad , hotkeys : 6+20 keys (with zoom , gadget , windows live call buttons) , battery status indicator , 5 buttons rechargable laser mouse with 4-way scrolling + magnifier - usb - retail pack
KE-MWED8		Microsoft Wireless Entertainment Desktop 8000 , bluetooth , silver+gray+brushed aluminum , rechargable backlit blue led kb , ultra-thin comfort curve design keys , with navigation pad , hotkeys : 6+20 keys (with zoom , gadget , windows live call buttons) , battery status indicator , 5 buttons rechargable laser mouse with 4-way scrolling + magnifier - usb with 4 port usb hub - retail pack

Logitech	http://www.logitech.com/index.cfm/products/productlist/ZA/EN,crid=2200&categoryid=428
keyboard only - corded	
KE-LoVB	Logitech 967648 Oem Value keyboard , Black - ps2 - oem pack
KE-LoD250B	Logitech 967642 Oem delux 250 keyboard , black - ps2 - oem pack
KE-LoD250UB	Logitech 967647/967738 Oem delux 250 keyboard , black - usb - oem pack
KE-Loi350	Logitech 967718 Oem internet 350 keyboard , 8 hot keys , ivory - ps2 - oem pack
KE-Loi350B	Logitech 967674 Oem internet 350 keyboard , 8 hot keys , Black - ps2 - oem pack
KE-Loi350UB	Logitech 967740 Oem internet 350 keyboard , 8 hot keys , Usb , Black - oem pack
KE-LoUX	Logitech 920-000173 Oem UltraX premium media keyboard , 6 hot keys , silver+black , flat profile and flat notebook-style - usb - oem pack
KE-LC200B	Logitech 968019-0100 Classic keyboard 200 , Black , with elegant polished design , spill-resistant , UV coated key printing - USB - retail pack
KE-LM	Logitech 967560 Media , black , 12 hot keys , extra F1-F12 function keys , ultra flat zero degree tilt design - ps2 - retail pack
KE-LUFB	Logitech 967653 Ultra-Flat keyboard , Black , ultra-low profile , compact size (40cm) - ps2+usb - retail pack
KE-LM600	Logitech 920-000046 Media keyboard 600 , black , with volumn control dial , extra F1-F12 function keys , ultra flat zero degree tilt design - usb - retail pack

KE-LW	N	Logitech 920-000351 Wave keyboard , contoured + wave keys design , cushioned+contoured palm rest , with audio cable management , programmable F-Keys , black - usb
KE-LG11		Logitech 967929 G11 gaming keyboard , backlit keys with 3 level brightness , with 18 programmable game keys , media keys , with detachable palmrest
KE-LG15		Logitech 920-000367 G15 gaming keyboard , foldable backlit LCD shows you crucial information during game play , Backlit keys with 3 level brightness , with 18 programmable game keys , media keys , with detachable palmrest - usb
KE-LG13	C	Logitech 920-000947 G13 avanced gameboard , with high-visibility gamepanel LCD , naturally contoured design , programmable mini-joystick under thumb , onboard memory for gaming profile , quick macros , 25 programmable keys, with palmrest - usb
KE-Li	N	Logitech 920-001175 Illuminated kb , with laser-etched white backlit keys , ultra-thin, 9.3 mm profile , transparent frame , with soft-touch palmrest - usb
KE-LG19	C	Logitech 920-000947 G19 gaming keyboard , tiltable color gamepanel LCD (320x240) shows you crucial information during game play , backlit keys with 3 level brightness + 5 selectable colors , with 12 programmable game keys with 3 macros per key, upto 5 multi-key input , built-in cable management , with detachable palmrest - usb + usb downstream hub
keyboard only - cordless		
KE-LCNP		Logitech 920-000222 Cordless Number Pad for notebook , snap-in receiver , with protective pouc + 3 hotkeys - usb
KE-LDN	C	Logitech 920-001215 Dinono kb for Notebooks , Cordless , with battery life indicator , palmrest - usb
KE-LAC		Logitech 920-000413 Alto Cordless , full-size kb for notebook (angle adjustable to line-up lcd to eye level) , foldable , with LED dashboard , built-in 3 port usb downstream hub , cable management system) , with palmrest - usb
KE-LDM	N	Logitech 920-000587 DiNovo Mini - bluetooth 2.0 upto 10m , 152x90x27mm palm-sized mini-keyboard with 63 backlight keys 2 colors scheme (dual purpose : orange for touch pad / green for MCE) , with transparent protection cover , black , usb , rechargeable Li-ion batteries - for PC or PS3
KE-LDE		Logitech 967685 DiNovo Edge , with TouchDisc - touch sensitive for scrolling + PerfectStroke micro-scissors mechanism , backlit stealth controls (touch sensitive) , vertical stand charging station , bluetooth2.0 , black + silver - usb
desktop (kb+mouse) - cordless		
KE-LoCDD650		Logitech 967741 Oem Cordless Desktop Delux 650 , beige , (cordless kb+800dpi mouse) , 3 hot keys , low-profile keyframe , black - usb
KE-LoCDD660B	N	Logitech 920-000463 Oem Cordless Desktop Delux 660 , Black , (cordless kb+800dpi mouse+tilt) , 3 hot keys , low-profile keyframe , black - usb
KE-LoCDi1500		Logitech 967743 Oem Cordless Desktop Internet 1500 (cordless kb + LX7 5 buttons 1000dpi laser mouse) , 8 hot keys , black - usb
KE-LoCD1500R		Logitech 920-000547 Oem Cordless Desktop 1500 Rechargable (cordless kb + rechargable 1000dpi laser mouse) , 8 hot keys , black - usb
KE-LoCDP2400		Logitech 967744 Oem Cordless Desktop Pro 2400 (cordless kb+ LX5 wireless mouse) mouse with battery-saving Invisible Light + 4 ways tilt wheel plus zoom + battery indicator light , power on/off switch on both kb+mouse , 14 hot keys , black - usb

KE-LCDEX100	N	Logitech 920-000916 Cordless Desktop EX100 (cordless kb+1000dpi mouse) , enhanced function keys , black - usb
KE-LCDEX110		Logitech 967561 Cordless Desktop EX110 (cordless kb+800dpi mouse) , enhanced function keys , black - keyboard : usb + ps2 / mouse : ps/2
KE-LCDS510		Logitech 967557 Cordless Desktop S510 , black silver , encrypted, secure cordless , ultra-flat profile with zero-degree tilt , programmable F-Keys , media controls with new shuffle hotkey at right hand side , photo rotate+zoom in/out ate left hand side , battery indicator on keyboard , palmrest , LX5 mouse with tilt wheel plus zoom - usb + ps2
KE-LCDS520	N	Logitech 920-001013 Cordless Desktop S520 , black silver , encrypted, secure cordless , ultra-flat profile with zero-degree tilt , programmable F-Keys , media controls with new shuffle hotkey at right hand side , battery indicator on keyboard , palmrest , LX5 mouse with tilt wheel plus zoom - usb
KE-LCDS530		Logitech 967664 Cordless Desktop S530 for MAC , white , with 2 dedicated one-touch controls for Mac , encrypted, secure cordless , ultra-flat profile with zero-degree tilt , programmable F-Keys , media controls with new shuffle hotkey at right hand side , photo rotate+zoom in/out ate left hand side , battery indicator on keyboard , palmrest , MX600 mouse with tilt wheel plus zoom - usb + ps2
KE-LCDLX710L		Logitech 967670 Cordless Desktop LX710 Laser (cordless kb+ LX7 c/less laser mouse) , ultra-flat profile with zero-degree tilt , zoom in/out on kb , 18 extra keys, mouse (LX7) with barrery indicator , web forward/backward, tilt wheel tilt with zoom ; black + silver - usb
KE-LCDCL		Logitech 967692 Cordless Desktop Comfort Laser , split-key natural design (cordless kb+ mx600 cordless laser mouse) , detachable soft-touch palm rest , zero-degree tilt , black - ps2/usb
KE-LCDMX3200L		Logitech 967688 Cordless Desktop MX3200 Laser (cordless kb+ mx600 cordless laser mouse) , Lcd display , AgION™ antimicrobial technology , soft-touch palm rest , Dynamic search and zoom , SecureConnect technology , programmable F-Keys , zero-degree tilt , mouse with DocFlip , battery indiciator, black - ps2/usb
KE-LCDW		Logitech 920-000292 Cordless Desktop Wave , contoured + wave keys design , (cordless kb+ LX8 cordless laser mouse) , cushioned+contoured palm rest , programmable F-Keys , battery indiciator, black - usb
KE-LCDEC		Logitech 967689 Cordless Desktop EasyCall (EasyCall cordless kb + mx600 cordless laser mouse + with bundled EasyCall speakphone , interchat chat headset) , AgION™ antimicrobial technology , soft-touch palm rest , SecureConnect technology , programmable F-Keys , zero-degree tilt , mouse with DocFlip , battery indiciator, black - ps2/usb
KE-LCDMX5000		Logitech 967558 Cordless Desktop MX5000 LASER , bluetooth wireless , with Lcd display (for IM / email messages , view application information, date and time, caps lock status ..) touch-sensitive media control (microsoft media center ready) , mx1000 laser bluetooth rechargable mouse (800dpi , 5.8MP , with Illuminated 4-level battery indicator + recharge station) , black + metallic blue , usb

KE-LCDMX5500R	N	Logitech 920-000458 Cordless Desktop MX5500 Revolution , bluetooth wireless , with Lcd display (for IM / email messages , view application information, date and time, caps lock status ..) touch-sensitive media control (microsoft media center ready) , MX Revolution duall-wheel bluetooth rechargable mouse , black , usb
KE-LCDWP	N	Logitech 920-000292 Cordless Desktop Wave Pro , contoured + wave keys design , (cordless kb+ Mx1100 cordless laser mouse) , cushioned+contoured palm rest , programmable F-Keys , battery indiciator, black - usb
KE-LDCD		Logitech 967428 DiNovo Cordless Desktop for notbooks - ultra flat cordless kb+ mouse + detached numeric keypad with LCD display (with media + volumn control ; also works as standalone calcualtor , PC remote control , incoming email/IM alert) , black/silver , usb+ps2
KE-LDMDL		Logitech 967562 DiNovo Media Desktop Laser for notbooks - ultra flat cordless kb+ mx1000 laser for bluetooth , 800dpi , 5.8mp , with Illuminated 4-level battery indicator + recharge station + detached media pad with LCD display (works as standalone calcualtor , PC remote control , incoming email/IM alert) , bluetooth wireless hub as bluetooth center to connect other bluetooth device , black + dark blue , works as stand , usb+ps2

Mouse and mouse prepherial

mouse prepherial

PR-ZMP1000	N	Zalman MP1000 gaming mouse pad , high density poly jersey for smooth and slick finish , 400x300x3mm - retail pack
PR-CMQ01KL	C	Choiix c-MQ01-KL 3in1 mouse Pad for PC or 12"-17" notebook , work as mouse pad / laptop screen protectror / laptop duster , 225x170mm - retail pack
PR-CDSMP		Coolermaster R8-PEA-DUAK-GP Dual-Sided Mouse Pad , Anodized Aluminum mousing surfaces , anti-reflective , abrasion resistant hard coat , 330x265x2.5mm - retail pack
PR-MS822G		Moby S-822 silcon mouse pad , luminous light green - 2mm ultra thin reduce wrist burden
PR-MS821L		Moby S-821 silcon mouse pad , luminous blue - 2mm ultra thin reduce wrist burden
PR-MS823G		Moby S-823 silcon optical mouse pad , gray - 2mm ultra thin reduce wrist burden
PR-MS721S		Moby S-721 optical glass mouse pad , silver , 21x17x0.5cm ; equiped with high-speed silent mouse keeper to reduce friction force of mouse
PR-MS722B		Moby S-722 optical glass mouse pad , black , 21x17x0.5cm ; equiped with high-speed silent mouse keeper to reduce friction force of mouse
PR-MS779B		Moby S-779 optical glass mouse pad , black , 205x247x5mm ; equiped with high-speed silent mouse keeper to reduce friction force of mouse
PR-MS775T		Moby S-775 optical glass mouse pad , Transparent , 205x247x5mm ; dual purpose surface - rough (low sensitivity) or exquiustie (high sensitivity) ; equiped with high-speed silent mouse keeper to reduce friction force of mouse
PR-ZZ		Zboard Z-fragmat - gaming mouse pad - Non slip under-padding , 1.8mm slimprofile , permium gliding surfaces, 300x240mm
PR-ZV		Zboard Vanguard : saga of heros fragmat - gaming mouse pad - Non slip under-padding , 1.8mm slimprofile , permium gliding surfaces, 300x240mm

PR-ZEQ2		Zboard EverQuest II : rise of kunark : saga of heros fragmat - gaming mouse pad - Non slip under-padding , 1.8mm slimprofile , permium gliding surfaces, 300x240mm
PR-ZDoD		Zboard Day of Defeat - gaming mouse pad - Non slip under-padding , 1.8mm slimprofile , permium gliding surfaces, 300x240mm
PR-ZWOWEC		Zboard world of warcarft Eternal Conflict fragmat - gaming mouse pad - Non slip under-padding , 1.8mm slimprofile , permium gliding surfaces, 300x240mm
PR-RGCo	N	Razer Goliathus Control edition Omega size , for lower RPG/RTS games , heavily textured weave , rubber base for secure grip on smooth surface , 270x215x4mm - retail pack
PR-RGCS	N	Razer Goliathus Control edition Standard size , for lower RPG/RTS games , heavily textured weave , rubber base for secure grip on smooth surface , 355x254x4mm - retail pack
PR-RGCA	N	Razer Goliathus Control edition Alpha size , for lower RPG/RTS games , heavily textured weave , rubber base for secure grip on smooth surface , 444x355x4.3mm - retail pack
PR-RGSo	N	Razer Goliathus Speed edition Omega size , for lower RPG/RTS games , advanced cloth weave for unbridled speed and effortless Control , 270x215x4mm - retail pack
PR-RGSS	N	Razer Goliathus Speed edition Standard size , for lower RPG/RTS games , advanced cloth weave for unbridled speed and effortless Control , 355x254x4mm - retail pack
PR-RGSA	N	Razer Goliathus Speed edition Alpha size , for lower RPG/RTS games , advanced cloth weave for unbridled speed and effortless Control , 444x355x4.3mm - retail pack
PR-RXMRB		Razer eXact Mat+Rest , Black , include gel-filled wrist rest , two-sided for control or speed , Anodized Aluminum mousing surfaces , anti-reflective , abrasion resistant hard coat , 330x265x2.5mm - retail pack
PR-RPSW		Razer ProSloution White , two-sided for control+speed , Anodized Aluminum mousing surfaces , anti-reflective , abrasion resistant hard coat , 330x265x2.5mm - retail pack
PR-RD	N	Razer Destructor , Razer Fractal™ textured surface with gunmetal coating , optimized to improve gaming-grade mouse , non-slip rubber base for frim grip on smooth surface , with reinforced carry case , 350x280x2.3mm - retail pack
PR-RDW	C	Razer Destructor White special edition , Razer Fractal™ textured surface with gunmetal coating , optimized to improve gaming-grade mouse , non-slip rubber base for frim grip on smooth surface , with reinforced carry case , 350x280x2.3mm - retail pack
PR-RNPMB		Razer NeoPrene Mat pack - Black , protection + carry bag for eXactMat mouse pad - retail pack
PR-RNPMW		Razer NeoPrene Mat pack - White , protection + carry bag for ProSloution White mouse pad - retail pack
Mo-RALPB		Razer Lan Pack Black - neoprene mouse carry bag
Mo-RALPW		Razer Lan Pack White - neoprene mouse carry bag
Mo-RAA		Razer Amardillo mouse cable management system - prevents unwanted mouse movements caused by long wires
Cyber-e-sport		
Mo-Co	N	Cyber-e-sport Orbita - wireless 3D mouse/input device , rechargable with recharging station , for 2d/3d application , 8000dpi , continuous 360º scroll/jog wheel, 4 buttons (horizontal , push , squeeze , orientation) - also for mac
APC		

Mo-ABioM34	N	APC BioM34-ec - optical wheel mouse with touch biometric pod password manager (Fingerprint Reader) - usb - to replace the type-in of password
HP		
Mo-HRJ316AA		HP RJ316AA bluetooth pc card mouse , pcmcia / pc card card size , can be stored + charged in the pc card / pcmcia slot , with kickstand for the usage as presenter
Zalman		
Mo-ZFG1000		Zalman FG1000 FPSGUN gaming mouse , gun type design optimized for FPS Gaming ; front located optical sensor allowing large/quick manipulation from small hand movements , on-the-fly switching 400/800/1600/2000dpi optical with different color led , 6400 FPS , 40iPS (Inch Per Sec) , 15G acceleration , 16bit ultra-data path , OMRON trigger buttons , 5 programable buttons , non-slip rubberized - usb - retail pack
Zboard		
Mo-ZR		Zboard Reaper gaming mouse , black with orange light , on-the-fly switching 400/800/1600dpi optical , 6469 FPS , 40iPS (Inch Per Sec) , 7 programable buttons , non-slip rubberized - usb - retail pack
Mo-ZRE		Zboard Reaper Edge gaming mouse , black with orange light , on-the-fly switching 800/1200/1600/3200dpi optical , 6469 FPS , 45iPS (Inch Per Sec) , 5 programable buttons , non-slip rubberized - usb - retail pack
Creative		http://www.creative.com/products/welcome.asp?category=10
Mo-CF1010		Creative Fatal1ty 1010 gaming mouse , interchangable Modular Weight System (3.5/11/26 gram) , 400/800/1600 cpi , 15G acceleration , 5.8MP per sec , Teflon mouse feet , 5 buttons , optical - usb - retail pack
3d connexion		
Mo-3SN		3dconnexion Space Navigator personal edition - 3d mouse/input device for 3d application , pan+zoom+rotate the 3d model , 2 programmable buttons , 2.99"x2.99"x2.17" - also support linux + mac / supports only noncommercial use - 30 days licensed software
Mo-3SNN		3dconnexion Space Navigator for Notebook - portable 3d mouse/input device for 3d application , pan+zoom+rotate the 3d model , 2 programmable buttons , 2.68"x2.68"x1.81" , with - also support linux + mac - with full licensed software
Mo-3SE		3dconnexion Space Explorer - 3d mouse/input device for 3d application , pan+zoom+rotate the 3d model , integrated keypad with palmrest - upto 15 programmable buttons , also support unix + linux
Mo-3SP		3dconnexion Space Pilot - 3d mouse/input device for 3d application , pan+zoom+rotate the 3d model , integrated keypad with Lcd + palmrest - upto 21 programmable buttons , also support unix + linux
Razer		http://www.razerzone.com/Products/Gaming-Mice/
Mo-RALPB		Razer Lan Pack Black - neoprene mouse carry bag
Mo-RALPW		Razer Lan Pack White - neoprene mouse carry bag
Mo-RAA		Razer Amardillo mouse cable management system - prevents unwanted mouse movements caused by long wires
Mo-RMBK	N	Razer Pro]Click Mobile Bluetooth blacK - for bluetooth ready notebook / pc (no bluetooth adapter included) , with on/off switch - retail pack with travel pouch
Mo-RMBP	N	Razer Pro]Click Mobile Bluetooth Pink - for bluetooth ready notebook / pc (no bluetooth adapter included) , with on/off switch - retail pack with travel pouch

Mo-RMBR	**N**	Razer Pro]Click Mobile Bluetooth Red - for bluetooth ready notebook / pc (no bluetooth adapter included) , with on/off switch - retail pack with travel pouch
Mo-RMBW	**N**	Razer Pro]Click Mobile Bluetooth White - for bluetooth ready notebook / pc (no bluetooth adapter included) , with on/off switch - retail pack with travel pouch
Mo-RPSW		Razer Pro Solution White , with blue Led , 1600dpi optical , 6400 FPS , 40iPS (Inch Per Sec) , 5.8 MegaPixel/sec , 16bit ultra-data path , non-slip 7 buttons (independently programable) , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - retail pack
Mo-RSAPGE	**N**	Razer Salmosa Asia Pro-Gamer Edition , 95.9x54.4x33.3mm , light + compact design , 60-120iPS (Inch Per Sec) , 32k on-board memory support upto 5 game profile , 16bit ultra-data path , 1800dpi 3G optical with additional toggle switches for 800/1800dpi and 125/500/1000Hz polling rate adjustments , 7800 FPS , 7 MegaPixel/sec , 1ms response time , non-slip 3 buttons (independently programable) , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - metal collector retail pack
Mo-RS	**N**	Razer Salmosa , 115x63x37mm , light + compact design , 60-120iPS (Inch Per Sec) , 32k on-board memory support upto 5 game profile , 16bit ultra-data path , 1800dpi 3G optical with additional toggle switches for 800/1800dpi and 125/500/1000Hz polling rate adjustments , 7800 FPS , 7 MegaPixel/sec , 1ms response time , non-slip 3 buttons (independently programable) , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - metal collector retail pack
Mo-RD3GL		Razer Diamondback 3G frost bLue , with blue Led , 1800dpi 3G optical , 6400FPS , 60-120iPS (Inch Per Sec) , 5.8 MegaPixel/sec , 16bit ultra-data path , non-slip 7 buttons (independently programable) , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - retail pack
Mo-RD3GG		Razer Diamondback 3G earth Green , with green Led , 1800dpi 3G optical , 6400FPS , 60-120iPS (Inch Per Sec) , 5.8 MegaPixel/sec , 16bit ultra-data path , non-slip 7 buttons (independently programable) , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - retail pack
Mo-RD3GR		Razer Diamondback 3G flame Red , with red Led , 1800dpi 3G optical , 6400FPS , 60-120iPS (Inch Per Sec) , 5.8 MegaPixel/sec , 16bit ultra-data path , non-slip 7 buttons (independently programable) , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - retail pack
Mo-RCL		Razer Copperhead tempest bLue , black with bLue led , 32k on-board memory support upto 5 game profile , 2000dpi laser , 7800 FPS , 7 MegaPixel/sec , 1000hz ultrapooling , 1ms response time , non-slip 7 buttons (independently programable) , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - retail pack
Mo-RCR		Razer Copperhead anarchy Red , black with Red led , 32k on-board memory support upto 5 game profile , 2000dpi laser , 7800 FPS , 7 MegaPixel/sec , 1000hz ultrapooling , 1ms response time , non-slip 7 buttons (independently programable) , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - retail pack

Mo-RCG		Razer Copperhead chaos Green , black with green led , 32k on-board memory support upto 5 game profile , 2000dpi laser , 7800 FPS , 7 MegaPixel/sec , 1000hz ultrapooling , 1ms response time , non-slip 7 buttons (independently programable) , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - retail pack
Mo-RDAL		Razer Death Adder , black with bLue led , 3G infrared sensor , 1800dpi 3G optical , 6400 FPS , 5.8 MegaPixel/sec , 60-120iPS (Inch Per Sec) , 32k on-board memory support upto 5 game profile , 16bit ultra-data path , 1000hz ultrapooling , 1ms response time , non-slip 5 buttons (independently programable) , right-handed ergonomic design with rubber coated buttons , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - retail pack
Mo-RDAW		Razer Death Adder , black with White led (for Mac or windows) , 3G infrared sensor , 1800dpi 3G optical , 6400 FPS , 5.8 MegaPixel/sec , 60-120iPS (Inch Per Sec) , 32k on-board memory support upto 5 game profile , 16bit ultra-data path , 1000hz ultrapooling , 1ms response time , non-slip 5 buttons (independently programable) , right-handed ergonomic design with rubber coated buttons , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - retail pack
Mo-RDAGE		Razer Death Adder Guildwar Edition , black with Orange led , 3G infrared sensor , 1800dpi 3G optical , 6400 FPS , 5.8 MegaPixel/sec , 60-120iPS (Inch Per Sec) , 32k on-board memory support upto 5 game profile , 16bit ultra-data path , 1000hz ultrapooling , 1ms response time , non-slip 5 buttons (independently programable) , right-handed ergonomic design with rubber coated buttons , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - retail pack
Mo-RBS	**N**	Razer BoomSlang Collector Edition 2007 , limited qty of 10000 units worldwide with unique serial coard + exclusive certificate of ownership , black with green led , 32k on-board memory support upto 5 game profile , 1800dpi 3G optical , 7800 FPS , 7 MegaPixel/sec , 1000hz ultrapooling , 1ms response time , non-slip 7 buttons (independently programable) , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - metal collector retail pack
Mo-RLBL		Razer Lachesis banshee blue , Black with bLue led , 4000dpi 3G laser , 25G accleration , 60-100iPS (Inch Per Sec) , 32k on-board memory support upto 5 game profile , 16bit ultra-data path , 1000hz ultrapooling , 1ms response time , non-slip 9 buttons (independently programable) , ergonomic design with rubber coated buttons , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - retail pack
Mo-RLBW		Razer Lachesis phantom white , Black with White led , 4000dpi 3G laser , 25G accleration , 60-100iPS (Inch Per Sec) , 32k on-board memory support upto 5 game profile , 16bit ultra-data path , 1000hz ultrapooling , 1ms response time , non-slip 9 buttons (independently programable) , ergonomic design with rubber coated buttons , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - retail pack
Mo-RM	**C**	Razer Mamba , wired+wireless dual mode with charging dock , black with blue led, 200iPS (Inch Per Sec), synapse on-board memory support upto 5 game profile , 5600dpi 3.5G optical , 7800 FPS , 1000hz ultrapooling , 1ms response time , non-slip 7 buttons (independently programable) , always-on instant response , Zero-Acoustic Ultraslick Teflon feet - usb - metal collector retail pack

Microsoft		http://www.microsoft.com/hardware/mouseandkeyboard/ProductList.aspx?Type=Mouse
Wired		
Mo-MBoD		Microsoft Basic Optical Dsp , ivory , 400dpi , 1500FPS , 3 buttons optical mouse - usb+ps2
Mo-MBoBD		Microsoft Basic Optical Dsp , Black , 400dpi , 1500FPS , 3 buttons optical mouse - usb+ps2
Mo-MBoB		Microsoft Basic Optical Black , 400dpi , 1500FPS , 3 buttons optical mouse - usb+ps2 - retail pack
Mo-Mo		Microsoft wheel Optical , ivory , 400dpi , 9000FPS , 3 buttons optical mouse - usb+ps2 - retail pack
Mo-MoBD		Microsoft wheel Optical Black Dsp , 400dpi , 9000FPS , 3 buttons optical mouse - usb+ps2
Mo-MCo1		Microsoft Comfort Optical 1000 , Silver+black , 1000dpi , 3 buttons optical mouse - usb - retail pack
Mo-MCo3S		Microsoft Comfort Optical 3000 , Silver , 1000dpi , 6000FPS , 4 buttons laser mouse with 4-way scrolling + magnifier - usb+ps2 - retail pack
Mo-MSX5		Microsoft Sidewinder X5 laser gaming mouse - with custom tuning (macro recording) , black , adjustable on the fly 400/800/2000 dpi , 45iPS (Inch Per Sec) , 7080 FPS , 20G acceleration , 16bit ultra-data path , 500hz ultrapooling , 5 programable buttons - usb - retail pack
Mo-MSD		Microsoft Sidewinder laser gaming mouse Dsp pack - with Lcd dpi dsiplay + custom tuning (macro recording) + metal scroll wheel + 2 x metal side buttons + 4 x weight adjust cartridge + 3 sets of different material mouse feet for glide preference + cable anchor + accessories storage box , black with red led , adjustable on the fly 400/800/2000 dpi , 45iPS (Inch Per Sec) , 7080 FPS , 20G acceleration , 16bit ultra-data path , 500hz ultrapooling , 10 (5+3+1+1) buttons - usb
Mo-MS		Microsoft Sidewinder laser gaming mouse - with Lcd dpi dsiplay + custom tuning (macro recording) + metal scroll wheel + 2 x metal side buttons + 4 x weight adjust cartridge + 3 sets of different material mouse feet for glide preference + cable anchor + accessories storage box , black with red led , adjustable on the fly 400/800/2000 dpi , 45iPS (Inch Per Sec) , 7080 FPS , 20G acceleration , 16bit ultra-data path , 500hz ultrapooling , 10 (5+3+1+1) buttons - usb - retail pack
Mo-MH		Microsoft Habu laser gaming mouse - powered by Razer , black with blue Led , 32k on-board memory support upto 5 game profile , adjustable on the fly 400/800/1600/2000 dpi , 45iPS (Inch Per Sec) , 7080 FPS , 16bit ultra-data path , 1000hz ultrapooling , Zero-lag response time , 7 buttons with removable side panels for different palm size - usb - retail pack
Mo-MCo500BD	N	Microsoft Compact Optical 500 Black for notebook , Dsp , 3 buttons optical , 800dpi , 3000FPS - usb
Mo-MCo500B		Microsoft Compact Optical 500 Black for notebook , 3 buttons optical , 800dpi , 3000FPS - usb - retail pack
Mo-MNoS		Microsoft Notebook Optical Silver , 400dpi , 1500FPS , 3 buttons optical - usb - retail pack
Mo-MNoB		Microsoft Notebook Optical Black , 400dpi , 1500FPS , 3 buttons optical - usb - retail pack
Mo-MNo3		Microsoft Notebook Optical 3000 , silver + gray + blue buttons , 1000dpi , 6000FPS , 4 buttons mouse with 4-way scrolling + magnifier - usb - retail pack
Wireless		
Mo-MWo2B		Microsoft Wireless Optical 2000 Black , 1000dpi , 6000FPS , 3 buttons - usb - retail pack

Mo-MWo2S		Microsoft Wireless Optical 2000 Silver , 1000dpi , 6000FPS , 3 buttons - usb - retail pack
Mo-MWoD		Microsoft Wireless Optical Dsp , silver+black , 400dpi , 6000FPS , 3 buttons , 4-way scrolling - usb+ps/2
Mo-MWL5B		Microsoft Wireless Laser 5000 , Black , 1000dpi , 5 buttons laser , 4-way scrolling + magnifier - usb - retail pack
Mo-MNWL6D		Microsoft Natural Wireless Laser 6000 Dsp pack , drak gray , Soft-touch materials + ergonomic design , 1000dpi , 6000FPS , 5 buttons laser , 4-way scrolling + magnifier + instant viewer (through scroll wheel to view different opened windows) - usb
Mo-MNWL6		Microsoft Natural Wireless Laser 6000 , drak gray , Soft-touch materials + ergonomic design , 1000dpi , 6000FPS , 5 buttons laser , 4-way scrolling + magnifier + instant viewer (through scroll wheel to view different opened windows) - usb - retail pack
Mo-MWNo3B		Microsoft Wireless Notebook Optical 3000 Black , 400 dpi , 6000FPS , receiver storable into the mouse , 3 buttons - usb - retail pack
Mo-MWNo3L		Microsoft Wireless Notebook Optical 3000 bLue , 400 dpi , 6000FPS , receiver storable into the mouse , 3 buttons - usb - retail pack
Mo-MWNo4BD		Microsoft Wireless Notebook Optical 4000 Dsp , Black , 1000 dpi , 6000 FPS , receiver storable into the mouse , 4 buttons , 4-way scrolling + magnifier - usb
Mo-MWNo4B		Microsoft Wireless Notebook Optical 4000 Black , 1000 dpi , 6000 FPS , receiver storable into the mouse , 4 buttons , 4-way scrolling + magnifier - usb - retail pack
Mo-MWM3B	**N**	Microsoft Wireless Mobile 3000 , 1000 dpi , 6000 FPS , receiver storable into the mouse , 4 buttons , 4-way scrolling + magnifier, battery status indicator - usb - retail pack
Mo-MBN5D		Microsoft Bluetooth Notebook 5000 Dsp - for bluetooth ready notebook / pc (no bluetooth adapter included) , grey+silver , 1000 dpi , 6000 FPS , receiver storable into the mouse , 4 buttons , 4-way scrolling + magnifier, battery status indicator + power on/off switch
Mo-MBN5		Microsoft Bluetooth Notebook 5000 - for bluetooth ready notebook / pc (no bluetooth adapter included) , grey+silver , 1000 dpi , 6000 FPS , receiver storable into the mouse , 4 buttons , 4-way scrolling + magnifier, battery status indicator + power on/off switch - retail pack
Mo-MWNL6S		Microsoft Wireless Notebook Laser 6000 , Silver , 1000dpi , 4 buttons laser mouse with 4-way scrolling + magnifier , receiver storable into the mouse - usb - retail pack
Mo-MWNL7SD		Microsoft Wireless Notebook Laser 7000 Dsp , Silver+black , 1000dpi , 5 buttons laser mouse with 4-way scrolling + flip-3d + magnifier button , battery status indicator + power on/off switch , receiver storable into the mouse , - usb
Mo-MWNL7S		Microsoft Wireless Notebook Laser 7000 , silver+black , 1000dpi , 5 buttons laser mouse with 4-way scrolling + flip-3d + magnifier button , battery status indicator + power on/off switch , receiver storable into the mouse , - usb - retail pack
Mo-MWL6V2D	**N**	Microsoft Wireless Laser 6000 V2 Dsp , silver+grey , ergonomic design , 5 buttons laser mouse with 4-way scrolling + flip-3d + magnifier + instant viewer (through scroll wheel to view different opened windows) , battery status indicator + power on/off switch , receiver storable into the mouse , - usb - retail pack

Mo-MWL6V2		Microsoft Wireless Laser 6000 V2 , silver+grey , ergonomic design , 5 buttons laser mouse with 4-way scrolling + flip-3d + magnifier + instant viewer (through scroll wheel to view different opened windows) , battery status indicator + power on/off switch , receiver storable into the mouse , - usb - retail pack
Mo-MEMD	N	Microsoft Explorer Mini Dsp - with bluetrack technology (works on virtually any surface) , wireless , silver+grey , ergonomic design , 5 buttons bluetrack mouse with 4-way scrolling + flip-3d + magnifier + instant viewer (through scroll wheel to view different opened windows) , battery status indicator + power on/off switch , snap-in receiver , - usb
Mo-MEM		Microsoft Explorer Mini - with bluetrack technology (works on virtually any surface) , wireless , silver+grey , ergonomic design , 5 buttons bluetrack mouse with 4-way scrolling + flip-3d + magnifier + instant viewer (through scroll wheel to view different opened windows) , battery status indicator + power on/off switch , snap-in receiver , - usb - retail pack
Mo-MMM8		Microsoft Mobile Memory 8000 , transceiver with 1 Gb flash memory , USB rechargeable with magnetic connectors , silver+black , bluetooth , with battery status indicator + power on/off switch , 1000dpi , 5 buttons , with 4-way scrolling + flip-3d + magnifier + instant viewer (through scroll wheel to view different opened windows) , with hardshell carry case - usb - retail pack
Mo-MAB	N	Microsoft Arc Black - 2.4ghz wireless laser mouse , foldable for portability - work as desktop or nb mouse , with battery status indicator , snap-in micro receiver , with 4-way scrolling + flip-3d - usb - retail pack
Mo-MWL7	N	Microsoft Wireless Laser 7000 , black , rechargable+charging station , ergonomic Design , 1000dpi , 5 buttons laser mouse with 4-way scrolling + flip-3d + magnifier button , battery status indicator + power on/off switch - usb - retail pack
Mo-ME	N	Microsoft Explorer - with recharge docking station , bluetrack technology (works on virtually any surface) , wireless , silver+grey , ergonomic design , 5 buttons bluetrack mouse with 4-way scrolling + flip-3d + magnifier + instant viewer (through scroll wheel to view different opened windows) , battery status indicator + power on/off switch , snap-in receiver , - usb - retail pack
Mo-MWNP8		Microsoft Wireless Notebook Presenter 8000 , silver+gray , bluetooth , with integrated slide presenter, laser pointer, and media remote control , battery status indicator + power on/off switch , 1000dpi , 6+6 buttons , with 4-way scrolling + magnifier + instant viewer (through scroll wheel to view different opened windows) , with hardshell carry case - usb - retail pack
Logitech		
with cord		http://www.logitech.com/index.cfm/products/productlist/ZA/EN,crid=2139
Mo-LoVo		Logitech 953544-1000 Oem Value Optical (S90) , ivory - 3 buttons - ps/2
Mo-LoVoB		Logitech 953819-0000 Oem Value Optical (S90) , Black - 3 buttons - ps/2
Mo-Loo		Logitech 953686 Oem Optical (S96) , ivory - 3 buttons - ps/2
Mo-LooB		Logitech 953688 Oem Optical (S96) , black - 3 buttons - ps/2
Mo-LooU		Logitech 931142 Oem Optical (U96) , beige - 3 buttons - Usb
Mo-LooUB		Logitech 931646 Oem Optical (U96) , Black - 3 buttons - Usb
Mo-LoRX250B		Logitech 910-000199 Oem RX250 , Black , with 4-way tilt wheel+zoom , 1000dpi - 3 buttons - usb + ps/2

Mo-LoRX300	Logitech 931433/910-000430 Oem RX300 , White , with 4-way tilt wheel+zoom , 800dpi - 3 buttons - usb + ps/2
Mo-LoNX50	Logitech 910-000317 Oem NX50 notebook optical plus , black+silver , 3 buttons , 1000dpi , with integrated cord management (to wind the cord neatly into the mouse) , shock-resistant bumper
Mo-LoUX	Logitech 931157 Oem UltraX (B85) , silver+black - 4 buttons , quick switch program selector , Internet forward/back - usb + ps/2
Mo-LoRX1000	Logitech 931710 Oem RX1000 , silver+black - 1000dpi , 4 buttons , with 4-way tilt wheel + zoom - usb
Mo-LVo	Logitech 910-000275 Value Optical , black - 3 buttons - usb + ps/2 - retail pack
Mo-LMo	Logitech 930732 Mini Optical - 3 buttons - usb - retail pack
Mo-LPoS	Logitech 931781 Pilot Optical , metalic Silver - 3 buttons , with 4-way tilt wheel + zoom , 1000 dpi - usb + ps2 - retail pack
Mo-LPoB	Logitech 910-000133 Pilot Optical , metalic Black - 3 buttons , with 4-way tilt wheel + zoom , 1000 dpi - usb + ps2 - retail pack
Mo-LLX3	Logitech 931622 LX3 optical mouse , silver+black , with soft comfort grip, 1000dpi , 3 buttons , with 4-way tilt wheel + zoom - usb + ps/2 - retail pack
Mo-LV100	Logitech 931641 V100 optical mouse for notebook , silver+black , 3 buttons , with 4-way tilt wheel + zoom - usb - retail pack
Mo-LMT	Logitech 939-000073 - 15.4" notebook carry bag + V100 optical mouse for notebook - silver+black , 3 buttons , with 4-way tilt wheel + zoom - usb - retail pack
Mo-LLS1Bo	Logitech 910-000764 LS1 laser mouse , black+orange highlight , with soft comfort grip, 3 buttons , with 4-way tilt wheel + zoom - usb - retail pack
Mo-LLS1BG	Logitech 910-000761 LS1 laser mouse , black+green highlight , with soft comfort grip, 3 buttons , with 4-way tilt wheel + zoom - usb - retail pack
Mo-LLS1WG	Logitech 910-000765 LS1 laser mouse , white+green highlight , with soft comfort grip, 3 buttons , with 4-way tilt wheel + zoom - usb - retail pack
Mo-LV150	Logitech 931755 V150 laser mouse for notebook , silver+gray , 3 buttons , with 4-way tilt wheel + zoom - usb - retail pack
Mo-LM518	Logitech 931352/910-000616 Mx518 , blue , adjustable 1600/800/400 dpi MX™ optical engine , 5.8mp/sec , Max. acceleration: 15g , speed 1m/sec , dedicated controls to switch “on-the-fly” from pixel-precise targeting to fast-twitch evasive moves , 8 buttons , Internet forward/back , cruise control , quick switch program selector , 8 buttons in total , - usb + ps/2
Mo-LG5SE	Logitech 910-000094 G5 Special Edition laser gaming mouse with Dual thumb buttons , adjustable 2000/800/400 dpi laser engine with adjustable weight cartridge , polytetrafluoroethylene gaming feet , 6.4mp/sec , Max. Acceleration: 20g , speed 1.65m/sec , 7 buttons , with 4-way tilt wheel + zoom , dedicated controls to switch “on-the-fly” from pixel-precise targeting to fast-twitch evasive moves - usb , silver + blue

Mo-LG9		Logitech 910-000175 G9 gaming mouse with Interchangeable Grips , Dual thumb buttons , 32kb memory store up to 5 profiles , MicroGear precision scroll wheel for Hyper-fast scrolling , adjustable 3200-200 dpi laser engine with adjustable weight cartridge , polytetrafluoroethylene gaming feet , 6.4mp/sec , Max. Acceleration: 20g , speed 1.65m/sec , 7 buttons , with 4-way tilt wheel + zoom , dedicated controls to switch “on-the-fly” from pixel-precise targeting to fast-twitch evasive moves - usb , silver + blue
cordless		http://www.logitech.com/index.cfm/products/productlist/ZA/EN,crid=2134
Mo-LoRX650	N	Logitech 910-000342 Oem RX650 cordlrss optical , 3 buttons , 1000dpi , with smart power management , black - usb
Mo-LoNX60		Logitech 931502/910-000431 Oem NX60 cordlrss notebook optical , 3 buttons , conserve power by on/off switch , with carry bag , black - usb
Mo-LoRX700		Logitech 931509/910-000432 Oem RX700 (LX5 Silver) cordless mouse , battery-saving Invisible Light , 3 buttons , 4 ways tilt wheel plus zoom , with smart power management (automatic standby mode + on/off switch) , with battery indicator light - usb+ps2
Mo-LLX6	N	Logitech 910-000488 LX6 cordless mouse , silver+black , battery-saving Invisible Light , 3 buttons , 4 ways tilt wheel plus zoom , with smart power management (automatic standby mode + on/off switch) , with battery indicator light , soft rubber grip - usb+ps2
Mo-LV220B	N	Logitech 910-000166 V220 cordless mouse , Black , soft rubber grips , 3 buttons , 4 ways tilt wheel plus zoom , with smart power management (automatic standby mode + on/off switch) , with battery indicator light - usb+ps2
Mo-LV220S		Logitech 910-000447 V220 cordless mouse , Silver , soft rubber grips , 3 buttons , 4 ways tilt wheel plus zoom , with smart power management (automatic standby mode + on/off switch) , with battery indicator light - usb+ps2
Mo-LV320B		Logitech 910-000497 V320 cordless notebook , silver+gray , 2.4 GHz cordless , soft side grips, finger grooves , with battery-saving Invisible Light , 4 ways tilt wheel plus zoom , smart power management (automatic standby mode + on/off switch) , wireless receiver stored into the mouse - usb
Mo-LLX7MB		Logitech 931395 LX7 cordless mouse , metallic blue , 1200dpi with battery-saving Invisible Light , 5 buttons , 4 ways tilt wheel plus zoom , smart power management (automatic standby mode + on/off switch) , Universal Forward/Back buttons , soft-touch rubber sides grip - usb
Mo-LM610L		Logitech 931571 Mx610 laser for Left-hand , 2.4 GHz cordless , with Email and IM notification buttons led , 8 buttons , 4 ways tilt wheel plus zoom , internet forward , back , volume controls and mute , battery indicator , auto turn-off when pc in sleep mode or shut down - usb + ps/2
Mo-LLX8	N	Logitech 910-000325 LX8 cordless laser mouse , black + metalic blue , 1200dpi with battery-saving Invisible Light , 5 buttons , 4 ways tilt wheel plus zoom , smart power management (automatic standby mode + on/off switch) , Universal Forward/Back buttons , soft-touch rubber sides grip - usb
Mo-LV450NG	N	Logitech 910-000621 V450 Nano laser cordless notebook , Grey , 2.4 GHz cordless , 3 buttons , tilt wheel plus zoom , soft comfort grip , battery indicator light , micro receiver , with carry bag - usb

Mo-LV450NB	N	Logitech 910-000624 V450 Nano laser cordless notebook , Black , 2.4 GHz cordless , 3 buttons , tilt wheel plus zoom , soft comfort grip , battery indicator light , micro receiver , with carry bag - usb
Mo-LV550NG	N	Logitech 910-000699 V550 Nano laser cordless notebook , Silver , with clip-and-go dock on notebook (for less thing to carry) , , 2.4 GHz cordless , 4 buttons , application/window switch button , tilt wheel + Hyper-fast scrolling , battery indicator light , micro receiver , with carry bag - usb
Mo-LV550NW	N	Logitech 910-000700 V550 Nano laser cordless notebook , White+blue highlight , with clip-and-go dock on notebook (for less thing to carry) , , 2.4 GHz cordless , 4 buttons , application/window switch button , tilt wheel + Hyper-fast scrolling , battery indicator light , micro receiver , with carry bag - usb
Mo-LM620		Logitech 910-000241 Mx620 laser , silver+black , 2.4 GHz cordless , with MicroGear precision scroll wheel for Hyper-fast scrolling , 6 buttons , 4 ways tilt wheel plus zoom , internet forward , battery indicator , auto turn-off when pc in sleep mode or shut down - usb
Mo-LV470L		Logitech 910-000300 V470 bluetooth cordless , metalic bLue , laser , 3 buttons , with battery indicator + smart power management (automatic standby mode + on/off switch) , no bluetooth adapter included - with carry case , usb
Mo-LV470W		Logitech 910-000301 V470 bluetooth cordless , metalic White , laser , 3 buttons , with battery indicator + smart power management (automatic standby mode + on/off switch) , no bluetooth adapter included - with carry case , usb
Mo-LoNX80		Logitech 910-000665 Oem NX80 cordless notebook laser mouse , with MicroGear precision scroll wheel , Hyper-fast scrolling , 5 buttons + high-resolution Zoom slider , Ergonomic design for right-hand , 2.4 GHz cordless , with protective pouch - USB
Mo-LVXN		Logitech 10-000255 VX Nano cordless notebook laser mouse , with MicroGear precision scroll wheel , Hyper-fast scrolling , One-Touch search , 6 buttons + high-resolution Zoom slider , Ergonomic design for right-hand , 2.4 GHz cordless , with protective pouch - USB
Mo-LM1100	N	Logitech 910-000720 Mx1100 Laser Cordless , with elegantly contoured shape + microGear precision scroll wheel for Hyper-fast scrolling , adjustable-dpi upto 1600 , Illuminated 4-level battery indicator , new thumb-button controls , 8 buttons , 4 ays tilt wheel plus zoom , with application switch - usb
Mo-LMXR		Logitech 931689 MX Revolution cordless laser mouse , with SmartShift technology (automatically detects your current application and applies the scrolling mode) , MicroGear precision scroll wheel + 2nd wheel for document quick-flip , Hyper-fast scrolling , One-Touch search , 6 buttons + high-resolution Zoom slider, Illuminated 4-level battery indicator , Ergonomic design for right-hand , 2.4 GHz cordless , with recharge station , micro receiver storable into mouse - USB
Mo-LMXA	N	Logitech 931633 MX Air rechargable cordless laser air mouse , with gesture controls (by waving or flip without clik the buttons) , Freespace motion sensing , Scroll panel by touch control , 2.4 GHz cordless , with recharge station
trackballs		http://www.logitech.com/index.cfm/products/productlist/ZA/EN,crid=2141
Mo-LTM		Logitech 910-000808 Trackman Marble , trackball , 4 buttons , with left hand support - usb

Mo-LTW		Logitech 910-000809 Trackman Wheel , trackball , 3 buttons , usb + ps/2
Mo-LCTW		Logitech 904371 Cordless Trackman Wheel , trackball , 3 buttons , usb + ps/2
Mo-LCTo		Logitech 904369 Cordless Trackman Optical , trackball , 8 buttons , web forward / backward , cruise control ; usb + ps/2
Mo-LCoT	C	Logitech 910-000810 Cordless Optical Trackman , trackball , 8 buttons , web forward / backward , cruise control ; usb + ps/2
cordless presenter		http://www.logitech.com/index.cfm/products/productlistns/ZA/EN,crid=1999&categoryid=371
Mo-LoCPR		Logitech 931342 Oem Cordless Presenter , 2.4Ghz RF - with LCD timer + built-in vibration alerts + laser pointer , ranged 15m , button for launch/end slideshow , slide forward , slide back , black screen , volume control ; Includes carry case.
Mo-LCPR		Logitech 931307 Cordless Presenter , 2.4Ghz RF - with LCD timer + built-in vibration alerts + laser pointer , ranged 15m , button for launch/end slideshow , slide forward , slide back , black screen , volume control ; Includes carry case.
REmote control		
RE-HMCE		Hauppauge Remote control for MCE (Media Center Edition) , oem pack - usb receiver included
RE-CK100		Compro K100 remote control for MCE (Media Center Edition) , ideal for upgrading vista home preminum / ultimate to MCE , 51-keys , with bundled microsoft certified MPEG-2 encoder , reatil pack - usb receiver included
RE-CK200	N	Compro K200 remote control for MCE (Media Center Edition) , ideal for upgrading vista home preminum / ultimate to MCE , 48-keys , with bundled microsoft certified MPEG-2 encoder , reatil pack - usb receiver included
RE-AVEZ	N	Antec Veris E-Z remote control for MCE (Media Center Edition) , clipable design usb receiver for Lcd or notebook , designed by iMON , ideal for upgrading vista home preminum / ultimate to MCE , 18-keys , with bundled microsoft certified MPEG-2 encoder , reatil pack
RE-AVB	N	Antec Veris Basic remote control for MCE (Media Center Edition) , receiver for 3.5" bay , black , designed by iMON , ideal for upgrading vista home preminum / ultimate to MCE , 18-keys , with bundled microsoft certified MPEG-2 encoder , reatil pack
CH-AAVE	N	Antec Veris Elite VFD module with MCE (Media Center Edition) remote control + control knob , for 5.25" bay , black , designed by iMON , ideal for upgrading vista home preminum / ultimate to MCE , 58-keys , with bundled microsoft certified MPEG-2 encoder , reatil pack
CH-AAVP	N	Antec Veris Premier VFD module with MCE (Media Center Edition) remote control + 2 x control knob + multimedia buttons , for 2 x 5.25" bay , black , designed by iMON , ideal for upgrading vista home preminum / ultimate to MCE , 58-keys , with bundled microsoft certified MPEG-2 encoder , reatil pack
logitech		
RE-LHR525		Logitech 966191 Harmony Remote 525 , blue backlit keypad , 2mb memory , mono lcd , 50 buttons , 4 one-touch activity buttons , 4 x Interactive display keys - manage all your home entertainment system with infrared commands ; support upto 15 devices like TV, DVD, VCR, Satellite box .... , upto 255 activity
RE-LHR555		Logitech 966208 Harmony Remote 555 , blue backlit keypad , 2mb memory , mono lcd , 52 buttons , 4 one-touch activity buttons , 4 x Interactive display keys - manage all your home entertainment system with infrared commands ; support upto 15 devices like TV, DVD, VCR, Satellite box .... , upto 255 activity

RE-LHR785		Logitech 966207 Harmony Remote 785 , backlit keypad , 2mb memory , color lcd , 55 buttons , 8 one-touch activity buttons , 8 x Interactive display keys , 5 way joystick - manage all your home entertainment system with infrared commands ; support upto 15 devices like TV, DVD, VCR, Satellite box .... , upto 255 activity - with recharging station
RE-LHRo	N	Logitech 915-000036 Harmony Remote One , full color touch-screen lcd , manage all your home entertainment system with infrared commands ; support upto 15 devices like TV, DVD, VCR, Satellite box .... , upto 255 activity - with recharging station
RE-LHR895		Logitech 966193 Harmony Remote 895 , backlit keypad , 2mb memory , color lcd , 55 buttons , 8 one-touch activity buttons , 8 x Interactive display keys , 5 way joystick - manage all your home entertainment system with infrared commands ; support upto 15 devices like TV, DVD, VCR, Satellite box .... , upto 255 activity - with interchangable face plate , recharging station , pre-program for microsoft MCE (Media Center Edition) - optional wireless extender support upto 30m/100 feet
RE-LHR1000	N	Logitech 966230 Harmony Remote 1000 , 3.5" colour touch screen for one-touch activity-based control , rechargeable Lithium-ion battery , brushed aluminum surfaces - manage all your home entertainment system with infrared commands ; support upto 15 devices like TV, DVD, VCR, Satellite box .... , upto 15 separate devices , recharging station - optional wireless extender support upto 30m/100 feet
RE-LAHWE	N	Logitech 966195 Harmony RF Wireless Extender upto 30m/100 feet - for Harmony Remote 895/1000
other Input Device		
pc-winner		
iD-PRD902	N	Pc winner RD9-02 , usb flash drive type with retractable USB connector , sliding sensor - touch biometric password manager (Fingerprint Reader) - to replace the type-in of password
iD-PoR01	N	Pc winner oR-01 , cmos optical sensor - touch biometric password manager (Fingerprint Reader) - to replace the type-in of password
FD-P8GFP	N	pc-winner Fingerprint Reader + 8Gb flash drive with retractable USB connector , sliding sensor, with lanyard - 1 year warranty
APC		
iD-ABioPoD	N	APC BioPoD-ec - touch biometric pod password manager (Fingerprint Reader) - usb - to replace the type-in of password
Mo-ABioM34	N	APC BioM34-ec - optical wheel mouse with touch biometric pod password manager (Fingerprint Reader) - usb - to replace the type-in of password
ACECAD		
iD-AMSN		Acecad MyScript Note - DigiMemo Handwriting Recognition software - converts your handwritten notes from ACECAD DigiMemo into digital text - support 13 major language (Danish, Dutch, English (UK), English (US), Finnish, French, German, Italian, Japanese, Portuguese, Simplified Chinese, Spanish, Swedish)
iD-APF100		Acecad PF-100 deluxe zip portfolio for digimemo A501/502 , 326x245x40mm - PVC leather and polyester , 3 x pen loops , 5 x card pockets , 3 x multi-function pockets , 1x exterior document compartment
GAming device		
Playseats for motor sport		
GA-PSC		PlaySeat Classic - 70004 , foldable + adjustable seats for motor sport games - pedals + steering wheel stand - for all gaming platform

GA-PSE		PlaySeat Evoluation - 72000 , foldable + adjustable seats for motor sport games - pedals + steering wheel stand - for all gaming platform
GA-PSA1GP	N	PlaySeat A1GP - 73000 , a1 Grand Prix licensed , white , foldable + adjustable seats for motor sport games - pedals + steering wheel stand - for all gaming platform
GA-PSGH		PlaySeat Gearshift Holder - 8009 - for steering wheel with separate gearshift box - (ie. Logitech G25) - for PlaySeat Evoluation , A1
Microsoft for PC and XBOX		
GA-MXC		Microsoft Xbox360 Controller - for PC or XBOX , with vibration feedback
GA-MXWC	N	Microsoft Xbox360 Wireless Controller - for PC or XBOX , with vibration feedback
Lgoitech for PC		http://www.logitech.com/index.cfm/gaming/pc_gaming/&cl=za,en
Joystick		http://www.logitech.com/index.cfm/gaming/pc_gaming/joysticks/&cl=za,en
GA-LJA3		Logitech 963291 Attack 3, 11 programable buttons upto 22 by shift button , rapid fire, usb
GA-LJE3P		Logitech 963290 Extreme 3D Pro , 12 programable buttons upto 24 by shift button , throttle, rapid fire, twist handle - usb
GA-LJFC		Logitech 963283 Freedom Cordless 2.4 , 10 button, throttle, rapid fire, twist handheld, cordless, usb
GA-LJF3P		Logitech 963352 Force 3D Pro , 12 button, throttle, twist handheld , force feed back, usb
Gamepad		http://www.logitech.com/index.cfm/gaming/pc_gaming/gamepads/&cl=za,en
GA-LGP		Logitech 963335 Precesion , 8 button - usb
GA-LGDA		Logitech 963292 Dual Action , 12 programmable buttons upto 24 by shift button , 2 analogue joystick - usb
GA-LGR2		Logitech 963325 Rumblepad 2 , 10 programmable buttons , 2 analogue joystick , dual vibration feed back - usb
GA-LGCS	N	Logitech 963435 ChillStream , 3 level speed adjustable fan to keep hands cool , 10 programmable buttons , 2 analogue joystick - usb
GA-LGCR2		Logitech 963326 Cordless Rumblepad 2 , 2.4Ghz RF , 10 programmable buttons , 2 analogue joystick , dual vibration feed back - usb
Wheel		http://www.logitech.com/index.cfm/gaming/pc_gaming/wheels/&cl=za,en
GA-LWFVF		Logitech 963339 Formula Vibration Feedback steering wheel , dual vibration force feedback , 10 buttons + 8way d-pad , with statuis indicator , gas/brake padals , status indicator light - usb
GA-LWFFEX		Logitech 963357 Formula Force EX , 4 buttons upto 12 by shift button , force feed back , gas/brake padals - usb
GA-LWMR		Logitech 963282 Mono Racing , vibration force feedback , 6 programable buttons upto 12 by shift button , gas/brake padals , gear shifter , 240 degrees of rotation - usb
GA-LWG25		Logitech 963416 G25 racing wheel for PC or sony PS3 , force feedback , 6-speed shifter , separate leather-wrapped gearshift knob , 6-speed and sequential shifting modes , carpet grip system , stainless steel gas, brake, and clutch pedals , 11" leather-wrapped steering wheel rim - usb
Lgoitech for XBOX		http://www.logitech.com/index.cfm/products/categories/ZA/EN,crid=1579

GA-LXDFF		Logitech 963368 DriveFX , vibration Feedback Wheel , for XBOX 360 , with vibration feedback (with on/off switch) , black , with Module Expansion Slot for headset or memory card , 8-way D-pad , 11 buttons
Logitech for SONY PS2 / PS3		
GA-LHV	N	Logitech 981-000045 Vantage headset for sony PS3 , black , with noise-canceling mic
GA-LHCV	N	Logitech 980362-0914 Cordless Vantage headset for sony PS3 , black , bluetooth 2.0 cordless , rechargable , with noise-canceling mic
GA-LKCM		Logitech 920-000206 Cordless Mediaboard for sony PS3 , silver + black , Integrated touchpad with vertical scrolling + 2 buttons
GA-LKCMP		Logitech 920-000010 Cordless Mediaboard Pro for sony PS3 , black , Integrated touchpad with vertical scrolling + 2 buttons , with 5 hotkeys
GA-LGPC		Logitech 963354 Precesion Controller for sony PS2 , dual analog sticks , rubber grips , turbo button , vibration feedback , 8-foot cable
GA-LGCSS		Logitech 963375-0914 ChillStream Silver for sony PS3 , 3 level speed adjustable fan to keep hands cool , usb
GA-LGCSB		Logitech 963497-0914 ChillStream Black for sony PS3 , 3 level speed adjustable fan to keep hands cool , usb
GA-LGCAC		Logitech 963320 Cordless Action Controller for sony PS2 , 2.4GHz Cordless , dual analog sticks , vibration feedback
GA-LGCPCPS3		Logitech 940-000019 Cordless Precesion Controller for sony PS3 , 2.4GHz Cordless , dual analog sticks
GA-LWRVF		Logitech 963323 Rally Vibration Force wheel for sony PS2 , force feedback , 12 buttons , gas/brake padals - usb
GA-LWDFE		Logitech 963356/941-000029 Driving Force EX for sony PS2/ PS3 , force feedback , 8 buttons , gas/brake padals , rubber grips - usb
GA-LWDFW	N	Logitech 941-000038/58 Driving Force Wireless for sony PS2/ PS3 , 2.4ghz wireless , force feedback , 12 buttons , gas/brake padals , rubber grips , ac power supply included
GA-LWDFGT	N	Logitech 941-000021 Driving Force GT for sony PS2/PS3 , force feedback , 24-position realtime adjustment dial , 900° Rotation (2½ rotations) , 14 buttons , gas/brake padals , Full rubber rim - usb
GA-LWG25		Logitech 963416 G25 racing wheel for PC or sony PS2 / PS3 , force feedback , 6-speed shifter , leather-wrapped shift knob , 6-speed and sequential shifting modes , carpet grip system , stainless steel gas, brake, and clutch pedals , 11" leather-wrapped steering wheel rim - usb
Logitech for SONY PSP		
GA-LPS		Logitech 970210 PlayGear Skin - Create and print upto custom skins (upto 30) got PlayGear Pocket
GA-LPM		Logitech 970161 PlayGear Mod headphone - 30mm neodymium drivers , water-resistant polycarbonate design , 2 years warranty
SPeaker		
Razer		
SP-RM		Razer Mako , 2.1 with THX Ground Plane™ + THX Slot Speaker + ClassHD™ Digital Amplifier , The bi-amplified 50W satellites with DSP control , All-in-one remote control pod with touch-sensitive LED dial , 300w RMS (200+2x50) , RCA + 3.5mm AUX input + headphone jack
Tanko		

SP-TJM180		Tanko JM-180 portable presenter speaker + headset , with belt clip , rechargable Lithium-Ion battery , 10sec recording , 5w , 106x85x57mm , 380g - ideal for teaching , touring environment
SP-TJM250		Tanko JM-250 wireless portable presenter speaker + headset , with belt clip carry case , rechargable Lithium-Ion battery , 5w , 106x85x57mm , 400g , with carry case - ideal for teaching , touring environment - wireless within 25m in open space
Labtec		http://www.labtec.com/index.cfm/gear/listing/EUR/EN,crid=18
SP-LSPiN46		Labtec SPiN 46 speaker , 2.0 , 2w (2x1)
SP-LSPiN85		Labtec SPiN 85 speaker , 2.0 , 3w (2x1.5)
Creative		http://www.creative.com/products/welcome.asp?category=4
2.0		http://www.creative.com/products/welcome.asp?category=4
SP-CS245		Creative SBS245 speaker with built-in bass port , 2.0 , 2x2w RMS - black
SP-CTS500		Creative TravelSound 500 speaker , 1 piece compact size 4.7x21.3x3.3cm with clip for lcd , 2.0 , 4w (2x2) RMS , 2 x NeoTitanium micro drivers - run on 4 x AA batteries or usb powered , with travel pouch - silver
2.1		http://www.creative.com/products/welcome.asp?category=4
SP-CSA300		Creative SBS-A300 speaker , 2.1 , 21w (11 + 5x2) RMS , ported MDF wood subwoofer with 5" driver , adjustable bass leve - black
Logitech		
2.0		
SP-LoS100		Logitech 970143 Oem S-100 , 2.0 channel , 5w (2x2.5) , with headphone jack - ivory
SP-LoS120		Logitech 980-000018 Oem S-120 beige , 2.0 channel , 2.3w (2x1.15) , with headphone jack
SP-LoS120B		Logitech 980-000010 Oem S-120 Black , 2.0 channel , 2.3w (2x1.15) , with headphone jack
SP-LoS150U		Logitech 980-000029 Oem S-150 Usb , black , 2.0 channel , 1.2w (2x0.6) , with headphone jack + travel bag
SP-LLS11		Logitech 980-000048 LS11 , 2.0 channel , 3w (2x1.5) , with headphone jack , volumn control - black + silver
SP-LX140		Logitech 970264 X-140 , 2.0 channel , 5w (2x2.5) , 2.75" high-excursion driver with 3" pressure driver , with headphone jack - black
SP-LV10		Logitech 970194 V10 portable USB speaker , USB powered , 2.0 channel , 2w (2x1) , quad micro pressure driver , with protective travel case - silver + black
SP-LV20		Logitech 970155 V20 portable USB speaker , USB powered , 2.0 channel , 2w (2x1) , 2" high-excursion driver with 3" pressure driver , with protective travel case - silver + black
SP-LZ5	N	Logitech 980-000169 Z5 omni-directional sound speaker , USB powered , 2.0 channel , 2w (2x1) , with wirelss remote control - black
SP-LZ10		Logitech 970243 Z-10 interactive speaker system , built-in touch-sensitive multimedia controls with and backlighted display , bi-amp design, 25.4 mm dome tweeters and 76 mm high-excursion woofers , 4 convenient presets to save / recall favourite Internet radio stations and playlists , 30w , with headphone jack - USB + 3.5mm
SP-LQCUS		Logitech 980440 QuickCall Usb Speakerphoone + dual mic , with RightSound Technology , 1-touch button calling , with mic + speaker jack - ideal for Skype/msn/VoiP
2.0 for iPoD/MP3		

SP-LMM28		Logitech 970174 MM28 , portable NXT flat panel speakers , 3.5mm audio jack , 1.24" thickness , foldable with protective cover , integrated cable management , powered from ac-adapter or AA battery
SP-LMM32W		Logitech 970218 MM32 , white , portable speakers for iPod or other 3.5mm jack audio player , with protective travel case , 2 channel quad micro drivers , powered from ac-adapter or AA battery
SP-LPFX		Logitech 984-000045 Pure-Fi eXpress , white + black dual tone design , portable speakers for iPod or other 3.5mm jack audio player , with wireless remote control , 2.5" Max-X™ high-excursion drivers , charge iPod when docked , RCA video output jack , powered from ac-adapter or AA batteries
SP-LPFXP	N	Logitech 984-000188 Pure-Fi eXpress Plus , black , portable speakers for iPod/iPhone or other 3.5mm jack audio player , clock with alarm , with wireless remote control , charge iPod/iPhone when docked , powered from ac-adapter or AA batteries
SP-LPFAT	N	Logitech 980-000193 Pure-Fi AnyTime , Black , speakers for iPod/iPhone or other 3.5mm jack audio player , motion-activated backlighted controls , dual alarm with motion-sensing snooze , digital AM/FM radio , with wireless remote control
SP-LPFA2B	N	Logitech PN 984-000061 Pure-Fi Anywhere 2 , Black , portable speakers for iPod (1G-3G) or other 3.5mm jack audio player , with wireless remote control , protective travel case , 2 channel - 4 x drivers (3" pressure for bass + 2" Max-X active,high-excursion), powered from ac-adapter or rechargeable Li-ion batteries (with battery level indicator)
SP-LPFA2W	N	Logitech PN 984-000060 Pure-Fi Anywhere 2 , White , portable speakers for iPod (1G-3G) or other 3.5mm jack audio player , with wireless remote control , protective travel case , 2 channel - 4 x drivers (3" pressure for bass + 2" Max-X active,high-excursion), powered from ac-adapter or rechargeable Li-ion batteries (with battery level indicator)
SP-LPFM	N	Logitech 984-000028 Pure-Fi Mobile , bluetooth wireless , with Integrated microphone array work as wireless speaker or speakerphone , black , portable speakers for iPod or other 3.5mm jack audio player , protective travel case , 2 channel - 4 x drivers (2" pressure for bass + 2" Max-X active , high-excursion), powered from ac-adapter or rechargeable Li-ion batteries (with battery level indicator) - wireless , 3.5, or usb
SP-LPFD	N	Logitech 984-000050 Pure-Fi Dream , black , light- and motion-sensing , light sensor automatically dims the display at night , dual alarm with battery backup , digital AM/FM radio , portable speakers for iPod or other 3.5mm jack audio player , with wireless remote control , protective travel case , 2 channel - 19 mm high-definition soft-dome tweeters + 76 mm long-throw woofers , charge iPod when docked , powered from ac-adapter
SP-LPFE	N	Logitech 980-000128 Pure-Fi Elite , black , for iPod or other 3.5mm jack audio player , Touch-sensitive, backlit controls , digital AM/FM radio + clock , with wireless remote control , 80w RMS , 1.5cm soft-dome tweeters + 10cm long-throw woofers , charge iPod when docked , RCA+S-Video video output jack
2.1		
SP-LoS220		Logitech 980-000021 Oem S-220 , 2.1 , 17w (9+2x4) , piano-finish control base , with headphone+mic jack- black
SP-LLS21		Logitech 980-000058 LS21 , 2.1 , 7w (4+2x1.5) , with headphone jack + Wired remote control - black

SP-LX210		Logitech 970191 X-210 , 2.1 , FDD2 (Frequency Directed Dual Driver) , 25w (15+2x5) , with headphone jack - black
SP-LX240		Logitech 970285 X-240 , 2.1 , FDD2 (Frequency Directed Dual Driver) , 25w (15+2x5) , Stow-away device cradle with 3.5mm AUX input for MP3 player + headphone jack - black
SP-LX230		Logitech 970123 X-230 , 2.1 , FDD2 (Frequency Directed Dual Driver) , 32w (20+2x6) , with headphone jack - black
SP-LAH		Logitech 980-000103 Audio Hub , single piece designed usb speaker with 3 x usb downstream hub , height adjustable webcam stand , idal of lcd or notebook on desktop , 2.1 channel , 15w RMS with 2 x 5cm tweeters + 1 x 7.6cm sub-woofer driver - silver + black
SP-LZ4B		Logitech 970175 Z-4 Black , 2.1 , 40w (23+2x8.5) , 3 drivers satellite - wired remote control with headphone jack , cast-metal stands
SP-LZ4i		Logitech 970186 Z-4 white , 2.1 , 40w (23+2x8.5) , 3 drivers satellite - wired remote control with headphone jack , cast-metal stands
SP-LZ2300		Logitech 970118 Z-2300 , THX digital , 2.1 channel , 200w (120 + 2x40) , wired remote control with headphone jack
SP-LZC		Logitech 980-000086 Z-Cinema advanced surround sound system - surround sound without rear speakers , SRS® TruSurround HD 2.1 , 180w total rms , 110w 20cm long-throw subwoofer with flared bass port , 2x35w (26w midwoofer+9w tweeter) satellite speakers , wireless MCE ready remote control , with headphone jack + 3.5mm AUX input for other audio - usb - 24-bit digital
5.1		
SP-LX530		Logitech 970114 X-530 , 5.1 , FDD2 (Frequency Directed Dual Driver) , 70w (25+4x7.4+ 15.5) , with headphone jack - black
SP-LX540		Logitech 970223 X-540 , 5.1 , FDD2 (Frequency Directed Dual Driver) , 70w (25+4x7.4+ 15.5) , wall-mountable satellite + LCD clip for center speaker , with headphone jack - black
SP-LG51		Logitech 980-000116 G51 , 5.1 , FDD2 (Frequency Directed Dual Driver) , 155w (56w 13.3cm sub-wooofer with down-firing high-excursion driver + 4 x 20w 5.1 cm laser-tuned drivers + 19w center speaker) , wall-mountable satellite + LCD clip for center speaker , with headphone jack , dual mute buttons (for audio/mic) , customable speaker skins (blue/black/white) - black
SP-LZ5500		Logitech 970115 Z-5500 Digital , 5.1 , Dolby Digital Pro Logicii , DTS® 96/24 , THX ; Digital SoundTouch Control Center with backlit Lcd , digital audio with Spdif (optical/coax) , 5.1 channel, 505w (188+4x62+69)
Web Cam		
Compro		
WC-CiP50	C	Compro iP50 - 2-way audio + 3G mobile video internet camera (iP camera) , 10/100 , 1/4" Cmos VGA sensor , PAN+TiLT , 4x digital zoom , motion detection triggers recording and sends e-mail alerts , 640x480@30fps , listen and talk to anyone at camera site by adding speaker , remote management software support upto 16 cameras
WC-CiP50W	C	Compro iP50W - 2-way audio + 3G mobile video internet camera (iP camera) , 10/100 or 802.11G wireless , 1/4" Cmos VGA sensor , PAN+TiLT , motion detection triggers recording and sends e-mail alerts , 640x480@30fps , listen and talk to anyone at camera site by adding speaker , remote management software support upto 16 cameras

Microsoft		http://www.microsoft.com/hardware/digitalcommunication/Productlist.aspx?type=LifeCam
WC-MVX700	N	Microsoft Lifecam VX700 , black , with bundled Mic - usb - Retail pack
WC-MVX1000		Microsoft Lifecam VX1000 , CMOS VGA , 55° diagonal field of view , black , built-in Mic , windows live messenger call button , 1.3 mega pixel , 3 x digital zoom , pan and tilt , auto face-tracking , video effect , image : 640x480 ; video : 640x480 @ 30 FPS - usb - Retail pack
WC-MVX3000D		Microsoft Lifecam VX3000 Dsp , CMOS VGA , 55° diagonal field of view , black , built-in Mic , windows live messenger call button , 1.3 mega pixel , 3 x digital zoom , pan and tilt , auto face-tracking , video effect , image : 1280x960 ; video : 640x480 @ 30 FPS - usb - dsp pack
WC-MVX3000		Microsoft Lifecam VX3000 , CMOS VGA , 55° diagonal field of view , black , built-in Mic , windows live messenger call button , 1.3 mega pixel , 3 x digital zoom , pan and tilt , auto face-tracking , video effect , image : 1280x960 ; video : 640x480 @ 30 FPS - usb - Retail pack
WC-MVX5000	N	Microsoft Lifecam VX5000 , CMOS VGA , with auto low-light adjustment , fun flexible base , 55° diagonal field of view , black , built-in Mic , windows live messenger call button , 1.3 mega pixel , 4 x digital zoom , pan and tilt , auto face-tracking , video effect , image : 1280x960 ; video : 640x480 @ 30 FPS - usb - Retail pack
WC-MNX3000		Microsoft Lifecam NX3000 , CMOS VGA , 55° diagonal field of view , black , built-in Mic , windows live messenger call button , 1.3 mega pixel , 3 x digital zoom , pan and tilt , auto face-tracking , video effect , image : 640x480 ; video : 640x480 @ 30 FPS - usb
WC-MVX6000D		Microsoft Lifecam VX6000 Dsp , CMOS SXGA , 72° diagonal field of view , silver , built-in Mic , wide-angle len , windows live messenger call button , 1.3 mega pixel , 3 x digital zoom , pan and tilt , auto face-tracking , video effect , image : 1280x960 ; video : upto 1280x1024 @ 30 FPS - usb - dsp pack
WC-MVX6000		Microsoft Lifecam VX6000 , CMOS SXGA , 72° diagonal field of view , silver , built-in Mic , wide-angle len , windows live messenger call button , 1.3 mega pixel , 3 x digital zoom , pan and tilt , auto face-tracking , video effect , image : 1280x960 ; video : upto 1280x1024 @ 30 FPS - usb - Retail pack
WC-MVX5500	N	Microsoft Lifecam VX5500 , CMOS VGA , with Interchangeable Faceplates , auto low-light adjustment , foldable , 55° diagonal field of view , built-in noise cancelling mic , windows live messenger call button , 1.3 mega pixel , 3 x digital zoom , pan and tilt , auto face-tracking , video effect , image : 1280x960 ; video : 640x480 @ 30 FPS - usb - Retail pack
WC-MNX6000D		Microsoft Lifecam NX6000 Dsp , CMOS SXGA , with notebook mobility , 71° diagonal field of view , silver , built-in Mic , wide-angle len , windows live messenger call button , 3 x digital zoom , pan and tilt , auto face-tracking , video effect , image : 7.6mega pixel 3200x2380 (interpolated) ; video : 2.0 mega pixel upto 1600x1190 @ 30 FPS - usb - dsp pack
WC-MNX6000		Microsoft Lifecam NX6000 , CMOS SXGA , with notebook mobility , 71° diagonal field of view , silver , built-in Mic , wide-angle len , windows live messenger call button , 3 x digital zoom , pan and tilt , auto face-tracking , video effect , image : 7.6mega pixel 3200x2380 (interpolated) ; video : 2.0 mega pixel upto 1600x1190 @ 30 FPS - usb - retail pack with carry case

WC-MSHoW	N	Microsoft Lifecam Show , ultra-thin mobile design , HD CMOS , with desktop stannd + laptop clip + attachment disc , built-in noise cancelling mic , windows live messenger call button , 5 x digital zoom , pan and tilt , auto face-tracking , video effect , image : 2.0mega pixel 3200x2380 (interpolated) ; video : 2.0 mega pixel upto 1600x1190 @ 30 FPS - usb - retail pack with carry case
WC-MVX7000		Microsoft Lifecam VX7000 , CMOS SXGA , 72° diagonal field of view , silver , built-in Mic , wide-angle len , windows live messenger call button , 2.0 mega pixel , 3 x digital zoom , pan and tilt , auto face-tracking , video effect , image : 3200x2380 ; video : upto 1600x1190 @ 30 FPS - usb - Retail pack
SMC		
WC-LQNPSCK		Logitech QuickCam Notebook Pro (with RightSound technology , VGA CCD, 1.3mega pixel with RightLight technology , image: 1280x900 , video : 640x480, digital zoom , auto face-tracking , universal fit) , bundle with carry case + earphone + built-in mic + VMEET conference software (support upto 16 way conference)
Logitech		
for desktop / notebook		
WC-LQN		Logitech 961404/960-000011 Quickcam for Notebook , compact & portable design , CMOS, manual focus , image 640x480 , video 320x240, universal fit - usb
WC-LQNDo		Logitech 961442 Quickcam Notebook Delux Oem pack , compact & portable design , VGA CCD , auto face-tracking , image : 1.3 megapixel , video : 640x480 @ 15FPS , universal fit , with neoprene travel case - usb
WC-LQDN		Logitech 960-000044 Quickcam Delux for Notebook , with built-in mic , with RightSound technology , compact & portable design , VGA CCD , auto face-tracking , image : 1.3 megapixel , video : 640x480 @ 15FPS , universal fit , with neoprene travel case - usb
WC-LQNP		Logitech 961398 QuickCam Notebook Pro with built-in headphone + mic , with RightSound technology , VGA CCD, 1.3mega pixel with RightLight technology , image: 1280x900 , video : 640x480, digital zoom , auto face-tracking , universal fit , with video editing software , neoprene travel case - usb
WC-LQPN		Logitech 960-000047 QuickCam Pro for Notebook , with Carl Zeiss optics , desktop stand (up to 30.5cm) , with built-in mic , with RightSound technology , VGA CCD, 2/8 mega pixel with RightLight2 technology , image: 1960x1440 , 1800x1200 / 960x720 HD video @ 30FPS , digital zoom , auto face-tracking , universal fit , with video editing software , neoprene travel case - usb
WC-LQE2500	N	Logitech 960-000227 Quickcam E2500 , CMOS , built-in mic with RightSound technology , image+video : 640x480 @ 30 FPS , manual focusing - usb
WC-LQE3500	N	Logitech 960-000222 Quickcam E3500 , CMOS , built-in mic with RightSound technology , image: 1.3 megapixel with RightLight technology , video : 640x480 @ 30FPS , manual focusing - usb
WC-LQCSP		Logitech 961410-5914 Quickcam Communicate STX Plus , bundled stereo headset+mic , VGA CCD , fixed focus , image: 1.3 megapixel , video : 640x480 @ 30FPS , adjustable clip - usb
WC-LQE3500P	N	Logitech 960-000235 Quickcam E3500 Plus , bundled stereo headset+mic , CMOS , built-in mic with RightSound technology , image: 1.3 megapixel with RightLight technology , video : 640x480 @ 30FPS , manual focusing - usb

WC-LQS5500	N	Logitech 960-000245 Quickcam S5500 , built-in Microphone with RightSound technology , VGA CCD, 1.3mega pixel with RightLight technology , auto face-tracking , activity light while on live , image: 1280x960 , video : 640x480 , digital zoom , support Logitech Video Effects - usb
WC-LQCD		Logitech 961465 Quickcam Communicate Delux , built-in mic , VGA CCD , fixed focus , image: 1.3 megapixel , HD video : 960x720 @ 30FPS , adjustable clip - usb
WC-LQUV		Logitech 961471 Quickcam Ultra Vision , built-in Microphone with RightSound2 technology , quick preview button , 5 precision engineered lens elements , VGA , 1.3mega pixel with RightLight technology , auto face-tracking , image: 1280x900 , video : 640x480 , digital zoom , support Logitech Video Effects - usb
WC-LQS7500	N	Logitech 960-000252 Quickcam S7500 , built-in mic with RightSound 2 technology , VGA CCD , fixed focus , 1.3mega pixel with RightLight technology , HD video : 960x720 @ 30FPS , adjustable clip - usb
WC-LQP9		Logitech 960-000053 Quickcam Pro 9000 , with Carl Zeiss optics , built-in Microphone with RightSound 2 technology , VGA CCD , 2/8 mega pixel with RightLight 2 technology , auto face-tracking , image: 1960x1440 , 1600x1200 / 960x720 HD video @ 30FPS , digital zoom , support Logitech Video Effects - usb
WC-LQVP	N	Logitech 960-000301 Quickcam Vision Pro - for mac , with Carl Zeiss optics , built-in Microphone with RightSound 2 technology , VGA CCD , 2/8 mega pixel with RightLight 2 technology , auto face-tracking , image: 1960x1440 , 1600x1200 / 960x720 HD video @ 30FPS , digital zoom , support Logitech Video Effects - usb
WC-LQSAF		Logitech 960-000116 Quickcam Sphere AF , with Carl Zeiss optics , extendable stand (up to 23cm) , motorised pan and tilt , with built-in mic , VGA CCD, 2/8 mega pixel with RightLight 2 technology , image: 1280x900 , video : 1600x1200 / 960x720 , digital zoom , auto face-tracking - usb
for internet security		http://www.logitech.com/index.cfm/webcam_communications/video_security_systems/&cl=za,en
WC-LiVSMS	N	Logitech 961-000005 Indoor Video Security Master System , home plug network technology (transmit video over existing electrical wires) , usb receiver to pc , iP camera , motion detection triggers recording and sends e-mail alerts , support upto 6 cameras , with wall-mount / window-mount
WC-LoVSMS	N	Logitech 961-000273 Outdoor Video Security Master System , home plug network technology (transmit video over existing electrical wires) , usb receiver to pc , iP camera , motion detection triggers recording and sends e-mail alerts , support upto 6 cameras - with weatherproof housing
WC-LiAoSC	N	Logitech 961-000278 Indoor Add-On Security Camera , home plug network technology (transmit video over existing electrical wires) , usb receiver to pc
WC-LoAoSC	N	Logitech 961-000280 Outdoor Add-On Security Camera , home plug network technology (transmit video over existing electrical wires) , usb receiver to pc
D-Link internet camera		
WC-DCS910	N	D-Link DCS-910 internet camera (iP camera) - 10/100 , 1/4" Cmos VGA sensor , 1.0 Lux @ F2.8 , motion detection triggers recording and sends e-mail alerts , 320x240@30fps - 640x480@15fps , remote management software support upto 32 cameras

WC-DCS920	N	D-Link DCS-920 internet camera (iP camera) - 10/100 or 802.11G wireless , 1/4" Cmos VGA sensor , 1.0 Lux @ F2.8 , motion detection triggers recording and sends e-mail alerts , 320x240@30fps - 640x480@15fps , remote management software support upto 32 cameras
WC-DCS2102	N	D-Link DCS-2102 , 2-way audio - 10/100 , 64mb+8mb with SD slot (upto 16gb for front-end storage) , captures video in minimal lighting - 0.5 Lux @ F2.8 , record to remote HDD or NAS , 16x digital zoom , motion detection triggers recording and sends e-mail alerts , 640x480@30fps - 1280x1024@10fps , remote management software support upto 32 cameras
WC-DCS950G		D-Link DCS-950G internet camera (iP camera) - 10/100 or 802.11G wireless , captures video in minimal lighting - 0.5 Lux @ F1.4 , record to remote HDD or NAS , motion detection triggers recording and sends e-mail alerts , 640x480@30fps , remote management software support upto 4 cameras
WC-DCS2121	N	D-Link DCS-2121 2-way audio + 3G mobile video internet camera (iP camera) - 10/100 or 802.11G wireless , 64mb+8mb with SD slot (upto 16gb for front-end storage) , captures video in minimal lighting - 0.5 Lux @ F2.8 , record to remote HDD or NAS , 16x digital zoom , motion detection triggers recording and sends e-mail alerts , 640x480@30fps - 1280x1024@10fps , remote management software support upto 32 cameras
WC-DCS3220	R	D-Link DCS-3220 2-way audio internet camera (iP camera) with CCD Sensor - 10/100 , captures video in minimal lighting - 1.0 Lux @ F2.0 , 4x digital zoom , motion detection triggers recording and sends e-mail alerts , 352x240@30fps - 704x480@10fps - listen and talk to anyone at camera site by adding speaker , remote management software support upto 16 cameras
WC-DCS3220G		D-Link DCS-3220G 2-way audio internet camera (iP camera) with CCD Sensor - 10/100 or 802.11G wireless , captures video in minimal lighting - 1.0 Lux @ F2.0 , 4x digital zoom, motion detection triggers recording and sends e-mail alerts , 352x240@30fps - 704x480@10fps - listen and talk to anyone at camera site by adding speaker , remote management software support upto 16 cameras
WC-DCS5220	R	D-Link DCS-5220 internet camera (iP camera) with CCD Sensor - PAN+TiLT+ZOOM , 10/100 or 802.11G wireless + 3G video support to mobile phone or PDA , 4x digital zoom , captures video in minimal lighting - 0.5 Lux @ F2.0 , motion detection triggers recording and sends e-mail alerts , 640x480@30fps
WC-DCS3420	R	D-Link DCS-3420 with day/night vision , 2-way audio internet camera (iP camera) with CCD Sensor - BNC + 10/100 + 802.11G wireless, All-Weather Aluminum Housing , 16mb+4mb memory , 4x digital zoom - 0.05 Lux @ F2.0 / 0 Lux in 10m via optional IR lens , motion detection triggers recording and sends e-mail alerts , 352x288@25fps - 704x576@12fps - listen and talk to anyone at camera site by adding speaker , remote management software support upto 16 cameras
WC-DCS6620	R	D-Link DCS-6620 2-way audio internet camera (iP camera) - PAN+TiLT+ZOOM + TV-OUT (for video recording) , 10/100 , 10 times optical zoom , captures video in minimal lighting - 0.05 Lux @ F1.8 , motion detection triggers recording and sends e-mail alerts , 352x240@30fps - 704x480@10FPS - listen and talk to anyone at camera site by adding speaker , support 20 user accounts / 10 simultaneous users

WC-DCS6620G	R	D-Link DCS-6620G 2-way audio internet camera (iP camera) - PAN+TiLT+ZOOM + TV-OUT (for video recording) , 10/100 or 802.11G wireless , 10 times optical zoom , captures video in minimal lighting - 0.05 Lux @ F1.8 , motion detection triggers recording and sends e-mail alerts , 352x240@30fps - 704x480@10FPS - listen and talk to anyone at camera site by adding speaker , support 20 user accounts / 10 simultaneous users
NE-DWLP50		D-Link DWL-P50 POE (Power Over Ethernet) terminal unit to work with P200 base unit or PoE switch , transmit data+power through network (1port) , upto 100m , ideal to work with 5V/12V networking device like access point , bridge , switch , router , internet security camera … etc , with power surge protection
NE-DWLP200		D-Link DWL-P200 POE (Power Over Ethernet) terminal unit + base unit , transmit data+power through network (1port) , upto 100m , ideal to work with 5V/12V networking device like access point , bridge , switch , router , internet security camera … etc
WC-DADCS45		D-Link DCS-45 outdoor enclosure with thermal barrier - for DCS-2000 series , DCS-3220 series , DCS3420
WC-DADCS50	R	D-Link DCS-50 outdoor enclosure with built-in power supply , industrial grade , with IP66 certification - for DCS-2000 series , DCS-3220 series , DCS3420
WC-DADCS60	R	D-Link DCS-60 outdoor enclosure with built-in power supply , heater , blower , industrial grade , with IP66 certification - for DCS-2000 series , DCS-3220 series , DCS3420
WC-DADCS70	R	D-Link DCS-70 outdoor enclosure with built-in power supply , heater , blower , industrial grade , with IP66 certification - for DCS-5300 series , DCS-6620 series

HeadSet , Headphone , Mic

Razer

HS-RMB		Razer M100/Moray earphone , Black , In-The-Ear design with ProBass , with asymmetrical cable design (allows the user to run the longer cable behind the neck when the earphones are temporarily removed from the ear) , Noise isolation , 16 ohms , with carrying case - with 3.5mm audio jack + jet-set adaptor for air travel
HS-RMW		Razer M100/Moray earphone , White , In-The-Ear design with ProBass , with asymmetrical cable design (allows the user to run the longer cable behind the neck when the earphones are temporarily removed from the ear) , Noise isolation , 16 ohms , with carrying case - with 3.5mm audio jack + jet-set adaptor for air travel
HS-RM250B		Razer M250 Pro|Tone earphone , Black , Rubber-coated clip arms + aluminum casings design with ProBass , Noise isolation , 32 ohms , with carrying case , with 3.5mm audio jack + jet-set adaptor for air travel
HS-RM250S		Razer M250 Pro|Tone earphone , Silver , Rubber-coated clip arms + aluminum casings design with ProBass , Noise isolation , 32 ohms , with carrying case , with 3.5mm audio jack + jet-set adaptor for air travel
HS-RP		Razer Piranha gaming communicator - headset with noise-filtering mic , in-line control with volume Control , 3.5mm
HS-RC	**C**	Razer carcharias gaming headset - full over-ear coverage , noise-filtering mic , 40mm Neodymium magnet drivers , in-line control with volume Control , 3.5mm

HS-RM	C	Razer Megalodon 7.1ch gaming headset with Mic , 3D 140° , military-grade audio engine , built-in amplifier , uni-directional noise-canceling ultra-sensitive mic , 6 discrete driver + 2 sub-woofer , 24bit , 105db SNR , 99% oxygen-free copper cable , in-line control with Individual channel volume Control + master volume touch-control dial ; usb
Asus		
mic / headset for PC		
HS-AHS1000W	C	Asus HS-1000W - 2.4 GHz wireless headset with mic upto 20m , 40mm driver , with NCAT , plush headband , Quick-access audio controls + flexible boom - usb
Zalman		
HS-ZMiC		Zalman ZM-MIC1; high sensitivity Mic ; with 3 x mini Clips for tidy arrangement
HS-ZDS4FB		Zalman headphone ZM-DS4F , Black , 2-way 4 speaker system , 3-point foldable headphone with 4 diaphragms , 28mm Tweeters high sound and 40mm PEI Woofers for full powered Bass ; Electro Dynamic Round Type Micro Speaker
HS-ZDS4FW		Zalman headphone ZM-DS4F , White , 2-way 4 speaker system , 3-point foldable headphone with 4 diaphragms , 28mm Tweeters high sound and 40mm PEI Woofers for full powered Bass ; Electro Dynamic Round Type Micro Speaker
HS-ZRS6F		Zalman headphone ZM-RS6F 5.1ch surround headphone ; Electro Dynamic Round Type Micro Speaker
HS-ZRS6FM		Zalman headphone ZM-RS6F+M 5.1ch surround headphone with Mic ; Electro Dynamic Round Type Micro Speaker
HS-ZRS6FU		Zalman headphone ZM-RS6F Usb - 5.1ch surround headphone , built-in in-line C-Media CM6206 5.1 usb sound card + volumn control ; Electro Dynamic Round Type Micro Speaker
Zboard		
HS-ZGH100		zboard GH-100 gaming headset , behind head design , 30mm driver , in-line volumn control - with 3.5mm audio jack
HS-ZB		zboard Banshee gaming headset , maximum comfort with dual suspension , L+R stereo mic , 40mm driver , with in-line control , with 3.5mm + 6.5mm stereo jack
Microsoft		
HS-MLX2000	N	Microsoft lifechat LX-2000 stereo headset with microphone , foldable + behind-the-head design , In-line volume controls- with carry case
HS-MLX3000		Microsoft lifechat LX-3000 stereo headset with noise-cancelling microphone , In-line volume controls , usb
HS-MZX6000	N	Microsoft lifechat ZX-6000 2.4Ghz wireless headset with noise-cancelling mic , single ear piece , padded ear cup and adjustable earband , volume controls + live call button , usb
Creative		
earphone/headphone for 3.5mm audio		
HS-CEP480B		Creative EP-480 stereo earphone , black , in-ear design , 15mm drivers , in-line volumn control - with 3.5mm audio jack
HS-CEP480L		Creative EP-480 stereo earphone , blue , in-ear design , 15mm drivers , in-line volumn control - with 3.5mm audio jack
HS-CEP480P		Creative EP-480 stereo earphone , pink , in-ear design , 15mm drivers , in-line volumn control - with 3.5mm audio jack
HS-CHQ1900	N	Creative HQ-1900 stereo earphone , foldable design , 30mm Neodymium magnet drivers , 1.2m oxygen-free copper cable , in-line volumn control - with 3.5mm audio jack
Skullcandy		http://www.skullcandy.com/shop/
Chops ear-hanger		http://www.skullcandy.com/shop/chops-p-84.html
HS-SCB		Skullcandy Chops Black , stereo ear hanger ; 15mm speaker, 16 ohms, 18-20K Hz , 30mw input power

HS-SCG		Skullcandy Chops Grey , stereo ear hanger ; 15mm speaker, 16 ohms, 18-20K Hz , 30mw input power
HS-SCP		Skullcandy Chops Purple , stereo ear hanger ; 15mm speaker, 16 ohms, 18-20K Hz , 30mw input power
HS-SCWT	C	Skullcandy Chops White-Turquoise , stereo ear hanger ; 15mm speaker, 16 ohms, 18-20K Hz , 30mw input power
INK'D earbuds		http://www.skullcandy.com/shop/inkd-p-107.html
HS-SiNKDDG		Skullcandy INK'D Dark Grey stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power , with In-line voulmn control
HS-SiNKDMB		Skullcandy INK'D Metal Blue stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power , with In-line voulmn control
HS-SiNKDPi		Skullcandy INK'D Pink stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power , with In-line voulmn control
HS-SiNKDB	N	Skullcandy INK'D Black stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power , with In-line voulmn control
HS-SiNKDW	N	Skullcandy INK'D White stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power , with In-line voulmn control
HS-SiNKDS	N	Skullcandy INK'D Silver stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power , with In-line voulmn control
HS-SiNKDY	C	Skullcandy INK'D Yellow stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power , with In-line voulmn control
HS-SiNKDMG	N	Skullcandy INK'D Metal Green stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power , with In-line voulmn control
HS-SiNKDMR	N	Skullcandy INK'D Metal Red stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power , with In-line voulmn control
HS-SiNKDPU	C	Skullcandy INK'D PUrple stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power , with In-line voulmn control
Icon / Recruit headphone		http://www.skullcandy.com/shop/smokin-buds-p-10.html
HS-SiC	C	Skullcandy Icon/recruit - Chrome , stereo headphone ; 30mm speaker, 45g light-weight , double headband - 3.5mm input
HS-SiM	C	Skullcandy Icon/recruit - Mix , stereo headphone ; 30mm speaker, 45g light-weight , double headband - 3.5mm input
Smokin Buds earbuds		http://www.skullcandy.com/shop/smokin-buds-p-10.html
HS-SSBR		Skullcandy Smokin Buds Rasta stereo earbuds ; 9mm speaker, 16 ohms, 100-18K Hz , with In-line voulmn control
HS-SSBB		Skullcandy Smokin Buds Black stereo earbuds ; 9mm speaker, 16 ohms, 100-18K Hz , with In-line voulmn control
HS-SSBP		Skullcandy Smokin Buds Pink stereo earbuds ; 9mm speaker, 16 ohms, 100-18K Hz , with In-line voulmn control
HS-SSBW		Skullcandy Smokin Buds White stereo earbuds ; 9mm speaker, 16 ohms, 100-18K Hz , with In-line voulmn control
HS-SSBL		Skullcandy Smokin Buds Lime stereo earbuds ; 9mm speaker, 16 ohms, 100-18K Hz , with In-line voulmn control
HS-SSBY		Skullcandy Smokin Buds Yellow stereo earbuds ; 9mm speaker, 16 ohms, 100-18K Hz , with In-line voulmn control
HS-SSBM		Skullcandy Smokin Buds Mint stereo earbuds ; 9mm speaker, 16 ohms, 100-18K Hz , with In-line voulmn control
HS-SSBC		Skullcandy Smokin Buds Culurful stereo earbuds ; 9mm speaker, 16 ohms, 100-18K Hz , with In-line voulmn control
Lowrider series headphone		http://www.skullcandy.com/shop/lowrider-p-26.html

HS-SLB		Skullcandy Lowrider - Black , stereo headphone ; 40mm speaker, 32 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SLBG		Skullcandy Lowrider - Black-Gold , stereo headphone ; 40mm speaker, 32 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SLBS		Skullcandy Lowrider - Black-Silver , stereo headphone ; 40mm speaker, 32 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SLCL		Skullcandy Lowrider - Chrome-bLue , stereo headphone ; 40mm speaker, 32 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SLCY		Skullcandy Lowrider - Chrome-Yellow , stereo headphone ; 40mm speaker, 32 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SLLB		Skullcandy Lowrider - Lime-Black , stereo headphone ; 40mm speaker, 32 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SLMR		Skullcandy Lowrider - MacRed , stereo headphone ; 40mm speaker, 32 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SLNB		Skullcandy Lowrider - Native-Black , stereo headphone ; 40mm speaker, 32 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SLNBR		Skullcandy Lowrider - Native-BRown , stereo headphone ; 40mm speaker, 32 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SLSR		Skullcandy Lowrider - Silver-Red , stereo headphone ; 40mm speaker, 32 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SLWG	C	Skullcandy Lowrider - White-Gold , stereo headphone ; 40mm speaker, 32 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SLRW		Skullcandy Lowrider - Red-White , stereo headphone ; 40mm speaker, 32 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
Titan earbuds		http://www.skullcandy.com/shop/titan-p-82.html
HS-STDG		Skullcandy Titan Dark Grey stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power
HS-STML		Skullcandy Titan Metal bLue stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power
HS-STC		Skullcandy Titan Chrome stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power
HS-STMR		Skullcandy Titan Mac Red stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power
HS-STMP		Skullcandy Titan Mac Pink stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power
HS-STS		Skullcandy Titan Silver stereo earbuds ; 11mm speaker, 16 ohms, 20-20K Hz , 100mw input power
Hesh series headphone		http://www.skullcandy.com/shop/hesh-p-5.html
HS-SHB		Skullcandy Hesh - Black , stereo headphone ; 50mm speaker, 32 ohms, 100-18K Hz , 100mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SHBG	C	Skullcandy Hesh - Black-Green , stereo headphone ; 50mm speaker, 32 ohms, 100-18K Hz , 100mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SHBR		Skullcandy Hesh - Black-Red , stereo headphone ; 50mm speaker, 32 ohms, 100-18K Hz , 100mw input power , soft leather touch head wrap pad - 3.5mm input

HS-SHBW		Skullcandy Hesh - Black-White , stereo headphone ; 50mm speaker, 32 ohms, 100-18K Hz , 100mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SHS	C	Skullcandy Hesh - Stripe , stereo headphone ; 50mm speaker, 32 ohms, 100-18K Hz , 100mw input power , soft leather touch head wrap pad - 3.5mm input
SkullCrusher series		http://www.skullcandy.com/shop/skullcrushers-p-92.html
HS-SSCBC		Skullcandy SkullCrushers Black-Checker , stereo headphone ; 30mm neodymium magnet speaker , 30mm vibration speaker, 32 ohms, 20-20K Hz , soft leather touch head wrap pad , with In-line vibration level adjustment and on/off switch - 3.5mm / 6.3mm input
HS-SSCBP		Skullcandy SkullCrushers Black-Pinstripe , stereo headphone ; 30mm neodymium magnet speaker , 30mm vibration speaker, 32 ohms, 20-20K Hz , soft leather touch head wrap pad , with In-line vibration level adjustment and on/off switch - 3.5mm / 6.3mm input
HS-SSCG		Skullcandy SkullCrushers Gold , stereo headphone ; 30mm neodymium magnet speaker , 30mm vibration speaker, 32 ohms, 20-20K Hz , soft leather touch head wrap pad , with In-line vibration level adjustment and on/off switch - 3.5mm / 6.3mm input
HS-SSCL		Skullcandy SkullCrushers bLue , stereo headphone ; 30mm neodymium magnet speaker , 30mm vibration speaker, 32 ohms, 20-20K Hz , soft leather touch head wrap pad , with In-line vibration level adjustment and on/off switch - 3.5mm / 6.3mm input
HS-SSCMB		Skullcandy SkullCrushers Multimedia (with Mic) , Black , stereo headphone ; 30mm neodymium magnet speaker , 30mm vibration speaker, 32 ohms, 20-20K Hz , soft leather touch head wrap pad , with In-line vibration level adjustment and on/off switch - 3.5mm / 6.3mm input
Gi series headphone		http://www.skullcandy.com/shop/gi-p-6.html
HS-SGiR		Skullcandy Gi - Rasta , stereo headphone ; 40mm speaker, 50 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SGiRC		Skullcandy Gi - Red-Core , stereo headphone ; 40mm speaker, 50 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SGiGN		Skullcandy Gi - GreeN-core , stereo headphone ; 40mm speaker, 50 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SGiGY		Skullcandy Gi - GreY-core , stereo headphone ; 40mm speaker, 50 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SGiWC		Skullcandy Gi - Winter-Camo , stereo headphone ; 40mm speaker, 50 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
HS-SGiDC		Skullcandy Gi - Desert-Camo , stereo headphone ; 40mm speaker, 50 ohms, 100-18K Hz , 400mw input power , soft leather touch head wrap pad - 3.5mm input
FMJ earbuds		http://www.skullcandy.com/shop/full-metal-jacket-p-30.html
HS-SFMJDG		Skullcandy FMJ (Full Mretal Jacket) Dark-Grey stereo earbuds , with aluminum foil cable ; 11mm speaker, 16 ohms, 16-20K Hz , for iPhone / backberry / 3.5mm audio - with bundled carry bag
HS-SFMJS		Skullcandy FMJ (Full Mretal Jacket) Silver stereo earbuds , with aluminum foil cable ; 11mm speaker, 16 ohms, 16-20K Hz , for iPhone / backberry / 3.5mm audio - with bundled carry bag

HS-SFMJML		Skullcandy FMJ (Full Mretal Jacket) Metal bLue stereo earbuds , with aluminum foil cable ; 11mm speaker, 16 ohms, 16-20K Hz , for iPhone / backberry / 3.5mm audio - with bundled carry bag
HS-SFMJP		Skullcandy FMJ (Full Mretal Jacket) Pink stereo earbuds , with aluminum foil cable ; 11mm speaker, 16 ohms, 16-20K Hz , for iPhone / backberry / 3.5mm audio - with bundled carry bag
HS-SFMJC		Skullcandy FMJ (Full Mretal Jacket) Chrome stereo earbuds , with aluminum foil cable ; 11mm speaker, 16 ohms, 16-20K Hz , for iPhone / backberry / 3.5mm audio - with bundled carry bag
iPhone FMJ earbuds		http://www.skullcandy.com/shop/iphone-fmj-p-72.html
HS-SiPFMJB		Skullcandy iPhone FMJ Black stereo earbuds , with aluminum foil cable ; 11mm speaker, 16 ohms, 16-20K Hz , 500mw input power , with in-line control , for iPhone / backberry / 3.5mm audio
HS-SiPFMJC		Skullcandy iPhone FMJ Chrome stereo earbuds , with aluminum foil cable ; 11mm speaker, 16 ohms, 16-20K Hz , 500mw input power , with in-line control , for iPhone / backberry / 3.5mm audio
HS-SiPFMJS		Skullcandy iPhone FMJ Silver stereo earbuds , with aluminum foil cable ; 11mm speaker, 16 ohms, 16-20K Hz , 500mw input power , with in-line control , for iPhone / backberry / 3.5mm audio
Ti series headphone		http://www.skullcandy.com/shop/ti-p-7.html
HS-STiBF		Skullcandy Ti Black Fur , stereo headphone ; 40mm Titanium speaker, 32/50 ohms, 100-18K Hz , 400mw input power , with in-line control , soft leather touch head wrap pad
HS-STiBG		Skullcandy Ti Brown Gold , stereo headphone ; 40mm Titanium speaker, 32/50 ohms, 100-18K Hz , 400mw input power , with in-line control , soft leather touch head wrap pad
HS-STiWF		Skullcandy Ti White-Fur , stereo headphone ; 40mm Titanium speaker, 32/50 ohms, 100-18K Hz , 400mw input power , with in-line control , soft leather touch head wrap pad + Fur
HS-STiPF		Skullcandy Ti Pink-Fur , stereo headphone ; 40mm Titanium speaker, 32/50 ohms, 100-18K Hz , 400mw input power , with in-line control , soft leather touch head wrap pad + Fur
HS-STiGF		Skullcandy Ti Gold Foil , stereo headphone ; 40mm Titanium speaker, 32/50 ohms, 100-18K Hz , 400mw input power , with in-line control , soft leather touch head wrap pad
HS-STiPGY		Skullcandy Ti Patent-Green-Yellow , stereo headphone ; 40mm Titanium speaker, 32/50 ohms, 100-18K Hz , 400mw input power , with in-line control , soft leather touch head wrap pad
double agent headphone		http://www.skullcandy.com/shop/double-agent-p-86.html
HS-SDABK	C	Skullcandy Double Agent , BlacK - headphone with SD card slot for digital music, wireless music player + built-in player ; 40mm speaker, 32 ohms, 18-20K Hz , soft leather touch head wrap pad , also with 3.5mm audio jack
HS-SDABR	C	Skullcandy Double Agent , BRown - headphone with SD card slot for digital music, wireless music player + built-in player ; 40mm speaker, 32 ohms, 18-20K Hz , soft leather touch head wrap pad , also with 3.5mm audio jack
HS-SDAGR	C	Skullcandy Double Agent , GReen - headphone with SD card slot for digital music, wireless music player + built-in player ; 40mm speaker, 32 ohms, 18-20K Hz , soft leather touch head wrap pad , also with 3.5mm audio jack
SK Pro headphone		http://www.skullcandy.com/shop/sk-pro-p-13.html
HS-SSKPB	C	Skullcandy SK Pro Black , stereo headphone ; 50mm speaker + 50mm power drivers , 64 ohms , 20-20K Hz , 100mw input power , 90-degree swivel ear cups for studio monitoring , soft leather touch head wrap pad - 3.5/6.3mm input - with travel bag

HS-SSKPL	C	Skullcandy SK Pro bLue , stereo headphone ; 50mm speaker + 50mm power drivers , 64 ohms , 20-20K Hz , 100mw input power , 90-degree swivel ear cups for studio monitoring , soft leather touch head wrap pad - 3.5/6.3mm input - with travel bag
HS-SSKPY	C	Skullcandy SK Pro Yellow , stereo headphone ; 50mm speaker + 50mm power drivers , 64 ohms , 20-20K Hz , 100mw input power , 90-degree swivel ear cups for studio monitoring , soft leather touch head wrap pad - 3.5/6.3mm input - with travel bag
HS-SSKPR	C	Skullcandy SK Pro Red , stereo headphone ; 50mm speaker + 50mm power drivers , 64 ohms , 20-20K Hz , 100mw input power , 90-degree swivel ear cups for studio monitoring , soft leather touch head wrap pad - 3.5/6.3mm input - with travel bag
Logitech		
headphone		
HS-LoD220		Logitech 980177 Oem Dialogue 220 stereo headphone with volumn control
HS-Li		Logitech 980377 Identity for mp3 , with 4 exchangable color plates (white, black , orange , green) , 30mm neodymium drivers , behind-head design , with volume control , with 3.5mm audio jack
mic / headset for PC		
HS-LoD320		Logitech 980178 Oem Dialogue 320 beige desktop microphone , with NCAT , pivots on weighted, stable base - 3.5mm
HS-LDM		Logitech 980240 Desktop Microphone , with NCAT , pivots on weighted, stable base - 3.5mm
HS-LUDM		Logitech 980186 USB Desktop Microphone , with NCAT , pivots on weighted, stable base - usb
HS-Lo850	N	Logitech 981-000096 Oem 850 mono headset with mic , with NCAT, inline volume and mute control - 3.5mm
HS-Lo860		Logitech 981-000094 Oem 860 stereo headset with mic , with NCAT, inline volume and mute control - 3.5mm
HS-Lo880	N	Logitech 981-000075 Oem 880 stereo headset with mic , with NCAT, inline volume and mute control , behind head design - 3.5mm
HS-LCCSTE		Logitech 981-000025 ClearChat STEreo with mic , with NCAT, inline volume and mute control - 3.5mm
HS-L120		Logitech 980447 pc headset 120 stereo headset with mic , with NCAT, inline volume and mute control , behind head design - 3.5mm
HS-Lo960U	N	Logitech 981-000100 PC Headset 960 USB stereo headset with mic , with NCAT , inline volume and mute control - USB
HS-LCCP		Logitech 980369 ClearChat Premium headset with mic , with NCAT , inline volume and mute control - 3.5mm
HS-LCCSTY		Logitech 981-000019 ClearChat STYle with mic , with NCAT, inline volume and mute control, behind head design , with 4 interchangeable plat - 3.5mm
HS-LDPG		Logitech 981-000041 Digital Precesion Gaming headset with mic , with NCAT , inline volume and mute control , behind head + open air design - USB or 3.5mm
HS-LCCCU		Logitech 981-000015 ClearChat Comfort Usb , stereo headset with mic , adjustable, padded headband , plush ear pads , with NCAT , inline volume and mute control - usb
HS-LCCPU		Logitech 981-000011 ClearChat Pro Usb stereo headset with mic , laser-tuned audio drivers , flexible boom , audio controls + equalizer on headset with mute indicator, with NCAT - usb
HS-LPN		Logitech 980445 Premium Notebook headset with mic , with NCAT , adjustable earpieces , travel case , inline volume and mute control , plush earpads - usb (include Analog-to-USB adapter)

HS-LCCPCW	N	Logitech 981-000069 ClearChat PC Wireless - 2.4 GHz wireless headset with mic upto 10m , with NCAT , plush headband , Quick-access audio controls + flexible boom - usb
HS-LG35		Logitech 981-000117 G35 surround gaming headset with mic , 7.1 surround sound , 3 sizes swappable contoured headband pads , plush ear pads + headband adjustment , 3 customizable G-keys , on-ear audio inline controls, 6x real-time voice morphing , with microphone mute light , 40mm drivers with neodymium magnets - USB
bluetooth headset for cellphone		
HS-LME		Logitech 980408 Mobile Express headset for cellphone , bluetooth 1.2 , range 10m , inline volume and mute control
HS-LMF		Logitech 980228 Mobile Freedom headset for cellphone with WindStop mic , bluetooth 1.2 , range 10m , inline volume and mute control
HS-LMT		Logitech 980399/939-000073 Mobile Traveller headset for cellphone , with WindStop mic , bluetooth 1.2 , range 10m , inline volume and mute control - 2 years warranty
Add-on Audio		
internal sound card		
ASONIC		
AA-A87386		Asonic 8738-6C 5.1 pci sound card , C-MEDIA CMi8768 chipset , HRTF-based 3D
AA-A87688		Asonic 8768/8868-8C 7.1 pci sound card , C-MEDIA CMi8768 chipset , HRTF-based 3D
Asus		
Pci		
AA-AXD1	N	Asus Xonar D1 , ultra fidelity 7.1 pci sound card , support DS3D GX 2.0 , VocalFX , Dolby®/DTS + Pro Logic IIx , SNR up to 116db , HD Audio at 192KHz/24Bit , EAX advanced HD , with optical SPDiF out + HDMi out (via header to VGA card with HDMi out) + 3.5mm + CD-In + Aux-In - retail pack + bundled software - include low-profile bracket for 2u or minuet350
AA-AXD2		Asus Xonar D2/pm , ultra fidelity 7.1 pci sound card with metal shielding , Dolby®/DTS + Pro Logic IIx + ALT DRM backup + AEC , SNR up to 118db , HD Audio at 192KHz/24Bit , EAX advanced HD , with coaxial/optical optical SPDiF in/out + 3.5mm + CD-In + Aux-In + midi port (in+out) - retail pack + bundled software
Pci-Express		
AA-AXDX	N	Asus Xonar DX , ultra fidelity 7.1 pci-express sound card , support DS3D GX 2.0 , VocalFX , Dolby®/DTS + Pro Logic IIx , SNR up to 116db , HD Audio at 192KHz/24Bit , EAX advanced HD , with optical SPDiF out + HDMi out (via header to VGA card with HDMi out) + 3.5mm + CD-In + Aux-In - retail pack + bundled software - include low-profile bracket for 2u or minuet350
AA-AXES	N	Asus Xonar Essence Stx , ultra fidelity 7.1 pci-express sound card , support DS3D GX 2.0 , VocalFX , Dolby®/DTS + Pro Logic IIx , SNR up to 124db , HD Audio at 192KHz/24Bit , EAX advanced HD , with optical SPDiF out + HDMi out (via header to VGA card with HDMi out) + RCAx2 analog out + 3.5mm + CD-In + Aux-In - retail pack + bundled software
AA-AXD2X		Asus Xonar D2X , ultra fidelity 7.1 pci-express sound card with metal shielding , support DS3D GX Dolby®/DTS + Pro Logic IIx + ALT DRM backup + AEC , SNR up to 118db , HD Audio at 192KHz/24Bit , EAX advanced HD , with coaxial/optical optical SPDiF in/out + 3.5mm + CD-In + Aux-In + midi port (in+out) - retail pack + bundled software

AA-AXH	N	Asus Xonar Hdav1.3 , HDMI 1.3 compliance , 1080p Full-HD audio/video digital output with splendid technology video enhancement , ultra fidelity 7.1 pci-express sound card with metal shielding , support Dolby trueHD + DTS-HD + Pro Logic IIx , SNR up to 123db , HD Audio at 192KHz/24Bit , EAX advanced HD , with HDMi in/out + RCAx2 analog out + coaxial/optical optical SPDiF in/out + 3.5mm + CD-In + Aux-In - retail pack + bundled software
AA-AXHD	N	Asus Xonar Hdav1.3 Deluxe , HDMI 1.3 compliance , 1080p Full-HD audio/video digital output with splendid technology video enhancement , ultra fidelity 7.1 pci-express sound card with metal shielding , support Dolby trueHD + DTS-HD + Pro Logic IIx , SNR up to 123db , HD Audio at 192KHz/24Bit , EAX advanced HD , with HDMi in/out + RCAx8 analog out + coaxial/optical optical SPDiF in/out + 3.5mm + CD-In + Aux-In - retail pack + bundled software
Creative		
AA-CAV		Creative SBS0570 sound blaster Audigy Value 7.1 pci sound card , 64-bit support , 24-bit advanced HD (24bit/96kHz/100dB SNR) , EAX advanced HD , coaxial SPDiF out - include low-profile bracket for Flex ATX (antec minuet) or 2U rackmount
external audio		
AA-SUWR		Sv-tech Usb Web Radio , recorder & player - usb interface , for over 7000 worldwide radio chanel
AA-SUTA2051		Sunix UTA2051 5.1 Usb Audio , C-Media CM101 chipset ; Xear 3D Sound , Dolby Digital 5.1, HRTF3D , EAX , 16bit 48KHz , with analog + optical SPDiF out
AA-SUTA3100		Sunix UTA3100 5.1 Usb Audio , with mic , rec+play , volumn control , C-Media CM101 chipset ; Xear 3D Sound , Dolby Digital 5.1, HRTF3D , EAX , 16bit 48KHz , with analog in/out + optical SPDiF in/out
AA-ZUA		Zalman ZM-RSSC 5.1 Usb Audio , 24bit 96KHz , with built-in amplifier ; with mic-in + analog/SPDiF out (optical+coaxial) , 3 individual volume control for front , rear , center/sub-woofer
AA-ZAA		Zalman ZM-RSA , 5.1 Audio Amplifier - Dual interface with Independent volume control for for TWO USERS , support home theater systems AV amplifier or reciver , gaming consoles , desk-top PC soundcards
AA-AXU1	N	Asus Xonar U1 audio station , 5.1 usb audio , silver , Dolby Digital & Pro-Logic II surround sound , 24bit 96KHz , EAX and DirectSound HW support , with mic-in , analog/digital combo output , volume control - with bundle mic
wireless add-on audio		
AA-LWMPC		Logitech 980414 , Wireless Music system for PC , with USB extension stand , remote control - usb interface to PC , wireless reciver with RCA (R+L) interface to stereo system
AA-LWMiP		Logitech 980441 , Wireless Music system for iPOD , with remote control - 3.5mm interface to iPOD , wireless reciver with RCA (R+L) interface to stereo system
AA-LWDJ		Logitech 966194 , Wireless DJ music system , with USB extension stand , full size remote control with LCD + recharge station - usb interface to PC (Access to PC music , Internet Radio and broadcasts.) , wireless reciver with RCA (R+L) interface to stereo system
AA-LSB		Logitech 930-000023 , SqueezeBox , with 802.11g wireless + UTP network connection , VFD display + On-screen clock with 7-day alarm , remote control ; digital optical / coaxial + analog connectors

AA-LSBD	N	Logitech 930-000034 , SqueezeBox Duet , multi-room wireless remote control with 2.4-inch colour display , 802.11g wireless + UTP network connection ; digital optical / coaxial + analog connectors
AA-LSBR	N	Logitech 930-000041 , SqueezeBox Receiver , 802.11g wireless + UTP network connection ; digital optical / coaxial + analog connectors
AA-LSBC	N	Logitech 930-000040 , SqueezeBox Controller , multi-room wireless remote control with 2.4-inch colour display , 802.11g wireless - for SqueezeBox / Transporter
AA-LT	R	Logitech 930-000052 , Transporter network music player , with AK4396 “Miracle DAC driver , 325 MIPS eight-way multithreaded cpu , 8 MB audio buffer and SlimDSP , internet radio broadcasts , UTP network connection + 802.11g wireless (require optional access point) , dual VFD display + On-screen clock with 7-day alarm , remote control ; digital input/output - optical + coaxial , analog connectors

Multimedia Accessories

PP-M35HC	Moby 3.5HC lcd Protective Paster - for 3.5" Lcd (camera , printer … etc) , scratch resistant , increase lcd brightness
PP-MPSP3	Moby PSP-3 3in1 Protective Paster with Nano silica film - for sony PSP , self-adhesive , 3 pieces for complete PSP surface protection
PP-MiNANo	Moby NS-Nanohc Protective Paster - for iPOD Nano , for both side panels
PP-MiViDEo	Moby NS-ivideo Protective Paster - for iPOD video , for both side panels

Disk Storage

DS-D101		dacal DC-101G; CD library II; stroae up to 150 cd/DVD with USB interface , support daisyhain upto 127 unit - management software bundled
DS-D300G		dacal DC-300 gray ; CD library II ; store 150 x DVD , CD , usb interface , support daisyhain upto 127 unit - management software bundled
DS-D300i		dacal DC-300 ivory ; CD library II ; store 150 x DVD , CD , usb interface , support daisyhain upto 127 unit - management software bundled
DS-D300B	N	dacal DC-300 Black ; CD library II ; store 150 x DVD , CD , usb interface , support daisyhain upto 127 unit - management software bundled
DS-D016RW	N	dacal powerdrive DC-106RW - cd/dvd library + built-in super-multi dvd writer (8X DVD / 24X CD / 8xDVD±RW / 6X DVD±RDL/ 5X DVD-RAM) , ivory ; upto 100 x DVD , CD , usb interface with 1 x usb downstream hub , support daisychain upto 127 unit - management software bundled

HUB - Usb / Firewire

HU-VU	ViZO HUB-C4 UFO 4port USB 2.0 mini hub , usb-powered - round shape with rotary cover , dust free
HU-VMH500W	N Vantec ugt-mh500 , 3 port USB 2.0 mini hub , usb-powered - round shape edsign , 50x50x25mm
HU-DUB104	D-link DUB-104 4port USB 2.0 hub , usb-powered , plastic - 77x38x9.6mm
HU-SSH4200MA	Sunix SH4200MA 4port USB 2.0 slim hub , with AC-adapter , plastic - 95x55x18mm , NEC UPD720101 chipset , support Linux, and Mac O.S.

HU-SPUB1300H	C	Sunix PUB1300H Powered USB 2.0 hub (1x24v + 3x12v) , with AC-adapter , with OCP , support DIN-Rail and Wall-Mount , aluminum - 110x70x18mm , NEC UPD720104 chipset - ideal for PoS application with no need of ac-adapter (scales,led diplay, digitizer, slip printer … etc)
HU-L4		Logitech 939-000013 4-Port usb hub , usb-powered - 3 years warranty
HU-L4P		Logitech 939-000014 Premium 4-Port usb hub with mirror finish + 4 individual led for connection acyivity , ac-adapter powered - 3 years warranty
HU-SUHB7200A		Sunix UHB7200A 7port USB 2.0 hub with AC-adapter , plastic , 185x65x26mm , NEC UPD720101 chipset , support Linux, and Mac O.S.
HU-VMH600	N	Vantec ugt-mh600 7port USB 2.0 hub , with piano black finish + vertical stand , with ac-adapter , plastic , 93x45x15mm
HU-DUBH7		D-link DUB-H7 7port USB 2.0 hub , with ac-adapter , plastic , 99.6x59x25.7mm
Docking Station		
DS-VLD		Vizo Lan Dock MLD-001 docking station / port replicator , USB2.0 to 2xPS/2 + 1x 9pin Serial + 1x10/100 lan + 4 x USB 2.0 downstream hub
DS-V200U2	C	Vantec DSH-200U2 docking station / port replicator with video out , USB2.0 to 1xDVi/D-Sub display (extended desktop, mirror or primary) + 2xPS/2 + 1x 9pin Serial + 1x10/100 lan + audio in/out + 4 x USB 2.0 downstream hub - support kensington security
modem		
MD-ASP9		APC PS9-DCE PROTECTNET surge protector for 9pin serial / RS232 modem , serial printer
MD-ASPA		Surge Protector for ADSL/RJ-45
MD-APDIGITEL	N	APC PDiGiTEL Surge Protector for RJ-45 iSDN / T1 protection
MD-APTEL2	N	APC PTEL2 Surge Protector for RJ-45 Modem/Fax/DSL
LG		
MD-Li56A		LG LM-i56A 56k v.92/v.90 internal pci voice/fax modem , agere chipset - retail pack - vista ready
MD-L56EU		LG LM-U56S 56k v.92/v.90 external usb voice/fax modem, support TAM - retail pack
D-Link		
MD-DFM562iS	N	D-Link DFM-562iS 56k v.92/v.90 internal pci serial voice/fax modem, support TAM, with mic+speaker jack - retail pack
MD-DFM562E		D-Link DFM-562E 56k v.92/v.90 external serial voice/fax modem, support TAM, with mic+speaker jack - retail pack
MD-DSL2500U		D-link DSL-2500U ADSL modem + router ; ADSL2/2+ 24Mbps downstream / 1Mbps upstream , with firewall + security protection , 1 x 10/100 utp
MD-DSL2540U		D-link DSL-2540U ADSL modem + router + 4port 10/100 switch ; ADSL2/2+ 24Mbps downstream / 1Mbps upstream , with firewall + security protection
MD-DSL2640U		D-link DSL-2640U ADSL modem + wireless router + 4port 10/100 switch , 802.11b/g ; ADSL2/2+ : 24Mbps downstream / 1Mbps upstream ; G.lite : 1.5Mbps downstream / 512Kbps upstream
MD-DSLG804V		D-link DSL-G804V ADSL modem + wireless router + 4port 10/100 switch + VPN tunnel , 802.11b/g ; ADSL2/2+ : 24Mbps downstream / 1Mbps upstream ; G.lite : 1.5Mbps downstream / 512Kbps upstream
MD-DSL2740U		D-link DSL-2740U rangebooster N ADSL modem + wireless router + 4port 10/100 switch , 802.11b/g/draft N , 270mbps ; ADSL2/2+ : 24Mbps downstream / 1Mbps upstream ; G.lite : 1.5Mbps downstream / 512Kbps upstream

Network Video phone

NV-DVC1000	R	D-Link DVC-1000 - i2eye broadband videophone , pc free stand-alone operation ; built-in mic , caller ID , 10 speed dial , audio/video privacy protection ; support PiP , 30fps ; with remote control ; audio + video out to TV , RJ45 connect to network
NV-DVC10	R	D-Link DVC-10 - wide angle len for DVC-1000 , DVC-1100 , focal length : 2.9mm + back focal length : 5.5mm , 4 glass element
NV-DVC20	R	D-Link DVC-20 - wide angle len with zoom for DVC-1000 , DVC-1100 , focal length : 4-8mm + back focal length : 7.6-11.4mm , 7 glass element

Network Adapter

powerline network adapter

NA-DHP300		D-Link DHP-300 powerline network adapter through home plug : 10/100 lan / 200mbps , support computers, game consoles, and multimedia devices , wireless network

Express Card

NA-SECL1400		Sunix ECL1400 : 1 x 10/100/1000 gigabit lan , Express Card 34 (for 34 or 54 slot) card , single lane pci-express link (2.5Gb/sec)

pcmcia / cardbus

NA-DGE660TD		D-Link DGE-660TD 10/100/1000 network pcmcia adapter , FiFo buffer : 8k/64k - 16/32bit pcmcia

USB

NA-SULK1200		Sunix ULK1200 , USB2.0 Data Link Cable for PC-to-PC (peer-to-peer) networking , ALi M5632 chipset , retail pack
NA-SUTL1200		Sunix UTL1200M , USB2.0 to 10/100 LAN adapter , MosChip MCS7830 chipset
NA-DUBE100		D-Link DUB-E100 10/100 network usb adapter , 7k buffer - usb2.0

Pci

NA-DFE520TX		D-Link DFE-520TX - 10/100 network pci adapter , 33mhz 32bit pci , FiFo : 8k/64k
NA-DFE580TX		D-Link DFE-580TX - 4 port 10/100 network pci server adapter , 33/66mhz 32/64bit pci , FiFo : 2k/2k
NA-DGE528T		D-Link DGE-528T - 10/100/1000 gigabit network pci adapter , 33/66mhz 32bit pci , FiFo : 8k/64k - include low-profile pci bracket for 2U rackmount or flex-atx (antec minuet)
NA-DGE530T		D-Link DGE-530T - 10/100/1000 gigabit network pci adapter , 33/66mhz 32bit pci , FiFo : 8k/64k , support WoL
NA-i8391	N	Intel PWLA8391GT , pci gigabit lan desktop adapter, 10/100/1000mbps , Intel 82541Pi chipset , support WoL , 802.3x , 802.1Q, 802.1P
NA-i8391L	N	Intel PWLA8391GT with Low-profile bracket , pci gigabit lan desktop adapter, 10/100/1000mbps , Intel 82541Pi chipset , support WoL , 802.3x , 802.1Q, 802.1P
NA-KK1		Killernic K1 - 10/100/1000 gigabit network pci adapter , on-board 333mhz Network Processing Unit to reduce CPU usage , on-board 64mb ddr333 memory , with LLR technology (Lag and Latency Reduction) + USB2.0 (enable gamers to access hardware accessories like USB drive , headset ... etc through NPU without impacting cpu resource) - with bundle games
NA-KM1		Killernic M1 - 10/100/1000 gigabit network pci adapter , on-board 400mhz Network Processing Unit to reduce CPU usage (with heatsink) , on-board 64mb ddr333 memory , with LLR technology (Lag and Latency Reduction) , FNApps + USB2.0 (enable gamers to access hardware accessories like USB drive , headset ... etc through NPU without impacting cpu resource) - with bundle games

Pci-Express		
NA-SLAN1400		Sunix LAN1400 , pci-Express (1x) gigabit lan , 10/100/1000mbps , Marvell 8503 chipset
NA-DGE560T		D-Link DGE-560T - gigabit network pci-Express (1x) adapter , with 802.1Q VLAN Tagging , 802.3ad Link Aggregation , 9kb jumbo frame size , WoL - include low-profile pci bracket for 2U rackmount or flex-atx (antec minuet)
NA-i9400	N	Intel expi9400pt , pci-Express (1x) gigabit lan server adapter, 10/100/1000mbps , Intel 82572Gi chipset - support upto 4 teaming connections
NA-i9402		Intel expi9402pt , pci-Express (4x) Dual-port gigabit lan server adapter , 10/100/1000mbps , Intel 82571Gb chipset - support upto 8 teaming connections
NA-i9404		Intel expi9404pt , pci-Express (4x) Quad-port gigabit lan server adapter , 10/100/1000mbps , 2x Intel 82571Gb chipset - support upto 8 teaming connections
NA-i9404L	R	Intel expi9404ptL , Low-profile pci-Express (4x) Quad-port gigabit lan server adapter , 10/100/1000mbps , 2x Intel 82571Gb chipset - support upto 8 teaming connections
Pci-X		
NA-i8490		Intel pwla8490mt , pci (32/64bit) / pci-X (100/133mhz) gigabit lan server adapter, 10/100/1000mbps , Intel 82545EMi chipset , 64k on-board memory - support teaming connections - comes with low-profile pci bracket
NA-i8492		Intel pwla8492mt , pci (32/64bit) / pci-X (100/133mhz) Dual-gigabit lan server adapter, 10/100/1000mbps , Intel NH82546GB chipset , 128k on-board memory - support teaming connections - comes with low-profile pci bracket
NA-i8494	R	Intel pwla8494gt , pci (32/64bit) / pci-X (100/133mhz) Quad-gigabit lan server adapter, 10/100/1000mbps , 2 x Intel NH82546GB chipset , 256k on-board memory - support teaming connections
network SWitch		
ASUS		
10/100		
SW-A1024		ASUS GigaX 1024 - 24 port 10/100 un-managed switch - auto-MDI/MDIX , 4096 MAC address - rackmount ready
10/100/1000 gigabit		
SW-AG1116		ASUS GigaX 1116 - 16 port 10/100/1000 gigabit un-managed switch , support VCT , rackmount ready - auto-MDI/MDIX , 4k MAC address
D-link		
10/100		
SW-DES1005D		D-Link DES-1005D - 5 port 10/100 un-managed switch - auto-MDI/MDIX , 8k MAC address , 256K ram buffer per device
SW-DES1008D		D-Link DES-1008D - 8 port 10/100 un-managed switch - auto-MDI/MDIX , 8k MAC address , 256K ram buffer per device
SW-DES1016D		D-Link DES-1016D - 16 port 10/100 un-managed switch - auto-MDI/MDIX , 8k MAC address , with rackmount kit
SW-DES1018DG		D-Link DES-1018DG - 16 x 10/100 + 2 x gigabit layer2 switch - auto-MDI/MDIX , 8k MAC address , rackmount ready
SW-DES1316	R	D-Link DES-1316 - 16 port 10/100 + 8 x PoE un-managed switch - auto-MDI/MDIX , 4k MAC address , 512k , with rackmount kit
SW-DES1024D		D-Link DES-1024D - 24 port 10/100 un-managed switch - auto-MDI/MDIX , 8k MAC address , 4MBits ram buffer per device , rackmount ready
SW-DES1024DG	N	D-Link DES-1024DG - 22 x 10/100 + 2 x gigabit layer2 switch - auto-MDI/MDIX , 8k MAC address , rackmount ready

SW-DES1026G		D-Link DES-1026G - 24 x 10/100 + 2 x gigabit layer2 switch - auto-MDI/MDIX , 8k MAC address , rackmount ready
SW-DES1226G	N	D-Link DES-1226G web smart Layer2 switch - 24 x 10/100 + 2 combo (10/100/1000base-T or SFP) , auto-MDI/MDIX , 6k MAC address , port trunking , 802.1Q VLAN , 802.1p priority tagging , rackmount ready
SW-DES1228		D-Link DES-1228 web smart Layer2 switch - 24 x 10/100 + 2 x 10/100/1000 base-t + 2 combo (10/100/1000base-T or SFP) , auto-MDI/MDIX , 8k MAC address , port trunking , 802.1Q VLAN , 802.1p priority tagging , 802.1x authentication , IGMP snooping , 802.1D spanning tree , SNMP management , rackmount ready
SW-DES1228P		D-Link DES-1228P web smart PoE Layer2 switch - 24 x 10/100 (with PoE 15.4w per port) + 2 x 10/100/1000 base-t + 2 combo (10/100/1000base-T or SFP) , auto-MDI/MDIX , 8k MAC address , port trunking , 802.1Q VLAN , 802.1p priority tagging , 802.1x authentication , IGMP snooping , 802.1D spanning tree , SNMP management , rackmount ready
SW-DES1050G		D-Link DES-1050G web smart Layer2 switch - 48 x 10/100 + 2 combo (10/100/1000base-T or SFP) , auto-MDI/MDIX , 8k MAC address , upto 4 port trunking , 802.1Q VLAN . rackmount ready
SW-DES1252	N	D-Link DES-1252 web smart Layer2 switch - 48 x 10/100 + 2 x 10/100/1000 base-t + 2 combo (10/100/1000base-T or SFP) , auto-MDI/MDIX , 8k MAC address , port trunking , 802.1Q VLAN , 802.1p priority tagging , 802.1x authentication , IGMP snooping , 802.1D spanning tree , SNMP management , rackmount ready
10/100/1000 gigabit		
SW-DGS1005D		D-Link GigaExpress DGS-1005D 5 port 10/100/1000 gigabit un-managed switch - auto-MDI/MDIX , 4k MAC address , 1MB ram buffer per device
SW-DGS1008D		D-Link GigaExpress DGS-1008D 8 port 10/100/1000 gigabit un-managed switch - auto-MDI/MDIX , 8k MAC address , 256k ram buffer per device
SW-DGS1016D		D-Link GigaExpress DGS-1016D 16 port 10/100/1000 gigabit un-managed layer2 switch - auto-MDI/MDIX , 8k MAC address , 512k ram buffer per device , rackmount ready
SW-DGS1216T	R	D-Link DGS-1216T web smart 16 port 10/100/1000 gigabit + 2 combo SFP fiber connection , un-managed layer2 switch - auto-MDI/MDIX , port mirroring , 8k MAC address , 512k buffer per device , rackmount ready
SW-DGS1024D		D-Link GigaExpress DGS-1024D 24 port 10/100/1000 gigabit un-managed layer2 switch - auto-MDI/MDIX , 8k MAC address , 512k ram buffer per device , rackmount ready
SW-DGS1224T	R	D-Link DGS-1224T web smart 24 port 10/100/1000 gigabit + 2 combo SFP fiber connection , un-managed layer2 switch - auto-MDI/MDIX , port mirroring , 8k MAC address , 512k buffer per device , rackmount ready
SW-DWS3024	R	D-Link DWS-3024 L2+ wireless switch , support 802.3af Power Over Ethernet (24x) - 24 port 10/100/1000 gigabit + 4 combo SFP port for wired/wireless network (support upto 48AP / 512 wireless user) - support optional dps-600 redundant psu , rs232 console port , auto-MDI/MDIX , port mirroring , 8k MAC address , 750k buffer , 64/128/152-bit WEP , WPA/WPA2 personal+enterprise , multiple SSiD , rackmount ready - automatically configure all connected DWL-3500AP

SW-DWS3026	R	D-Link DWS-3026 L2+ wireless switch , support 802.3af Power Over Ethernet (24x) - 24 port 10/100/1000 gigabit + 4 combo SFP port + 2 open slot for optional 10-gigabit attachment - for wired/wireless network (support upto 48AP / 512 wireless user) - support optional dps-600 redundant psu , rs232 console port , auto-MDI/MDIX , port mirroring , 8k MAC address , 750k buffer , 64/128/152-bit WEP , WPA/WPA2 personal+enterprise , multiple SSiD , rackmount ready - automatically configure all connected DWL-3500AP
SW-DGS1248T	N	D-Link DGS-1248T web smart 48 port 10/100/1000 gigabit + 4 combo SFP fiber connection , un-managed layer2 switch - auto-MDI/MDIX , port mirroring , 8k MAC address , 1.632mb buffer per device , rackmount ready
router - wired		
		click for router with built-in ADSL modem
D-Link		
NE-DiR100		D-Link DiR-100 broadband router with 4 port 10/100 switch , for ADSL / cable modem connection , firewall protection , web-based configuration , Support NAT with VPN passthrough, MAC Filtering, IP Filtering
NE-DiR120		D-Link DiR-120 broadband router with 4 port 10/100 switch + 1 port USB printer server , for ADSL / cable modem connection , firewall protection , web-based configuration , Support NAT with VPN passthrough, MAC Filtering, IP Filtering
NE-DiR130		D-Link DiR-130 broadband router with 8 port 10/100 switch , for ADSL / cable modem connection , firewall protection , web-based configuration , Support NAT with VPN +firewall , MAC Filtering, IP Filtering
NE-DiLB604		D-Link Di-LB604 broadband Load Balancing router with 4 port switch , 2 WAN port for load balancing , for ADSL / cable modem connection , firewall protection , web-based configuration , Support NAT with VPN passthrough, MAC Filtering, IP Filtering
NE-Di704P		D-Link Di-704P broadband router with 4 port 10/100 switch + 1 port parallel printer server , for ADSL / cable modem connection , firewall protection , web-based configuration , Support NAT with VPN passthrough, MAC Filtering, IP Filtering
NE-Di704UP		D-Link Di-704UP broadband router with 4 port 10/100 switch + 1 port USB printer server , for ADSL / cable modem connection , firewall protection , web-based configuration , Support NAT with VPN passthrough, MAC Filtering, IP Filtering
NE-Di804HV		D-Link Di-804HV broadband VPN router with 4 port 10/100 switch , with multiple VPN tunnel + parental control , with 9pin serial port , for ADSL , Cable , ISDN , 56k modem connection , firewall protection , web-based configuration , 168-bit 3DES IPSec advanced VPN security
NE-Di808HV		D-Link Di-808HV broadband VPN router with 8 port 10/100 switch , with multiple VPN tunnel + parental control , with 9pin serial port , for ADSL , Cable , ISDN , 56k modem connection , firewall protection , web-based configuration , 168-bit 3DES IPSec advanced VPN security
		router with built-in ADSL modem - please see MoDem section wireless router - please see Wireless section
Print Server		
PS-DP301P+		D-Link DP-301P+ - 1 port parallel print server , 10/100
PS-DP301U		D-Link DP-301U - 1 port usb 1.1 print server , 10/100
PS-DP300U		D-Link DP-300U - 2 x parallel + 1 x usb1.1 print server , 10/100
PS-DP300+		D-Link DP-300+ - 2 x parallel + 1 x serial port print server , 10/100
		wireless print server - please see Wireless section

wireless network		
BlueTooth wireless		
CA-U3E		3m usb 2.0 extension cable (type A male - type A female)
CA-U5E		5m usb 2.0 extension cable (type A male - type A female) - 1 port - ideal for wireless network USB adapter or other USB device
CA-U5E2		Sunix UEC2200 5m usb 2.0 extension cable (type A male - type A female) , NEC UPD720110 chipset - 2 port , retail pack - ideal for wireless network USB adapter or other USB device
NE-MSK2		MSi StarKey 2.0 usb bluetooth adapter , support PAN (Personal Area Network), 128bit encryption, support upto 7 slave device (pc , notebook , cellphone , printer , PDA … etc) - V2.0 - 100m
NE-DBT122		D-Link DBT-122 usb to Bluetooth , support PAN (Personal Area Network), range 10m, 128bit encryption, support upto 7 slave device (pc , notebook , cellphone , printer , PDA … etc)
NE-DBT320		D-Link DBT-320 Bluetooth Usb print adapter , turn your usb printer to a wireless bluetooth printer , range 10m - wireless print from bluetooth enabled device (PC , notebook , PDAs , cellphone ..) , with extension cable
wireless adapter		
pci-express		
NA-DWA556	N	D-Link DWA-556 rangebooster N , 2.4Ghz (802.11b/g/draft n) , 300Mbps wireless pci-e (1x) adapter , 3 x detachable PiFA 2dBi Gain antennas
pci		
NA-DWA510		D-Link DWA-510 AirPlusG 2.4Ghz (802.11b/g) 54Mbps wireless pci - include low-profile pci bracket for 2U rackmount or flex-atx (antec minuet)
NA-DWA520		D-Link DWA-520 AirPlusXtremeG 2.4Ghz (802.11b/g) 108Mbps wireless pci - include low-profile pci bracket for 2U rackmount or flex-atx (antec minuet)
NA-DWLAG530		D-Link DWL-AG530 AirPremier AG , Tri-mode Dualband , 5/2.4Ghz (802.11a/b/g) 108Mbps wireless pci - with 3m detatched antenna - include low-profile pci bracket for 2U rackmount or flex-atx (antec minuet)
NA-DWA547		D-Link DWA-547 rangebooster N , 2.4Ghz (802.11b/g/draft n) , 300Mbps wireless pci adapter , 3 x detachable PiFA 2dBi Gain antennas - include low-profile pci bracket for 2U rackmount or flex-atx (antec minuet)
usb		
CA-U3E	N	3m usb 2.0 extension cable (type A male - type A female)
CA-U5E		5m usb 2.0 extension cable (type A male - type A female) - 1 port - ideal for wireless network USB adapter or other USB device
CA-U5E2		Sunix UEC2200 5m usb 2.0 extension cable (type A male - type A female) , NEC UPD720110 chipset - 2 port , retail pack - ideal for wireless network USB adapter or other USB device
NA-DWA110	N	D-Link DWA-110 wireless G 802.11b/g 54Mbps wireless usb adapter , 60/128bit WEP , omni-driectional Antenna , usb drive look - with extension cradle
NA-DWA120	N	D-Link DWA-120 wireless G 802.11b/g 108Mbps wireless usb adapter , 60/128bit WEP , omni-driectional Antenna , usb drive look - with extension cradle
NA-DWA140	N	D-Link DWA-140 rangebooster N , 2.4Ghz (802.11b/g/draft n) , 300Mbps wireless usb adapter , 2 x integrated PiFA 2dBi Gain antennas
NA-DWA142		D-Link DWA-142 rangebooster N , 2.4Ghz (802.11b/g/draft n) , 300Mbps wireless usb adapter , 2 x integrated PiFA 2dBi Gain antennas - with extension cable

express card		
NA-DWA643	N	D-Link DWA-643 rangebooster N , 2.4Ghz (802.11b/g/draft N) 300Mbps wireless express card (34/54) - onboard Inverted-F antenna
pcmcia / cardbus		
NA-AWL106GM		ASUS WL-106GM , 802.11g , 240 MiMo pcmcia , 240mbps , (8x speed + 8xcoverage) , WPA+WPA2 - 3 on-board PCB antenna
NA-DWLG630		D-Link DWL-G630 AirPlusXtremeG+ , 2.4Ghz (802.11g) 54Mbps wireless pcmcia - 2 onboard Inverted-F antenna
NA-DWA610	N	D-Link DWA-610 AirPlusXtremeG+ , 2.4Ghz (802.11b/g) 54Mbps wireless pcmcia - 2 onboard Inverted-F antenna
NA-DWLG650		D-Link DWL-G650 AirPlusXtremeG , 2.4Ghz (802.11g) 108Mbps wireless pcmcia - 2 onboard Inverted-F antenna
NA-DWA620	N	D-Link DWA-620 AirPlusXtremeG , 2.4Ghz (802.11g) 108Mbps wireless pcmcia - 2 onboard Inverted-F antenna
NA-DWA645		D-Link DWA-645 rangebooster N , 2.4Ghz (802.11b/g/draft N) 300Mbps wireless pcmcia - 2 onboard Inverted-F antenna
wireless bridge		
NA-DGL3420		D-Link DGL-3420 108mbps gaming adapter , wireless bridge (10/100 to wireless) - 5/2.4Ghz dual band (802.11a/b/g) 108Mbps , xbox compatiable
AP (access point)		
NE-DAP1150	N	D-Link DAP-1150 - 2.4Ghz (802.11b/g) 54Mbps access point , support 7 modes (AP, repeater , wireless client)
NE-DAP1160	N	D-Link DAP-1160 AirPlusXtremeG - 2.4Ghz (802.11b/g) 54Mbps access point with 2 x 10/100 port , support 7 modes (AP, WDS, WDS with AP, PtP , PtMP , repeater , wireless client)
NE-DWL2100AP		D-Link DWL-2100AP AirPlusXtremeG - 2.4Ghz (802.11b/g) 108Mbps access point , support 5 modes (AP, PtP , PtMP , repeater , wireless client)
NE-DWL7100AP		D-Link DWL-7100AP AirPremier AG , Tri-mode Dualband - 5/2.4Ghz (802.11a/b/g) 108Mbps access point , 64/128/152bit WEP
NE-DWL3200AP		D-Link DWL-3200AP AirPremier 54Mbps managed access point for SMB , metal housing , support 802.3af PoE - 2.4Ghz (802.11g) , 2 x 5dbi antennas , 64/128/152bit WEP , with PoE base unit , wall mount kit
NE-DAP1353		D-Link DAP-1353AP rangebooster N 650 - 2.4Ghz (802.11b/g/draft n) , 300Mbps access point , support 5 modes (AP, PtP , PtMP , repeater , wireless client)
NE-DAP1522	N	D-Link DAP-1353AP Xtreme N duo , wireless bridge/access point - 2.4/5Ghz dual band (802.11b/g/draft n) , 300Mbps access point , 4 x gigabit switch - 2 x detachable antenna
NE-DWL8200AP		D-Link DWL-8200AP AirPremier AG , managed Dualband for enterprise , metal housing , support 802.3af PoE - 5/2.4Ghz (802.11a/b/g) 108Mbps access point , 2 x 5dbi antennas , 64/128/152bit WEP , mutiple SSiD , wall mount kit
NE-DWL3500AP	N	D-Link DWL-3500AP AirPremier 108Mbps managed access point for SMB , metal housing , support 802.3af PoE - 2.4Ghz (802.11g) , 2 x 5dbi antennas , 64/128/152bit WEP , with PoE base unit , wall mount kit
NE-DWL2700AP	R	D-Link DWL-2700AP AirPremier - 2.4Ghz (802.11b/g) 54Mbps OUTDOOR access point , support 5 modes (AP, PtP , PtMP , Repeater , Wireless Client) , watertight metal housing , built-in heater with temperature sensor , support 802.3af PoE , 2 x 5dbi antennas , 64/128/152bit WEP , wall mount kit

NE-DWL7700AP	R	D-Link DWL-7700AP AirPremier AG , Dualband - 5/2.4Ghz (802.11a/b/g) , 54mbps Outdoor AP/Bridge access point , support 4 modes (AP, PtP , PtMP , Wireless Client) , watertight metal housing , built-in heater with temperature sensor , support 802.3af PoE , 2 x 5dbi antennas , 64/128/152bit WEP , wall mount kit , PtP , PtMP

for Hot Spot

NE-DSA3600	R	D-Link DSA-3600 AirSpot public/private gateway , hardware based VPN , Built-in DHCP Server & Advanced Firewall , supports RADIUS/POP3/LDAP & local User Authentication , manages up to 500 user accounts , support up to 120 online users simultaneously , 7 x 10/100 UTP port (LAN + WAN + Authentication) - to be attached with access point
NE-DSA6100	R	D-Link DSA-6100 AirSpot public/private gateway , hardware based VPN , Built-in DHCP Server & Advanced Firewall , supports RADIUS/POP3/LDAP & local User Authentication , manages up to 2500 user accounts , support up to 500 online users simultaneously , 4 x gigabit UTP port (LAN + WAN + Authentication) , 1 x RS232 - to be attached with access point

router - wireless

click for router with built-in ADSL modem

NE-DiR300		D-Link DiR-300 54Mbps wireless G router with 4 port switch , enhanced 64/128bit WEP , DHCP server for automatic user IP assignment , Firewall protection with NAT, DMZ and Virtual Server Mapping support
NE-DiR320		D-Link DiR-320 54Mbps wireless G router with 4 port switch + built-in usb printer server , enhanced 64/128bit WEP , DHCP server for automatic user IP assignment , Firewall protection with NAT, DMZ and Virtual Server Mapping support
NE-DiR400		D-Link DiR-400 108Mbps wireless G router with 4 port switch , enhanced 64/128bit WEP , DHCP server for automatic user IP assignment , Firewall protection with NAT, DMZ and Virtual Server Mapping support
NE-Di824VUP+		D-Link Di-824VUP+ AirPlus G+ 802.11g 54Mbps wireless VPN router with 4 port switch + built-in usb+parallel printer server , enhanced 64/128/256-bit WEP , DHCP server for automatic user IP assignment , Firewall protection with & parental control , NAT, DMZ and Virtual Server Mapping support
NE-DiR330	N	D-Link DiR-330 54Mbps wireless G VPN router with 4 port switch + built-in usb printer server , enhanced 64/128bit WEP , DHCP server for automatic user IP assignment , Firewall protection with NAT, DMZ and Virtual Server Mapping support
NE-DiR615		D-Link DiR-615 rangebooster N wireless - 2.4Ghz , (802.11b/g/draft N) 300Mbps wireless router with 4 port switch , dual advanced firewall & parental control , 2 x detachable PiFA 2dBi Gain antennas
NE-DiR655		D-Link DiR-655 rangebooster N wireless - 2.4Ghz , (802.11b/g/draft N) 300Mbps wireless router with 4 port gigabit switch + built-in usb printer server , dual advanced firewall & parental control , 3 x detachable PiFA 2dBi Gain antennas
NE-DiR451		D-Link DiR-451 3G router with 3G + HSDPA support , plug in HSDPA/1xEV-DO/UMTS internet PC card to share online access - 802.11b/g 108Mbps wireless router with 4 port switch
NE-DiR855	N	D-Link DiR-855 xtreme N duo media router , with OLED network activity activity display led , optimized for HD video streaming - dualband 2.4 / 5Ghz , (802.11b/g/draft N) 300Mbps wireless router with 4 port gigabit switch + built-in usb printer server , 3 x detachable high-gain antenna

wireless print server

PS-DPG301		D-Link DP-G301 - 1 port parallel wireless print server , 2.4ghz , 802.11g , 54mbps , 64/128bit WEP
PS-DPG310		D-Link DP-G310 - 1 port usb 2.0 wireless print server , 2.4ghz , 802.11g , 54mbps , 64/128bit WEP
PS-DPR1260	N	D-Link DPR-1260 D-Link RangeBooster G wireless print server for multifunction printer (selected) , with ethernet port fro ethernet-enabled device (NAS , DVR ... etc) - 4 port usb 2.0 + 1 x UTP , 2.4ghz , 802.11g , 54mbps , 64/128bit WEP
PS-DPG321		D-Link DP-G321 - 2 port usb 2.0 + 1 x parallel wireless print server , 2.4ghz , 802.11g , 54mbps , 64/128bit WEP
Power Over Ethernet		
NE-DWLP50		D-Link DWL-P50 POE (Power Over Ethernet) terminal unit to work with P200 base unit or PoE switch , transmit data+power through network (1port) , upto 100m , ideal to work with 5V/12V networking device like access point , bridge , switch , router , internet security camera … etc , with power surge protection
NE-DWLP200		D-Link DWL-P200 POE (Power Over Ethernet) terminal unit + base unit , transmit data+power through network (1port) , upto 100m , ideal to work with 5V/12V networking device like access point , bridge , switch , router , internet security camera … etc , with power surge protection
antenna and accessories		
NE-DA0400		D-Link ANT24-0400 2.4Ghz 4dBi omni-directional indoor antenna , bean width - H: 360° V: 40° , wall-mountable design , RP-SMA or RP-TNC
NE-DA0500		D-Link ANT24-0500 2.4Ghz 5dBi indoor/outdoor omni-directional antenna , bean width - H:360° V:32° , N-Female to Reverse SMA
NE-DA0501C		D-Link ANT24-0501C 2.4Ghz 5dBi indoor omni-directional antenna - RP-SMA or RP-TNC
NE-DA0501		D-Link ANT24-0501 2.4Ghz 5dBi indoor omni-directional antenna - indluce 1.5m extensionn cable , RP-SMA or RP-TNC connector , with stand for desktop , wall mounting via screw or magentic
NE-DA0600		D-Link ANT24-0600 2.4Ghz 6dBi range extender antenna , panel directional , bean width - H:80° V:80° , RP-SMA or RP-TNC - Includes wall mounting Kit - 3 mounting methods , 1.5m etxension cable
NE-DAR60AT	C	D-Link DWL-R60AT 2.4Ghz 6dBi range extender microstrip patch antenna , panel directional , bean width - H:60° V:90° , RP-SMA only , ideal for access point , router
NE-DA0700C		D-Link ANT24-0700C 2.4Ghz 7dBi omni-directional antenna , bean width - H:360° V:24° - RP-SMA or RP-TNC
NE-DA0700		D-Link ANT24-0700 2.4Ghz 7dBi omni-directional antenna , bean width - H:360° V:24° - indluce 1.5m extensionn cable , SMA or TNC , with stand for desktop , wall mounting via screw or magentic
NE-DA0800		D-Link ANT24-0800 2.4Ghz 8dBi indoor/outdoor omni-directional antenna , bean width - H:360° V:15° , ideal for PtMP (Point to Multi-Point) , water proof for outdoor applications , SMA or TNC
NE-DA0800DB	R	D-Link ANT70-0800 Dual-Band 2.4/5Ghz 8dBi indoor/outdoor omni-directional antenna , bean width - H:360° V:15° , ideal for PtMP (Point to Multi-Point) , water proof for outdoor applications , SMA or TNC

NE-DA0801		D-Link ANT24-0801 2.4Ghz 8.5dBi indoor/outdoor pico cell patch antenna , bean width - H:70° V:65° , swivel mount for directional oriention , weatherproof and corrision resistant , RP SMA
NE-DA0801DB	R	D-Link ANT70-0801 Dual-Band 2.4/5Ghz 8.5dBi indoor/outdoor pico cell patch antenna , bean width - H:70° V:65° , swivel mount for directional oriention , weatherproof and corrision resistant , RP SMA
NE-DA1000DB	N	D-Link ANT70-1000 Dual-Band 2.4/5Ghz 10dBi directional outdoor antenna , range upto 1.5Km , bean width - H:58° V:55° , RP SMA
NE-DA1200		D-Link ANT24-1200 2.4Ghz 12dBi indoor high gain directional panel , bean width - H:80° V:23° , wall or window mounting. SMA
NE-DA1201		D-Link ANT24-1201 2.4Ghz 12dBi indoor/outdoor directional yagi high gain pico cell patch antenna , swivel mount for directional orientation , bean width - H:50° V:50° , swivel mount for directional orientation , weatherproof & corrosion resistant , N-female+SMA
NE-DA1202	N	D-Link ANT24-1202 2.4Ghz 12dBi outdoor omni-directional antenna , bean width - H:360° V:6°, ideal for PtMP (Point to Multi-Point) , weatherproof & corrosion resistant
NE-DA1400		D-Link ANT24-1400 2.4Ghz 14dBi indoor/outdoor high gain directional panel , weatherproof and made of corrosion-resistant , bean width - H:80° V:23° , wall or window mounting. N female + RP-SMA
NE-DA1800		D-Link ANT24-1800 2.4Ghz 18dBi indoor/outdoor high gain directional panel antenna , bean width - H:15° V:15°, weatherproof & corrosion resistant
NE-DA1800DB	N	D-Link ANT70-1800 Dual-Band 2.4/5Ghz 18dBi outdoor high gain directional panel antenna , range upto 8Km , bean width - H:30° V:30°, weatherproof & corrosion resistant
NE-DA1801	R	D-Link ANT24-1801 2.4Ghz 18dBi indoor/outdoor high gain directional yagi antenna , bean width - H:15° V:15°, weatherproof & corrosion resistant
NE-DA2100	R	D-Link ANT24-2100 2.4Ghz 21dBi indoor/outdoor high gain conner antenna , bean width - H:8° V:5°, weatherproof & corrosion resistant
NE-DACB03		D-Link ANT24-CB03N HDF-400 , extension cable for ANT24 series antenna - 3 meter
NE-DACB06		D-Link ANT24-CB06N HDF-400 , extension cable for ANT24 series antenna - 6 meter
NE-DACB09		D-Link ANT24-CB09N HDF-400 , extension cable for ANT24 series antenna - 9 meter
NE-DADLK3M		D-Link ANT24-DLK3M , 3m LMR200 low loss extension cable , RP-SMA to RP-TNC / RP-SMA
NE-DAoDU03M		D-Link ANT24-oDU03M , 0.3m LMR200 low loss extension cable , RP N Plug and N Plug
NE-DAoDU1M		D-Link ANT24-oDU1M , 1m LMR400 low loss extension cable , RP N Plug and N Plug
NE-DAoDU3M		D-Link ANT24-oDU3M , 3m LMR400 low loss extension cable , RP N Plug and N Plug
Cables - accessories		
CA-U1M		Usb 2.0 type A to Mini Usb - 1m
CA-U2M	N	Usb 2.0 type A to Mini Usb - 2m
CA-U2		2m usb 2.0 cable (type A - type B)
CA-U2VL		Vizo starlet USB-2M-BL 2m usb 2.0 cable (type A - type B) - UV+Led bLue, retail pack
CA-U2VG		Vizo starlet USB-2M-GR 2m usb 2.0 cable (type A - type B) - UV+Led Green, retail pack

CA-U2VR		Vizo starlet USB-2M-RD 2m usb 2.0 cable (type A - type B) - UV+Led Red, retail pack
CA-U2VY		Vizo starlet USB-2M-YL 2m usb 2.0 cable (type A - type B) - UV+Led Yellow, retail pack
CA-U5		5m usb 2.0 cable (type A - type B)
CA-U3E	N	3m usb 2.0 extension cable (type A male - type A female)
CA-U5E		5m usb 2.0 extension cable (type A male - type A female) - 1 port - ideal for wireless network USB adapter or other USB device
CA-U5E2		Sunix UEC2200 5m usb 2.0 extension cable (type A male - type A female) , NEC UPD720110 chipset - 2 port , retail pack - ideal for wireless network USB adapter or other USB device
CA-F642		ieee1394a firewire cable 6pin to 4pin cable - 2m - 4 pin normally use in video camera with 1394A (named as i-link)
CA-F662		ieee1394a firewire cable 6pin to 6pin cable - 2m
CA-F665		ieee1394a firewire cable 6pin to 6pin cable - 5m
CA-F962	N	ieee1394B firewire cable 9pin to 6pin cable - 2m
CA-F992	N	ieee1394B firewire cable 9pin to 9pin cable - 2m
Thermal Printer for PoS		
OKi		http://bulgaria.oki.com/fcgi-bin/public.fcgi?cid=107&pdflag=1&pid=1128&pcid=23
TP-o411P	R	OKiPos 411 thermal line printer for PoS , Parallel, 120/180/200 mm/sec, print width : 82.5mm, 4kb+384kb
TP-o411US	C	OKiPos 411 thermal line printer for PoS , Usb+Serial, 120/180/200 mm/sec, print width : 82.5mm, 4kb+384kb
TP-o411E	R	OKiPos 411 thermal line printer for PoS , Ethernet (RJ-45), 120/180/200 mm/sec, print width : 82.5mm, 48kb+384kb
TP-o412P	R	OKiPos 412 thermal line printer for PoS , Parallel, 120/180mm/sec, support 250mm/sec via optional 120w psu, print, width : 82.5mm, 4kb+384kb
TP-o412US	R	OKiPos 412 thermal line printer for PoS , Usb+Serial, 120/180mm/sec, support 250mm/sec via optional 120w psu, print, width : 82.5mm, 4kb+384kb
TP-o412E	R	OKiPos 412 thermal line printer for PoS , Ethernet (RJ-45), 120/180mm/sec, support 250mm/sec via optional 120w psu, print, width : 82.5mm, 48kb+384kb
Dotmatrix Printer		
Panasonic		
DP-P1150		panasonic kx-p1150 (9 pin, 80 clm, 240 cps ; 4kb , 1+3 copies), parallel
DP-P3200		panasonic kx-p3200 (9 pin, 80 clm, 330 cps, 12k , 1+4 parts), only for continuous paper ; parallel + serial
DP-P3196	R	panasonic kx-p3196 (9 pin, 80 clm, 500 cps ; 64k , 1+5 copies parts), 2 tractor unit ; parallel + serial
DP-P3696	R	panasonic kx-p3696 (9 pin, 136 clm., 500 cps , 13k , 1+4 copies) ; parallel
OKi		http://www.oki.co.uk/fcgi-bin/public.fcgi?pid=2&cid=125&chid=1
9pin		
DP-o1120	N	OKi microline 1120 - 9 pin, 80 clm, 333 cps , 128kb , 1+4 copies , parallel + usb + serial
DP-o280E	R	OKi microline 280 Elite - 9 pin, 80 clm, 375 cps , 128kb , 1+3 copies , parallel + usb
DP-o3320		OKi microline 3320 - 9 pin, 80 clm, 435 cps , 64kb , 1+4 copies , parallel + usb
DP-o5520		OKi microline 5520 - 9 pin, 80 clm, 570 cps , 128kb , 1+5 copies , parallel + usb
DP-o3321		OKi microline 3321 - 9 pin, 136 clm, 435 cps , 64kb , 1+4 copies , parallel + usb

DP-o5521		OKi microline 5521 - 9 pin, 136 clm, 570 cps , 128kb , 1+5 copies , parallel + usb
DP-o3410	R	OKi microline 3410 - 9 pin, 136 clm, 550 cps , 28kb , 1+7 copies , parallel + serial
DP-o4410	R	OKi microline 4410 - dual 9 pin, 136 clm, 1066 cps , 512kb , 1+9 copies , parallel + serial
24pin		
DP-o1190	R	OKi microline 1190 - 24 pin, 80 clm, 333 cps , 128kb , 1+4 copies , parallel + usb + serial
DP-o5590	R	OKi microline 5590 - 24 pin, 80 clm, 473 cps , 128kb , 1+4 copies , parallel + usb
DP-o3391	R	OKi microline 3391 - 24 pin, 136 clm, 390 cps , 64kb , 1+3 copies , parallel + usb
DP-o5591	R	OKi microline 5591 - 24 pin, 136 clm, 473 cps , 128kb , 1+4 copies , parallel + usb
DP-o6300F	R	OKi microline 6300 Flatbed - 24 pin, 106 clm, 450 cps , 64kb , 1+5 copies , parallel + usb
Oki accessories		
DP-oA0359	R	OKi 01-10-0359 RS232 serial interface - for microline 280
DP-oA0825	R	OKi 01-10-0825 RS232 serial interface - for microline 3320 , 3321 , 390 Flatbed , 5520, 5521, 5590
DP-oA0387	R	OKi 01-06-0387 pull tractor feeder - for microline 280
DP-oA1924	R	OKi 01-06-1924 bottom-push tractor feeder - for microline 3320, 3390, 5520, 5590
DP-oA1749	R	OKi 01-06-1749 bottom-push tractor feeder - for microline 3410
DP-oA0388	R	OKi 01-06-0388 roll paper stand - for microline 280, 320
DP-oA1933	R	OKi 01-06-1933 roll paper stand - for microline 3320, 3390, 5520, 5590
DP-oA2110	R	OKi 01-06-2110 roll paper stand - for microline 4410
Inkjet Printer		
Lexmark		
deskjet - home and home office		
iP-LZ2320		Lexmark Z2320 , 4 ink ; 4800x1200dpi ; mono/color : 22/16ppm , 100s input tray , duty : 3000pages per month - USB
iP-LZ1420		Lexmark Z1420 , wireless network ready , white , 4 ink ; 4800x1200dpi ; mono/color : 24/18ppm , 100s input tray , duty : 3000pages per month - USB
iP-LZ2420	N	Lexmark Z2420 , wireless network ready , black , 4 ink ; 4800x1200dpi ; mono/color : 25/18ppm , 100s input tray , duty : 3000pages per month - USB - 3 years warranty
All-In-One Print-Scan-Copy		
iP-LoX2650	N	Lexmark X2650 - Print-Scan-Copy , white ; a4 , 16mb , 4800x1200dpi ; mono/color : 22/16ppm , 100s input, duty : 3000pages per month ; scan : 600x1200/19200dpi , 48bit ; standalone copy , 25-400% - USB
iP-LoX3650	N	Lexmark X3650 - Print-Scan-Copy , white ; a4 , 16mb , 4800x1200dpi ; mono/color : 25/18ppm , 100s input, duty : 3000pages per month ; scan : 600x1200/19200dpi , 48bit ; standalone copy , 25-400% - USB + card reader
iP-LoX4650	N	Lexmark X4650 , wireless network ready - Print-Scan-Copy , black ; a4 , 16mb , 4800x1200dpi ; mono/color : 25/18ppm , 100s input, duty : 3000pages per month ; scan : 600x1200/19200dpi , 48bit ; standalone copy , 25-400% - USB + PictBridge + card reader
All-In-One Print-Scan-Copy-Fax		

iP-LoX5650	N	Lexmark X5650 - Print-Scan-Copy-Fax with 25s ADF , black ; a4 , 16mb , 4800x1200dpi ; mono/color : 25/18ppm , 100s input, duty : 3000pages per month ; scan : 600x1200/19200dpi , 48bit ; standalone copy , 25-400% - USB + PictBridge + card reader - 3 years warranty
iP-LoX5075	N	Lexmark X5075 - Print-Scan-Copy-Fax with 30s ADF , black ; a4 , 16mb , 4800x1200dpi ; mono/color : 24/17ppm , 100s input, duty : 3000pages per month ; scan : 600x1200/19200dpi , 48bit ; standalone copy , 25-400% - USB + PictBridge- 5 years warranty
iP-LoX6650	N	Lexmark X6650 , wireless network ready + auto-duplex unit - Print-Scan-Copy-Fax with 25s ADF , black ; a4 , 16mb , 4800x1200dpi ; mono/color : 28/24ppm , 100s input, duty : 3000pages per month ; scan : 600x1200/19200dpi , 48bit ; standalone copy , 25-400% - USB + PictBridge + card reader - 3 years warranty
iP-LoX7675	N	Lexmark X7675 , wireless network ready + auto-duplex unit , with 6cm lcd - Print-Scan-Copy-Fax with 25s ADF , black ; a4 , 16mb , 4800x1200dpi ; mono/color : 32/27ppm , 100s input, duty : 5000pages per month ; scan : 600x1200/19200dpi , 48bit ; standalone copy , 25-400% - USB + PictBridge + card reader , bundled 43XL+44XL high-yield ink - 5 years warranty
iP-LoX9575	R	Lexmark X9575 , wireless network ready + auto-duplex unit , with 6cm lcd - Print-Scan-Copy-Fax with 50s ADF , black ; a4 , 16mb , 4800x1200dpi ; mono/color : 33/28ppm , 150s input tray, duty : 3000pages per month ; scan : 600x1200/19200dpi , 48bit ; standalone copy , 25-400% - USB + PictBridge + card reader , bundled 43XL+44XL high-yield ink - 5 years warranty

HP

deskjet - home and home office

iP-HD1560		HP cb710a deskjet D1560 , 4 ink ; 4800x1200dpi ; mono/color : 18/12ppm , 80s input tray , 50sheets output , duty : 750pages per month - USB
iP-HD2563		HP cb671a deskjet D2563 , 4 ink ; 4800x1200dpi ; mono/color : 26/20ppm , 80s input tray , 20sheets output , duty : 1000pages per month - USB
iP-HD2663	C	HP CH366C deskjet D2663 , 4 ink ; 4800x1200dpi ; mono/color : 28/22ppm , 80s input tray , 20sheets output , duty : 1000pages per month - USB
iP-HD4363		HP cb700c deskjet D4363 , 4 ink , 4800x1200dpi ; mono/color : 30/23ppm , 80s input tray , 50sheets output , duty : 3000pages per month - USB
iP-HPD5363		HP q8361c photosmart D5363 with duplex printing unit + 3.8cm Lcd , 6 ink ; 4800x1200dpi ; mono/color : 32/24ppm , 125s+20 photo input tray + cd/dvd printing tray , 50sheets output , duty : 3000pages per month - USB + card reader
iP-HPD5463	N	HP q8421c photosmart D5463 + 3.8cm Lcd , 5 single ink , 64mb ; 9600x2400dpi ; mono/color : 33/31ppm , 125s+20 photo input tray + cd/dvd printing tray , 50sheets output , duty : 2500pages per month , duplex printing unit optional - USB + pictbridge + card reader
iP-H6943		HP c8970c deskjet 6943 , network ready , 6 ink ; a4 , 32mb , 4800x1200dpi ; mono/color : 30/20ppm , 150s input tray upto 400 , 50sheets output , duty : 5000pages per month , duplex printing unit optional - USB + pictbridge
iP-H6983		HP c8969c deskjet 6983 , network ready (utp + Wi-Fi 802.11g) , 6 ink ; a4 , 32mb , 4800x1200dpi ; mono/color : 30/20ppm , 150s input tray upto 400 , 50sheets output , duty : 5000pages per month , duplex printing unit optional - USB + pictbridge

iP-HPD7463		HP cc247c photosmart D7463 , network ready (utp + Wi-Fi 802.11g + bluetooth) , with 8.9cm flip-up touch screen Lcd , 6 single ink ; a4 , 64mb , 4800x1200dpi ; mono/color : 34/33ppm , 100s + 20 photo , 50sheets output , duty : 3000pages per month , duplex printing unit optional - USB + card reader + PictBridge
business inkjet - A4		
iP-HK5400N		HP c9282a officejet pro K5400N , network ready , individual ink ; 192 MHz ARM946 , 32mb , 4800x1200dpi ; mono/color : 36/35ppm , 250s input tray upto 600 , 150sheets output , duty : 7500pages per month , duplex printing unit optional - USB+UTP
iP-HK5400DN		HP c8185a officejet pro K5400DN with duplex printing unit , network ready , individual ink ; 192 MHz ARM946 , 32mb , 4800x1200dpi ; mono/color : 36/35ppm , 250s input tray upto 600 , 150sheets output , duty : 7500pages per month , duplex printing unit optional - USB
iP-HK5400DTN		HP c9277a officejet pro K5400DTN with duplex printing unit , network ready , individual ink ; 192 MHz ARM946 , 32mb , 4800x1200dpi ; mono/color : 36/35ppm , 250+350s input tray , 150sheets output , duty : 7500pages per month , duplex printing unit optional - USB
iP-H8000	C	HP cb092a officejet pro 8000 , with duplex printing unit + network ready , individual ink ; 384 MHz processor , 32mb , 4800x1200dpi ; mono/color : 35/34ppm , 250s input tray upto 500 , 150sheets output , duty : 15000pages per month - USB+UTP
iP-H8000W	C	HP cb047a officejet pro 8000 Wireless , with duplex printing unit + network ready (wired + wireless) , individual ink ; 384 MHz processor , 32mb , 4800x1200dpi ; mono/color : 35/34ppm , 250s input tray upto 500 , 150sheets output , duty : 15000pages per month - USB+UTP
dedicated photo printer		http://h10010.www1.hp.com/wwpc/za/en/ho/WF02a/1783261-1783663-1783717.html
iP-HPA320		HP q8517a photosmart A320 , with built-in handle ; for photo paper (4"x6", 4"x8",4"x12") , 32mb , 4800x1200dpi , speed : 45sec per page , 20s input , 20sheets output - wireless bluetooth (optional) , USB , PictBridge
iP-HPA526	R	HP q8531a photosmart A526 , with built-in handle ; with 3.8cm Lcd , for photo paper (4"x6", 4"x8",4"x12") , 32mb , 4800x1200dpi , speed : 39sec per page , 20s input , 20sheets output - wireless bluetooth (optional) , USB , PictBridge , flash memory (CF , MS , SD , MMC , XD ..)
iP-HPA626		HP q8541a photosmart A626 ; , built-in handle , with 12cm flip-up touch-screen Lcd - for photo paper upto 13x18 / 10x30 cm , 64mb , 4800x1200dpi , speed : 39sec per page , 20s input , 20sheets output - wireless via optional bluetooth , USB , PictBridge , flash memory card reader ; support optional rechargable battery
iP-HPA636	R	HP q8637a photosmart A636 ; , built-in handle , with 12cm flip-up touch-screen Lcd - for photo paper upto 13x18 / 10x30 cm , 64mb , 4800x1200dpi , speed : 27sec per page , 20s input , 20sheets output - wireless via optional bluetooth , USB , PictBridge , flash memory card reader ; support optional rechargable battery
iP-HPA826	R	HP q8550a photosmart A826 home photo centre ; with 18cm touch screen Lcd (also works as digital photo frame) - for photo paper upto 13x18 / 10x30 cm , 64mb , 4800x1200dpi , speed : 39sec per page , 100s input , 100sheets output - wireless via optional bluetooth , USB , PictBridge , flash memory card reader
deskjet for notebook		

iP-HH470	N	HP cb026a H470 portable printer ; 340x163x80mm , 2.09kg , a4 , 192mhz cpu , 32mb , 4800x1200dpi ; mono/color : 22/18ppm , 50s input , duty : 500pages per month - USB + PictBridge , card reader - support optional battery
iP-HH470B	N	HP cb027a H470B portable printer with Battery pack ; 340x163x80mm , 2.09kg , a4 , 192mhz cpu , 32mb , 4800x1200dpi ; mono/color : 22/18ppm , 50s input , duty : 500pages per month - USB + PictBridge , card reader
iP-HH470WBT	N	HP cb028a H470WBT portable printer with Battery pack + wirelss bluetooth module ; 340x163x80mm , 2.09kg , a4 , 192mhz cpu , 32mb , 4800x1200dpi ; mono/color : 22/18ppm , 50s input , duty : 500pages per month - USB + PictBridge , card reader
deskjet - A3+		
iP-HPB8553	N	HP cb981c Photosmart Pro B8553 , with 6.1cm lcd ; individual ink ; A3+ , 128mb , 9600x2400dpi ; mono/color : 33/31ppm , 150s+20s input , 50sheets output - USB , card reader
iP-HPB9180	R	HP q5736a Photosmart Pro B9180 , network ready ; individual ink ; A3+ , 64mb , 4800x1200dpi ; mono/color : 28/26ppm , 200s input + single-sheet specialty media tray , 50sheets output , duty : 1000pages per month - USB , UTP
iP-HPB9180GP	R	HP q5743a Photosmart Pro B9180GP , with HP Colorimeter for display calibration , network ready ; individual ink ; A3+ , 64mb , 4800x1200dpi ; mono/color : 28/26ppm , 200s input + single-sheet specialty media tray , 50sheets output , duty : 1000pages per month - USB , UTP
business inkjet - A3+		
iP-HK7103		HP cb041c officejet pro K7103 , A3+ ; 96 MHz ARM946E-S cpu , 32mb , 4800x1200dpi ; mono/color : 25/20ppm , Photoret III , 150s input tray , 100sheets output , duty : 5000 pages per month , duplex printing unit optional - USB + Parallel
iP-HK8600	N	HP cb015a officejet pro K8600 , A3+ , individual ink ; 192 MHz processor , 32mb , 4800x1200dpi ; mono/color : 35/35ppm , 250s input tray , 150sheets output , duty : 6250pages per month , duplex printing unit optional - USB
iP-HK8600DN	N	HP cb016a officejet pro K8600DN , with duplex printing unit , network ready , A3+ , individual ink ; 192 MHz processor , 32mb , 4800x1200dpi ; mono/color : 35/35ppm , 250s input tray , 150sheets output , duty : 6250pages per month - USB+UTP
iP-H2800	N	HP c8174a business inkjet 2800 , single ink , A3+ ; Motorola 32-bit ColdFire 4e RISC, 256 MHz , 96mb upto 544 , 4800x1200dpi ; mono/color : 24/21ppm , Photoret III/IV , 150s input tray upto 400 , 100sheets output , duty : 12000pages per month , duplex printing unit optional - USB + Parallel + open EIO slot
iP-H2800DT	R	HP c8163a business inkjet 2800DT with duplex printing unit , extra paper tray , singl ink , A3+ ; Motorola 32-bit ColdFire 4e RISC, 256 MHz , 96mb upto 544 , 4800x1200dpi ; mono/color : 24/21ppm , Photoret III/IV , 400 (150+250)s input tray , 100sheets output , duty : 12000pages per month - USB + Parallel + open EIO slot
iP-H2800DTN	R	HP c8164a business inkjet 2800DTN with duplex printing unit , network ready , extra paper tray , singl ink , A3+ ; Motorola 32-bit ColdFire 4e RISC, 256 MHz , 96mb upto 544 , 4800x1200dpi ; mono/color : 24/21ppm , Photoret III/IV , 400 (150+250)s input tray , 100sheets output , duty : 12000pages per month - USB + Parallel + EIO slot (used)
HP all-in-One inkjet		
All-In-One Print-Scan-Copy		

iP-HoF2280	N	HP CB683A F2280 - Print-Scan-Copy ; a4 , 32mb , 4800x1200dpi ; mono/color : 20/14ppm , 80s input , 50sheets output , duty : 1000pages per month ; scan : 600x600/19200dpi , 48bit ; standalone copy , 20/14ppm , 9 mutiple copies , 25-200% - USB
iP-HoF4283	N	HP CB656C F4283 - Print-Scan-Copy ; a4 , 16mb , 4800x1200dpi ; mono/color : 26/20ppm , 80s input , 20sheets output , duty : 3000pages per month ; scan : 1200x2400/19200dpi , 48bit ; standalone copy , 20/14ppm , 9 mutiple copies , 25-200% - USB - support high-yield cartridge
iP-HoC4483	N	HP Q8388C photosmart C4483 - Print-Scan-Copy with 3.8cm LCD ; 32mb , 4800x1200dpi ; mono/color : 30/23ppm , 100s input , 50sheets output , duty : 1000pages per month ; scan : 1200x2400/19200dpi , 48bit ; standalone copy , 50 mutiple copies , 50-400% - USB , Flash card reader
iP-HoC5383	N	HP q8291c photosmart C5383- Print-Scan-Copy with 6.1cm LCD ; 5 x single ink ; 64mb , 9600x2400dpi ; mono/color : 31/30ppm , 125+20s input + cd/dvd printing tray , 50sheets output , duty : 2500pages per month ; scan : 4800x9600/19200dpi , 48bit ; standalone copy , 50 mutiple copies , 50-400% - USB , PictBridge , Flash card reader
iP-HoC4583		HP Q8401C photosmart C4583 - Print-Scan-Copy with 3.8cm LCD + wireless network ready ; 32mb , 2400x1200dpi ; mono/color : 30/23ppm , 100+20s input , 50sheets output , duty : 1000pages per month ; scan : 1200x2400/19200dpi , 48bit ; standalone copy , 50 mutiple copies , 50-400% - USB , Flash card reader
iP-HoL7480		HP CB061A Officejet pro L7480 - Print-Scan-Copy , 4 x single ink, 192mhz , 64mb , support 2 x A4 borderless photos ; 4800x1200dpi ; mono/color : 36/35ppm , 250 sheet input upto 600, 150sheets output , duty : 7500pages per month ; scan : 2400x4800/19200dpi , 48bit ; standalone copy , 36/35cpm , 99 mutiple copies , 25-400% ; duplex printing unit optional - USB , UTP , PictBridge , flash card reader
iP-HoC6283		HP cc988c officejet C6283 - Print-Scan-Copy with 6.1cm LCD , auto duplex printing unit , network ready ; 5 x single ink : 64mb , 4800x1200dpi ; mono/color : 34/33ppm , 100s input , 50sheets output , duty : 3000pages per month ; scan : 9600x9600/19200dpi , 48bit ; standalone copy , 34/33cpm , 50 mutiple copies , 50-400% - USB , UTP , flash card reader
iP-HoC6383	N	HP cd028c officejet C6383 - Print-Scan-Copy with 6.1cm LCD , network ready (UTP+wireless) ; 5 x single ink : 64mb; mono/color : 33/31ppm , 125+20 sheets input , 50sheets output , duty : 2500pages per month ; scan : 4800x9600/19200dpi , 48bit ; standalone copy , 33/31cpm , 50 mutiple copies , 50-400% - USB , UTP , PictBridge , flash card reader
iP-HoC8183	N	HP L2526C officejet C8183 - Print-Scan-Copy with built-in lightscribe dvd writer + 8.9cm touch-screen LCD , network ready (UTP+wireless+bluetooth) : 64mb , 4800x1200dpi ; mono/color : 34/33ppm , 100s input + cd/dvd printing tray , 50sheets output , duty : 3000pages per month ; scan : 9600x9600/19200dpi , 96bit ; standalone copy , 34/33cpm , 50 mutiple copies , 50-400% ; duplex printing unit optional - USB , UTP , PictBridge , bluetooth , flash card reader

All-In-One Print-Scan-Copy-Fax

iP-HoJ3680	**N**	HP CB071A officejet J3680 , with phone handset , Print-Scan-Copy-Fax with 20s ADF , sheet feed (non-flatbed) ; 16mb , 4800x1200dpi ; mono/color : 20/14ppm , 100s input , 20sheets output , duty : 1500pages per month ; scan : 1200x1200/19200dpi , 48bit ; standalone copy , 20/13cpm , 80 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , support color fax , 200pages fax memory , 100 speed dial - USB
iP-HoJ4580	**N**	HP CB780A officejet J4580 , Print-Scan-Copy-Fax with 20s ADF ; 120mhz , 16mb , 4800x1200dpi ; mono/color : 28/22ppm , 100s input , 20sheets output , duty : 3000pages per month ; scan : 1200x2400/19200dpi , 48bit ; standalone copy , 20/13cpm , 90 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , support color fax , 100pages fax memory , 90 speed dial - USB
iP-HoJ4660		HP CB786A officejet J4660 , with phone handset , Print-Scan-Copy-Fax with 20s ADF ; 120mhz , 16mb , 4800x1200dpi ; mono/color : 28/22ppm , 100s input , 20sheets output , duty : 3000pages per month ; scan : 1200x2400/19200dpi , 48bit ; standalone copy , 20/13cpm , 90 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , support color fax , 100pages fax memory , 99 speed dial - USB
iP-Ho6313		HP q8061c officejet 6313 - Print-Scan-Copy-Fax with 35s ADF , network ready : 64mb , 4800x1200dpi ; mono/color : 30/24ppm , 100s input , 50sheets output , duty : 3000pages per month ; scan : 2400x4800/19200dpi , 48bit ; standalone copy , 30/24cpm , 100 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , support color fax , 100pages fax memory , 100 speed dial - USB , UTP , PictBridge , flash card reader
iP-Ho6500	**C**	HP CB815A officejet 6500 - Print-Scan-Copy-Fax with 35s ADF , network ready : 32mb , 4800x1200dpi ; mono/color : 32/31ppm , 250s input , 50sheets output , duty : 7000pages per month ; scan : 2400x4800/19200dpi , 48bit ; standalone copy , 30/24cpm , 100 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , support color fax , 100pages fax memory , 100 speed dial - USB , UTP , PictBridge , flash card reader
iP-Ho6500W	**C**	HP CB057A officejet 6500 Wireless - Print-Scan-Copy-Fax with 35s ADF , network ready (UTP+WiFi) : 64mb , 4800x1200dpi ; mono/color : 32/31ppm , 250s input , 50sheets output , duty : 7000pages per month ; scan : 2400x4800/19200dpi , 48bit ; standalone copy , 30/24cpm , 100 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , support color fax , 100pages fax memory , 100 speed dial - USB , UTP , PictBridge , flash card reader
iP-HoJ6413		HP CB029C officejet J6413 - Print-Scan-Copy-Fax with 35s ADF + auto duplex printing unit , network ready (UTP+WiFi) ; 64mb , 4800x1200dpi ; mono/color : 31/25ppm , 250s input , 50sheets output , duty : 5000pages per month ; scan : 4800x4800/19200dpi , 48bit ; standalone copy , 100 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , support color fax , 100 pages fax memory , 48 speed dial - USB , UTP , PictBridge , flash card reader
iP-HoL7590		HP CB822A Officejet pro L7590 - Print-Scan-Copy-Fax with 50s ADF , auto duplex printing unit , network ready , 4 x single ink, 192mhz , 64mb , support 2 x A4 borderless photos ; 4800x2400dpi ; mono/color : 35/34ppm , 250 sheet input upto 600, 150sheets output , duty : 7500pages per month ; scan : 2400x4800/19200dpi , 48bit ; standalone copy , 35/34cpm , 99 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , support color fax , 125pages fax memory , 20 speed dial - USB , UTP , PictBridge , flash card reader

iP-HoC7283		HP cc567c photosmart C7283 - Print-Scan-Copy-Fax with 6.4cm LCD + 50s ADF + auto duplex printing unit , network ready (UTP+WiFi) ; 6 x single ink , 64mb , 4800x1200dpi ; mono/color : 34/33ppm , 100+20s input , 50sheets output , duty : 3000pages per month ; scan : 4800x4800/19200dpi , 48bit ; standalone copy , 50 mutiple copies , 50-400% ; as standalone fax with 33.6k modem , support color fax , 90pages fax memory , 48 speed dial - optional wireless bluetooth , USB , UTP , PictBridge , flash card reader
iP-HoL7680		HP CB038A Officejet pro L7680 - Print-Scan-Copy-Fax with 50s ADF + 2.4" Lcd , auto duplex printing unit , network ready , support digital filing , 4 x single ink , 192mhz , 64mb , support 2 x A4 borderless photos ; 4800x1200dpi ; mono/color : 35/34ppm , 250 sheet input upto 600, 150sheets output , duty : 7500pages per month ; scan : 2400x4800/19200dpi , 48bit ; standalone copy , 35/34cpm , 99 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , support color fax , 125pages fax memory , 99 speed dial - USB , UTP , PictBridge , flash card reader
iP-Ho8500	C	HP cb022a officejet pro 8500 - Print-Scan-Copy-Fax , network ready + 35s ADF + auto duplex printing unit ; 250mhz cpu , 64mb, 4800x1200dpi ; mono/color : 35/34ppm , 250s input upto 500 , 150sheets output , duty : 15000pages per month ; scan : 2400x4800/19200dpi , 48bit ; standalone copy , 25/22cpm , 99 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , support color fax , 125pages fax memory , 99 speed dial - USB , UTP, card reader , PictBridge
iP-Ho8500W	C	HP cb022a officejet pro 8500 Wireless - Print-Scan-Copy-Fax , network ready (wired+wireless) + 35s ADF + auto duplex printing unit ; 250mhz cpu , 64mb, 4800x1200dpi ; mono/color : 35/34ppm , 250s input upto 500 , 150sheets output , duty : 15000pages per month ; scan : 2400x4800/19200dpi , 48bit ; standalone copy , 25/22cpm , 99 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , support color fax , 125pages fax memory , 99 speed dial - USB , UTP, card reader , PictBridge
iP-Ho309C	N	HP CC335C photosmart premium 309C - Print-Scan-Copy-Fax with 50s ADF + 6.1cm Lcd , auto duplex printing unit + network ready (UTP+WiF) , 4 x single ink , 64mb ; 9600x2400dpi ; mono/color : 33/32ppm , 125+20 sheet input + cd/dvd printing tray , 50sheets output , duty : 2500pages per month ; scan : 4800x4800/19200dpi , 48bit ; standalone copy , 35/34cpm , 50 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , support color fax , 90pages fax memory , 20 speed dial - USB , UTP , PictBridge , flash card reader
iP-HoL7780		HP CB039A Officejet pro L7780 - Print-Scan-Copy-Fax with 50s ADF + 2.4" Lcd + auto duplex printing unit + 2nd paper tray , network ready (UTP+wireless) , support digital filing , 4 single ink , 192mhz , 96mb , support 2 x A4 borderless photos ; 4800x1200dpi ; mono/color : 35/34ppm , 250+350 sheet input , 150sheets output , duty : 7500pages per month ; scan : 2400x4800/19200dpi , 48bit ; standalone copy , 35/34cpm , 99 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , support color fax , 125pages fax memory , 99 speed dial - USB , UTP , PictBridge , flash card reader , support digital filing , include readlris pro OCR software

iP-Ho9130		HP c8144a officejet 9130 - Print-Scan-Copy-Fax with digital sender keyboard + jetdirect 620n network ready + 50s ADF + auto duplex printing unit + EiO slot ; 250mhz cpu , 128mb upto 384 , 4800x1200dpi ; mono/color : 25/22ppm , 400 (150+250)s input upto 650 , 100sheets output , duty : 10000pages per month ; scan : 2400x2400/19200dpi , 48bit ; standalone copy , 25/22cpm , 99 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , support color fax , 250pages fax memory , 99 speed dial - USB , UTP , parallel , flash

HP inkjet accessories		
iP-HA3447	R	HP q3447a 250sheet paper tray - for Photosmart 2700 A-i-O series , Photosmart 7700, 8100, 8400 series; deskjet 5600, 5800, 6500, 6840 , 6940 , 6980 series
iP-HA8256	R	HP C8256a 350sheet paper tray - for HP business inkjet officejet pro k550
iP-HACB007	R	HP CB007a 350sheet paper tray - for HP business inkjet officejet pro L7480, L7580, L7680
iP-HACB009	R	HP CB009a 350sheet paper tray - for HP business inkjet officejet pro k5400
iP-HACB090	R	HP CB090a 250sheet paper tray - for HP officejet pro 8000 series
iP-HA6211		HP q6211a 250sheet paper tray - for HP Officejet 7300 series
iP-HA8237	R	HP c8237a 250sheet paper tray - for HP Officejet 9110 series
iP-HA8238	R	HP c8238a 500sheet paper tray - for HP Officejet 9110 series
iP-HA8261	R	HP c8261a 250sheet paper tray - for HP business inkjet 2800 series
iP-HA5582	R	HP q5582a auto two-sided printing accessory - Photosmart 3213 , 3313, D5463 , D7163, D7263, D7363, D7463 , 8253 / Photosmart all-in-one C6183, C7183, C58183
iP-HA8255	R	HP C8255A two-sided printing duplex unit - for business inkjet officejet pro k550
iP-HA9278	R	HP C9278A two-sided printing duplex unit - for business inkjet officejet pro k5400, L7480, L7580, L7590, L7680, L7780
iP-HA5712	R	HP q5712a auto two-sided printing accessory - for Photosmart 2600 series and 2700 All-in-One series , deskjet 6943, 6983
iP-HAB005	R	HP cb005a auto two-sided printing accessory - for business inkjet 1000
iP-HA8247	R	HP c8247a auto two-sided printing accessory - for business inkjet 2300
iP-HA8258	R	HP c8258a A3 wide format two-sided printing duplex unit - for business inkjet 2800, K850, K7103 series , 9803 / photosmart pro b8350
iP-HACB017	R	HP CB017A A3 wide format two-sided printing duplex unit - for officejet pro K8600
iP-HACB006	R	HP CB006A cartridge travel holder for black / photo ink
iP-HACB001		HP CB001A CF card WiFi adapter - for deskjet 460 series
iP-HA6274	R	HP Q6274A 802.11B/G usb wireless adapter
iP-HA6273		HP Q6273A BT500 usb bluetooth adapter
iP-HA8257		HP c8257a car adapter - for deskjet 450 , 460 series, H470 series
iP-HA9279	R	HP c9279a AC-adapter - for deskjet H470 series
iP-HA6410	R	HP q6410a carry case - for photosmart 325 , 335 , 375 , 385 , 428 , 475, A320, A432, A433, A440, A516, A526, A618, A717
iP-HA6281	R	HP q6281a printer sleeve for deskjet H470 series
iP-HA6282	R	HP q6282a carry case for notebook + deskjet H470 series
iP-HA8263		HP c8263a rechargable battery - for deskjet 450, 460 series, H470 series
iP-HA5599		HP q5599b rechargable battery ; recharge time : 4 hours , print upto 75 photos per charge - for photosmart 325 , 335 , 375 , 385 , 428, 475, A432, A440, A433, A516, A618, A626, A636, A717

iP-HACB012	R	HP CB012A rechargable battery + charger kit - for deskjet 460 series, H470 series

HP designjet and accessories

DJ-H70	R	HP Q6655A designet 70 , optional roll-feed+cutter ; A2 , 4-ink ; 64mb , 1200x600dpi ; A1: 90sec , 70s A2 input tray + manual feed : front and rear - USB + parallel + EiO slot
DJ-H90		HP Q6656A designet 90 , optional rear roll feed+auto cutter , A2 , 6-ink , 4pl ; 64mb , 2400x1200dpi ; A2: 6.3min , 100s input tray + manual feed : front and rear , 50sheets output - USB + parallel + 1 x EiO slot
DJ-H90R	R	HP Q6656B designet 90R , with rear roll feed+auto cutter , A2 , 6-ink , 4pl ; 64mb , 2400x1200dpi ; A2: 6.3min , 70s input tray + manual feed : front and rear , 50sheets output - USB + parallel + 1 x EiO slot
DJ-H90GP	R	HP Q6656C designet 90GP , with rear roll feed+auto cutter , HP colorimeter ; A2 , 6-ink , 4pl ; 64mb , 2400x1200dpi ; A2: 6.3min , Colorsmart III , 70s input tray + manual feed : front and rear , 50sheets output - USB + parallel + 1 x EiO slot
DJ-H110P	R	HP C7796D designet 110 plus , A1 , 4-ink ; 64mb , 1200x600dpi ; A1: 90sec , 150s A2+ input tray + A1 manual feed : front and rear , optional roll-feed + cutter - USB + 1 x EiO slot
DJ-H130	R	HP C7791C designet 130 , optional rear roll feed+auto cutter , A1 , 6-ink , 4pl ; 64mb , 2400x1200dpi ; A3: 4min , A1: 12min , Colorsmart III , 100s input tray + manual feed : front and rear , 50sheets output - USB + parallel + 1 x EiO slot
DJ-H130NR	R	HP C7791D designet 130NR , with rear roll feed+auto cutter , network ready , A1 , 6-ink , 4pl ; 64mb , 2400x1200dpi ; A3: 4min , A1: 12min , Colorsmart III , 100s input tray + manual feed : front and rear , 50sheets output - USB + parallel
DJ-H130GP	R	HP C7791E designet 130GP , with rear roll feed+auto cutter , network ready , plus Eye One Display with monitor calibrator , A1 , 6-ink , 4pl ; 64mb , 2400x1200dpi ; A3: 4min , A1: 12min , Colorsmart III , 100s input tray + manual feed : front and rear , 50sheets output - USB + parallel
DJ-H500PA1	R	HP C7769F designet 500 Plus A1/24" , with rear roll feed+auto cutter , HP GL/2 , 4-ink ; 32mb upto 160 , 1200x600dpi ; A1: 90sec , Color Layering - USB + parallel + 1 x EiO slot
DJ-H500PSPA1	R	HP C7769G designet 500PS Plus A1/24" , with EFI Designer Edition XL software RIP , PostScript3 , rear roll feed+auto cutter , HP GL/2 , 4-ink ; 16mb upto 160 , 1200x600dpi ; A1: 90sec , Color Layering - USB + parallel + 1 x EiO slot
DJ-H500PA0	R	HP C7770F designet 500 Plus A0/42" , with rear roll feed+auto cutter , include stand and media bin , HP GL/2 , 4-ink ; 32mb upto 160 , 1200x600dpi ; A1: 90sec , Color Layering - USB + parallel + 1 x EiO slot
DJ-H500PSPA0	R	HP C7770G designet 500PS Plus A0/42" , with EFI Designer Edition XL software RIP , PostScript3 , rear roll feed+auto cutter , include stand and media bin , HP GL/2 , 4-ink ; 32mb upto 160 , 1200x600dpi ; A1: 90sec , Color Layering - USB + parallel + 1 x EiO slot
DJ-H510A1	R	HP CH336A designet 510 610mm/A1/24" , 4/18pl , with rear roll feed+auto cutter (except canvas) , HP GL/2 , 160mb , 4-ink ; 160mb upto 416 , 2400x1200dpi ; A1: 55sec , Color Layering - USB + parallel + 1 x EiO slot
DJ-H510PSA1	R	HP CJ996A designet 510PS 610mm/A1/24" , with EFI Designer Edition XL software RIP , 4/18pl , with rear roll feed+auto cutter (except canvas) , HP GL/2 , 160mb , 4-ink ; 160mb upto 416 , 2400x1200dpi ; A1: 55sec , Color Layering - USB + parallel + 1 x EiO slot

DJ-H510A0	R	HP CH337A designet 510 1067mm/A0/42" , 4/18pl , with rear roll feed+auto cutter (except canvas) , include stand and media bin , HP GL/2 , 160mb , 4-ink ; 160mb upto 416 , 2400x1200dpi ; A1: 55sec , Color Layering - USB + parallel + 1 x EiO slot
DJ-H510PSA0	R	HP CJ997A designet 510PS 1067mm/A0/42" , with EFI Designer Edition XL software RIP , 4/18pl , with rear roll feed+auto cutter (except canvas) , include stand and media bin , HP GL/2 , 160mb , 4-ink ; 160mb upto 416 , 2400x1200dpi ; A1: 55sec , Color Layering - USB + parallel + 1 x EiO slot
DJ-HA7772	R	HP C7772A HP GL/2 accessory card with 16mb
DJ-HA2387	R	HP C2387A 64mb upgrade for designjet 500, 800 - require C7772A
DJ-HA2388	R	HP C2388A 128mb upgrade for designjet 500, 800 - require C7772A
DJ-HA1246	R	HP Q1246B A1(24") media bin and stand for designjet 100, 500, 510, 800
DJ-HA1247	R	HP C1247A auto roll-feed + cutter - for designjet 110 / 120 / 130
DJ-HA6662	R	HP Q6662A auto roll-feed + cutter - for designjet 70 / 90
DJ-HA6661	R	HP Q6661A A2 spindle accessories - for designjet 70 / 90
DJ-HA2389	R	HP C2389A A1/24" spindle accessories - for designjet 500A1, 510A1, 800A1
DJ-HA1264	R	HP C1264A A1/24" spindle accessories - for designjet 110 / 120 / 130
DJ-HA2390	R	HP C2390A A0/42" spindle accessories - for designjet 500A0, 510A0, 800A0
Canon bubblejet		
A4		http://www.canon.co.uk/for_home/product_finder/printers/bubble_jet/index.asp
iP-CiP1900	N	Canon pixma ip1900 Black ; a4 , 4800x1200dpi , 4 ink ; mono/color : 21/17ppm , 2pl Micro-Nozzles , input : 100s, USB
iP-CiP3600	N	Canon pixma ip3600 , black , 5 single ink ; a4 , 9600x2400dpi ; mono/color : 26/17ppm , 1pl Micro-Nozzles , input : 150+150s dual paper tray - USB + PictBridge direct print
iP-CiP4600	N	Canon pixma ip4600 , black + silver , 5 single ink , duplex printing ; a4 , 9600x2400dpi ; mono/color : 26/21ppm , 1pl Micro-Nozzles , FINE , input : 150+150s dual paper tray + cd/dvd printing tray - USB + PictBridge direct print
iP-CiP4500		Canon pixma ip4500 , black + silver , 5 single ink , duplex printing ; a4 , 9600x2400dpi ; mono/color : 31/24ppm , 1pl Micro-Nozzles , FINE , input : 150+150s dual paper tray + cd/dvd printing tray - USB + PictBridge direct print
A4 portable for notebook		http://www.canon.co.uk/for_home/product_finder/printers/bubble_jet/index.asp
iP-CiP100		Canon pixma ip100 - ultra portable designed for notebook , wireless printing ; a4 , 9600x2400dpi , 5 ink ; mono/color : 20/14ppm , 1pl Micro-Nozzles , FINE , input : 50s - USB , IrDA or optional BlueTooth module
iP-CiP100B		Canon pixma ip100B with battery - ultra portable designed for notebook , wireless printing ; a4 , 9600x2400dpi , 5 ink ; mono/color : 20/14ppm , 1pl Micro-Nozzles , FINE , input : 50s - USB , IrDA or optional BlueTooth module
dedicated photo printer		http://www.canon.co.uk/for_home/product_finder/printers/direct_photo/index.asp

iP-CM260		Canon pixma Mini260 compact photo inkjet printer with 2.5" Lcd , support optional battery pack , post card size printing : 59sec ; 4"x 6" , 4 ink , 1pl Micro-Nozzles , 9600x2400 dpi , input : 20 sheets - USB + PictBridge + flash card reader + IrDA (wireless print from camera or phone) + optional bluetooth
iP-CSCP530	N	Canon SELPHY CP530 compact photo printer , Dye-sublimation thermal transfer printing , post card size printing : 52sec ; 4"x 8" - USB + PictBridge + optional bluetooth
iP-CSCP760		Canon SELPHY CP760 compact photo printer with 2.5" LCD , Dye-sublimation thermal transfer printing , ultra fast when using a Canon camera with DIGIC II , post card size printing : 52sec ; 4"x 8" - USB + PictBridge + flash card reader + IrDA wireless printing + optional bluetooth + optional WiFi
iP-CSCP770		Canon SELPHY CP770 compact photo printer with 2.5" LCD , support optional battery , Dye-sublimation thermal transfer printing , ultra fast when using a Canon camera with DIGIC II , post card size printing : 52sec ; 4"x 8" - USB + PictBridge + flash card reader + IrDA wireless printing + optional bluetooth + optional WiFi
iP-CSES30	C	Canon SELPHY ES30 compact photo printer with 3" LCD , built-in carrying handle , vertical stand , support speech bubble to print images overlaid with the desired speech , Flexible framing to print the only area u want , support multi imgae printing per sheet , built-in calender printing with image , dedicated B/W/Gold/Silver printing , 300x600 Dye-sublimation thermal transfer printing , ultra fast when using a Canon camera with DIGIC II , post card size printing : 55sec ; 4"x 6" - USB + PictBridge + flash card reader + wireless printing via optional bluetooth module + optional WiFi
iP-CSES2		Canon SELPHY ES2 compact photo printer with 3.0" LCD , built-in carrying handle , support optional battery , vertical stand , support speech bubble to print images overlaid with the desired speech , Flexible framing to print the only area u want , support multi imgae printing per sheet , built-in calender printing with image , dedicated B/W printing , 300x300 Dye-sublimation thermal transfer printing , ultra fast when using a Canon camera with DIGIC II , post card size printing : 69sec ; 4"x 6" - USB + PictBridge + flash card reader + IrDa wireless printing + optional bluetooth / WiFi module
iP-CSES3	C	Canon SELPHY ES3 compact photo printer with 3.5" LCD , with built-in 1Gb memory , built-in carrying handle , vertical stand , support speech bubble to print images overlaid with the desired speech , Flexible framing to print the only area u want , support multi imgae printing per sheet , built-in calender printing with image , dedicated B/W/Gold/Silver printing , 300x600 Dye-sublimation thermal transfer printing , ultra fast when using a Canon camera with DIGIC II , post card size printing : 55sec ; 4"x 6" - USB + PictBridge + flash card reader + IrDa wireless printing + optional bluetooth / WiFi module
A3+		http://www.canon.co.uk/for_home/product_finder/printers/bubble_jet/index.asp
iP-CP9000	R	Canon pixma Pro 9000 , 8 single ink , manual duplex printing ; A3+ , 4800x2400dpi ; mono/color : 16/15ppm , 2pl Micro-Nozzles , FINE , input : 150s + cd/dvd printing tray , built-in flat paper path - USB + PictBridge direct print
iP-CP9500	R	Canon pixma Pro 9500 , 10 single ink , manual duplex printing ; A3+ , 4800x2400dpi ; mono/color : 9/8ppm , 3pl Micro-Nozzles , FINE , input : 150s + cd/dvd printing tray , built-in flat paper path - USB + PictBridge direct print

Canon multi-functin		
All-In-One Print-Scan-Copy		
iP-CMP190	N	Canon pixma mp190 , print+scan+copy - print 4800x1200dpi ; mono/color : 19/15 ppm , 2pl Micro-Nozzles , 100s paper tray ; scan 600x1200/19200dpi ; standalone copy , 9 mutiple copies - USB + PictBridge
iP-CMP140		Canon pixma mp140 , print+scan+copy - print 4800x1200dpi ; mono/color : 20/15 ppm , 2pl Micro-Nozzles , 100s paper tray ; scan 600x1200/19200dpi ; standalone copy , 9 mutiple copies - USB
iP-CMP240		Canon pixma mp240 , print+scan+copy , with self-opening paper tray - print 4800x1200dpi ; mono/color : 19/15ppm , 2pl Micro-Nozzles , 100s paper tray ; scan 1200x2400/19200dpi ; standalone copy , 9 mutiple copies - USB + PictBridge
iP-CMP540		Canon pixma mp540 , print+scan+copy - 5 single ink , 5cm LCD ; print 9600x2400dpi ; mono/color : 26/17 ppm , 1pl Micro-Nozzles , 150+150 sheet dual input tray ; scan 2400x4800 / 19200dpi ; standalone copy , 99 mutiple copies , 25-400% - USB 2.0 + PictBridge + flash card reader ; support optional bluetooth printing
iP-CMP620		Canon pixma mp620 , print+scan+copy - wired+wireless network ready , 5 single ink , 6.2cm LCD ; print 9600x2400dpi ; mono/color : 26/17 ppm , 1pl Micro-Nozzles , 150+150s dual input tray ; scan 4800x9600 / 19200dpi ; 99 mutiple copies , 25-400% - USB 2.0 + UTP + PictBridge + flash card reader ; support optional bluetooth printing
iP-CMP630		Canon pixma mp630 , print+scan+copy - 5 single ink , duplex printing , 6.2cm LCD ; print 9600x2400dpi ; mono/color : 25/21 ppm , 1pl Micro-Nozzles , 150+150s dual input tray + cd/dvd printing tray ; scan 4800x9600 / 19200dpi (support scan to flash card or usb flash drive) ; 99 mutiple copies , 25-400% - USB 2.0 + UTP + PictBridge + flash card reader ; support optional bluetooth printing
iP-CMP970		Canon pixma mp970 , print+scan+copy - built-in FAU (Filam Adapter Unit) , network ready - 7 single ink , duplex printing , 8.8cm LCD , 35mm film adapter ; print 9600x2400dpi ; mono/color : 30 / 22ppm , 1pl Micro-Nozzles , 150+150s dual input tray + cd/dvd printing tray ; scan 4800x9600 / 19200dpi ; 99 mutiple copies , 25-400% - UTP + USB 2.0 + PictBridge + flash card reader + IrDa wireless ; support optional bluetooth printing
All-In-One Print-Scan-Copy-Fax		
iP-CMX300		Canon pixma MX300 , print+scan+copy+fax , with 2-line lcd display ; print 4800x1200dpi ; mono/color : 22/17ppm , 2pl Micro-Nozzles , 100s input tray ; scan 600x1200 / 19200dpi , 48/24bit ; 99 mutiple copies , 25-400% ; as standalone fax with 33.6k G3 modem , support color fax , 50pages fax memory , 20 x speed dial - USB 2.0 + PictBridge direct print
iP-CMX320	N	Canon pixma MX320 , print+scan+copy+fax , with 2-line lcd display ; print 4800x1200dpi ; mono/color : 7.5/4.5ipm , 2pl Micro-Nozzles , 100s input tray ; with 30pages ADF , scan 1200x2400 / 19200dpi , 48/24bit ; 99 mutiple copies , 25-400% ; as standalone fax with 33.6k G3 modem , support color fax , 50pages fax memory , 20 x speed dial - USB 2.0 + PictBridge direct print + optional bluetooth module ; support scan to usb

iP-CMX330	N	Canon pixma MX330 , print+scan+copy+fax , with 4.5cm LCD lcd display ; print 4800x1200dpi ; mono/color : 7.5/4.5ipm , 2pl Micro-Nozzles , 100s input tray ; with 30pages ADF , scan 1200x2400 / 19200dpi , 48/24bit ; 99 mutiple copies , 25-400% ; as standalone fax with 33.6k G3 modem , support color fax , 50pages fax memory , 20 x speed dial - USB 2.0 + PictBridge direct print + optional bluetooth module ; support scan to usb
iP-CMX850		Canon pixma MX850 , print+scan+copy+fax - network ready , 5 single ink , duplex printing+copy , 6.2cm LCD ; print 9600x2400dpi ; mono/color : 31/24ppm , 1pl Micro-Nozzles , 150 sheets input tray + cd/dvd printing tray ; with 35pages duplex ADF , scan 4800x9600 / 19200dpi , 48/24bit ; 99 mutiple copies , 25-400% ; as standalone fax with 33.6k G3 modem , support color fax , 250pages fax memory , 100+8 x speed dial - UTP + USB 2.0 + PictBridge direct print + flash card reader
iP-CMX7600	R	Canon pixma MX7600 , print+scan+copy+fax - network ready , 6 single ink include clear-ink technology , duplex printing+copy , 4.5cm LCD ; print 4800x1200dpi ; mono/color : 28/23ppm , 2pl Micro-Nozzles , 20+150s dual input tray ; with 35pages duplex ADF , scan 4800x9600 / 19200dpi , 48/24bit ; 99 mutiple copies , 25-400% ; as standalone fax with 33.6k G3 modem , support color fax , 250pages fax memory , 100+8 x speed dial - UTP + USB 2.0 + PictBridge direct print + flash card reader

canon bubblejet accessories

iP-CABU20	R	Canon BU-20 bluetooth printer adapter for canon pixma iP6210D, iP6220D, iP6600D, iP6700D, mini220, mini260 / Selphy CP510, CP520, CP720, CP740, DS810, ES1, ES2, ES20 / multi-function MP460, MP500, MP510, MP520, MP600, MP610, MP800, MP810, MP970
iP-CABU30	R	Canon BU-30 bluetooth printer adapter for canon pixma iP100, iP100B, CP760, ES30 / multi-function MP480, MP540, MP620, MP630, MP980, MX320, MX330, MX860
iP-CALK60		Canon LK-60 rechargable battery for canon pixma mini260
iP-CANBCP2L		Canon NB-CP2L rechargable battery for canon Selphy CP510, CP600, CP710, CP730, CP750, CP770
iP-CANBES1L		Canon NB-ES1L rechargable battery for canon Selphy ES1, ES2
iP-CAPU100U	R	Canon PU-100U car charger - for canon BJC-50 , BJC-55 , i80 , pixma iP90
iP-CAPU200U	R	Canon PU-200U car charger - for canon pixma iP100 , iP100B
iP-CALK51B		Canon LK-51B battery + charger - for canon BJC-50, BJC-55, i70, i80 , pixma iP90, iP90V
iP-CALK62	R	Canon LK-62 battery + attachment - for canon pixma iP100, iP100V

Laser Printer

Lexmark

lexmark A4 mono - for home & small business

LP-LE120	Lexmark E120 , drak Gray ; 183 MHz processor , 16mb , 600/1200dpi ; 19ppm , 150+15 sheet input tray , 50sheets output , 8sec warm-up time , duty : 10000 pages per month - USB
LP-LE120N	Lexmark E120N , built-in Network , drak Gray ; 183 MHz processor , 16mb , 600/1200dpi ; 19ppm , 150+15 sheet input tray , 50sheets output , 8sec warm-up time , duty : 10000 pages per month - USB + UTP
LP-LE250D	Lexmark E250D , built-in auto duplex unit , grey ; 366 MHz processor , 32mb upto 96 , 600/2400dpi ; 28ppm , 250 sheet input tray upto 800 , 150sheets output , duty : 50000 pages per month - USB + parallel

LP-LE250DN		Lexmark E250DN , built-in auto duplex unit + netwrk ready , grey ; 366 MHz processor , 32mb upto 96 , 600/2400dpi ; 28ppm , 250 sheet input tray upto 800 , 150sheets output , duty : 50000 pages per month - USB + parallel + UTP
LP-LE350D	R	Lexmark E350D , built-in auto duplex unit , grey ; 366 MHz processor , 32mb upto 160 , 1200/2400dpi ; 33ppm , 250 sheet input tray upto 800 , 150sheets output , 7.5sec warm-up time , duty : 80000 pages per month - USB + parallel
LP-LE352DN	N	Lexmark E352DN , built-in auto duplex unit + netwrk ready , grey ; 366 MHz processor , 32mb upto 160 , 1200/2400dpi ; 33ppm , 250 sheet input tray upto 800 , 150sheets output , 7.5sec warm-up time , duty : 80000 pages per month - USB + parallel + utp
LP-LE450DN	R	Lexmark E450DN , built-in auto duplex unit + netwrk ready , grey ; 400 MHz processor , 64mb upto 320 , 1200/2400dpi ; 33ppm , 250 sheet input tray upto 800 , 150sheets output , 7.5sec warm-up time , duty : 80000 pages per month - USB + parallel + utp
LP-LT640	R	Lexmark T640 ; 400 MHz processor , 64mb upto 576 , 1200/2400dpi ; 33ppm , 100+250 sheet input tray upto 3850 , 250sheets output tray upto 2750 , 6sec warm-up time , duty : 200000 pages per month - USB + parallel
LP-LT640N	R	Lexmark T640N , network ready ; 400 MHz processor , 64mb upto 576 , 1200/2400dpi ; 33ppm , 100+250 sheet input tray upto 3850 , 250sheets output tray upto 2750 , 6sec warm-up time , duty : 200000 pages per month - USB + parallel + UTP
LP-LT640DN	R	Lexmark T640DN , built-in auto duplex unit + network ready ; 400 MHz processor , 64mb upto 576 , 1200/2400dpi ; 33ppm , 100+250 sheet input tray upto 3850 , 250sheets output tray upto 2750 , 6sec warm-up time , duty : 200000 pages per month - USB + parallel + UTP
LP-LT640DTN	R	Lexmark T640DTN , built-in extra 500sheet input tray + auto duplex unit + network ready ; 400 MHz processor , 64mb upto 576 , 1200/2400dpi ; 33ppm , 100+250+500 sheet input tray upto 3850 , 250sheets output tray upto 2750 , 6sec warm-up time , duty : 200000 pages per month - USB + parallel + UTP
LP-LT642	R	Lexmark T642 ; 457 MHz processor , 64mb upto 576 , 1200/2400dpi ; 43ppm , 100+500 sheet input tray upto 4100 , 500sheets output tray upto 3000 , 8.5sec warm-up time , duty : 225000 pages per month - USB + parallel
LP-LT642N	R	Lexmark T642N , network ready ; 457 MHz processor , 128mb upto 640 , 1200/2400dpi ; 43ppm , 100+500 sheet input tray upto 4100 , 500sheets output tray upto 3000 , 8.5sec warm-up time , duty : 225000 pages per month - USB + parallel + UTP
LP-LT642TN	R	Lexmark T642TN , extra 500sheets input tray + network ready ; 457 MHz processor , 128mb upto 640 , 1200/2400dpi ; 43ppm , 100+500+500 sheet input tray upto 4100 , 500sheets output tray upto 3000 , 8.5sec warm-up time , duty : 225000 pages per month - USB + parallel + UTP
LP-LT642DTN	R	Lexmark T642DTN , built-in auto duplex unit + extra 500sheets input tray + network ready ; 457 MHz processor , 128mb upto 640 , 1200/2400dpi ; 43ppm , 100+500+500 sheet input tray upto 4100 , 500sheets output tray upto 3000 , 8.5sec warm-up time , duty : 225000 pages per month - USB + parallel + UTP
LP-LT644	R	Lexmark T644 ; 514 MHz processor , 128mb upto 640 , 1200/2400dpi ; 48ppm , 100+500 sheet input tray upto 4100 , 500sheets output tray upto 3000 , 8.5sec warm-up time , duty : 250000 pages per month - USB + parallel

LP-LT644N	R	Lexmark T644N , network ready ; 514 MHz processor , 128mb upto 640 , 1200/2400dpi ; 48ppm , 100+500 sheet input tray upto 4100 , 500sheets output tray upto 3000 , 8.5sec warm-up time , duty : 250000 pages per month - USB + parallel + UTP
LP-LT644TN	R	Lexmark T644TN , extra 500sheets input tray + network ready ; 514 MHz processor , 128mb upto 640 , 1200/2400dpi ; 48ppm , 100+500 sheet input tray upto 4100 , 500sheets output tray upto 3000 , 8.5sec warm-up time , duty : 250000 pages per month - USB + parallel + UTP
LP-LT644DTN	R	Lexmark T644DTN , built-in auto duplex unit + extra 500sheets input tray + network ready ; 514 MHz processor , 128mb upto 640 , 1200/2400dpi ; 48ppm , 100+500 sheet input tray upto 4100 , 500sheets output tray upto 3000 , 8.5sec warm-up time , duty : 250000 pages per month - USB + parallel + UTP
LP-LW840	R	Lexmark W840 ; 625 MHz processor , 256mb upto 768 , 1200/2400dpi ; 50ppm , 100+500+500 sheet input tray upto 5100 , 500sheets output tray upto 3800 , 6.8sec warm-up time , duty : 300000 pages per month - USB + parallel
LP-LW840N	R	Lexmark W840N , network ready ; 625 MHz processor , 256mb upto 768 , 1200/2400dpi ; 50ppm , 100+500+500 sheet input tray upto 5100 , 500sheets output tray upto 3800 , 6.8sec warm-up time , duty : 300000 pages per month - USB + parallel + UTP
LP-LW840DN	R	Lexmark W840DN , built-in auto duplex unit + network ready ; 625 MHz processor , 256mb upto 768 , 1200/2400dpi ; 50ppm , 100+500+500 sheet input tray upto 5100 , 500sheets output tray upto 3800 , 6.8sec warm-up time , duty : 300000 pages per month - USB + parallel + UTP
Lexmark A4 mono All-In-One for home		
LP-LoX340	N	Lexmark X340 mfp , black - Print-Scan-Copy-Fax , with 50s ADF : 150mhz processor , 64mb ram , 25ppm , 600/1200 dpi , 250s input tray upto 800 , 150s output , duty : 15000pages per month ; scan : 600x600dpi , 24bit ; standalone copy, , 25-400% ; as standalone fax with 33.6k modem, 10 speed dial - usb
LP-LoX342N	R	Lexmark X342N mfp , network ready , black - Print-Scan-Copy-Fax , with 50s ADF : 150mhz processor , 64mb ram , 25ppm , 600/1200 dpi , 250s input tray upto 800 , 150s output , duty : 15000pages per month ; scan : 600x600dpi , 24bit ; standalone copy, , 25-400% ; as standalone fax with 33.6k modem, 10 speed dial - usb+UTP
Lexmark A4 mono All-In-One for business		
LP-LoX642E	R	Lexmark X642E mfp , network ready with touch screen interface , black - Print-Scan-Copy-Fax , with 50s ADF : 514mhz processor , 128mb ram upto 640 , 43ppm , 1200/2400 dpi , 100+500s input tray upto 3100 , 500s output , duty : 200000pages per month ; scan : 600x600dpi , 24bit ; standalone copy, , 25-400% ; as standalone fax with 33.6k modem - usb+UTP
LP-LoX644E	R	Lexmark X644E mfp , network ready with touch screen interface , black - Print-Scan-Copy-Fax , with 50s ADF : 514mhz processor , 256mb ram upto 768 , 48ppm , 1200/2400 dpi , 100+500s input tray upto 3100 , 500s output , duty : 225000pages per month ; scan : 600x600dpi , 24bit ; standalone copy, , 25-400% ; as standalone fax with 33.6k modem - usb+UTP
LP-LoX646E	R	Lexmark X646E mfp , network ready with touch screen interface , scan unit hdd , black - Print-Scan-Copy-Fax , with 50s ADF : 514mhz processor , 256mb ram upto 768 , 48ppm , 1200/2400 dpi , 100+500s input tray upto 3100 , 500s output , duty : 225000pages per month ; scan : 600x600dpi , 24bit ; standalone copy, , 25-400% ; as standalone fax with 33.6k modem - usb+UTP

LP-LoX646DTE	R	Lexmark X646DTE mfp , built-in auto duplex unit + extra 500sheets input tray + network ready with touch screen interface , scan unit hdd , black - Print-Scan-Copy-Fax , with 50s ADF : 514mhz processor , 256mb ram upto 768 , 48ppm , 1200/2400 dpi , 100+500+500s input tray upto 3100 , 500s output , duty : 225000pages per month ; scan : 600x600dpi , 24bit ; standalone copy, , 25-400% ; as standalone fax with 33.6k modem - usb+UTP
LP-LoX646EF	R	Lexmark X646EF mfp , with advanced finishing , built-in auto duplex unit + extra 500sheets input tray + network ready with touch screen interface , scan unit hdd , black - Print-Scan-Copy-Fax , with 50s ADF : 514mhz processor , 256mb ram upto 640 , 48ppm , 1200/2400 dpi , 100+500+500s input tray upto 3100 , 500+750s output , duty : 225000pages per month ; scan : 600x600dpi , 24bit ; standalone copy, , 25-400% ; as standalone fax with 33.6k modem - usb+UTP
Lexmark A3 mono All-In-One for business		
LP-LoX850EVE3	R	Lexmark X850E VE3 mfp , A3, built-in auto duplex unit + network ready with touch screen interface , scan unit hdd , black - Print-Scan-Copy , with 75s ADF : 625mhz processor , 256mb ram upto 768 , 35ppm , 1200/2400 dpi , 100+500+500s input tray upto 5100 , 500s output upto 3800, duty : 150000pages per month ; scan : 600x600dpi , 24bit ; standalone copy, , 25-400% - parallel+usb+UTP
LP-LoX850EVE4	R	Lexmark X850E VE4 mfp , A3, built-in auto duplex unit + network ready with touch screen interface , scan unit hdd , black - Print-Scan-Copy-Fax , with 75s ADF : 625mhz processor , 256mb ram upto 768 , 35ppm , 1200/2400 dpi , 100+500+500s input tray upto 5100 , 500s output upto 3800, duty : 150000pages per month ; scan : 600x600dpi , 24bit ; standalone copy, , 25-400% ; as standalone fax with 33.6k modem - parallel+usb+UTP - parallel+usb+UTP
LP-LoX850E	R	Lexmark X850E mfp , A3 , built-in auto duplex unit + network ready with touch screen interface , scan unit hdd , black - Print-Scan-Copy-Fax , with 50s ADF : 625mhz processor , 256mb ram upto 768 , 35ppm , 1200/2400 dpi , 100+500+500+2000s input tray upto 5100 , 500s output upto 3800, duty : 150000pages per month ; scan : 600x600dpi , 24bit ; standalone copy, , 25-400% ; as standalone fax with 33.6k modem - parallel+usb+UTP
LP-LoX852E	R	Lexmark X852E mfp , A3 , built-in auto duplex unit + network ready with touch screen interface , scan unit hdd , black - Print-Scan-Copy-Fax , with 50s ADF : 625mhz processor , 256mb ram upto 768 , 45ppm , 1200/2400 dpi , 100+500+500+2000s input tray upto 5100 , 500s output upto 3800, duty : 200000pages per month ; scan : 600x600dpi , 24bit ; standalone copy, , 25-400% ; as standalone fax with 33.6k modem - parallel+usb+UTP
LP-LoX854E	R	Lexmark X854E mfp , A3 , built-in auto duplex unit + network ready with touch screen interface , scan unit hdd , black - Print-Scan-Copy-Fax , with 50s ADF : 625mhz processor , 256mb ram upto 768 , 55ppm , 1200/2400 dpi , 100+500+500+2000s input tray upto 5100 , 500s output upto 3800, duty : 200000pages per month ; scan : 600x600dpi , 24bit ; standalone copy, , 25-400% ; as standalone fax with 33.6k modem - usb+UTP
lexmark A4 color laser		
LP-LC500N	**N**	Lexmark C500N color laser , network ready ; 200 MHz RISC processor , 64mb , 600/1200dpi ; 31/8ppm , 250s input tray upto 780 , 250sheets output , duty : 35000pages per month - USB + UTP

LP-LC530DN	R	Lexmark C530DN color laser , built-in auto duplex unit + network ready ; 375 MHz RISC processor , 128mb upto 640 , 1200x1200/4800dpi ; 22/21ppm , 100+250s input tray , 250sheets output , duty : 65000pages per month - USB + UTP
LP-LC532N	N	Lexmark C532N color laser , network ready ; 375 MHz RISC processor , 64mb upto 640 , 1200x1200/4800dpi ; 22/21ppm , 250s input tray upto 800 , 250sheets output , duty : 75000pages per month - USB + UTP
LP-LC532DN	N	Lexmark C532DN color laser , built-in auto duplex unit + network ready ; 375 MHz RISC processor , 64mb upto 640 , 1200x1200/4800dpi ; 22/21ppm , 250s input tray upto 800 , 250sheets output , duty : 75000pages per month - USB + UTP
LP-LC534N	R	Lexmark C534N color laser , network ready ; 500 MHz RISC processor , 128mb upto 640 , 1200x1200/4800dpi ; 22/21ppm , 100+250s input tray upto 900 , 250sheets output , duty : 100000pages per month - USB + UTP
LP-LC534DN	R	Lexmark C534N color laser , built-in auto duplex unit + network ready ; 500 MHz RISC processor , 256mb upto 768 , 1200x1200/4800dpi ; 22/21ppm , 100+250s input tray upto 900 , 250sheets output , duty : 100000pages per month - USB + UTP
LP-LC534DTN	R	Lexmark C534N color laser , built-in auto duplex unit + extra 550sheets input tray + network ready ; 500 MHz RISC processor , 256mb upto 768 , 1200x1200/4800dpi ; 22/21ppm , 100+250+550s input tray , 250sheets output , duty : 100000pages per month - USB + UTP
LP-LC780N	R	Lexmark C780N color laser , network ready ; 800 MHz RISC processor , 256mb upto 768 , 1200x1200/4800dpi ; 33/29ppm , 100+500s input tray upto 1100 , 250sheets output , duty : 120000pages per month - USB + UTP
LP-LC780DN	R	Lexmark C780DN color laser , built-in auto duplex unit + network ready ; 800 MHz RISC processor , 256mb upto 768 , 1200x1200/4800dpi ; 33/29ppm , 100+500s input tray upto 1100 , 250sheets output , duty : 120000pages per month - USB + UTP
LP-LC780DTN	R	Lexmark C780DTN color laser , built-in auto duplex unit + extra 500sheets input tray + network ready ; 800 MHz RISC processor , 256mb upto 768 , 1200x1200/4800dpi ; 33/29ppm , 100+500+500s input tray , 250sheets output , duty : 120000pages per month - USB + UTP
LP-LC782N	R	Lexmark C782N color laser , network ready , support finishing + MFP option ; 800 MHz RISC processor , 256mb upto 768 , 1200x1200/4800dpi ; 38/33ppm , 100+500s input tray upto 3100 , 250sheets output upto 900 , duty : 150000pages per month - USB + UTP
LP-LC782DN	R	Lexmark C782DN color laser , built-in auto duplex unit + network ready , support finishing + MFP option ; 800 MHz RISC processor , 256mb upto 768 , 1200x1200/4800dpi ; 38/33ppm , 100+500s input tray upto 3100 , 250sheets output upto 900 , duty : 150000pages per month - USB + UTP
LP-LC782DTN	R	Lexmark C782DTN color laser , built-in auto duplex unit + extra 500sheets input tray + network ready , support finishing + MFP option ; 800 MHz RISC processor , 256mb upto 768 , 1200x1200/4800dpi ; 38/33ppm , 100+500+500s input tray upto 3100 , 250sheets output upto 900 , duty : 150000pages per month - USB + UTP

lexmark A3 color laser

LP-LC935DN	R	Lexmark C935DN color laser , A3 , built-in auto duplex unit + network ready , support finishing + MFP option ; 1.25GHz RISC processor , 256mb upto 1024 , 2400dpi ; 45/40ppm , 100+520s input tray upto 3140 , 400sheets output upto 3500 , duty : 200000pages per month - USB + UTP
LP-LC935DTN	R	Lexmark C935DTN color laser , A3 , built-in auto duplex unit + extra 520sheets input drawer stand with cabinet + network ready , support finishing + MFP option ; 1.25GHz RISC processor , 512mb upto 1024 , 2400dpi ; 45/40ppm , 100+520+520s input tray upto 3140 , 400sheets output upto 3500 , duty : 200000pages per month - USB + UTP
LP-LC935HDN	R	Lexmark C935HDN color laser , A3 , built-in auto duplex unit + extra 3x520sheets input drawer stand with cabinet + network ready , support finishing + MFP option ; 1.25GHz RISC processor , 512mb upto 1024 , 2400dpi ; 45/40ppm , 100+520+520+520+520s input tray upto 3140 , 400sheets output upto 3500 , duty : 200000pages per month - USB + UTP
Lexmark A4 color all-in-one		
LP-LCoX500N		Lexmark Color O-in-1 X500N , network ready - Print-Scan-Copy , flatbed , with 35s ADF : 366 MHz processor , 128mb ram , 31/8ppm , 250s input tray upto 780 , 250s output , duty : 35000pages per month , scan : 1200x1200/19200dpi , 24bit ; standalone copy , 25-400% - usb+utp
LP-LCoX502N	N	Lexmark Color O-in-1 X502N , network ready - Print-Scan-Copy-Fax , flatbed , with 35s ADF : 366 MHz processor , 128mb ram , 31/8ppm , 250s input tray upto 780 , 250s output , duty : 35000pages per month , scan : 1200x1200/19200dpi , 24bit ; standalone copy , 25-400% ; as standalone fax with 33.6k modem , 70 speed dial - usb+utp
LP-LCoX560N	R	Lexmark Color O-in-1 X560N , network ready - Print-Scan-Copy-Fax , flatbed , with 50s ADF : 400 MHz processor , 384mb ram upto 1408, 31/20ppm , 150+250s input tray upto 950 , 350s output , duty : 60000pages per month , scan : 1200x1200/19200dpi , 24bit ; standalone copy , 25-400% ; as standalone fax with 33.6k modem , speed dial - usb+utp
LP-LCoX560DN	R	Lexmark Color O-in-1 X560DN , built-in auto duplex unit + network ready - Print-Scan-Copy-Fax , flatbed , with 50s ADF : 400 MHz processor , 384mb ram upto 1408, 31/20ppm , 150+250s input tray upto 950 , 350s output , duty : 60000pages per month , scan : 1200x1200/19200dpi , 24bit ; standalone copy , 25-400% ; as standalone fax with 33.6k modem , speed dial - usb+utp
LP-LCoX782E	R	Lexmark Color O-in-1 X782E , built-in auto duplex unit + network ready - Print-Scan-Copy-Fax , flatbed , with 50s ADF : 800 MHz processor , 768mb ram , 38/33ppm , 100+500+500+500s input tray , 250s output , duty : 150000pages per month , scan : 1200x1200/19200dpi , 24bit ; standalone copy , 25-400% ; as standalone fax with 33.6k modem , speed dial - usb+utp
Lexmark A3 color all-in-one		
LP-LCoX940E	R	Lexmark Color O-in-1 X940E , A3 , built-in auto duplex unit + network ready - Print-Scan-Copy-Fax , flatbed , with 75s ADF : 1250 MHz processor , 512mb ram upto 1024 , 80gb hdd , 40/30ppm , 100+520+520s input tray , 400s output upto 3500 , duty : 150000pages per month , scan : 1200x1200/19200dpi , 24bit ; standalone copy , 25-400% ; as standalone fax with 33.6k modem , speed dial - usb+utp

LP-LCoX945E	R	Lexmark Color O-in-1 X945E , A3 , built-in auto duplex unit + network ready - Print-Scan-Copy-Fax , flatbed , with 75s ADF : 1250 MHz processor , 512mb ram upto 1024 , 80gb hdd , 45/40ppm , 100+520+2520s input tray , 400s output upto 3500 , duty : 200000pages per month , scan : 1200x1200/19200dpi , 24bit ; standalone copy , 25-400% ; as standalone fax with 33.6k modem , speed dial - usb+utp

lexmark accessories		
LP-LA28S0803	R	Lexmark 0028S0803 550s A4 input tray for lexmark E34x series , E35x series , E45x series
LP-LA20G0887	R	Lexmark 0020G0887 250s A4 duplex unit for lexmark T630, T640 - optional furniture is required if more than 750 sheet input tray
LP-LA25A0015	R	Lexmark 0025A0015 A4 duplex unit for lexmark w840 series
LP-LA20G0888	R	Lexmark 0020G0888 A4 500sheets duplex unit for lexmark T642, T644 series
LP-LA20B2400	R	Lexmark 0020B2400 A4 duplex unit for lexmark C770, C772, C780, C782 series
LP-LA14A1121	R	Lexmark 0014A1121 A4 duplex unit for lexmark X560 series
LP-LA20G0889	R	Lexmark 0020G0889 250s A4 drawer for lexmark T630, T640, X644, X646 series - optional furniture is required if more than 750 sheet input tray
LP-LA20B2300	R	Lexmark 0020B2300 500s A4 drawer - for lexmark C770, C772 , C78x series
LP-LA20B2700	R	Lexmark 0020B2700 2000s A4 feeder - for lexmark C770, C772 , C78x series
LP-LA14A1120	R	Lexmark 0014A1120 550s A4 drawer with stand - for lexmark x560 series
LP-LA20G1224	R	Lexmark 0020G1224 250s (3"x5" - A4) UAT (universally adjustable tray) for lexmark T630, T640, X644, X646 series - optional furniture is required if more than 750 sheet input tray
LP-LA20G0890	R	Lexmark 0020G0890 500s A4 drawer for lexmark T630, T640, X644, X646 series - optional furniture is required if more than 750 sheet input tray
LP-LA20G0879	R	Lexmark 0020G0879 250s A4 input tray for lexmark T640, X644, X646 series
LP-LA22R0194	R	Lexmark 0022R0194 530s A4 input tray for lexmark C500 series
LP-LA36B1600	R	Lexmark 0036B1600 550s A4 input tray for lexmark C532 , C534 series
LP-LA20G0893	R	Lexmark 0020G0893 2000s A4 high capacity feeder for lexmark T630, T640, X644, X646 series - optional furniture is required if more than 750 sheet input tray
LP-LA15R0145	R	Lexmark 0015R0145 2000s A4 high capacity feeder for lexmark W840, X850e series
LP-LA15R0146	R	Lexmark 0015R0146 2 x 500s drawer for lexmark W840 series, X850e VE3
LP-LA15R0120	R	Lexmark 0015R0120 2000s A4 dual input tray for lexmark w840 series, X850e VE3
LP-LA20G1223	R	Lexmark 0020G1223 250s (3"x5" - A4) UAT (universally adjustable tray) with drawer for lexmark T630, T640, X644, X646 series - optional furniture is required if more than 750 sheet input tray
LP-LA20G1218	R	Lexmark 0020G1218 400s (3"x5" - A4) UAT (universally adjustable tray) with drawer for lexmark T630, T640, X644, X646 series - optional furniture is required if more than 750 sheet input tray
LP-LA20G0891	R	Lexmark 0020G0891 85s envelope feeder for lexmark T640, X644, X646 series
LP-LA20G0894	R	Lexmark 0020G0894 650s output expander for lexmark T630, T640, X644, X646 series - support upto 3 expander at one time

LP-LA20G0895	R	Lexmark 0020G0895 5-bin mailbox for lexmark T63x, T64x
LP-LA20G0896	R	Lexmark 0020G0896 1850 sheets output stacker for lexmark T63x, T64x

HP

HP A4 mono - for home & home office

LP-HP1005		HP CB410A laserjet P1005 ; 266 MHz processor , 2mb ram , 600/1200dpi ; 14ppm , HP FastRes and REt , 150s input tray , 100sheets output , no warm-up time , duty : 5000 pages per month - USB
LP-HP1006		HP CB411A laserjet P1006 ; 266 MHz processor , 8mb ram , 600/1200dpi ; 16ppm , HP FastRes and REt , 150+10s input tray , 100sheets output , no warm-up time , duty : 5000 pages per month - USB
LP-HP1505		HP CB412A laserjet P1505 ; 266 MHz RISC processor , 8mb ram , 600/1200dpi ; 24ppm , HP FastRes and REt , 250+10s input tray , 150sheets output , no warm-up time , duty : 8000pages per month - USB
LP-HP1505N		HP CB413A laserjet P1505N with network ready ; 266 MHz RISC processor , 8mb ram , 600/1200dpi ; 24ppm , HP FastRes and REt , 250+10s input tray , 150sheets output , no warm-up time , duty : 8000pages per month - USB+UTP

HP A4 mono - for SMB

LP-HP2035	N	HP CE461A laserjet P2035 ; 266MHz risc processor , 16mb , 1200/1200dpi ; 30ppm , 50+250s input tray , 150sheets output , 8sec instant-on from powersave mode , duty : 25000pages per month - USB+parallel
LP-HP2015D		HP CB367A laserjet P2015D with auto duplex printing unit ; 400MHz Motorola V5 Coldfire processor , 32mb ram upto 288 , 1200/1200dpi ; 26ppm , 50+250s input tray upto 550 , 125sheets output , 8.5s instant-on from powersave mode , duty : 15000pages per month - USB
LP-HP2015DN		HP CB368A laserjet P2015DN with auto duplex printing unit + built-in network ; 400MHz Motorola V5 Coldfire processor , 32mb ram upto 288 , 1200/1200dpi ; 26ppm , 50+250s input tray upto 550 , 125sheets output , 8.5s instant-on from powersave mode , duty : 15000pages per month - USB+UTP
LP-HP2055D	N	HP CE457A laserjet P2055D with auto duplex printing unit ; 600MHz risc processor , 128mb ram upto 384 , 1200/1200dpi ; 35ppm , 50+250s input tray upto 850 , 125sheets output , 8sec instant-on from powersave mode , duty : 50000pages per month - USB+UTP
LP-HP2055DN	N	HP CE459A laserjet P2055DN with auto duplex printing unit + built-in network ; 600MHz risc processor , 128mb ram upto 384 , 1200/1200dpi ; 35ppm , 50+250s input tray upto 850 , 125sheets output , 8sec instant-on from powersave mode , duty : 50000pages per month - USB+UTP
LP-HP3005		HP Q7812A laserjet P3005 ; 400MHz Motorola V5 Coldfire processor , 48mb ram upto 320 , 1200/1200dpi ; 33ppm , 100+500s input tray upto 1100 , 250 sheets output , 9.5s instant-on from powersave mode , duty : 100000pages per month - USB+Parallel
LP-HP3005D	R	HP Q7813A laserjet P3005D with auto duplex printing unit ; 400MHz Motorola V5 Coldfire processor , 64mb ram upto 320 , 1200/1200dpi ; 33ppm , 100+500s input tray upto 1100 , 250 sheets output , 9.5s instant-on from powersave mode , duty : 100000pages per month - USB+Parallel

LP-HP3005N		HP Q7814A laserjet P3005N with built-in network ; 400MHz Motorola V5 Coldfire processor , 80mb ram upto 320 , 1200/1200dpi ; 33ppm , 100+500s input tray upto 1100 , 250 sheets output , 9.5s instant-on from powersave mode , duty : 100000pages per month - USB+Parallel
LP-HP3005DN		HP Q7815A laserjet P3005DN with auto duplex printing + unit built-in network ; 400MHz Motorola V5 Coldfire processor , 80mb ram upto 320 , 1200/1200dpi ; 33ppm , 100+500s input tray upto 1100 , 250 sheets output , 9.5s instant-on from powersave mode , duty : 100000pages per month - USB+Parallel
LP-HP3005X	N	HP Q7816A laserjet P3005X with auto duplex printing + unit built-in network + extra inout tray ; 400MHz Motorola V5 Coldfire processor , 48mb ram upto 320 , 1200/1200dpi ; 33ppm , 100+500+500s input tray , 250 sheets output , 9.5s instant-on from powersave mode , duty : 100000pages per month - USB+Parallel
HP A4 mono - workgroup		
LP-HP4014	R	HP CB506A laserjet P4014 ; 540mhz Motorola ColdFire® V5e processor , 96mb DDR2 upto 608 , 1200/1200dpi ; 43ppm , 600 (100+500)s input tray upto 3600 , 600 (500+100)s output (support optional stacker , stapler/stacker , 5-bin mailbox) , upto 800 , duty : 175000pages per month , auto duplex printing unit optional - USB + EiO
LP-HP4014N	R	HP CB507A laserjet P4014N , gigabit network ready ; 540mhz Motorola ColdFire® V5e processor , 128mb DDR2 upto 640 , 1200/1200dpi ; 43ppm , 600 (100+500)s input tray upto 3600 , 600 (500+100)s output (support optional stacker , stapler/stacker , 5-bin mailbox) , upto 800 , duty : 175000pages per month , auto duplex printing unit optional - USB + UTP + EiO
LP-HP4014DN	R	HP CB512A laserjet P4014DN , gigabit network ready + auto duplex printing unit ; 540mhz Motorola ColdFire® V5e processor , 128mb DDR2 upto 640 , 1200/1200dpi ; 43ppm , 600 (100+500)s input tray upto 3600 , 600 (500+100)s output (support optional stacker , stapler/stacker , 5-bin mailbox) , upto 800 , duty : 175000pages per month - USB + UTP + EiO
LP-HP4015N		HP CB509A laserjet P4015N , gigabit network ready ; 540mhz Motorola ColdFire® V5e processor , 128mb DDR2 upto 640 , 1200/1200dpi ; 50ppm , 600 (100+500)s input tray upto 3600 , 600 (500+100)s output (support optional stacker , stapler/stacker , 5-bin mailbox) , upto 800 , duty : 225000pages per month , auto duplex printing unit optional - USB + UTP + EiO
LP-HP4015TN	R	HP CB510A laserjet P4015TN , gigabit network ready , with extra input tray3 ; 540mhz Motorola ColdFire® V5e processor , 128mb DDR2 upto 640 , 1200/1200dpi ; 50ppm , 1100 (100+500+500)s input tray upto 3600 , 600 (500+100)s output (support optional stacker , stapler/stacker , 5-bin mailbox) , upto 800 , duty : 225000pages per month , auto duplex printing unit optional - USB + UTP + EiO
LP-HP4015DN	R	HP CB526A laserjet P4015DN , gigabit network ready + auto duplex printing unit ; 540mhz Motorola ColdFire® V5e processor , 128mb DDR2 upto 640 , 1200/1200dpi ; 50ppm , 1100 (100+500+500)s input tray upto 3600 , 600 (500+100)s output (support optional stacker , stapler/stacker , 5-bin mailbox) , upto 800 , duty : 225000pages per month - USB + UTP + EiO

LP-HP4015X	R	HP CB511A laserjet P4015TN , gigabit network ready , with extra input tray3 + auto duplex printing unit ; 540mhz Motorola ColdFire® V5e processor , 128mb DDR2 upto 640 , 1200/1200dpi ; 50ppm , 1100 (100+500+500)s input tray upto 3600 , 600 (500+100)s output (support optional stacker , stapler/stacker , 5-bin mailbox) , upto 800 , duty : 225000pages per month - USB + UTP + EiO
LP-HP4515N	R	HP CB514A laserjet P4515N , gigabit network ready ; 540mhz Motorola ColdFire® V5e processor , 128mb DDR2 upto 640 , 1200/1200dpi ; 60ppm , 600 (100+500)s input tray upto 3600 , 600 (500+100)s output (support optional stacker , stapler/stacker , 5-bin mailbox) , upto 800 , duty : 275000pages per month , auto duplex printing unit optional - USB + UTP + EiO
LP-HP4515TN	R	HP CB515A laserjet P4515TN , gigabit network ready , with extra input tray3 ; 540mhz Motorola ColdFire® V5e processor , 128mb DDR2 upto 640 , 1200/1200dpi ; 60ppm , 1100 (100+500+500)s input tray upto 3600 , 600 (500+100)s output (support optional stacker , stapler/stacker , 5-bin mailbox) , upto 800 , duty : 275000pages per month , auto duplex printing unit optional - USB + UTP + EiO
LP-HP4515X	R	HP CB516A laserjet P4515X , gigabit network ready , with extra input tray3 + auto duplex printing unit ; 540mhz Motorola ColdFire® V5e processor , 128mb DDR2 upto 640 , 1200/1200dpi ; 60ppm , 1100 (100+500+500)s input tray upto 3600 , 600 (500+100)s output (support optional stacker , stapler/stacker , 5-bin mailbox) , upto 800 , duty : 275000pages per month - USB + UTP + EiO
LP-HP4515XM	R	HP CB517A laserjet P4515XM , gigabit network ready , with extra input tray3 + auto duplex printing unit + 500-sheet 5-bin mailbox ; 540mhz Motorola ColdFire® V5e processor , 128mb DDR2 upto 640 , 1200/1200dpi ; 60ppm , 1100 (100+500+500)s input tray upto 3600 , 1100 (500+500+100)s output (support optional stacker , stapler/stacker) , upto 800 , duty : 275000pages per month - USB + UTP + EiO
HP A3+ mono - workgroup		
LP-H5200	R	HP Q7543A A3+ laserjet 5200 ; 460 MHz MiPS processor , 48mb upto 512 , 1200/1200dpi ; a4/a3: 35/18.5ppm , 350s (100+250) input tray upto 850 , 250s output , duty : 65000pages per month , auto duplex printing unit optional - 2 x CF slot + USB + Parallel + EiO
LP-H5200TN	R	HP Q7545A A3+ laserjet 5200TN , network ready ; 460 MHz MiPS processor , 64mb upto 512 , 1200/1200dpi ; a4/a3: 35/18.5ppm , 850s (100+250+500) input tray , 250s output , duty : 65000pages per month , auto duplex printing unit optional - 2 x CF slot + USB + Parallel + EiO + UTP
LP-H5200DTN	R	HP Q7546A A3+ laserjet 5200DTN , include auto-duplex unit + network ready ; 460 MHz MiPS processor , 128mb upto 512 , 1200/1200dpi ; a4/a3: 35/18.5ppm , 850s (100+250+500) input tray , 250s output , duty : 65000pages per month - 2 x CF slot + USB + Parallel + EiO + UTP
LP-H9040	R	HP Q7697A A3 laserjet 9040 ; 533 MHz 20Kc MIPS processor , 64mb ddr upto 512 , 600/1200dpi ; a4/a3 : 40/26ppm , 1000 (500+500)s input tray upto 3100 , 600 (500+100)s output upto 3600 , duty : 300000pages per month , auto duplex printing unit optional - Parallel , 2 x EiO

LP-H9040N	R	HP Q7698A A3 laserjet 9040N with network ready ; 533 MHz 20Kc MIPS processor , 128mb ddr upto 512 , 600/1200dpi ; a4/a3 : 40/26ppm , 1100 (100+500+500)s input tray upto 3100 , 600 (500+100)s output upto 3600 , duty : 300000pages per month , auto duplex printing unit optional - Parallel , 2 x EiO
LP-H9040DN	R	HP Q7699A A3 laserjet 9040N with auto duplex printing unit , network ready ; 533 MHz 20Kc MIPS processor , 128mb ddr upto 512 , 600/1200dpi ; a4/a3 : 40/26ppm , 1100 (100+500+500)s input tray upto 3100 , 600 (500+100)s output upto 3600 , duty : 300000pages per month , auto duplex printing unit optional - Parallel , 2 x EiO
LP-H9050N	R	HP Q3722A A3 laserjet 9050N with network ready ; 533 MHz 20Kc MIPS processor , 128mb ddr upto 512 , 600/1200dpi ; a4/a3 : 50/28ppm , 1100 (100+500+500)s input tray upto 3100 , 600 (500+100)s output upto 3600 , duty : 300000pages per month , auto duplex printing unit optional - Parallel , 2 x EiO
LP-H9050DN	R	HP Q3723A A3 laserjet 9050DN with auto duplex printing unit , network ready ; 533 MHz 20Kc MIPS processor , 128mb ddr upto 512 , 600/1200dpi ; a4/a3 : 50/28ppm , 1100 (100+500+500)s input tray upto 3100 , 600 (500+100)s output upto 3600 , duty : 300000pages per month , auto duplex printing unit optional - Parallel , 2 x EiO

HP A4 mono All-In-One for home

LP-HoM1120	HP CB537A laserjet M1120 - Print-Scan-Copy , flatbed : Tensilica 230mhz , 32mb ram , 19ppm , 600/1200dpi , 260 (250+10)s input tray , 125s output , duty : 8000pages per month ; scan : 1200x1200/19200dpi , 24bit ; standalone copy , 99 mutiple copies , 25-400% - usb
LP-HoM1120N	HP CC459A laserjet M1120DN - Print-Scan-Copy , network ready : Tensilica 230mhz , 32mb ram , 19ppm , 600/1200dpi , 260 (250+10)s input tray , 125s output , duty : 8000pages per month ; scan : 1200x1200/19200dpi , 24bit ; standalone copy , 99 mutiple copies , 25-400% - usb + UTP
LP-HoM1319F	HP CB536A laserjet M1319F mfp - Print-Scan-Copy-Fax , sheet feed (non-flatbed) , with 30s ADF : 240mhz processor , 32mb ram , 19ppm , 600/1200 dpi , 260 (250+10)s input tray , 100s output , duty : 8000pages per month ; scan : 600x600/19200dpi , 24bit ; standalone copy, 99 mutiple copies, 25-400% ; as standalone fax with 33.6k modem, 500pages fax memory, 119 speed dial - usb
LP-HoM1522N	HP CC372A laserjet M1522N - Print-Scan-Copy , flatbed , with 50s ADF , network ready : 450mhz motorola Coldfire® v 5e , 64mb ram , 23ppm , 600/1200 dpi , 10+250s input tray , 125s output , duty : 8000pages per month ; scan : 1200x1200/19200dpi , 24bit ; standalone copy , 99 mutiple copies , 25-400% - usb + UTP
LP-HoM1522NF	HP CB534A laserjet M1522NF - Print-Scan-Copy-Fax , flatbed , with 50s ADF , network ready : 450mhz motorola Coldfire® v 5e , 64mb ram , 23ppm , 600/1200 dpi , 10+250s input tray , 125s output , duty : 8000pages per month ; scan : 1200x1200/19200dpi , 24bit ; standalone copy , 99 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , 300pages fax memory , 119 speed dial - usb + UTP

LP-HoM2727NF		HP CB532A laserjet M2727NF - Print-Scan-Copy-Fax , flatbed , with 50s ADF + auto-duplex unit , network ready : 450mhz motorola Coldfire® v 5e , 64mb ram upto 320 , 26ppm , 600/1200 dpi , 50+250s input tray upto 550 , 125s output , duty : 15000pages per month ; scan : 1200x1200/19200dpi , 24bit ; standalone copy , 99 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , 600pages fax memory , 119 speed dial - usb + UTP
LP-HoM2727NFS		HP CB533A laserjet M2727NFS - Print-Scan-Copy-Fax with Stapler , flatbed , with 50s ADF + auto-duplex unit , network ready : 450mhz motorola Coldfire® v 5e , 64mb ram upto 320 , 26ppm , 600/1200 dpi , 50+250s input tray upto 550 , 125s output , duty : 15000pages per month ; scan : 1200x1200/19200dpi , 24bit ; standalone copy , 99 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , 600pages fax memory , 119 speed dial - usb + UTP
HP A4 mono All-In-One for workgroup		
LP-HoM3027	R	HP CB416A laserjet M3027 MFP - Print-Scan-Copy , with 50 sheets ADF (duplex + reversing scanning) , network ready : 400 MHz RISC processor , 256mb upto 512 + 40gb EiO hdd , 27ppm, 1200/1200 dpi, 600 (100+500)s input tray upto 1100, 250s outputtry , duty: 75000 pages per month; scan: 600x600/9600dpi, scan to email; standalone copy, 1000 mutiple copies, 25-400%, auto duplex printing unit optional- parallel + EiO + UTP
LP-HoM3027X	N	HP CB417A laserjet M3027 MFP - Print-Scan-Copy-Fax , auto duplex printing unit , support double sided copying , with 50 sheets ADF (duplex + reversing scanning) , network ready : 400 MHz RISC processor , 256mb upto 512 + 40gb EiO hdd , 27ppm, 1200/1200 dpi, 600 (100+500)s input tray upto 1100, 250s outputtry , duty: 75000 pages per month; scan: 600x600/9600dpi, scan to email; standalone copy, 1000 mutiple copies, 25-400% - parallel + EiO + UTP
LP-HoM3035	R	HP CB414A laserjet M3035 MFP - Print-Scan-Copy , auto duplex printing unit , support double sided copying , with 50 sheets ADF (duplex + reversing scanning) , network ready : 400 MHz RISC processor , 256mb upto 512 + 40gb EiO hdd , 35ppm, 1200/1200 dpi, 600 (100+500)s input tray upto 1100, 250s outputtry , duty: 75000 pages per month; scan: 600x600/9600dpi, scan to email; standalone copy, 35cpm, 1000 mutiple copies, 25-400% - parallel + EiO + UTP
LP-HoM3035XS	R	HP CB415A laserjet M3035 MFP - Print-Scan-Copy-Fax , with 20-sheet convenience stapler , auto duplex printing unit , support double sided copying , with 50 sheets ADF (duplex + reversing scanning), network ready : 400 MHz RISC processor , 256mb upto 512 + 40gb EiO hdd , 35ppm, 1200/1200 dpi, 600 (100+500+500)s input tray , 250s outputtry , duty: 75000 pages per month; scan: 600x600/9600dpi, scan to email; standalone copy, 35cpm, 1000 mutiple copies, 25-400% - parallel + EiO + UTP
LP-HoM4345	R	HP CB425A laserjet M4345 MFP - Print-Scan-Copy , with 50 sheets ADF (duplex + reversing scanning) , network ready : 480 MHz RISC processor , 256mb upto 512 + 40gb EiO hdd , 45ppm, 1200/1200 dpi, 600 (100+500)s input tray upto 2100, 500s output upto 700, duty: 200k pages per month; scan: 600x600/9600dpi, scan to email; standalone copy, 43cpm, 1000 mutiple copies, 25-400%, auto duplex printing unit optional , fax module optional - USB + EiO + UTP

LP-HoM4345X	R	HP CB426A laserjet M4345X MFP - Print-Scan-Copy-Fax , with 50 sheets ADF (duplex + reversing scanning) , extra input tray , auto duplex printing unit , support double sided copying , network ready : 480 MHz RISC microprocessor , 256mb upto 512 + 40gb EiO hdd , 45ppm , 1200/1200 dpi , 1100 (100+500+500)s input tray upto 2100 , 500s output upto 700 , duty : 200000pages per month ; scan : 600x600/9600dpi , scan to email ; standalone copy , 43cpm , 1000 mutiple copies , 25-400% - USB + EiO + UTP
LP-HoM4345XS	R	HP CB427A laserjet M4345XS MFP - Print-Scan-Copy-Fax , with MFP stand + storage cabinet , with stacker/stapler, with 50 sheets ADF (duplex + reversing scanning) , extra input tray , auto duplex printing unit , support double sided copying , network ready : 480 MHz RISC microprocessor , 256mb upto 512 + 40gb EiO hdd , 45ppm , 1200/1200 dpi , 1100 (100+500+500)s input tray upto 2100 , 530(500+30)s output with stapler/stacker , duty : 200000pages per month ; scan : 600x600/9600dpi , scan to email ; standalone copy , 43cpm , 1000 mutiple copies , 25-400% - USB + EiO + UTP
LP-HoM4345XM	R	HP CB428A laserjet M4345XM MFP - Print-Scan-Copy-Fax , with MFP stand + storage cabinet , with 3bin-mailbox stacker, with 50 sheets ADF (duplex + reversing scanning) , extra input tray , auto duplex printing unit , support double sided copying , network ready : 480 MHz RISC microprocessor , 256mb upto 512 + 40gb EiO hdd , 45ppm , 1200/1200 dpi , 1100 (100+500+500)s input tray upto 2100 , 700(500+100+100)s output , duty : 200000pages per month ; scan : 600x600/9600dpi , scan to email ; standalone copy , 43cpm , 1000 mutiple copies , 25-400% - USB + EiO + UTP
HP A3 mono All-In-One for workgroup		
LP-HoM5025	R	HP Q7840A laserjet M5025 MFP A3 - Print-Scan-Copy , with 50 sheets ADF (duplex + reversing scanning) , network ready : 460 MHz RISC processor , 256mb upto 512 + 40gb EiO hdd , 25ppm, 1200/1200 dpi, 600 (100+250+250)s input tray upto 2100, 250s output tray , duty: 200k pages per month; scan: 600x600/9600dpi, scan to email; standalone copy , 1000 mutiple copies, 25-400%, auto duplex printing unit optional , fax module optional - USB + EiO + UTP
LP-HoM5035	R	HP Q7829A laserjet M5035 MFP A3 - Print-Scan-Copy , with 50 sheets ADF (duplex + reversing scanning) , network ready : 460 MHz RISC processor , 256mb upto 512 + 40gb EiO hdd , 35ppm, 1200/1200 dpi, 600 (100+250+250)s input tray upto 2100, 250s output tray , duty: 200k pages per month; scan: 600x600/9600dpi, scan to email; standalone copy , 1000 mutiple copies, 25-400%, auto duplex printing unit optional- USB + EiO + UTP
LP-HoM5035X	R	HP Q7830A laserjet M5035X MFP A3 - Print-Scan-Copy-FAX , with extra input tray + built-in stand / storage cabinet , auto duplex printing unit , support double sided copying , with 50 sheets ADF (duplex + reversing scanning) , network ready : 460 MHz RISC processor , 256mb upto 512 + 40gb EiO hdd , 35ppm, 1200/1200 dpi, 1100 (100+250+250+500)s input tray upto 2100, 250s output tray , duty: 200k pages per month; scan: 600x600/9600dpi, scan to email; standalone copy , 1000 mutiple copies, 25-400% - USB + EiO + UTP

LP-HoM5035XS	R	HP Q7831A laserjet M5035XS MFP A3 - Print-Scan-Copy-FAX , with extra input tray + built-in stand / storage cabinet , auto duplex printing unit , support double sided copying , with 50 sheets ADF (duplex + reversing scanning) , network ready : 460 MHz RISC processor , 256mb upto 512 + 40gb EiO hdd , 35ppm, 1200/1200 dpi, 2100 (100+250+250+500+500+500)s input tray upto 2100, 750 (250+500)s output tray with 30-sheet automatic stapler/stacker , duty: 200k pages per month; scan: 600x600/9600dpi, scan to email; standalone copy , 1000 mutiple copies, 25-400% - USB + EiO + UTP
LP-HoM9040	R	HP CC394A laserjet M9040MFP A3 - Print-Scan-Copy-FAX + built-in stand / storage cabinet, auto duplex printing unit , support double sided copying , with 100 sheets ADF (duplex + reversing scanning) , network ready : 533 MHz MiPS processor , 384mb upto 512 , 40ppm, 600/600 dpi , 3100 (100+250+250+500+500+500)s input tray , duty: 300k pages per month; scan: 600x600/9600dpi, scan to email; standalone copy , 999 mutiple copies, 25-400% - USB + EiO + UTP - require optional output tray upto 3100 sheets
LP-HoM9050	R	HP CC395A laserjet M9050MFP A3 - Print-Scan-Copy-FAX + built-in stand / storage cabinet, auto duplex printing unit , support double sided copying , with 100 sheets ADF (duplex + reversing scanning) , network ready : 533 MHz MiPS processor , 384mb upto 512 , 50ppm, 600/600 dpi , 3100 (100+250+250+500+500+500)s input tray , duty: 300k pages per month; scan: 600x600/9600dpi, scan to email; standalone copy , 999 mutiple copies, 25-400% - USB + EiO + UTP - require optional output tray upto 3100 sheets
HP A4 color		
LP-HCCP1215	**N**	HP CC376A color laserjet CP1215 ; 264 MHz Custom RISC processor , 16mb , 600/600dpi ; 8/12ppm , HP Imageret 2400 , 150s input tray , 125sheets output , duty : 25000pages per month - USB
LP-HCCP1515N		HP CC377A color laserjet CP1515N , network ready ; 450 MHz Motorola Coldfire® V5x processor , 96mb upto 352 , 600/600dpi ; 8/12ppm , HP Imageret 3600 , 150s input tray , 125sheets output , duty : 30000pages per month - USB + UTP
LP-HCCP2025N		HP CB494A color laserjet CP2025N , network ready ; 540 MHz Motorola Coldfire® V5x processor , 128mb upto 384 , 600/600dpi ; 20/20ppm , HP Imageret 3600 , 50+250s input tray upto 550 , 150 sheets output , duty : 40000pages per month - USB + UTP
LP-HCCP2025DN	**N**	HP CB495A color laserjet CP2025dN , with auto-duplex printing unit + network ready ; 540 MHz Motorola Coldfire® V5x processor , 128mb upto 384 , 600/600dpi ; 20/20ppm , HP Imageret 3600 , 50+250s input tray upto 550 , 150 sheets output , duty : 40000pages per month - USB + UTP
LP-HC2605DTN		HP Q7823A color laserjet 2605DTN with auto-duplex printing unit + network ready ; 300 MHz Freescale Coldfire V5e processor , 64mb upto 320mb , 600/600dpi ; 12/10ppm , HP Imageret 2400 , 250+250s input tray , 125sheets output , duty : 35000pages per month - USB+UTP
LP-HCCP3525N		HP CC469A color laserjet CP3525N network ready ; 515 MHz processor Motorola Coldfire , 256mb upto 1024 ; 30ppm , HP Imageret 3600 , 350 (100+250)s input tray upto 850 , 250s output , duty : 75000pages per month , auto duplex printing unit optional - USB + UTP + EiO

LP-HCCP3525DN		HP CC470A color laserjet CP3525DN , with auto-duplex printing unit + network ready ; 515 MHz processor Motorola Coldfire , 384mb upto 1024 ; 30ppm , HP Imageret 3600 , 350 (100+250)s input tray upto 850 , 250s output , duty : 75000pages per month - USB + UTP + EiO
LP-HCCP3525X	R	HP CC471A color laserjet CP3525X , with extra 500sheet+postcard input tray + auto-duplex printing unit + network ready ; 515 MHz processor Motorola Coldfire , 512mb upto 1024 ; 30ppm , HP Imageret 3600 , 350 (100+250)s input tray upto 850 , 250s output , duty : 75000pages per month - USB + UTP + EiO
HP A4 color - workgroup		
LP-HC4700	R	HP Q7491A color laserjet 4700 ; 533mhz MIPS RISC processor , 160mb (128+32) upto 544 , 600/600dpi ; 30ppm , HP Imageret 3600 , 600 (100+500)s input tray upto 2600 , 500s output , duty : 100000pages per month - USB + 2 x EiO + parallel - 1 year on-site warranty
LP-HC4700N	R	HP Q7492A color laserjet 4700N , network ready ; 533mhz MIPS RISC processor , 160mb (128+32) upto 544 , 600/600dpi ; 30ppm , HP Imageret 3600 , 600 (100+500)s input tray upto 2600 , 500s output, duty : 100000pages per month - USB + 1x EiO + parallel - 1 year on-site warranty
LP-HC4700DN	R	HP Q7493A color laserjet 4700DN , with auto duplex printing unit , network ready ; 533mhz MIPS RISC processor , 288mb (256+32) upto 544 , 600/600dpi ; 30ppm , HP Imageret 3600 , 600 (100+500)s input tray upto 2600 , 500s output, duty : 100000pages per month - USB + 1x EiO + parallel - 1 year on-site warranty
LP-HC4700DTN	R	HP Q7494A color laserjet 4700DTN , with auto duplex printing unit , network ready , printer stand ; 533mhz MIPS RISC processor , 288mb (256+32) upto 544 , 600/600dpi ; 30ppm , HP Imageret 3600 , 1600 (100+500+500+500)s input tray upto 2600 , 500s output, duty : 100000pages per month - USB + 1x EiO + parallel - 1 year on-site warranty
HP A3 color - workgroup		
LP-HC5550	R	HP Q3713A A3 color laserjet 5550 ; 533mhz MIPS 64 20kc processor , 160mb (128+32) upto 544 , 600/600dpi ; 28ppm , HP Imageret 3600 , 600 (100+500)s input tray upto 2100 , 250s output , duty : 120000pages per month - USB + 3 x EiO + parallel + 2 flash slot
LP-HC5550N	R	HP Q3714A A3 color laserjet 5550N , network ready ; 533mhz MIPS 64 20kc processor, 160mb (128+32) upto 544, 600/600dpi; 28ppm, hp Imageret 3600 , 600 (100+500)s input tray upto 2100, 250s output, duty : 120000pages per month - USB + 2 x EiO + parallel + 2 flash slot
LP-HC5550DN	R	HP Q3715A A3 color laserjet 5550DN , network ready with auto duplex printing unit ; 533mhz MIPS 64 20kc processor , 160mb (128+32) upto 544 , 600/600dpi ; 28ppm , HP Imageret 3600 , 600 (100+500)s input tray upto 2100 , 250s output , duty : 120000pages per month - USB + 2 x EiO + parallel + 2 flash slot
LP-HC5550DTN	R	HP Q3716A A3 color laserjet 5550DTN , network ready with extra input tray + auto duplex printing unit ; 533mhz MIPS 64 20kc processor , 288mb (256+32) upto 544 , 600/600dpi ; 28ppm , HP Imageret 3600 , 1100 (100+500+500)s input tray upto 2100 , 250s output , duty : 120000pages per month - USB + 2 x EiO + parallel + 2 flash slot

LP-HC5550HDN	R	HP Q3717A A3 color laserjet 5550HDN , network ready with 20gb EiO hdd + extra input tray + auto duplex printing unit ; 533mhz MIPS 64 20kc processor , 288mb (256+32) upto 544 , 600/600dpi ; 28ppm , HP Imageret 3600 , 2100 (100+500+500+500+500)s input tray , 250s output , duty : 120000pages per month - USB + 1 x EiO + parallel + 2 flash slot
LP-HCCP6015N	R	HP Q3931A A3 color laserjet CP6015N , network ready ; 835mhz PMC processor, 512mb upto 1024 , 1200/600dpi ; 41ppm, hp Imageret 3600 , 600 (100+500)s input tray upto 2100, 500s output, duty upto 1600 : 175000pages per month - USB + 2 x EiO
LP-HCCP6015DN	R	HP Q3932A A3 color laserjet CP6015DN , auto Duplex printing unit + network ready ; 835mhz PMC processor, 512mb upto 1024 , 1200/600dpi ; 41ppm, hp Imageret 3600 , 600 (100+500)s input tray upto 2100, 500s output, duty upto 1600 : 175000pages per month - USB + 2 x EiO
LP-HCCP6015XH	R	HP Q3934A A3 color laserjet CP6015XH , auto Duplex printing unit + network ready ; 835mhz PMC processor, 512mb upto 1024 , 1200/600dpi ; 41ppm, hp Imageret 3600 , 2100 (100+500+500+500)s input tray upto 2100, 1600s output , duty : 175000pages per month - USB + 2 x EiO
HP A4 color all-in-one		
LP-HCM1312		HP CC430A Color Multi-function laserjet CM1312 - Print-Scan-Copy , flatbed : 450 MHz Coldfire® v5x processor , 128mb ram , 12/8ppm , 150s input tray , 125s output , duty : 30000pages per month , scan : 1200x1200/19200dpi , 24bit ; standalone copy , 99 mutiple copies , 25-400% - usb
LP-HCM1312NFi		HP CC431A Color Multi-function laserjet CM1312NFi - Print-Scan-Copy-Fax , flatbed , with 50s ADF , network ready , 6.1cm color lcd control panel : 450 MHz Coldfire® v5x processor , 160mb ram , 12/8ppm , 150s input tray , 125s output , duty : 30000pages per month , scan : 1200x1200/19200dpi , 24bit ; standalone copy , 99 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , 250pages fax memory , 120+5 speed dial - usb+UTP + flash reader
LP-HCo2820		HP Q3948A color laserjet all-in-one 2820 - Print-Scan-Copy , flatbed , with 50s ADF , network ready : 264 MHz, Motorola Coldfire® v 4e processor , 96mb ram upto 224 , 19/4ppm , 600/1200 dpi , 125s input tray upto 375 , 125s output , duty : 30000pages per month ; scan : 1200x1200/19200dpi , 24bit ; standalone copy , 99 mutiple copies , 25-400% - usb + utp + flash reader
LP-HCM2320NF		HP CC436A color laserjet all-in-one CM2320NF - Print-Scan-Copy-Fax , flatbed , with 50s ADF , network ready : 264 MHz, 450 MHz Coldfire® v5x processor , 160mb ram upto 416, 20/20ppm , 600/1200 dpi , 300 (50+250)s input tray upto 550 , 150s output , duty : 40000pages per month ; scan : 1200x1200/19200dpi , 42bit ; standalone copy , 99 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , 250pages fax memory , 120+4 speed dial - usb + utp + flash reader
LP-HCM2320FXi		HP CC435A color laserjet all-in-one CM2320FXi - Print-Scan-Copy-Fax , with auto duplex printing unit , flatbed , with 50s ADF , extra input tray , network ready : 264 MHz, 450 MHz Coldfire® v5x processor , 160mb ram upto 416, 20/20ppm , 600/1200 dpi , 550 (50+250+250)s input tray , 150s output , duty : 40000pages per month ; scan : 1200x1200/19200dpi , 42bit ; standalone copy , 99 mutiple copies , 25-400% ; as standalone fax with 33.6k modem , 250pages fax memory , 120+4 speed dial - usb + utp + flash reader
HP color all-in-one for workgroup		

LP-HCM3530	R	HP CC519A Color Multi-function laserjet CM3530 MFP - Print-Scan-Copy , with auto duplex printing unit , 50s ADF, network ready : 515 MHz RISC processor , 512mb upto 1024 + +128mb flash + embedded 80gb hdd , 31ppm, 600 dpi, 350 (100+250)s input tray upto 850 , 250s output , duty: 75000 pages per month ; scan: 600dpi, scan to email; standalone copy, 31cpm, 999 mutiple copies, 25-400% , fax module optional - parallel + usb2.0 + EiO + UTP
LP-HCM3530FS	R	HP CC520A Color Multi-function laserjet CM3530FS MFP - Print-Scan-Copy-Fax , with auto duplex printing unit , 50s ADF, network ready : 515 MHz RISC processor , 512mb upto 1024 + +128mb flash + embedded 80gb hdd , 31ppm, 600 dpi, 350 (100+250)s input tray upto 850 , 250s output , duty: 75000 pages per month ; scan: 600dpi, scan to email; standalone copy, 31cpm, 999 mutiple copies, 25-400% - parallel + usb2.0 + EiO + UTP
LP-HCM4730	R	HP CB480A Color Multi-function laserjet CM4730 MFP - Print-Scan-Copy , with auto duplex printing unit , 50s ADF, network ready : 533 MHz RISC processor , 256mb upto 576 , 30ppm, 600 dpi, 1600 (100+500+500+500)s input tray , 500s output upto 700, duty: 175000 pages per month ; scan: 600dpi, scan to email; standalone copy, 30cpm, 999 mutiple copies, 25-400% , fax module optional - parallel + usb2.0 + EiO + UTP
LP-HCM4730F	R	HP CB481A Color Multi-function laserjet CM4730F MFP - Print-Scan-Copy+Fax , with auto duplex printing unit , 50s ADF, network ready : 533 MHz RISC processor , 256mb upto 576 , 30ppm, 600 dpi, 1600 (100+500+500+500)s input tray , 500s output upto 700, duty: 175000 pages per month ; scan: 600dpi, scan to email; standalone copy, 30cpm, 999 mutiple copies, 25-400% - parallel + usb2.0 + EiO + UTP
LP-HCM4730FSK	R	HP CB482A Color Multi-function laserjet CM4730XS MFP - Print-Scan-Copy+Fax , with stapler/stacker , auto duplex printing unit , 50s ADF, network ready : 533 MHz RISC processor , 256mb upto 576 , 30ppm, 600 dpi, 1600 (100+500+500+500)s input tray , 500s output upto 700, duty: 175000 pages per month ; scan: 600dpi, scan to email; standalone copy, 30cpm, 999 mutiple copies, 25-400% - parallel + usb2.0 + EiO + UTP
LP-HCM4730FM	R	HP CB483A Color Multi-function laserjet CM4730XS MFP - Print-Scan-Copy+Fax , with 3bin mail box , auto duplex printing unit , 50s ADF, network ready : 533 MHz RISC processor , 256mb upto 576 , 30ppm, 600 dpi, 1600 (100+500+500+500)s input tray , 700 (500+100+100)s output, duty: 175000 pages per month ; scan: 600dpi, scan to email; standalone copy, 30cpm, 999 mutiple copies, 25-400% - parallel + usb2.0 + EiO + UTP
LP-HCM6030	R	HP CE664A Color Multi-function laserjet CM6030 MFP , A3 - Print-Scan-Copy , with auto duplex printing unit , 50s ADF, network ready : 835mhz PMC-Sierra RM7965 64-bit Microprocessor , 512mb upto 1024 , 31ppm, 1200 dpi, 1100 (100+500+500)s input tray , 500s output upto 700, duty: 200000 pages per month ; scan: 600dpi, scan to email; standalone copy, 40cpm, 999 mutiple copies, 25-200% - usb2.0 + EiO + UTP
LP-HCM6030F	R	HP CE665A Color Multi-function laserjet CM6030F MFP , A3 - Print-Scan-Copy-Fax , with auto duplex printing unit , 50s ADF, network ready : 835mhz PMC-Sierra RM7965 64-bit Microprocessor , 512mb upto 1024 , 31ppm, 1200 dpi, 2100 (100+500+500+500+500)s input tray , 500s output upto 700, duty: 200000 pages per month ; scan: 600dpi, scan to email; standalone copy, 40cpm, 999 mutiple copies, 25-200% - usb2.0 + EiO + UTP

LP-HCM6040	R	HP Q3938A Color Multi-function laserjet CM6040 MFP , A3 - Print-Scan-Copy , with auto duplex printing unit , 50s ADF, network ready : 835mhz PMC-Sierra RM7965 64-bit Microprocessor , 512mb upto 1024 , 40ppm, 1200 dpi, 1100 (100+500+500)s input tray , 500s output upto 700, duty: 200000 pages per month ; scan: 600dpi, scan to email; standalone copy, 40cpm, 999 mutiple copies, 25-200% - usb2.0 + EiO + UTP
LP-HCM6040F	R	HP Q3939A Color Multi-function laserjet CM6040F MFP , A3 - Print-Scan-Copy-Fax , with auto duplex printing unit , 50s ADF, network ready : 835mhz PMC-Sierra RM7965 64-bit Microprocessor , 512mb upto 1024 , 40ppm, 1200 dpi, 2100 (100+500+500+500+500)s input tray , 500s output upto 700, duty: 200000 pages per month ; scan: 600dpi, scan to email; standalone copy, 40cpm, 999 mutiple copies, 25-200% - usb2.0 + EiO + UTP
HP accessories		
LP-HA524	R	HP CB524A 75s envelope feeder for laserjet P4014 series , P4015 series , P4515 series
LP-HA2438	R	HP Q2438B 75s envelope feeder for laserjet 4200 series , 4300 series , 4345mfp series , M4345mfp series
LP-HA518	R	HP CB518A 500s input tray for laserjet P4014 series , P4015 series , P4515 series
LP-HA523	R	HP CB523A 1500s input tray for laserjet P4014 series , P4015 series , P4515 series
LP-HA5931	R	HP Q5931A 250s input tray for laserjet 1320 , P2014, P2015 series
LP-HA464	R	HP CE464AA 500s input tray for laserjet P2055 series
LP-HA5968	R	HP Q5968A 500s input tray for laserjet 4345 series , M4345mfp series
LP-HA5985	R	HP Q5985A 500s input tray for color laserjet 2700series, 3600 series . 3800 series , 3000 series, CP3505 series
LP-HACE522A	R	HP CE522A 500s input tray for color laserjet CP3525, CM3530 series
LP-HA497	R	HP CC497A 4"x6" postcard media tray for color laserjet CP3525 series
LP-HA500	R	HP CB500A 250s input tray for color laserjet CM2320 series , CP2025 series
LP-HA6459	R	HP Q6459A 250s input tray for color laserjet 1600, 2600N, 2605, 2605DN, M3027mfp, M3027Xmfp, CM1015MFP, CM1017MFP
LP-HA7130	R	HP Q7130B 500s input tray for color laserjet 5550 series
LP-HA7499	R	HP Q7499A 500s input tray for color laserjet 4700 series
LP-HA7548	R	HP Q7548A 500s input tray for laserjet 5200 series
LP-HA7556	R	HP Q7556A 250s input tray for multi-function laserjet 3390, M2727NF
LP-HA7817	R	HP Q7817A 500s input tray for laserjet P3005 series , M3035MFP series
LP-HA7834	R	HP Q7834A 500s input tray + stand for laserjet M5025mfp, M5035mfp
LP-HA7835	R	HP Q7835A 1500s (500+500+500) input tray + stand for laserjet M5025mfp, M5035mfp
LP-HA473	R	HP CB473A 500s input tray + cabinet + stand for laserjet cp6015N
LP-HA474	R	HP CB474A 1500s (500+500+500) input tray + stand for laserjet cp6015N
LP-HA8531	R	HP C8531A 1000s input tray for laserjet 9000 series
LP-HA8568	R	HP C8568A 100s multi-purpose tray for laserjet 9000 series
LP-HA519	R	HP CB519A auto duplex unit for laserjet P4014 series , P4015 series , P4515 series

LP-HA5969	R	HP Q5969A auto duplex unit for laserjet 4345mfp series , M4345mfp series
LP-HA7549	R	HP Q7549A auto duplex unit for laserjet 5200 series , M5025mfp, M5035mfp
LP-HA8532	R	HP C8532A auto duplex unit for laserjet 9000 series
LP-HA9674	R	HP C9674A auto duplex unit for laserjet 9500 series
LP-HA6073	R	HP J6073G 20gb EiO hard disk
LP-HA7989	R	HP J7989G 40gb EiO hard disk
LP-HA6998	R	HP Q6998A Stapler/Stacker unit (500sheet output tray) upto 1600 sheets - for color laser CP6015
LP-HA6999	R	HP Q6999A Booklet Maker/Finisher unit (500sheet output tray) upto 2x1000 sheets - for color laser CP6015
LP-HA7521	R	HP Q7521A Stapler/Stacker unit (500sheet output tray) for laserjet 4730mfp , CM4730mfp
LP-HACB522A	R	HP CB522A Stapler/Stacker unit (500sheet output tray) for laserjet P4014 series , P4015 series , P4515 series
LP-HA521	R	HP CB522A stacker unit (500sheet output tray) for laserjet P4014 series , P4015 series , P4515 series
LP-HA5692	R	HP Q5692A 3-bin mail box stacker unit - 700 (500+100+100) output tray for laserjet 4345mfp series , M4345mfp series , 4730mfp series
LP-HA5691	R	HP Q5691A stacker unit (500sheet output tray) with stapler for laserjet 4345mfp series , M4345mfp series , 4730mfp series
LP-HA487	R	HP CE487A ADF roller kit for laserjet CM6030mfp , CM6040mfp series
LP-HA516	R	HP CC516A Miscellaneous Paper Handling Accessories (2000sheet + 25 saddle-stitched booklets) for laserjet CM6030mfp , CM6040mfp series
LP-HA517	R	HP CC517A Mailboxes with Stapler (1600sheet output tray) for laserjet CM6030mfp , CM6040mfp series
LP-HA520	R	HP CB520A 5-bin Mailboxes with Stapler (500sheet output tray) for laserjet P4014 series , P4015 series , P4515 series
LP-HA5693	R	HP Q5693A 8-bin mailbox with stapler for laserjet 9000 series , M9040mfp , M9050mfp
LP-HA8084	R	HP C8084A stacker unit (3000sheet output tray) for laserjet 9000 series , color laserjet 9500 series, M9040mfp , M9050mfp
LP-HA8085	R	HP C8085A stacker unit (3000sheet output tray) with stapler for laserjet 9000 series , color laserjet 9500 series , M9040mfp , M9050mfp
LP-HA8088	R	HP C8088B multifunction finisher , MFP upgrade unit for laserjet 9000 series , color laserjet 9500 series , M9040mfp , M9050mfp
LP-HA525	R	HP CB525A printer stand with wheel for laserjet P4014 series , P4015 series , P4515 series
LP-HA9669	R	HP C9669B printer stand + storage cabinet for laserjet 5550 series
LP-HA5970	R	HP Q5970A printer stand with storage for laserjet 4345mfp series , M4345mfp series
LP-HA7501	R	HP Q7501A printer stand for laserjet CP4005 series, 4700 series
LP-HA3216	R	HP Q3216A stapler cartridge (3 x 1000 units) for laserjet 4200 series , 4250 series , 4300 series , 4350 series , P4014 series , P4015 series , P4515 series
LP-HA7432	R	HP Q7432A stapler cartridge (2 x 1500 units) for laserjet M3035mfp, M2727NFS, CM3530 series
LP-HA8091		HP C8091A stapler cartridge (3000 units) for laserjet 9000 series , color laserjet 4700 series , 9500 series , 4345mfp series , M4345mfp series , 4730mfp series , M5035mfp series , cp6015 series , CM6040 series
LP-HA8092	R	HP C8092A stapler cartridge (5000 units) for C8088B MFP stacker (for laserjet 9000 series , color laserjet 9500 series)

LP-HA389	R	HP CB389A maintenance kit (transfer kit) 220v for laserjet P4014 series , P4015 series , P4515 series
LP-HA9153	R	HP C9153A maintenance kit (transfer kit) 220v for laserjet 9000 series
LP-HA5999	R	HP Q5999A maintenance kit 220v for laserjet 4345mfp series
LP-HA3701	R	HP Q3701A analog fax module for laserjet 4345mfp series , M4345mfp series, M5025mfp, M5035mfp , 4730mfp series , M9040mfp series , M9050mfp series , CM6030 series , CM6040 series

Canon

Canon A4 mono

LP-C3010		Canon Lbp-3010 ; 2mb buffer , 8.5 sec warm up time , 2mb buffer , a4 , 600 / 2400x600dpi ; 14ppm , 150s input tray , 100sheets output tray , duty : 5000pages per month - USB 2.0
LP-C3100	R	Canon Lbp-3100 ; 2mb buffer , 8.5 sec warm up time , 2mb buffer , a4 , 600 / 2400x600dpi ; 16ppm , 150s input tray , 100sheets output tray , duty : 5000pages per month - USB 2.0
LP-C3250	R	Canon lasershot Lbp-3250 , 10 sec warm up time . 8mb buffer , a4 , 600 / 2400x600dpi ; 23ppm , 250s input tray upto 500 , 100 sheets output tray , duty : 8000pages per month - USB 2.0 ; support optional network add-on interface
LP-C3310	R	Canon lasershot Lbp-3310 , with auto-duplex unit , 0 sec warm up time , 8mb buffer , a4 , 600 / 2400x600dpi ; 26ppm , 50+250s input tray upto 550 , 125 sheets output tray , duty : 10000pages per month - USB 2.0 ; support optional network add-on interface
LP-C3360	R	Canon i-SENSYS Lbp-3360 , network ready + auto-duplex unit , 64mb buffer , a4 , 600 / 2400x600dpi ; 21ppm , 250s input tray upto 500 , 100 sheets output tray , duty : 10000pages per month - USB 2.0 ; support optional network add-on interface
LP-C3370	R	Canon i-SENSYS Lbp-3370 , network ready + auto-duplex unit , 0 sec warm up time , R4000-333MHz processor , 64mb buffer , a4 , 600 / 2400x600dpi ; 26ppm , 50+250s input tray upto 550 , 125 sheets output tray , duty : 15000pages per month - USB 2.0
LP-C3460	R	Canon lasershot Lbp-3460 , with auto-duplex unit , network ready ; 64mb buffer , a4 , 600 / 2400x600dpi ; 33ppm , 100+250s input tray upto 850 , 250+50 sheets output tray , duty : 90000pages per month - USB 2.0 + UTP

Canon A4 mono - Multi-function

LP-CMF4010	N	Canon i-SENSE MF4010 , print+scan+copy - a4 , 32mb , print 1200x600dpi ; mono : 20ppm , 250s input tray ; scan 9600x9600dpi , 99 mutiple copies , 50-200% , CAPT windowed based - USB 2.0
LP-CMF4140		Canon i-SENSE MF4140 , print+scan+copy+fax , duplex printing - a4 , 32mb , print 1200x600dpi ; mono : 20ppm , 250s input tray ; scan 9600x9600dpi , 99 mutiple copies , 50-200% ; as standalone fax with 33.6k G3 modem , 256pages fax memory , 100+7 x speed dial , CAPT windowed based , duty : 10000pages per month - USB 2.0
LP-CMF4150		Canon i-SENSE MF4150 , print+scan+copy+fax , duplex printing - a4 , 32mb , print 1200x600dpi ; mono : 20ppm , 250s input tray + 35pages ADF ; scan 9600x9600dpi , 99 mutiple copies , 50-200% ; as standalone fax with 33.6k G3 modem , 256pages fax memory , 100+7 x speed dial , CAPT windowed based , duty : 10000pages per month - USB 2.0

LP-CMF4350D	R	Canon i-SENSE MF4350D , print+scan+copy+fax , duplex printing - a4 , 32mb , print 1200x600dpi ; mono : 22rpm , 250s input tray + 35pages ADF , 100s output ; scan 600x1200/9600dpi , 99 mutiple copies , 50-200% ; as standalone fax with 33.6k G3 modem , 256pages fax memory , 100+7 x speed dial , duty : 10000pages per month - USB 2.0
LP-CMF4370DN	R	Canon i-SENSE MF4370Dn , print+scan+copy+fax , duplex printing , network ready - a4 , 32mb , print 1200x600dpi ; mono : 22rpm , 250s input tray + 35pages ADF , 100s output ; scan 600x1200/9600dpi , 99 mutiple copies , 50-200% ; as standalone fax with 33.6k G3 modem , 256pages fax memory , 100+7 x speed dial , duty : 10000pages per month - USB 2.0
LP-CMF4690PL		Canon i-SENSE MF4690PL , print+scan+copy+fax , duplex printing , network ready - a4 , 128mb , print 1200x600dpi ; mono : 20ppm , 250s input tray + 35pages ADF , 100sheet output tray ; scan 9600x9600dpi , 99 mutiple copies , 50-200% ; as standalone fax with 33.6k G3 modem , 512pages fax memory , 198 x speed dial , PCL5e/6 based , duty : 10000pages per month - USB 2.0+UTP
LP-CMF6580PL	R	Canon laserbase MF6580PL , network ready , print+scan+copy+fax - a4 , 128mb , duplex printing+copying , print 1200x600dpi ; mono : 22ppm , 500s input tray + 50pages duplex ADF ; scan 600x600/9600dpi , 99 mutiple copies , 50-200% , support 2-sided copy ; as standalone fax with 33.6k G3 modem , 20mb/1280 pages fax memory , 100+23 x speed dial , PCL5e/6 based , duty : 15000pages per month - USB 2.0+UTP
Canon A4 color		
LP-CC5050	R	Canon Lbp-5050 color laser ; 16mb buffer , a4 , 600 / 9600x600dpi ; mono/color : 12/8ppm , 150s input tray , 125s output tray , CAPT windowed based - USB 2.0
LP-CC5050N	R	Canon Lbp-5050N color laser , network ready ; 16mb buffer , a4 , 600 / 9600x600dpi ; mono/color : 12/8ppm , 150s input tray , 125s output tray , CAPT windowed based - USB 2.0+UTP
LP-CC5100	R	Canon Lbp-5100 color laser + auto-duplex unit ; 16mb buffer , a4 , 600 / 9600x600dpi ; mono/color : 12/10ppm ,250s input tray upto 500 , 125s output tray , CAPT windowed based - USB 2.0
LP-CC5300	R	Canon i-SENSYS LBP-5300 color laser , network ready + auto-duplex unit ; 16mb buffer , a4 , 600 / 9600x600dpi ; mono/color : 21/21ppm , 250+100s input tray upto 850 , 200s output tray , CAPT windowed based - USB 2.0+UTP
LP-CC5360	R	Canon i-SENSYS LBP-5360 color laser , network ready + auto-duplex unit ; 128mb buffer upto 384 + optional 20gb hdd , a4 , 600 / 9600x600dpi ; mono/color : 21/21ppm , 250+100s input tray upto 850 , 200s output tray , PCL5c/ PCL 6/ UFR II based - USB 2.0+UTP
Canon A4 color - Multi-function		
LP-CMF8180C		Canon laserbase MF8180C , color all-in-1 , network ready , print+scan+copy+fax - a4 , 128mb , print 2400x600dpi ; mono / color : 19/4ppm , 250+125s input tray + 50pages ADF ; scan 1200x2400/9600dpi , 99 mutiple copies , 50-200% ; as standalone fax with 33.6k G3 modem , 256 pages fax memory , 100+18 x speed dial , duty : 30000pages per month - USB 2.0+UTP

LP-CMF8450	R	Canon laserbase MF8450 , color all-in-1 , network ready , duplex print+copy+fax+scan , 3.5" lcd , a4 , 384mb , print 2400x600dpi ; mono / color : 17/17ppm , 250+100s input tray + 50pages DADF (Duplex Automatic Document Feeder) upto 900 , 250sheets output tray ; scan 600x600dpi , 99 mutiple copies , 50-200% ; as standalone fax with 33.6k G3 modem , 1000 pages fax memory , 200 speed dial , duty : 50000pages per month - USB 2.0+ UTP+ 2xusb flash drive slot
LP-CMF9170	R	Canon laserbase MF9170 , color all-in-1 , network ready , duplex print+copy+scan+fax , 3.5" lcd , a4 , 512mb , print 2400x600dpi ; mono / color : 21/21ppm , 250+100s input tray + 50pages DADF (Duplex Automatic Document Feeder) upto 900 , 250sheets output tray ; scan 600x600dpi (support scan to flash card or usb flash drive) , 99 mutiple copies , 50-200% ; as standalone fax with 33.6k G3 modem , 1000 pages fax memory , 200 speed dial , duty : 65000pages per month - USB 2.0+ UTP+ flash card reader+ 2xusb flash drive slot
Canon accessories		
LP-CAPF35	R	Canon PF-35 250 sheets input tray for LBP-3300
LP-CAPF35P	R	Canon PF-35P 250 sheets input tray for LBP-3310, 3360. 3370
LP-CAPF92	R	Canon PF-92 250 sheets input tray for LBP-5000, 5100
LP-CAPF96	R	Canon PF-96 250 sheets input tray for LBP-5200
LP-CAPF93	R	Canon PF-93 500 sheets input tray for LBP-5300, 5360
LP-CAPF36	R	Canon PF-36 500 sheets input tray for LBP-3460
LP-CANBC2	R	Canon NB-C2 network board for LBP-3300, 3100, 5100
FaX machine		
Canon laser fax		http://www.canon.co.uk/for_home/product_finder/facsimile/laser/index.asp
FX-CL140H	R	Canon Fax-L140 + Handset ; a4 plain paper laser fax , 256 shades grey scales halftone , 30 pages ADF, 150s auto feeder , 340pages fax memory , 33.6kbps super G3 modem , direct mail prevention , 15 1-touch dial + 100 coded dial ; 99 mutiple copies ; 600/300 dpi , print : 12ppm / fax : 3sec per page , 50-200% zoom , support error re-transmission + relay broadcast + forced memory reception + system management password
FX-CL160	R	Canon Fax-L160 ; a4 plain paper laser fax with usb laser printer function , 256 shades grey scales halftone , 30 pages ADF, 150s auto feeder , 340pages fax memory , 33.6kbps super G3 modem , direct mail prevention , 15 1-touch dial + 100 coded dial ; 99 mutiple copies ; 600/300 dpi, print : 12ppm / fax : 3sec per page , 70-200% zoom , support error re-transmission + relay broadcast + forced memory reception + system management password
FX-CL160H	R	Canon Fax-L160 + Handset ; a4 plain paper laser fax with usb laser printer function , 256 shades grey scales halftone , 30 pages ADF, 150s auto feeder , 340pages fax memory , 33.6kbps super G3 modem , direct mail prevention , 15 1-touch dial + 100 coded dial ; 99 mutiple copies ; 600/300 dpi, print : 12ppm / fax : 3sec per page , 70-200% zoom , support error re-transmission + relay broadcast + forced memory reception + system management password
FX-CL380S	R	Canon i-SENSYS Fax-L380S ; a4 plain paper laser fax with usb laser printer function , 50 pages ADF, 250s auto feeder , 510pages fax memory with backup support , 33.6kbps super G3 modem , direct mail prevention , 31 1-touch dial + 100 coded dial ; 99 mutiple copies , 50-200% ; 1200x600dpi , print : 18ppm / fax : 3sec per page , 50-200% zoom , Password user restriction

FX-CL390	R	Canon i-SENSYS Fax-L390 ; a4 plain paper laser fax with usb laser printer function , 50 pages ADF, 500s auto feeder , 510pages fax memory with backup support , 33.6kbps super G3 modem , direct mail prevention , 31 1-touch dial + 169 coded dial ; 99 mutiple copies , 50-200% ; 1200x600dpi , print : 18ppm / fax : 3sec per page , 50-200% zoom , Password user restriction
FX-CL3000	R	Canon i-SENSYS Fax-L3000 ; a4 plain paper laser fax , 50 pages Duplex ADF (37 ipm / 18ppm) , 100+500s input upto 1100 sheets , output : 100 sheets , 512pages fax memory with backup support , 33.6kbps super G3 modem , direct mail prevention , 80 1-touch dial + 200 coded dial ; 99 mutiple copies , 50-200% ; 1200x600dpi , print : 22ppm / fax : 3sec per page , 50-200% zoom , Password user restriction
FX-CL3000iP	R	Canon i-SENSYS Fax-L3000iP , network reafdy + internet fax ; a4 plain paper laser fax with usb + network laser printer function , 50 pages Duplex ADF (45 ipm / 23ppm) , 100+500s input upto 1100 sheets , output : 100 sheets , 1500pages fax memory with backup support , 33.6kbps super G3 modem , direct mail prevention , 80 1-touch dial + 200 coded dial uupto 500 ; 99 mutiple copies , 50-200% ; 1200x600dpi , print : 22ppm / fax : 3sec per page , 50-200% zoom , Password user restriction

Scanner

HP

general purpose

SN-H2400		HP Q3841A scanjet 2400 , 1200x1200 dpi , preview 12sec , 48bit , 2 x quick buttons - usb
SN-HG2410		HP L2694A scanjet G2410 , 1200x1200 dpi , preview 10sec , 48bit , 2 x quick buttons - usb
SN-HG2710		HP L2696A scanjet G2710 , 2400x4800 dpi , preview 12sec , 48bit , 3 x quick buttons - usb
SN-HG3110	N	HP L2698A scanjet G3110 CCD scanner with built-in TMA (4x 35mm slides / 5 x negatives frames) , 4800x9600 dpi , preview 11sec , 48bit , 4 x quick buttons - usb
SN-HG4010		HP L1956A scanjet G4010 with built-in TMA (5x 35mm slides / 6x 35 negatives) , 4800x9600 dpi , preview 8.5sec , 48bit , 4 x quick buttons - usb
SN-H5590P	N	HP L1912A scanjet 5590P with built-in TMA , 2400x2400 dpi , preview 7sec , 48bit , 5 x quick buttons with 7 functions , optional ADF optional (50 sheets / 8ppm) - usb
SN-HG4050		HP L1957A scanjet G4050 with built-in TMA (16 x 35mm slides / 30x 35mm negatives) , 4800x9600 dpi , preview 8.5sec , 96bit , 4 x quick buttons - usb
SN-H5590	R	HP L1910A scanjet 5590 with built-in TMA , ADF (50 sheets / 8ppm) , 2400x2400 dpi , preview 7sec , 48bit , 5 x quick buttons with 7 functions - usb
SN-H8300		HP L1960A scanjet 8300 professional image scanner , with built-in TMA , 4800x4800 dpi , preview 4.5sec , 48bit , 4 programmable buttons, 1 Scan-to-destination button with selection buttons, Copy button with number of copies & colour/black-and-white selectors, Power button, Cancel button, Button settings button - exrta software : Adobe Photoshop Elements , I.R.I.S. Readiris Pro OCR, SilverFast AI , IT8 reflective calibration , support optional 100sheet 50ipm/25ppm ADF - usb
SN-H7650		HP L1940A scanjet 7650 with built-in TMA , ADF (50s / 12ppm) , 2400x2400 dpi , preview 6sec , 48bit , 5 x quick buttons - usb - Adobe Photoshop Elements included

SN-H7650N		HP L1942A scanjet 7650N network ready with ADF (50s / 12ppm) , 600x600 dpi , 48bit , with AXIS 70U Network Document Server (CPU: 32-bit RISC processor (ETRAX 100LX) , flash memory: 2mb ; RAM: 16mb - RJ45 (10/100 UTP)
SN-H8270	R	HP L1975A scanjet 8270 with built-in TMA , 50sheets duplex ADF (50ipm / 25ppm) , 4800x4800 dpi , preview 4sec , 48bit , 9 x quick buttons with 11 functions - include Adobe Photoshop Elements - usb + optional SCSI
heavy duty document scanner		
SN-HN6010		HP L1983A scanjet N6010 document scanner , A4 , with 50 sheets duplex ADF (36 ipm / 18 ppm) , 600x600 dpi , 48bit , 6 x quick buttons , recommended duty : 1000 pages per day - usb
SN-HN6310	R	HP L2700A scanjet N6310 document scanner , A4 , with built-in TMA , with 50 sheets duplex ADF (6 ipm / 15 ppm) , 600/2400 dpi , 48bit , 3 x quick buttons - usb
SN-H7800	R	HP L1980A scanjet 7800 document scanner , A4 , with 50 sheets duplex ADF (50 ipm / 25 ppm) , 1200dpi , 48bit , 4 x quick buttons , recommended duty : 1000 pages per day - usb
SN-H5000	R	HP L2715A scanjet N5000 document scanner , A4 , sheet-feed / non-flatbed , 50 sheets duplex ADF , 25ppm/50ipm , hardware 600dpi , 48bit , recommended duty : 1500 pages per day - usb
SN-HN7710	R	HP L1989A scanjet N7710 document scanner , A4 , with 50 sheets duplex ADF , hardware 600dpi , 48bit , 4 x quick buttons , recommended duty : 1500 pages per day - usb
SN-H7000	R	HP L2706A scanjet N7000 document scanner , A4 , sheet-feed / non-flatbed , 50 sheets duplex ADF , 40ppm/80ipm , hardware 600dpi , 48bit , recommended duty : 2000 pages per day - usb
SN-HN8420	R	HP L2689A scanjet N8420 document flatbed scanner , A4 , 100 sheets duplex ADF (50 ipm / 25 ppm) , hardware 600dpi , preview 4.5sec , 48bit , 4 programmable buttons, 1 Scan-to-destination button with selection buttons, Copy button with number of copies & colour/black-and-white selectors, Power button, Cancel button, Button settings button - exrta software : Adobe Photoshop Elements , I.R.I.S. Readiris Pro OCR ; recommended duty : 1500pages per day - usb
SN-HN8460	R	HP L2690A scanjet N8460 document flatbed scanner , A4 , 100 sheets duplex ADF (70 ipm / 35 ppm) , hardware 600dpi , preview 4.5sec , 48bit , 4 programmable buttons, 1 Scan-to-destination button with selection buttons, Copy button with number of copies & colour/black-and-white selectors, Power button, Cancel button, Button settings button - exrta software : Adobe Photoshop Elements , I.R.I.S. Readiris Pro OCR ; recommended duty : 1500pages per day - usb
SN-HN9120	R	HP L2683A scanjet N9120 document flatbed scanner , A3 , 200 sheets duplex ADF (100 ipm / 50 ppm) , hardware 600dpi , 48bit , 5 quick buttons (Scan, Copy, Cancel, Tools, Powersave) - exrta software : Kofax® VirtualReScan® Pro, I.R.I.S. Readiris™ Pro ; recommended duty : 5000pages per day - usb
Canon		http://www.canon.co.uk/Products_Solutions/index.asp
SN-CL100	N	Canon canoscan LiDE 100 cis scanner with clip-on vertical stand , usb-powered , 2400x4800 / 19200 dpi , preview 14sec , 48+48/24bit , 4 x ez buttons ; with Z-lid , vertical stand - usb 2.0
SN-CL90		Canon canoscan LiDE 90 cis scanner with clip-on vertical stand , usb-powered , 2400x4800 / 19200 dpi , preview 9sec , 48+48/24bit , 4 x ez buttons ; with Z-lid , vertical stand - usb 2.0
SN-CL200	N	Canon canoscan LiDE 200 cis scanner with clip-on vertical stand , usb-powered , 4800x4800 / 19200 dpi , preview 9sec , 48+48/24bit , 4 x ez buttons ; with Z-lid , vertical stand - usb 2.0

SN-C8400F	N	Canon CanoScan 8400F + FAU (12 x 35mm) CCD scanner - 3200x6400/19200 dpi, preview 2.1sec, 48+48/24bit, 4x ez buttons ; with Z-lid, FARE level 3 - usb 2.0
SN-C4400F		Canon CanoScan 4400F + FAU (6 x 35mm film strip + 4 x 35mm slides) CCD scanner - 4800x9600 / 19200 dpi , preview 5sec , 48+48/24bit , 7 x ez buttons - usb 2.0
SN-CL600F		Canon canoscan LiDE 600F + FAU (6 x 35mm negatives) cis scanner, drop-in vertical scanning , 4800x9600 / 19200 dpi , preview 9sec , 48+48/24bit , 7 x configurable ez buttons ; with Z-lid , vertical stand , FARE level 3 - usb 2.0
SN-C5600F	N	Canon CanoScan 5600F + FAU (6 x 35mm film strip + 4 x 35mm slides) CCD scanner - 4800x9600 / 19200 dpi , preview 3sec , 48+48/24bit , 7 x ez buttons - usb 2.0
SN-C8800F		Canon CanoScan 8800F + FAU (12 x 35mm film strip and 4 x 35mm slides) ccd scanner - 4800x9600/19200 dpi, preview 3sec, 48+48/24bit , 7x ez buttons ; with Z-lid, FARE level 3 - usb 2.0

Add-on Card Storage (ata , s-ata , scsi , SAS)

IDE

Pci

AC-SSi4700		Sunix Ide4700 - ata133 pci controller , 4 x ata133 (2 channels) with raid 0/1/0+1/10 , iTE 8212F chipset - bootable - for HDD only
AC-SSi3710		Sunix Ide3710 - ata133 pci controller , 4 x ata133 (2 channels) with raid 0/1/0+1/10 , Silicon Image sil0680 chipset - bootable - for HDD or optical

IDE+SATA combination

Pci-Express

AC-SS2400P		Sunix SATA2400P - 1 x ATA133 (2 devices) + 2 x internal SATA2 , PCI-Express(1x) , with raid 0/1/0+1 - JMicron JMB360 , support LCQ , NCQ
AC-SS2400PL		Sunix SATA2400P , Low profile PCI-Express(1x) - 1 x ATA133 (2 devices) + 2 x internal SATA2 , with raid 0/1/0+1 - JMicron JMB360 , support LCQ , NCQ - low-profile for 2U rackmount or flex-atx (antec minuet)
AC-SS2400P+L	C	Sunix SATA2400P - 1 x ATA133 (2 devices) + 2 x internal SATA2 , PCI-Express(1x) , with raid 0/1/0+1 - JMicron JMB360 , support LCQ , NCQ - with extra Low-profile bracket for 2U rackmount or flex-atx (antec minuet)
AC-SS1414P		Sunix SATA1414P - 1 x ATA133 (2 devices) + 1 x internal SATA2 + 1 x external e-SATA , PCI-Express(1x) , with raid 0/1/0+1 - JMicron JMB363 , support LCQ , NCQ
AC-SS1414PL		Sunix SATA1414PL , Low profile bracket - 1 x ATA133 (2 devices) + 1 x internal SATA2 + 1 x external e-SATA , PCI-Express(1x) , with raid 0/1/0+1 - JMicron JMB363 , support LCQ , NCQ - low-profile for 2U rackmount or flex-atx (antec minuet)
AC-SS4400P	N	Sunix SATA4400P - 1 x ATA133 (2 devices) + 4 x internal SATA2 + 1 x external e-SATA , PCI-Express(1x) , with raid 0/1/0+1 , Marvell 88SE6145 chipset

SATA / SAS (Searial attached Scsi)

accessories

AC-AA800T	R	Adaptec 800T backup battry module for adaptec raid 5085/51245/51645/52445/5405/5445/5805/3085/31205/31605/3405/3805

Pci / Pci-X

AC-SSS1111		Sunix Sata1111 - 2 port (1 external +1 x internal) sata pci card with raid 0/1 , support NCQ - Initio INI1622

AC-SSS1111+L	C	Sunix Sata1111 - 2 port (1 external +1 x internal) sata pci card with raid 0/1 , support NCQ - Initio INI1622 - include extra low-profile for 2U rackmount or flex-atx (antec minuet)
AC-SSS2100		Sunix Sata2100 - 2 port sata pci card with raid 0/1 , support NCQ - initio ini1622 chipset
AC-SSS2100+L	C	Sunix Sata2100 - 2 port sata pci card with raid 0/1 , support NCQ - initio ini1622 chipset - include extra low-profile for 2U rackmount or flex-atx (antec minuet)
AC-A1210SA	R	Adaptec 1210SA with on-board - 2 port SATA-2 , 32/64bit 66mhz pci , raid 0/1 , support TCQ , NCQ , with 2 sata cable + low-profile pci bracket
AC-SSS2020		Sunix Sata2020 - 4 port (2 external +2 x internal) sata pci card with raid 0/1/0+1 - Silicon Image Sil3114
AC-SSS4000		Sunix Sata4000 - 4 port sata pci card with raid 0/1/0+1 , bootable - Silicon Image Sil3114 , with 1 sata cable
AC-SSS4000+L	C	Sunix Sata4000 - 4 port sata pci card with raid 0/1/0+1 , bootable - Silicon Image Sil3114 , with 1 sata cable- include extra low-profile for 2U rackmount or flex-atx (antec minuet)
AC-A1420SA	R	Adaptec 1420SA - 4 port SATA-2 , 32/64bit pci or 133mhz pci-x , raid 0/1/0+1/10 , support TCQ , NCQ , with 4 sata cable + low-profile pci bracket
AC-PTX4310		Promise TX4310 - 4 port SATA-2 , 32bit 66mhz pci , raid 0/1/0+1/5/10 - support TCQ , NCQ , with 4 sata cable + low-profile pci bracket
AC-A2410SA	R	Adaptec 2410SA with on-board 64mb ECC memory - 4 port SATA-2 , 32/64bit 66mhz pci , raid 0/1/0+1/5/10 , intel 80302 66mhz , support TCQ , NCQ , with 4 sata cable + low-profile pci bracket
AC-A2820SA	R	Adaptec 2820SA - 8 port SATA-2 , 32/64bit 133mhz pci-x , raid 0/1/0+1/5/10/50 , support TCQ , NCQ , with 8 sata cable + low-profile pci bracket
Pci-Express		
AC-SSS0014		Sunix sata0014 - 1 port external e-SATA , PCI-Express(1x) - JMicron JMB360 , support LCQ , NCQ
AC-SSS0014L		Sunix sata0014L , Low profile pci bracket - 1 port external e-SATA , PCI-Express(1x) - JMicron JMB360 , support LCQ , NCQ - low-profile for 2U rackmount or flex-atx (antec minuet)
AC-SSS0014+L	N	Sunix sata0014 - 1 port external e-SATA , PCI-Express(1x) - JMicron JMB360 , support LCQ , NCQ - include extra low-profile for 2U rackmount or flex-atx (antec minuet)
AC-VST400		Vantec UGT-ST400 - 2 port (1 external eSATA + 1 x internal SATA2) , pci-express(1x) card - Silicon Image Sil3112 , support LCQ , NCQ ; Includes extra Low Profile pci bracket for 2U rackmount case or flex-atx - (antec minuet)
AC-SSS1414		Sunix sata1414 - 2 port SATA-2 , PCI-Express(1x) , (1 x external eSATA + 1 x internal) , raid 0/1 - Silicon Image Sil3112a , support LCQ , NCQ , with 1 sata cable
AC-SSS2400		Sunix sata2400 - 2 port SATA-2 , PCI-Express(1x) , raid 0/1 - Silicon Image Sil3112a , support LCQ , NCQ , with 1 sata cable
AC-A1220SA	R	Adaptec 1220SA - 2 port SATA , pci-express (1x) , raid 0/1 , support TCQ , NCQ , with sata cables + extra low-profile pci bracket
AC-A1430SA	R	Adaptec 1430SA - 4 port SATA , pci-express (4x) , raid 0/1/0+1/10 , support TCQ , NCQ , with sata cables + low-profile pci bracket
AC-A3405	N	Adaptec 3405 with on-board 128mb ECC memory - 4 port SAS / SATA , pci-express (4x) , raid 0/1/0+1/5/6/10/50/60 , support TCQ , NCQ , Intel 80333 500mhz processor , support battery back-up module , with sata cables + low-profile pci bracket

AC-A5405	R	Adaptec 5405 with on-board 256mb ECC memory - 4 port SAS / SATA , pci-express (8x) , raid 0/1/0+1/5/6/10/50/60 , support TCQ , NCQ , , 1.2Ghz dual ROC (Raid On Chip) , support battery back-up module , with sata cables + low-profile pci bracket
AC-PEX8350	R	Promise EX8350 with on-board 64mb ECC memory - 8 port SATA , pci-express (4x) , raid 0/1/0+1/5/6/10/50 , support TCQ , NCQ , Intel IOP333 500mhz XScale processor , support battery back-up module , with sata cables + low-profile pci bracket
AC-PEX8650	R	Promise EX8650 with on-board 256mb ECC memory - 8 port SAS / SATA , pci-express (8x) , raid 0/1/0+1/5/6/10/50/60 , support TCQ , NCQ , Intel 81348 800mhz XScale processor , support battery back-up module , with sata cables + low-profile pci bracket
AC-A3805	R	Adaptec 3805 with on-board 128mb ECC memory - 8 port SAS / SATA , pci-express (4x) , raid 0/1/0+1/5/6/10/50/60 , support TCQ , NCQ , Intel 80333 500mhz processor , support battery back-up module , with sata cables + low-profile pci bracket
AC-iSRCSASRB	N	intel SRCSASRB with on-board 256mb ECC memory - 8 port SAS / SATA , pci-express (4x) , raid 0/1/0+1/5/6/10/50/60 , support TCQ , NCQ , LSI Logic 1078 500mhz processor , support battery back-up module , with sata cables + low-profile pci bracket
AC-A5805	R	Adaptec 5805 with on-board 512mb ECC memory - 8 port SAS / SATA , pci-express (8x) , raid 0/1/0+1/5/6/10/50/60 , support TCQ , NCQ , , 1.2Ghz dual ROC (Raid On Chip) , support battery back-up module , with sata cables + low-profile pci bracket
AC-PEX12350	R	Promise EX12350 with on-board 256mb ECC memory - 12 port SATA , pci-express (8x) , raid 0/1/0+1/5/6/10/50 , support TCQ , NCQ , Intel IOP333 500mhz XScale processor , support battery back-up module , with sata cables + low-profile pci bracket
AC-A31205	R	Adaptec 31205 with on-board 256mb ECC memory - 12 port SAS / SATA , pci-express (8x) , raid 0/1/0+1/5/6/10/50/60 , support TCQ , NCQ , Intel 80333 800mhz processor , support battery back-up module , with sata cables
AC-PEX16350	R	Promise EX16350 with on-board 256mb ECC memory - 16 port SATA , pci-express (8x) , raid 0/1/0+1/5/6/10/50 , support TCQ , NCQ , Intel IOP333 500mhz XScale processor , support battery back-up module , with sata cables
AC-A31605	R	Adaptec 31605 with on-board 256mb ECC memory - 16 port SAS / SATA , pci-express (8x) , raid 0/1/0+1/5/6/10/50/60 , support TCQ , NCQ , Intel 80333 800mhz processor , support battery back-up module , with sata cables

cardbus / pcmcia	
AC-SSCBSA20	Sunix CBSA20 - 2 port external SATA , cardbus pcmcia - Silicon Image Sil3112a chipset , bundle 1 x sata cable
AC-SSCBSA20i	Sunix CBSA20i - 2 port external e-SATA , cardbus pcmcia - initio 1620 chipset

Express Card	
AC-SSECSA14	Sunix ECSA14 - 1 port external e-SATA , Express Card 34 (for 34 or 54 slot) , One-lane 2.5 Gb/sec expresscard , JMicron JMB363
AC-SSECSA24J	Sunix ECSA24J - 2 port external e-SATA , Express Card 34 (for 34 or 54 slot) , One-lane 2.5 Gb/sec expresscard , JMicron JMB363
AC-SSECSA24	Sunix ECSA24 - 2 port external e-SATA , Express Card 54 , One-lane 2.5 Gb/sec expresscard , Silicon Image Sil312A , bundle 1 x sata2 cable

Add-on card i/o (usb / firewire , serial / parallel)		
others		
AC-S9501	N	Sunix 9501 post-code / de-bug pci card - for pcmcia card to be used in normal desktop

AC-SPTC1010		Sunix PTC1010R pci to pcmcia adapter - for pcmcia card to be used in normal desktop
AC-SPTE1414	N	Sunix PTE1414 pci-e (1x) to express card (34/54) adapter , with internal USB port - ideal for 35mm/54mm express card to be used in normal desktop
usb / firewire		
Pci		
AC-SiUSB2200L		Sunix USB2200NL - 2 x usb2.0 pci card , NEC chipset - low-profile for 2U rackmount or flex-atx (antec minuet)
AC-SiUSB4212		Sunix USB4212V - usb2.0 pci card , 4 x external +1 x internal , VIA VT6212 chipset
AC-SiPUB0400P	N	Sunix PUB0400P - 4x 12V powered usb pci card , 4 x external +1 x internal , powered by internal 4-pin molex power connector to psu , NEC UPD720102 chipset , ideal for PoS application with no need of ac-adapter (scales, led diplay, digitizer, slip printer … etc)
AC-SiPUB1300P	N	Sunix PUB1300P - 1x24v + 3x12V powered usb pci card , 4 x external +1 x internal , powered by 2x internal 4-pin molex power connector to psu , NEC UPD720102 chipset , ideal for PoS application with no need of ac-adapter (scales, led diplay, digitizer, slip printer … etc)
AC-SiPUB1210P	N	Sunix PUB1210P - 1x24v + 2x12V + 1x5v powered usb pci card , 4 x external +1 x internal , powered by 2x internal 4-pin molex power connector to psu , NEC UPD720102 chipset , ideal for PoS application with no need of ac-adapter (scales, led diplay, digitizer, slip printer, barcode scanner … etc)
AC-SiFW2010		Sunix FW2010G - 2 x external + 1 x internal iEEE1394A pci card , LSI FW323 chipset
AC-SiFW3010G		Sunix FW3010G - 3 x external + 1 x internal iEEE1394A pci card , agere FW323 chipset
AC-SiFW3010GSC		Sunix FW3010G - 3 x external + 1 x internal iEEE1394A pci card , agere FW323 chipset , with Ulead video studio 8 SE + 4-6 pin firewire cable
AC-SiFW3010VSC		Sunix FW3010 - 3 x external + 1 x internal iEEE1394A pci card , via6306 chipset , with Ulead video studio 8 SE + 4-6 pin firewire cable
AC-SiFW3010L		Sunix FW3010L - 3 x external + 1 x internal iEEE1394A pci card , VIA chipset - low-profile for 2U rackmount or flex-atx (antec minuet)
AC-SiFWB3100SC	N	Sunix FWB3100SC - 3 x external iEEE1394B (9 pin) 32/64bit pci card , TI chipset , with Ulead video studio 8 SE + 9-6 pin firewire cable
AC-SiUFC3212		Sunix UFC3212V , usb2.0 + Firewire iEEE1394A - usb2.0 : 3 x external + 1 x internal ; iEEE1394A : 2 x external+1 x internal , pci card , VIA VT6212 + VT6306 chipset
AC-SiUFC2221		Sunix UFC2221 , usb2.0 + Firewire iEEE1394B - usb2.0 : 2 x external + 1 x internal ; iEEE1394B : 2 x external+1 x internal , pci card , TI + NEC chipset
Pci-Express		
AC-SiUSB4414	N	Sunix USB4414N , pci-Express (1x) - 4 x external + 1 x internal usb2.0 , NEC UPD720101+ TI XIO2000 chipset
AC-SiFWA2414		Sunix FWA2414 , pci-Express (1x) , iEEE1394A - 2 x external + 1 x internal , TI XIO2200 chipset
AC-SiFWA3414	N	Sunix FWA3414G , pci-Express (1x) , iEEE1394A - 3 x external + 1 x internal , LSI FW643 chipset
AC-SiFWB3414		Sunix FWB3414 , pci-Express (1x) , iEEE1394B (2 x external) + iEEE1394A - (1 x external + 1 x internal) , TI XIO2200 chipset

AC-SiUFC2412		Sunix UFC2412 , pci-Express (1x) , usb2.0 + Firewire iEEE1394B - usb2.0 : 2 x external + 1 x internal ; iEEE1394B : 2 x external+1 x internal , NEC UPD720101+ TI TSB82AA2+ TI XIO2000 chipset
cardbus / pcmcia		
AC-SiCBU2200		Sunix CBU2200NC - 2 x usb2.0 cardbus/pcmcia , NEC UPD720101 chipset
AC-SiCBU1080		Sunix 1080NC - 3 x usb2.0 cardbus/pcmcia , NEC UPD720101/2 chipset
AC-SiCBU3200	N	Sunix CBU3200E - 3 x usb2.0 cardbus/pcmcia , NEC UPD720102 chipset
AC-SiCBF2000		Sunix CBF2000 - 2 x 6pin ieee1394A cardbus/pcmcia , VIA VT6306 / Agree chipset
AC-SiCBF3000SC		Sunix CBF3000SC - 3 x 6pin ieee1394A cardbus/pcmcia , VIA VT6306 chipset + 4-6 pin cable & Ulead 8.0 SE video editing software
AC-SiCBC2220		Sunix CBC2220A - 2 x usb2.0 + 2 x ieee1394A (1x6pin + 1x4pin) cardbus/pcmcia , Ali M5273 chipset
AC-SiCBF3100S		Sunix CBF3100S - 1 x ieee1394B (9pin) + 2 x ieee1394A (1x6pin + 1x4pin) cardbus/pcmcia , TI TSB81BA3 (PHY) and TSB82AA2 (LYNX) chipset + Ulead 8.0 SE video editing software
Express Card		
AC-SiECF2400		Sunix ECF2400 - 2 x 6pin 1394A (400mb/sec) , expresscard 34 (for 34 or 54 slot) , single lane pci-express link (2.5Gb/sec)
AC-SiECC1424		Sunix ECC1424 - 2 x 6pin 1394A + 1 x usb2.0 expresscard 34 (for 34 or 54 slot) , single lane pci-express link (2.5Gb/sec)
AC-SiECB2400		Sunix ECB2400 - 2 x 6pin 1394B (800mb/sec) expresscard 34 (for 34 or 54 slot) , single lane pci-express link (2.5Gb/sec)
optional firewire cable - 6/4 , 6/6 , 6/9 pin		
		optional firewire cable available in 6-4pin , 6-6pin , 6-9pin
serial		
Serial to bluetooth converter		
AC-SiBTS1009		Sunix BTS1009C RS232 Serial to wireless Bluetooth converter , CSR bluecore with 8mb flash , Bluetooth Class 1 Version 1.2 , upto 100m , transfer rate upto 460.8Kbps , ideal for ALL serial device like barcode scanner, slip printer and other POS device - Pairing for point to point communication or pair with BT dongle for master to slave connection
utp interface		
AC-SiSLS0100D	C	sunix SL-S0100D ethernet (UTP/RJ45) to 1x serial port (9pin) adapter , SUN8989 chipset , 16 byte hardware FIFO , 115 Kbps , built-in ±2KV ESD protection
AC-SiSLS0200D	N	sunix SL-S0200D ethernet (UTP/RJ45) to 2x serial port (9pin) adapter , SUN8989 chipset , 16 byte hardware FIFO , 115 Kbps , built-in ±2KV ESD protection
usb interface		
AC-VUSB20SR	N	Vantec cb-USB20SR - usb to 1 serial port (9pin) adapter
AC-SiUTS1009		sunix UTS1009 usb to 1 serial port (9pin) adapter , 16 byte hardware FIFO , 115 Kbps , Prolific PL2303 chipset
AC-SiUTS2009		sunix UTS2009 usb to 2 serial port (9pin) adapter , 16 byte hardware FIFO , 115 Kbps , MOSCHIP MS7720 chipset
AC-SiUTS4009		sunix UTS4009 usb to 4 serial port adapter , 16 byte hardware FIFO , 115 Kbps , MOSCHIP MS7720 chipset , WHQL, CE, FCC certified
AC-SiUTS7009		sunix UTS7009P usb to 7 serial port adapter , 16 byte hardware FIFO , 115 Kbps , MOSCHIP MS7720 chipset , WHQL, CE, FCC certified
Pci interface		

AC-Si4027A		Sunix 4027A - 1 port serial (16c550) , 32/64bit 3.5/5V pci card , 32byte hardware + 128k software FiFo, SUN1889 chipset , 115.2Kbps , 2KV ESD protection
AC-Si4027AL		Sunix 4027AL - 1 port serial (16c550) , 32/64bit 3.5/5V low-profile pci card , 32byte hardware + 128k software FiFo, SUN1889 chipset , 115.2Kbps , 2KV ESD protection - low-profile bracket for slim case or 2u rackmount
AC-Si4027DL		Sunix 4027DL - 1 port serial (16c550) , 32/64bit 3.5/5V low-profile pci card , 32byte hardware + 128k software FiFo, SUN1688+1889 chipset , 115.2Kbps , support Re-Map to legacy ISA address , 2KV ESD protection - low-profile bracket for slim case or 2u rackmount
AC-Si4037To		Sunix 4037T Oem pack - 2 port serial (16c550) , 32/64bit 3.5/5V pci card , 32byte hardware + 128k software FiFo, SUN1889 chipset , 115.2Kbps , 32/64bit 3.5/5V pci card, 2KV ESD protection
AC-Si4037A		Sunix 4037 - 2 port serial (16c550) , 32/64bit 3.5/5V pci card , 32byte hardware + 128k software FiFo, SUN1889 chipset , 115.2Kbps , 32/64bit 3.5/5V pci card, 2KV ESD protection
AC-Si4037AL		Sunix 4037AL - 2 port serial (16c550) 32/64bit 3.5/5V low-profile pci card , SUN1889 chipset , 32byte hardware + 128k software FiFo, SUN1889 chipset , 115.2Kbps , 2KV ESD protection - low-profile bracket for slim case or 2u rackmount
AC-Si4037D		Sunix 4037D - 2 port serial (16c550) , 32/64bit 3.5/5V pci card pci , 32byte hardware + 128k software FiFo, SUN1688+1889 chipset, 115.2Kbps , support Re-Map to legacy ISA address , 2KV ESD protection
AC-Si4037P+L	N	Sunix 4037P - 2 port serial (16c550) , 5V/12V/Ri (no power) selectable for each serial port (enable serial devices to function without ac-adapter) , 32byte hardware + 128k software FiFo, SUN1889 chipset , 115.2Kbps , 32/64bit 3.5/5V pci card , 2KV ESD protection - include extra Low-profile pci bracket
AC-Si4056A		Sunix 4056A - 4 port serial (16c550) , 32/64bit 3.5/5V pci card , SUN1889 chipset , 115.2Kbps , 32byte hardware + 128k software FiFo, SUN1889 chipset , 115.2Kbps , 32/64bit 3.5/5V pci card, 2KV ESD protection
AC-Si4056AL	N	Sunix 4056AL - 4 port serial (16c550) 32/64bit 3.5/5V low-profile pci card , SUN1889 chipset , 115.2Kbps , 32byte hardware + 128k software FiFo, SUN1889 chipset , 115.2Kbps , 2KV ESD protection
AC-Si4056D		Sunix 4056D - 4 port serial (16c550) , 32/64bit 3.5/5V pci card , 32byte hardware + 128k software FiFo, SUN1688+1889 chipset , 115.2Kbps , support Re-Map to legacy ISA address , 2KV ESD protection
AC-Si4056P+L	N	Sunix 4056P - 4 port serial (16c550) pci card , 5V/12V/Ri (no power) selectable for each serial port (enable serial devices to function without ac-adapter) , SUN1889 chipset , 115.2Kbps , 32byte hardware + 128k software FiFo , 32/64bit 3.5/5V pci card , 2KV ESD protection - with extra low-profile bracket for slim case or 2u rackmount
AC-Si4000A+L	R	Sunix 4000A - 4 port high-speed serial (16c550) , 32/64bit 3.5/5V pci card , 32byte hardware + 128k software FiFo, sunix Matrix UL7512EQ , 921.6 Kbps , 32/64bit 3.5/5V 33/66MHz pci card, 15KV ESD protection - with extra low-profile bracket for slim case or 2u rackmount

AC-Si4000P+L	R	Sunix 4000P - 4 port high-speed serial (16c550) , 32/64bit 3.5/5V pci card , 5V/12V/Ri (no power) selectable for each serial port (enable serial devices to function without ac-adapter) , 32byte hardware + 128k software FiFo, sunix Matrix UL7512EQ , 921.6 Kbps , 32/64bit 3.5/5V 33/66MHz pci card, 15KV ESD protection - with extra low-profile bracket for slim case or 2u rackmount
AC-Si4066Ro	N	Sunix 4066R Oem pack - 8 port serial (16c550) pci card , 32byte hardware + 128k software FiFo, SUN1889 chipset , 115.2Kbps , 32/64bit 3.5/5V pci card , 2KV ESD protection
AC-Si4066R		Sunix 4066R - 8 port serial (16c550) pci card , 32byte hardware + 128k software FiFo, SUN1889 chipset , 115.2Kbps , 32/64bit 3.5/5V pci card , 2KV ESD protection
AC-Si8000A	C	Sunix 8000A - 8 port high-speed serial (16c550) pci card , 64byte hardware + 128k software FiFo, sunix Matrix UL7522EQ , 921.6 Kbps , 32/64bit 3.5/5V 33/66MHz pci card , 15KV ESD protection
AC-Si8000AL	R	Sunix 8000AL - 8 port high-speed serial (16c550) Low-profile pci / pci-x card , 64byte hardware + 128k software FiFo, sunix Matrix UL7522EQ , 921.6 Kbps , 32/64bit 3.5/5V 33/66MHz pci/pci-x card , 15KV ESD protection
AC-Si1600	N	Sunix ser1600A - 16 port high-speed serial (16c550) , sunix Matrix UL7534EB chipset , 64byte hardware + 128k software FiFo, sunix Matrix UL7534EB , 921.6 Kbps , 32/64bit 3.5/5V 33/66MHz pci card , built-in 15KV ESD protection
Pci-Express interface		
AC-Si4437		Sunix 4437A - 2 port serial (16c550) , pci-Express (1x) , 32byte hardware + 128k software FiFo, SUN1889 chipset , 115.2Kbps - 15KV ESD protection , WHQL certified
AC-Si4456		Sunix 4456A/AM - 4 port serial (16c550) , pci-Express (1x) , 32byte hardware + 128k software FiFo, SUN1889 chipset , 115.2Kbps - 15KV ESD protection , WHQL certified
AC-Si4456+L	N	Sunix 4456A/AM - 4 port serial (16c550) , pci-Express (1x) , 32byte hardware + 128k software FiFo, SUN1889 chipset , 115.2Kbps - 15KV ESD protection , WHQL certified - with extra low-profile bracket for slim case or 2u rackmount
AC-Si4400+L	C	Sunix 4400A - 4 port high-speed serial (16c550) , pci-Express (1x) , 32byte hardware + 128k software FiFo, sunix martrix UL7512EQ chipset , 921.6k bps , 15KV ESD protection , WHQL certified - with extra low-profile bracket for slim case or 2u rackmount
AC-Si4466	N	Sunix 4466A - 8 port serial (16c550) , pci-Express (1x) , 32byte hardware + 128k software FiFo, SUN1889 chipset , 115.2Kbps - 15KV ESD protection , WHQL certified
cardbus / pcmcia interface		
AC-SiCBS1009		Sunix CBS1009 : 1 x RS232 serial port (9pin) cardbus / pcmcia adapter , sunix Matrix UL7512EQ chipset , 128byte FiFo , 50bps~230.4Kbps
AC-SiCBS2009	N	Sunix CBS2009 : 2 x RS232 serial port (9pin) cardbus / pcmcia adapter , sunix Matrix UL7512EQ chipset , 128byte FiFo , 50bps~230.4Kbps
AC-SiCBS4009	R	Sunix CBS4009 : 4 x RS232 serial port (9pin) cardbus / pcmcia adapter , sunix Matrix UL7512EQ chipset , 128byte FiFo , 50bps~230.4Kbps
Express card interface		
AC-SiECS1400		Sunix ECS1400 : 1 x RS232 serial port (9pin) Express card 34 (for 34 or 54 slot) , sunix Matrix UL7512EQ chipset , 32byte hardware FiFo , 50bps~921.6Kbps - WHQL certified

AC-SiECS2400	N	Sunix ECS2400 : 2 x RS232 serial port (9pin) Express card 34 (for 34 or 54 slot) , sunix Matrix UL7512EQ chipset , 32byte hardware FiFo , 50bps~921.6Kbps - WHQL certified
AC-SiECS4400	N	Sunix ECS4400 : 4 x RS232 serial port (9pin) Express card 34 (for 34 or 54 slot) , sunix Matrix UL7512EQ chipset , 32byte hardware FiFo , 50bps~921.6Kbps - WHQL certified

parallel

usb interface

AC-SiUTP1025		sunix UTP1025 usb to parallel (SPP/BPP/ECP/EPP) adapter, 32 byte hardware FIFO, 2.7mb/sec, no IRQ, DMA required , Prolific PL2305 chipset

Pci interface

AC-Si4008		Sunix 4008/PAR4008B - 1 port parallel (SPP/BPP/ECP/EPP) pci , 32byte hardware FiFo , 32/64bit 3.5/5V pci card, ready for 64 bit system , support Re-Map to ISA address, sun1888 chipset - WHQL certified
AC-Si4008L		Sunix 4008L/PAR4008BL - 1 port parallel (SPP/BPP/ECP/EPP) low-profile pci , 32byte hardware FiFo , 32/64bit 3.5/5V pci card, ready for 64 bit system, support Re-Map to ISA address, sun1888 chipset - WHQL certified
AC-Si4018To		Sunix 4018T Oem pack - 2 port parallel (SPP/BPP/ECP/EPP) , 32byte hardware FiFo , 32/64bit 3.5/5V pci card, ready for 64 bit system, support Re-Map to ISA address, sun1888 chipset - WHQL certified
AC-Si4018		Sunix 4018 - 2 port parallel (SPP/BPP/ECP/EPP) , 32byte hardware FiFo , 32/64bit 3.5/5V pci card, ready for 64 bit system, support Re-Map to ISA address, sun1888 chipset - WHQL certified
AC-Si4018+L	C	Sunix 4018 - 2 port parallel (SPP/BPP/ECP/EPP) , 32byte hardware FiFo , 32/64bit 3.5/5V pci card, ready for 64 bit system, support Re-Map to ISA address, sun1888 chipset - WHQL certified - with extra low-profile bracket for slim case or 2u rackmount

Pci-Express interface

AC-Si4408A	N	Sunix 4408A - 1 port parallel (SPP/BPP/ECP/EPP) pci-express (1x) , 32byte hardware FiFo , ready for 64 bit system , sun1888 chipset - WHQL certified
AC-Si4418A	N	Sunix 4418A - 2 port parallel (SPP/BPP/ECP/EPP) pci-express (1x) , 32byte hardware FiFo , ready for 64 bit system , sun1888 chipset - WHQL certified

cardbus / pcmcia interface

AC-SiCBP0020		Sunix CBP0020 / CBP0020M : 2 x parallel port (SPP/BPP/ECP/EPP) cardbus / pcmcia adapter , support Re-map to ISA , sunix1888 /Matrix UL7512EQ chipset, 16byte hardware FiFo , 2.7MBps - WHQL certified

Multi-i/o (serial + parallel)

usb interface

AC-SiUTM1925		sunix UTM1925B usb to multi i/o (1 serial + 1 parallel) adapter , 16 byte hardware FIFO , 115kbps + 2.7mb/sec , No IRQ, DMA, I/O, address resources required , MOSCHIP MCS7715 chipset

Pci interface

AC-Si4079A		Sunix 4079A/Mio1079AM - 2 port serial (16c550) + 1 port parallel (SPP/BPP/ECP/EPP) pci , 5V/12V/Ri (no power) selectable for each serial port (enable serial devices to function without ac-adapter) , 16byte hardware + 128k software FiFo , 32/64bit 3.5/5V pci card, SUN1998 chipset , 115.2Kbps , 15KV ESD protection

AC-Si4079AL		Sunix 4079AL/Mio4079LM , Low-profile pci - 2 port serial (16c550) + 1 port parallel (SPP/BPP/ECP/EPP) pci , 5V/12V/Ri (no power) selectable for each serial port (enable serial devices to function without ac-adapter) , 16byte hardware + 128k software FiFo , 32/64bit 3.5/5V pci card, SUN1998 chipset , 115.2Kbps , 15KV ESD protection
AC-Si4079D		Sunix 4079D - 2 port serial (16c550) + 1 port parallel (SPP/BPP/ECP/EPP) pci , 32byte hardware + 128k software FiFo , 32/64bit 3.5/5V pci card, ready for 64 bit system, support LPT+ Serial , support parallel+Serial Re-Map to legacy ISA address , sun1689+1889 chipset , 115.2Kbps , 15KV ESD protection
AC-Si4089A		Sunix mio4089AM - 2 port high-speed serial (16c550) + 2 port parallel (SPP/BPP/ECP/EPP) pci , 32byte hardware + 128k software FiFo , 32/64bit 3.5/5V pci card, ready for 64 bit system, sunix matrix UL7522EQ chipset , 921.6Kbps , 15KV ESD protection
AC-Si4096A	C	Sunix mio4096AM - 4 port high-speed serial (16c550) + 2 port parallel (SPP/BPP/ECP/EPP) pci , 32byte hardware + 128k software FiFo , 32/64bit 3.5/5V pci card, ready for 64 bit system, sunix matrix UL7522EQ chipset , 921.6Kbps , 15KV ESD protection
Pci-Express interface		
AC-Si4469	C	Sunix mio4469fx - 1 port high-speed serial (16c550) + 1 port parallel (SPP/BPP/ECP/EPP) pci-express (1x) , 16+32byte hardware + 128k software FiFo , ready for 64 bit system , sunix Matrix UL7512EQ chipset , 230.4kbps , 15KV ESD protection
AC-Si4479A	N	Sunix 4479A/Mio4479AM - 2 port serial (16c550) + 1 port parallel (SPP/BPP/ECP/EPP) pci-express (1x) , 5V/12V/Ri (no power) selectable for each serial port (enable serial devices to function without ac-adapter) , 16+32byte hardware + 128k software FiFo , ready for 64 bit system , sun1998 chipset , 115.2kbps , 15KV ESD protection
cardbus / pcmcia interface		
AC-SiCBM2925	N	Sunix CBM2925 : 2 port serial (16c550) + 1 x parallel (SPP/BPP/ECP/EPP) , cardbus / pcmcia , sunix Matrix UL7512EQ chipset , 230.4kbps , 230.4k BPS , 32+16byte hardware
Kvm Switch		
kvm switch cables		
KS-CBP3		3m PS2 kvm switch cable set for host (2 x ps2 + vga)
KS-CBP5		5m PS2 kvm switch cable set for host (2 x ps2 + vga)
KS-CBU2		1.8m USB kvm switch cable set for host (1 usb + vga)
KS-CBU3		3m USB kvm switch cable set for host (1 usb + vga)
KS-CBU5	N	5m USB kvm switch cable set for host (1 usb + vga)
Sunix		
KS-SKMC102PV		Sunix KMC102PV , 2 port PS/2 mini KVM Switch with audio , console : VGA+PS2+audio in/out , host : VGA+PS2+audio , with built-in cable
KS-SKMC102U		Sunix KMC102U , 2 port USB mini KVM Switch , console : VGA+PS2 , host : VGA+USB , with built-in cable
KS-SKMC102UV		Sunix KMC102UV , 2 port USB mini KVM Switch with audio , console : VGA+PS2+audio in/out , host : VGA+USB+audio , with built-in cable
KS-SKMS122U		Sunix KMS122U , 2 port USB mini KVM Switch with built-in 2 port USB hubs (for 2 host PCs to share same usb devices) , console : VGA+PS2 , host : VGA+USB ; cable optional
KS-SKMS124U		Sunix KMS124U , 4 port USB mini KVM Switch with built-in 3 port USB hubs (for 4 host PCs to share same usb devices) , console : VGA+PS2 , host : VGA+USB ; cable optional
D-Link		

KS-DKVMiP1	R	D-link KVM-iP1 , 1 port KVM Switch over iP , adds remote KVM IP access to existing server , console : VGA+PS2+ UTP+RS232 (for serial modem as backup if network is down) , host : VGA+PS2+USB , with 256bit SSL encryption , support up to 15 users login at the same time , with rackmount kit
KS-DKVM121	N	D-link KVM-121 , 2 port KVM Switch with audio , console : VGA+PS2+audio out , host : VGA+PS2+audio in - with built-in cables
KS-DKVM221	N	D-link KVM-221 , 2 port KVM Switch with audio , console : VGA+USB+audio out , host : VGA+USB+audio in - with built-in cables
KS-DKVM4		D-link DKVM-4K , 4 port KVM Switch , console : VGA+PS2 , host : VGA+PS2 - include 2 x cable set only
KS-DKVM4U		D-link DKVM-4U , 4 port KVM Switch , console : VGA+USB , host : VGA+USB - include 2 x cable set only
KS-DKVM8		D-link DKVM-8E , 8 port KVM Switch with OSD , stackable upto 8 units (64 PCs) , console : VGA+PS2 , host : VGA+PS2 - cable optional
KS-DKVM16		D-link DKVM-16 , 16 port KVM Switch with OSD , stackable upto 8 units (128 PCs) , password protected security , console : VGA+PS2 , host : VGA+PS2 - cable optional

UPS	
APC - 2 years on site warranty / helpdesk : 011-4655414 / 0861 272 877	
Surge protection	
CA-APNPC8	APC PNotePro8-ec , 2 pin plug , surge protector for RJ-11 (modem) / RJ-45 (UTP ethernet)
CA-APNPC6	APC PNotePro6-ec , 3 pin plug , surge protector for RJ-11 (modem) / RJ-45 (UTP ethernet)
CA-AP5B	APC P5B-sa Essential SurgeArrest 5 outlets with surge protection - with cable management
CA-AP5BT	APC P5BT-sa Essential SurgeArrest 5 outlets with surge protection + RJ-11 phone/modem protection - with cable management
CA-AP5BV	APC P5BV-sa Essential SurgeArrest 5 outlets with surge protection + coax DSTV protection - with cable management
Line-R	
UP-ALE600	APC Line-R LE600i , 600VA line conditioner/voltage rugularator - for protection against brownouts + overvoltage - ideal for power generator
UP-ALE1200	APC Line-R LE1200i , 1200VA line conditioner/voltage rugularator - for protection against brownouts + overvoltage - ideal for power generator
Back-UPS CS	http://www.apc.com/products/family/index.cfm?id=17
UP-ABCS325N	APC Back-ups CS BK325i , offline , 350VA - No software + interface
UP-ABCS350	APC Back-ups CS BK350ei , offline , 350VA , RJ-11 modem/fax protection ; with monitoring software, usb + serial interface
UP-ABCS500	APC Back-ups CS BK500ei , offline , 500VA , RJ-11 modem/fax protection ; with monitoring software , usb + serial interface
UP-ABCS650	APC Back-ups CS BK650as / ei , offline , 650VA , RJ-11 modem/fax protection ; with monitoring software , usb + serial interface (no power cable included)
Back-UPS HS	http://www.apc.com/products/family/index.cfm?id=3
UP-ABHS500	APC Back-ups HS BH500iNET , with network + coaxial protection , offline , 500VA , RJ-11 modem/fax protection + 5 x RJ-45 UTP + Co-axial Video / Cable protection ; with monitoring software , usb + serial interface
Back-UPS RS	http://www.apc.com/products/family/index.cfm?id=23

UP-ABRS500		APC Back-ups RS BR500i , line interactive with AVR+power conditioning , 500VA , RJ-11 modem/fax protection ; with monitoring software , usb interface
UP-ABRS650N		APC Back-ups RS BR650Ci , black , line interactive with AVR+power conditioning , 650VA , RJ-11 modem/fax protection - No software + interface
UP-ABRS800		APC Back-ups RS BR800i , line interactive with AVR+power conditioning , 800VA , RJ-11 modem/fax + RJ-45 UTP protection ; with monitoring software , usb interface
UP-ABRS1100N		APC Back-ups RS BR1100Ci , line interactive with AVR+power conditioning , 1.1KVA , RJ-11 modem/fax protection , with cooling fan - No software + interface
UP-ABRS1200N	C	APC Back-ups RS BR1200LCDi , line interactive with AVR+power conditioning , with LCD graphics display , 1.2KVA , RJ-11 modem/fax + RJ-45 UTP protection , with cooling fan - No software + interface
UP-ABRS1500		APC Back-ups RS BR1500i , line interactive with AVR+power conditioning , 1.5KVA , RJ-11 modem/fax + RJ-45 UTP protection ; with monitoring software , usb interface , with cooling fan - support extended-run optional battery pack (BR24BP)
UP-ABRS1500N	C	APC Back-ups RS BR1500LCDi , line interactive with AVR+power conditioning , with LCD graphics display , 1.2KVA , RJ-11 modem/fax + RJ-45 UTP protection , with cooling fan - No software + interface
Smart-UPS		http://www.apc.com/products/family/index.cfm?id=165
UP-AS750		APC Smart-UPS SUA750i , line interactive with AVR+power conditioning , 750VA ; with monitoring software , usb+serial interface , with smart slot
UP-AS750RM2U		APC Smart-UPS SUA750RMi2U , 2U rackmount , line interactive with AVR+power conditioning , 750VA ; with monitoring software , usb+serial interface , with smart slot
UP-AS750RM1U	N	APC Smart-UPS SUA750RMi1U , 1U rackmount , line interactive with AVR+power conditioning , 750VA ; with monitoring software , usb+serial interface , with smart slot
UP-AS1000		APC Smart-UPS SUA1000i , line interactive with AVR+power conditioning , 1000VA ; with monitoring software , usb+serial interface , with smart slot
UP-AS1000RM2U		APC Smart-UPS SUA1000RMi2U , 2U rackmount , line interactive with AVR+power conditioning , 1000VA ; with monitoring software , usb+serial interface , with smart slot
UP-AS1000RM1U	N	APC Smart-UPS SUA1000RMi1U , 1U rackmount , line interactive with AVR+power conditioning , 1000VA ; with monitoring software , usb+serial interface , with smart slot
UP-AS1500		APC Smart-UPS SUA1500i , line interactive with AVR+power conditioning , 1500VA ; with monitoring software , usb+serial interface , with smart slot
UP-AS1500RM2U	N	APC Smart-UPS SUA1500RMi2U , 2U rackmount , line interactive with AVR+power conditioning , 1500VA ; with monitoring software , usb+serial interface , with smart slot , with cooling fan
UP-AS2200		APC Smart-UPS SUA2200i , line interactive with AVR+power conditioning , 2200VA ; with monitoring software , usb+serial interface , with smart slot , with cooling fan
UP-AS2200RM2U	N	APC Smart-UPS SUA2200RMi2U , 2U rackmount , line interactive with AVR+power conditioning , 2200VA ; with monitoring software , usb+serial interface , with smart slot , with cooling fan

UP-AS3000	N	APC Smart-UPS SUA3000i , line interactive with AVR+power conditioning , 3000VA ; with monitoring software , usb+serial interface , with smart slot , with cooling fan
UP-AS3000RM2U	R	APC Smart-UPS SUA3000RMi2U , 2U rackmount , line interactive with AVR+power conditioning , 3000VA ; with monitoring software , usb+serial interface , with smart slot , with cooling fan
UP-AS5000RM5U	R	APC Smart-UPS SUA5000RMi5U , 5U rackmount , with AP9617 (Network Management Card) installed in smart slot , line interactive with AVR+power conditioning , 5000VA ; RJ-45 UTP protection ; with monitoring software , serial interface , with smart slot , with cooling fan
Smart-UPS SC		http://www.apc.com/products/family/index.cfm?id=251
UP-ASSC420		APC Smart-UPS SC SC420i , line interactive with AVR+power conditioning , 420VA , RJ-11 modem/fax + RJ-45 UTP protection ; with monitoring software , serial interface
UP-ASSC450RM		APC Smart-UPS SC SC450RMi1U , 1U rackmount , line interactive with AVR+power conditioning , 450VA , RJ-11 modem/fax + RJ-45 UTP protection ; with monitoring software . serial interface
UP-ASSC620		APC Smart-UPS SC SC620i , line interactive with AVR+power conditioning , 620VA , RJ-11 modem/fax + RJ-45 UTP protection ; with monitoring software , serial interface
UP-ASSC1000T2U		APC Smart-UPS SC SC1000i , Tower or 2U rackmount , line interactive with AVR+power conditioning , 1000VA , RJ-11 modem/fax + RJ-45 UTP protection ; with monitoring software , serial interface
UP-ASSC1500T2U		APC Smart-UPS SC SC1500i , Tower or 2U rackmount , line interactive with AVR+power conditioning , 1500VA , RJ-11 modem/fax + RJ-45 UTP protection ; with monitoring software , serial interface
Smart-UPS XL		http://www.apc.com/products/family/index.cfm?id=164
UP-ASXL750		APC Smart-UPS XL SUA750XLi , line interactive with AVR+power conditioning , 750VA ; with monitoring software , usb+serial interface , with smart slot , support multiple extended-run optional battery pack (SUA24XLBP / UXBP24)
UP-ASXL1000		APC Smart-UPS XL SUA1000XLi , line interactive with AVR+power conditioning , 1000VA ; with monitoring software , usb+serial interface , with smart slot , support multiple extended-run optional battery pack (SUA24XLBP / UXBP24)
UP-ASXL1400RM	R	APC Smart-UPS XL SU1400RMXLiB3U , 3U rackmount , line interactive with AVR+power conditioning , 1400VA ; with monitoring software , serial interface , with smart slot , with smart slot , support multiple extended-run optional battery pack (SU24R2XLBP)
UP-ASXL1500T2U	R	APC Smart-UPS XL SUM1500RMXLi2U , Tower or 2U rackmount , with AP9619 (Network Management Card + Environmental Monitoring) installed in smart slot , line interactive with AVR+power conditioning , 1500VA ; with monitoring software , usb+serial+utp interface , support multiple extended-run optional battery pack (SUM48RMXLBP2U)
UP-ASXL2200		APC Smart-UPS XL SUA2200XLi , 5U rackmount convertible , line interactive with AVR+power conditioning , 2200VA ; with monitoring software , usb+serial interface , with smart slot , support multiple extended-run optional battery pack (SUA48XLBP)

UP-ASXL22003U	R	APC Smart-UPS XL SUA2200RMXLi3U , 3U rackmount , line interactive with AVR+power conditioning , 2200VA ; with monitoring software , usb+serial interface , with smart slot , support multiple extended-run optional battery pack (SUA48RMXLBP3U)
UP-ASXL3000	R	APC Smart-UPS XL SUA3000XLi , 5U rackmount convertible , line interactive with AVR+power conditioning , 3000VA ; with monitoring software , usb+serial interface , with smart slot , support multiple extended-run optional battery pack (SUA48XLBP)
UP-ASXL30003U	R	APC Smart-UPS XL SUA3000RMXLi3U , 3U rackmount , on-line with AVR+power conditioning , 3000VA ; with monitoring software , usb+serial interface , with smart slot , support multiple extended-run optional battery pack (SUA48RMXLBP3U)
UP-ASXL3000T2U	R	APC Smart-UPS XL SUM3000RMXLi2U , tower or 2U rackmount , with AP9619 (Network Management Card + Environmental Monitoring) installed in smart slot , line interactive with AVR+power conditioning , 3000VA ; with monitoring software , usb+serial+utp interface , with smart slot , support multiple extended-run optional battery pack (SUM48RMXLBP2U)
Smart-UPS RT		http://www.apc.com/products/family/index.cfm?id=223
UP-ASRT1000		APC Smart-UPS RT SURT1000XLi , Double Conversion Online , 1000VA ; with monitoring software , serial interface , with smart slot , support multiple extended-run optional battery pack (SURT48XLBP) , with cooling fan , 2U rackmount convertiable via SURTRK
UP-ASRT1000RM	R	APC Smart-UPS RT SURT1000RMXLi , 2U rackmount , Double Conversion Online , 1000VA ; with monitoring software , serial interface , with smart slot , support multiple extended-run optional battery pack (SURT192XLBP) , with cooling fan
UP-ASRT2000	N	APC Smart-UPS RT SURT2000XLi , Double Conversion Online , 2000VA ; with monitoring software , serial interface , with smart slot , support multiple extended-run optional battery pack (SURT48XLBP) , with cooling fan , 2U rackmount convertiable via SURTRK
UP-ASRT2000RM	R	APC Smart-UPS RT SURT2000RMXLi , 2U rackmount , Double Conversion Online , 2000VA ; with monitoring software , serial interface , with smart slot , support multiple extended-run optional battery pack (SURT48XLBP) , with cooling fan
UP-ASRT3000		APC Smart-UPS RT SURT3000XLi/SURTD3000XLi , Double Conversion Online , 3000VA ; with monitoring software , serial interface , with smart slot , support multiple extended-run optional battery pack (SURT192XLBP) , 3U rackmount convertiable via SURTRK2
UP-ASRT3000RM	R	APC Smart-UPS RT SURTD3000RMXLi , 3U rackmount , Double Conversion Online , 3000VA ; with monitoring software , serial interface , with smart slot , support multiple extended-run optional battery pack (SURT192XLBP) , with cooling fan
UP-ASRT5000	N	APC Smart-UPS RT SURTD5000XLi with AP9619 (Network Management Card + Environmental Monitoring) installed in smart slot , Double Conversion Online , 5000VA ; with monitoring software , serial + UTP interface , support multiple extended-run optional battery pack (SURT192XLBP) , 3U rackmount convertiable via SURTRK2 , with cooling fan
UP-ASRT5000RM	R	APC Smart-UPS RT SURTD5000RMXLi , 3U rackmount , with AP9619 (Network Management Card + Environmental Monitoring) installed in smart slot , Double Conversion Online , 5000VA ; with monitoring software , serial + UTP interface , with cooling fan

UP-ASRT6000		APC Smart-UPS RT SURT6000XLi with AP9619 (Network Management Card + Environmental Monitoring) installed in smart slot , Double Conversion Online , 6000VA ; with monitoring software , serial + UTP interface , support multiple extended-run optional battery pack (SURT192XLBP) , 3U rackmount convertiable via SURTRK2 , with cooling fan
UP-ASRT6000RM	R	APC Smart-UPS RT SURT6000RMXLi , 3U rackmount , with AP9619 (Network Management Card + Environmental Monitoring) installed in smart slot , Double Conversion Online , 6000VA ; with monitoring software , serial + UTP interface , support multiple extended-run optional battery pack (SURT192XLBP) , with cooling fan
UP-ASRT8000	R	APC Smart-UPS RT SURT8000XLi with AP9619 (Network Management Card + Environmental Monitoring) installed in smart slot , Double Conversion Online , 8000VA ; with monitoring software , serial interface , support multiple extended-run optional battery pack (SURT192XLBP) , 6U rackmount convertiable via 2 x SURTRK2 , with cooling fan
UP-ASRT8000RM	R	APC Smart-UPS RT SURT8000RMXLi , 6U rackmount , with AP9619 (Network Management Card + Environmental Monitoring) installed in smart slot , Double Conversion Online , 8000VA ; with monitoring software , serial interface , support multiple extended-run optional battery pack (SURT192XLBP) , with cooling fan
UP-ASRT10000	N	APC Smart-UPS RT SURT10000XLi with AP9619 (Network Management Card + Environmental Monitoring) installed in smart slot , Double Conversion Online , 10KVA ; with monitoring software , serial interface , support multiple extended-run optional battery pack (SURT192XLBP) , 6U rackmount convertiable via 2 x SURTRK2 , with cooling fan
UP-ASRT10000RM	R	APC Smart-UPS RT SURT10000RMXLi , 6U rackmount , with AP9619 (Network Management Card + Environmental Monitoring) installed in smart slot , Double Conversion Online , 10000VA ; with monitoring software , serial interface , support multiple extended-run optional battery pack (SURT192XLBP) , with cooling fan
UP-ASRT15KRM	R	APC Smart-UPS RT SURT15KRMXLi , 12U rackmount , with AP9619 (Network Management Card + Environmental Monitoring) installed in smart slot , Double Conversion Online , 15K VA ; support multiple extended-run optional battery pack (SURT192RMXLBP2) , with cooling fan
UP-ASRT20KRM	R	APC Smart-UPS RT SURT20KRMXLi , 12U rackmount , with AP9619 (Network Management Card + Environmental Monitoring) installed in smart slot , Double Conversion Online , 20K VA ; support multiple extended-run optional battery pack (SURT192RMXLBP2) , with cooling fan
Rackmount rail kit		
UP-ASURTRK	R	APC SURTRK - 19" 2U rackmount kit for Smart-UPS RT SURT1000XLi , SURT2000XLi
UP-ASURTRK2	N	APC SURTRK2 - 19" 3U rackmount kit for Smart-UPS RT SURT3000XLi, SURT5000XLi, SURT6000XLi, SURT7500XLi, SURT8000XLi, SURT10000XLi / SURT192XLBP , SURT48RMXLBP / SURT001, SURT002, SURT003, SURT004
UP-AASU032A	R	APC SU032A 4-post rack-rail - sc1500i , SUA48XLBP
UP-AAP9625	R	APC AP9625 2-post rack-rail - 19" rackmount kit for Smart-UPS RT SURT1000XLi , SURT2000XLi , SURT3000XLi , SURT5000XLi , SURT7500XLi , SURT10000XLi , SURT192XLBP
Smart Slot Module		
UP-AAP9617	R	APC AP9617 Smart-Slot module for network management

UP-AAP9619	R	APC AP9619 Smart-Slot module for network management + enviornmental monitoring
UP-AAP9618	R	APC AP9618 Smart-Slot module for network management + enviornmental monitoring + RJ-11 modem monitoring
Extend-Run Battery		
UP-ABR24BP		APC BR24BP extended run battery , Volt-Amp-Hour Capacity : 372 - for Back-UPS RS BR1500i / BX1500
UP-ASU24R2	R	APC SU24R2XLBP 2U rackmount extended run battery , Volt-Amp-Hour Capacity : 864 - for Smart-ups XL SU1400RMXLIB3U
UP-ASUA24		APC SUA24XLBP extended run battery , Volt-Amp-Hour Capacity : 816 - for Smart-UPS XL SUA750XLi , SUA1000XLi
UP-AUXBP24		APC UXBP24 extended run battery , Volt-Amp-Hour Capacity : 3360 - for Smart-UPS XL SUA750XLi , SUA1000XLi
UP-ASURT48		APC SURT48XLBP extended run battery , Volt-Amp-Hour Capacity : 864 - for Smart-UPS RT SURT1000XLi , SURT2000XLi
UP-ASURT48RM	R	APC SURT48RMXLBP rackmount extended run battery , Volt-Amp-Hour Capacity : 864 - for Smart-UPS RT SURT1000RMXLi , SURT2000RMXLi
UP-ASUA48		APC SUA48XLBP extended run battery , support SU032a rackmount kit , Volt-Amp-Hour Capacity : 1632 - for Smart-UPS XL SUA2200XLi , SUA3000XLi
UP-ASUA48RM	R	APC SUA48RMXLBP3U rackmount extended run battery , Volt-Amp-Hour Capacity : 1728 - for Smart-ups XL SUA2200RMXLI3U , SUA3000RMXLI3U
UP-ASUM48RM	R	APC SUM48RMXLBP2U tower/rackmount extended run battery , Volt-Amp-Hour Capacity : 1300 - for Smart-ups XL SUM1500RMXLi2U , SUM3000RMXLi2U
UP-ASURT192	N	APC SURT192XLBP extended run battery , support SURTRK2 rackmount kit , Volt-Amp-Hour Capacity : 1920 - for Smart-UPS RT SURT3000XLi , SURTD3000XLi , SURTD5000XLI, SURT5000XLi , SURT6000XLi , SURT7500XLi , SURT8000XLi , SURT10000XLi
UP-ASURT192RM	R	APC SURT192RMXLBP rackmount extended run battery , Volt-Amp-Hour Capacity : 1920 - for Smart-UPS RT SURT3000RMXLi, SURTD5000RMXLI, SURT5000RMXLi , SURT6000RMXLi , SURT7500RMXLi , SURT8000RMXLi , SURT10000RMXLi
UP-ASURT192RM2	R	APC SURT192RMXLBP2 rackmount extended run battery , Volt-Amp-Hour Capacity : 3840 - for Smart-UPS RT SURT15KRMXLI, SURT15KRMXLI-CC, SURT15KRMXLICH, SURT15KUXI, SURT20KRMXLI, SURT20KRMXLI-CC, SURT20KRMXLICH, SURT20KUXI
OThers		
OT-UL		SV-tech Usb Lock - with 1 key + 4 locks on usb port - to prevent lost of data from usb port for security - ideal for notebook or office PC
OT-B35		3.5" to 5.25" mounting bracket
OT-B35F		3.5" to 5.25" mounting bracket - with Front panel (beige)
oT-H2535S	N	icydock MB882 2.5" -> 3.5" sata hdd / SSD converter / housing (work as standard 3.5" hdd) - screwless + anti-vibration + airflow vents design